

SUBCONSULTAS

COMPARACIONES

```
SELECT avg(salary) FROM employees;
```

```
SELECT last_name FROM employees  
WHERE salary < result_of_previous_query;
```

```
SELECT last_name FROM employees  
WHERE salary < (      SELECT avg(salary) FROM employees      );
```

SUBCONSULTAS

COMPARACIONES

```
SELECT department_name FROM departments
WHERE department_id IN
    (SELECT DISTINCT(department_id) FROM employees);
```

=

```
SELECT department_name
FROM    departments
    JOIN employees ON employees.department_id = departments.department_id
GROUP BY department_name;
```

SUBCONSULTAS

TRANSFORMACION EN ESTRELLA

```
SELECT count(quantity_sold)
FROM sales s, products p, customers c, channels ch
WHERE s.prod_id=p.prod_id
      AND s.cust_id=c.cust_id
      AND s.channel_id=ch.channel_id
      AND p.prod_name='Comic Book Heroes'
      AND c.cust_city='Oxford'
      AND ch.channel_desc='Internet';
```

SUBCONSULTAS

TRANSFORMACION EN ESTRELLA

```
SELECT count(quantity_sold) FROM sales  
  
WHERE prod_id IN (  SELECT prod_id FROM products  
                   WHERE prod_name='Comic Book Heroes')  
  
AND cust_id IN (  SELECT cust_id FROM customers  
                 WHERE cust_city='Oxford')  
  
AND channel_id IN (  SELECT channel_id FROM channels  
                   WHERE channel_desc='Internet');
```

SUBCONSULTAS

TABLA EN ORIGEN

```
SELECT avg(salary), country_id
FROM (
    SELECT salary, country_id
    FROM employees
    NATURAL JOIN departments
    NATURAL JOIN locations
)
GROUP BY country_id;
```

SUBCONSULTAS

PARA INSERTAR

```
INSERT INTO sales_hist  
  SELECT * FROM sales  
  WHERE date > sysdate-1;
```

...

```
UPDATE employees  
  SET salary = (SELECT avg(salary) FROM employees);
```

...

```
DELETE FROM departments  
WHERE department_id NOT IN (  
  SELECT department_id  
  FROM employees  
  WHERE department_id is not null);
```

SUBCONSULTAS

TIPOS

DE REGISTRO UNICO

ESCALARES

DE MULTIPLES REGISTROS

CORRELACIONADAS

SUBCONSULTAS

CORRELACIONADAS

```
SELECT last_name  
FROM employees  
WHERE salary < (      SELECT avg(salary) FROM employees      );
```

...

```
SELECT p.last_name, p.department_id  
FROM employees p  
WHERE p.salary < (      SELECT avg(s.salary)  
                        FROM employees s  
                        WHERE s.department_id=p.department_id );
```