



1

- NOTES:
1. PART SHALL BE PRINTED WITH FACE ON BUILD PLATE
2. PART SHALL BE 3D PRINTED WITH THE FOLLOWING SLICER SETTINGS:
- 1. INFILL DENSITY: 30%
 - 2. ROOF AND WALL LAYERS: 4
 - 3. WALL LAYERS: 4

REVISIONS			
REV.	DESCRIPTION	DATE	APPR.
1	INITIAL RELEASE	2023-02-03	
2	UPDATED TUBE ADAPTER LENGTH TO 80MM	2023-03-23	



UNLESS OTHERWISE SPECIFIED:		NAME	DATE	<div>UOROVER</div> <div>TUBE ADAPTER</div>		
<div>DIMS. ARE IN MILLIMETERS TOLERANCE ON ANGLES 0.5° 0 PLACE DECIMAL ± 0.5mm 1 PLACE DECIMAL ± 0.25mm 2 PLACE DECIMAL ± 0.13mm BREAK ALL SHARP EDGES .25-.50mm</div>		DRAWN	V. COTE-LAROCHE			
		CHECKED				
		MFG APPR.				
INTERPRET THIS DRAWING IN ACCORDANCE WITH: ASME Y14.5-2018		MATERIAL		TITLE		
		MARKFORGED ONYX		SIZE		
		MATL. SPEC.	SURFACE TEXTURE			
		HEAT TREAT				
DO NOT SCALE DRAWING		FINISH		REV		
				1		
				SCALE: 1.5:1		
				WEIGHT: [g]		
				SHEET 1 OF 1		