

# Loops and Iteration


## Chapter 5



Python for Everybody  
[www.py4e.com](http://www.py4e.com)



# Repeated Steps



Program:


```
n = 5
while n > 0 :
    print(n)
    n = n - 1
print('Blastoff!')
print(n)
```

Output:

5  
4  
3  
2  
1  
Blastoff!  
0


Loops (repeated steps) have **iteration variables** that change each time through a loop. Often these **iteration variables** go through a sequence of numbers.

# An Infinite Loop



```
n = 5
while n > 0 :
    print('Lather')
    print('Rinse')
print('Dry off!')
```

What is wrong with this loop?



# Another Loop

```
n = 0
while n > 0 :
    print('Lather')
    print('Rinse')
print('Dry off!')
```

What is this loop doing?

# Breaking Out of a Loop

- The **break** statement ends the current loop and jumps to the statement immediately following the loop
- It is like a loop test that can happen anywhere in the body of the loop


```
while True:
    line = input('> ')
    if line == 'done' :
        break
    print(line)
print('Done!')
```

```
> hello there
hello there
> finished
finished
> done
Done!
```

# Breaking Out of a Loop

- The **break** statement ends the current loop and jumps to the statement immediately following the loop
- It is like a loop test that can happen anywhere in the body of the loop

```
while True:
    line = input('> ')
    if line == 'done' :
        break
    print(line)
print('Done!')
```




```
> hello there
hello there
> finished
finished
> done
Done!
```

```
while True:
    line = input('> ')
    if line == 'done' :
        break
    print(line)
print('Done!')
```



[http://en.wikipedia.org/wiki/Transporter\\_\(Star\\_Trek\)](http://en.wikipedia.org/wiki/Transporter_(Star_Trek))



# Finishing an Iteration with `continue`

The `continue` statement ends the current iteration and jumps to the top of the loop and starts the next iteration

```
while True:
    line = input('> ')
    if line[0] == '#' :
        continue
    if line == 'done' :
        break
    print(line)
print('Done!')
```


```
> hello there
hello there
> # don't print this
> print this!
print this!
> done
Done!
```



# Finishing an Iteration with **continue**


The **continue** statement ends the **current iteration** and jumps to the **top of the loop** and starts the next iteration

```
while True:
    line = input('> ')
    if line[0] == '#' :
        continue
    if line == 'done' :
        break
    print(line)
print('Done!')
```



```
> hello there
hello there
> # don't print this
> print this!
print this!
> done
Done!
```

```
while True:
    line = raw_input('> ')
    if line[0] == '#' :
        continue
    if line == 'done' :
        break
    print(line)
print('Done!')
```



# Indefinite Loops

- While loops are called “indefinite loops” because they keep going until a logical condition becomes **False**
- The loops we have seen so far are pretty easy to examine to see if they will terminate or if they will be “infinite loops”
- Sometimes it is a little harder to be sure if a loop will terminate

# Definite Loops

Iterating over a set of items...

# Definite Loops

- Quite often we have a **list** of items of the **lines in a file** - effectively a **finite set** of things
- We can write a loop to run the loop once for each of the items in a set using the Python **for** construct
- These loops are called “**definite loops**” because they execute an exact number of times
- We say that “**definite loops iterate through the members of a set**”

# A Simple Definite Loop

```
for i in [5, 4, 3, 2, 1] :  
    print(i)  
print('Blastoff!')
```

5

4

3

2

1

Blastoff!


# A Definite Loop with Strings

```
friends = ['Joseph', 'Glenn', 'Sally']  
for friend in friends :  
    print('Happy New Year:', friend)  
print('Done!')
```

Happy New Year: Joseph  
Happy New Year: Glenn  
Happy New Year: Sally

Done!

# A Simple Definite Loop



```
for i in [5, 4, 3, 2, 1] :  
    print(i)  
print('Blastoff!')
```

5  
4  
3  
2  
1  
Blastoff!

Definite loops (for loops) have explicit **iteration variables** that change each time through a loop. These **iteration variables** move through the sequence or set.




# Looking at in...

- The **iteration variable** “iterates” through the **sequence** (ordered set)
- The **block (body)** of code is executed once for each value **in** the **sequence**
- The **iteration variable** moves through all of the values **in** the **sequence**


Iteration variable



Five-element  
sequence




```
for i in [5, 4, 3, 2, 1] :  
    print(i)
```




```
for i in [5, 4, 3, 2, 1] :  
    print(i)
```

- The **iteration variable** “iterates” through the **sequence** (ordered set)
- The **block (body)** of code is executed once for each value **in** the **sequence**
- The **iteration variable** moves through all of the values **in** the **sequence**



```
for i in [5, 4, 3, 2, 1] :  
    print(i)
```



# Loop Idioms: What We Do in Loops

Note: Even though these examples are simple,  
the patterns apply to all kinds of loops

# Making “smart” loops

The trick is “knowing” something about the whole loop when you are stuck writing code that only sees one entry at a time

Set some variables to initial values

for thing in data:

Look for something or do something to each entry separately, updating a variable

Look at the variables

# Looping Through a Set

```
print('Before')
for thing in [9, 41, 12, 3, 74, 15] :
    print(thing)
print('After')
```

\$ python basicloop.py

Before

9

41

12

3

74

15

After

# What is the Largest Number?

# What is the Largest Number?

3



# What is the Largest Number?

41

# What is the Largest Number?

12

# What is the Largest Number?

9

# What is the Largest Number?

74

# What is the Largest Number?

15

# What is the Largest Number?

# What is the Largest Number?

3      41      12      9      74      15

# What is the Largest Number?

largest\_so\_far

-1



# What is the Largest Number?

3

largest\_so\_far

3

# What is the Largest Number?

41

largest\_so\_far

41

# What is the Largest Number?

12

largest\_so\_far

41

# What is the Largest Number?

9

largest\_so\_far

41

# What is the Largest Number?

74

largest\_so\_far

74

# What is the Largest Number?

15

74

# What is the Largest Number?

3      41      12      9      74      15

74

# Finding the Largest Value

```
largest_so_far = -1
print('Before', largest_so_far)
for the_num in [9, 41, 12, 3, 74, 15] :
    if the_num > largest_so_far :
        largest_so_far = the_num
    print(largest_so_far, the_num)

print('After', largest_so_far)
```

\$ python largest.py

Before -1

9 9

41 41

41 12

41 3

74 74

74 15

After 74

We make a variable that contains the largest value we have seen so far. If the current number we are looking at is larger, it is the new largest value we have seen so far.



More Loop Patterns...

# Counting in a Loop

```
zork = 0
print('Before', zork)
for thing in [9, 41, 12, 3, 74, 15] :
    zork = zork + 1
    print(zork, thing)
print('After', zork)
```

```
$ python countloop.py
```

```
Before 0
```

```
1 9
```

```
2 41
```

```
3 12
```

```
4 3
```

```
5 74
```

```
6 15
```

```
After 6
```

To **count** how many times we execute a loop, we introduce a **counter variable** that starts at 0 and we add one to it each time through the loop.

# Summing in a Loop

```
zork = 0
print('Before', zork)
for thing in [9, 41, 12, 3, 74, 15] :
    zork = zork + thing
    print(zork, thing)
print('After', zork)
```

```
$ python countloop.py
```

```
Before 0
```

```
9 9
```

```
50 41
```

```
62 12
```

```
65 3
```

```
139 74
```

```
154 15
```

```
After 154
```

To add up a value we encounter in a loop, we introduce a sum variable that starts at 0 and we add the value to the sum each time through the loop.

# Finding the Average in a Loop

```
count = 0
sum = 0
print('Before', count, sum)
for value in [9, 41, 12, 3, 74, 15] :
    count = count + 1
    sum = sum + value
    print(count, sum, value)
print('After', count, sum, sum / count)
```

```
$ python averageloop.py
```

```
Before 0 0
```

```
1 9 9
```

```
2 50 41
```

```
3 62 12
```

```
4 65 3
```

```
5 139 74
```

```
6 154 15
```

```
After 6 154 25.666
```

An **average** just combines the **counting** and **sum** patterns and divides when the loop is done.

# Filtering in a Loop

```
print('Before')
for value in [9, 41, 12, 3, 74, 15] :
    if value > 20:
        print('Large number',value)
print('After')
```

\$ python search1.py

Before

Large number 41

Large number 74

After

We use an **if** statement in the **loop** to catch / filter the values we are looking for.

# Search Using a Boolean Variable

```
found = False
print('Before', found)
for value in [9, 41, 12, 3, 74, 15] :
    if value == 3 :
        found = True
    print(found, value)
print('After', found)
```

```
$ python search1.py
```

```
Before False
```

```
False 9
```

```
False 41
```

```
False 12
```

```
True 3
```

```
True 74
```

```
True 15
```

```
After True
```

If we just want to search and know if a value was found, we use a variable that starts at **False** and is set to **True** as soon as we find what we are looking for.

# How to Find the Smallest Value

```
largest_so_far = -1
print('Before', largest_so_far)
for the_num in [9, 41, 12, 3, 74, 15] :
    if the_num > largest_so_far :
        largest_so_far = the_num
    print(largest_so_far, the_num)

print('After', largest_so_far)
```

\$ python largest.py

Before -1

9 9

41 41

41 12

41 3

74 74

74 15

After 74

How would we change this to make it find the smallest value in the list?

# Finding the Smallest Value

```
smallest_so_far = -1
print('Before', smallest_so_far)
for the_num in [9, 41, 12, 3, 74, 15] :
    if the_num < smallest_so_far :
        smallest_so_far = the_num
    print(smallest_so_far, the_num)

print('After', smallest_so_far)
```

We switched the variable name to `smallest_so_far` and switched the `>` to `<`



# Finding the Smallest Value

```
smallest_so_far = -1
print('Before', smallest_so_far)
for the_num in [9, 41, 12, 3, 74, 15] :
    if the_num < smallest_so_far :
        smallest_so_far = the_num
    print(smallest_so_far, the_num)

print('After', smallest_so_far)
```

\$ python smallbad.py

Before -1

-1 9

-1 41

-1 12

-1 3

-1 74

-1 15

After -1

We switched the variable name to `smallest_so_far` and switched the `>` to `<`

# Finding the Smallest Value

```
smallest = None
print('Before')
for value in [9, 41, 12, 3, 74, 15] :
    if smallest is None :
        smallest = value
    elif value < smallest :
        smallest = value
    print(smallest, value)
print('After', smallest)
```

\$ python smallest.py

Before

9 9

9 41

9 12

3 3

3 74

3 15

After 3

We still have a variable that is the **smallest** so far. The first time through the loop **smallest** is **None**, so we take the first **value** to be the **smallest**.

# The `is` and `is not` Operators

```
smallest = None
print('Before')
for value in [3, 41, 12, 9, 74, 15] :
    if smallest is None :
        smallest = value
    elif value < smallest :
        smallest = value
    print(smallest, value)

print('After', smallest)
```

- Python has an `is` operator that can be used in logical expressions
- Implies “`is the same as`”
- Similar to, but stronger than `==`
- `is not` also is a logical operator

# Summary

- While loops (indefinite)
- Infinite loops
- Using break
- Using continue
- None constants and variables
- For loops (definite)
- Iteration variables
- Loop idioms
- Largest or smallest



# Acknowledgements / Contributions



These slides are Copyright 2010- Charles R. Severance ([www.dr-chuck.com](http://www.dr-chuck.com)) of the University of Michigan School of Information and [open.umich.edu](http://open.umich.edu) and made available under a Creative Commons Attribution 4.0 License. Please maintain this last slide in all copies of the document to comply with the attribution requirements of the license. If you make a change, feel free to add your name and organization to the list of contributors on this page as you republish the materials.

Initial Development: Charles Severance, University of Michigan School of Information

... Insert new Contributors and Translators here

...