

Classes and objects - an introduction

Programação (L.EIC009)

Eduardo R. B. Marques, DCC/FCUP

Outline

- Using classes and objects - fundamentals
 - The lifecycle of an object
 - Constructors, destructor, member functions
 - Illustration using `std::string`
- Examples
 - Use of `std::string` in more detail
 - Use of `std::vector`
 - Streams for I/O and text parsing

Using classes and objects - fundamentals

Classes and objects

A class `SomeClass` is a data type declared with the keyword `class`:

```
class SomeClass { ... };
```

We will see later how classes are *defined*, but first we will understand how they are *used*.

An **object** is an instance of a class. The lifecycle of an object goes through the following stages:

- When an object variable is declared, it is initialised through a special function, a **constructor**;
- We can then use the class functionality for the object, typically through the invocation of **member functions**.
- A special function, called the **class destructor** is automatically invoked when an object goes out of scope.

Example - `std::string`

Class `std::string`, defined by header `<string>`, can be used to represent strings. Internally, a `string` object is implemented using a `char` array that grows dynamically in size when necessary.

```
// A few of the constructors
string (const string& str);
string (const char* s);
string (const char* s, size_t n);
. . .
// Destructor
~string();
// Some of the member functions
std::string& append(const std::string);
const char& at (size_t pos) const;
size_t length() const;
void push_back (char c);
. . .
```

Constructors

A constructor of `SomeClass` is a function with the same name `SomeClass` that can have several parameters.

```
SomeClass(); // default constructor  
SomeClass(const SomeClass& other); // copy constructor  
SomeClass(int a, int b); // another constructor
```

There can be several constructors. In particular, a constructor without parameters is called the **default constructor**, and a constructor that takes parameter a single `SomeClass` value or (more usually a `const`) reference parameter is called the **copy constructor**.

Use of constructors

For:

```
SomeClass();  
SomeClass(const SomeClass& other);  
SomeClass(int a, int b);
```

a variable for an object of type `SomeClass` is declared with the following generic syntax

```
SomeClass var1 (arg_1, . . . , arg_n);
```

The arguments are matched with a corresponding constructor, e.g.,

```
SomeClass v1; // invokes default constructor  
SomeClass v2(v1); // copy constructor  
SomeClass v3 = v1; // copy constructor (variation)  
SomeClass v4 { v1 }; // copy constructor (variation)  
SomeClass v5(1, 2); // another constructor
```

Example - constructors in `std::string`

`std::string` defines several constructors, for instance:

```
// Default constructor (empty string)
string();
// Copy constructor.
string (const string& str);
// Constructor from C string
string (const char* s);
// Constructor from C string up to n bytes
string (const char* s, size_t n);
. . .
```


Example - constructors in `std::string`

A few `std::string` variables:

```
#include <string>
using namespace std;
. . .
string a; // empty string (default constructor)
string b("ABC"); // from C string
string c = "DEF"; // from C string (syntactic alternative)
string d("IJKL", 3); // from C string, up to 3 chars
string e(d); // use of copy constructor
string f = d; // use of copy constructor also
```

Note: `SomeClass a = v;` corresponds to the invocation of a single-argument constructor, i.e., `SomeClass obj(v);`.

Member functions

We can invoke **member functions** over an object using the `.` operator:

```
SomeClass obj(. . .);  
. . .  
obj.member_function_name(. . . member function arguments . . .)
```

A member function can:

- return or derive information related to the internal object state **without changing it** - typically these functions are declared as `const`;
- **change** the internal state of the object - not declared as `const`

Example - `std::string` member functions

A few member functions in `std::string`:

```
int length() const;
const char& at(size_t pos) const;
char& at(size_t pos);
const char* c_str() const;
std::string& append(const char*);
void push_back(char c);
```

Example use:

```
string s = "ABC";           // s <-- "ABC"
int n = s.length();         // n <-- 3
char c = s.at(2);           // c <-- 'C'
s.append("DEF");            // s <-- "ABCDEF"
s.push_back('G');           // s <-- "ABCDEFG"
s.at(2) = '_';              // s <-- "AB_DEFG"
const char* str = s.c_str(); // str <-- "AB_DEFG"
```

Member functions and operator overloading

Some member functions can correspond to the **overloading of operators**. An example is the attribution operator (=), usually overloaded to copy state between objects (similarly to a copy constructor).

Declaration:

```
SomeClass& operator=(const SomeClass& other)
```

Use:

```
SomeClass a(. . .)
SomeClass b(. . .)
. . .
a = b; // invokes operator= member function
```

std::string - operator overloading

std::string for instance defines operators =, += e [] as member functions:

```
string& operator=(const std::string& str);
string& operator=(const char* s);
. . .
string& operator+= (const string& str);
string& operator+= (char c);
. . .
const char& operator[](size_t pos) const;
char& operator[](size_t pos);
```

Example use:

```
string a("ABC"), b("DEF");
a += b;      // a <-- "ABCDEF"
a += b[0];   // a <-- "ABCDEFD"
b = a;       // b <-- "ABCDEFD"
a = "XYZ";   // a <-- "XYZ"
```

Destructors

The **destructor** for class `SomeClass` is a function named `~SomeClass`.

```
~SomeClass(); // Destructor
```

When an object goes out of the scope, the destructor is **automatically invoked**. You should never call it explicitly.

The role of the destructor is to **free any internal resources used by the object**, in particular dynamically allocated memory segments if they are used by the object.

Destructor invocation

`~SomeClass()` is automatically invoked:

- at the end of an instruction body where an object of type `SomeClass` is declared;
- at the end of program execution if an object of type `SomeClass` is declared globally;
- when the `delete` operator over a pointer of type `SomeClass*` that refers to an object defined using `new`.

Destructors - invocation

```
SomeClass global_obj;
void f() {
    SomeClass local_obj1;
    if ( . . . ) {
        SomeClass local_obj2;
        ...
        // ~SomeClass() implicitly called for local_obj2
    }
    // ~SomeClass() implicitly called for local_obj1
}
```

The constructor and destructor of `global_obj` are invoked during program initialisation and shutdown respectively.

Use of new e delete

`new` and `delete` can be used to allocate and free objects in dynamic memory. The operators work in conjunction with constructors and destructors.

`new` invokes a constructor:

```
SomeClass* p = new SomeClass(. . . arguments . . .);
```

`delete` invokes `~SomeClass()` before freeing memory:

```
delete p; // invokes ~SomeClass() automatically
```

Use of new e delete (cont.)

The `->` operator can be used (similarly to `struct` types) to invoke member functions using a pointer. `&` and `*` work as before for pointer types.

```
string* pa = new string();  
string* pb = new string("abcdef");  
string c("ghi"); // stack-allocated  
string* pc = &c;  
pa->append(*pb);  
(*pa).append(*pc);  
cout << *pa << ' ' << pa->length() << '\n';  
delete pa;  
delete pb;
```

`std::string` in more detail

`std::basic_string` and `std::string`

`string` is defined as an instantiation of a general template class for strings called `basic_string`

```
typedef std::basic_string<char> string;
```

`basic_string` is used to defined strings that have multi-byte characters, e.g., `wstring` (among others):

```
typedef basic_string<wchar_t> wstring;
```

In any case, all `basic_string<CharT>` objects work similarly: an internal `CharT` array holds the string characters, that grows dynamically in size when needed.

String member functions - brief summary

(check the [documentation](#) for reference)

Construction and assignment: several constructors are defined, as well as string assignment through `assign` and `operator=`.

Length: `length` or `size`

Element access: `operator[]`, `at`, `front`, `back`, ...

String/character operations: `operator+=`, `operator+`, `append`, `push_back`, `insert`, `erase`, `find`, `clear`, `substr`

String comparison: relational operators (`<`, `==`, `!=`, ...), `compare`

Buffer capacity: `capacity`, `reserve`, `shrink_to_fit`, ...

Range-based for loops

Strings can be used with range-based **for** loops, e.g.

```
string s = "abcde";  
// Convert string to upper case  
for (char& c : s) {  
    c = toupper(c);  
}  
// Iterate characters and print them  
for (char c : s) {  
    cout << c;  
}
```

ABCDE

(note: **toupper** used above to convert from lowercase to uppercase characters)

To discuss later in the semester: range-based **for** loops implicitly use **iterators** obtained through member functions like **begin()** and **end()**.

Example 2

Test if given string is a **heterogram**, i.e., contains no repeated letters.

```
bool heterogram(const string& s, string& r) {
    int count[26] = { 0 };
    for (size_t i = 0; i < s.length(); i++) {
        if (s[i] != ' ') {
            if (s[i] >= 'a' && s[i] <= 'z') count[s[i] - 'a']++;
            else count[s[i] - 'A']++;
        }
    }
    // determines repeated letters
    r.clear();
    for (char c = 'a'; c <= 'z'; c++)
        if (count[c - 'a'] > 1) r.push_back(c);
    return r.empty();
}
```

`std::vector`

Basic aspects

`vector` is a template class that is part of the C++ library known as the **Standard Template Library (STL)** or “**containers library**”. The STL defines template classes for common data structures (e.g., lists, sets, and maps) and algorithms (e.g., sorting or searching).

`vector` stores a sequence of elements of a parameterised type using a dynamic array. As with strings, the internal array associated to a vector grows when needed. In fact, many member functions in `vector` have similar names and functionality to those found in `string`:

```
vector<int> iv { 1, 2, 3 };  
iv.push_back(4);  
vector<string> sv { "A", "B", "C" };  
for (size_t i = 0; i < sv.size(); i++) cout << sv[i];
```

Example 2

```
vector<int> v;
while (true) {
    int x; cin >> x;
    if (x == 0) break;
    v.push_back(x);
}
sort(v.begin(), v.end());
for (int x : v) cout << x << ' ';

5 -8 1 0
-8 1 5
```

Program fragment: reads a sequence of integers terminated by 0 onto a **vector**; sorts the vector using **sort**, and; prints the vector contents at the end using a range-based for loop.

Stream-based I/O

Overview of the stream classes

Base stream classes, defined in header `iostream`:

- `std::istream`: base input stream (the class of globally declared object `std::cin`), specialisation of template `basic_istream` for `char` character input;
- `std::ostream` base output stream (the class of `std::cout`), specialisation of the template `basic_ostream` for `char` character output;

File stream classes in header `fstream`:

- `std::ifstream`: file input stream;
- `std::ofstream`: file output stream;


String streams (use strings as streams!), defined in header `sstream`:

- `std::istringstream`: string input stream;
- `std::ostringstream`: string output stream;

There are also stream classes that allow both input and output: `iostream`, `fstream`, and `stringstream`.

Overview of the stream classes (cont.)

The stream classes form a **class hierarchy**, a concept la later in the semester. The basic intuition is that a **class** can reuse and extend the functionality of a **parent class**.



(image from cppreference.com - “Input/Output library”)

Example - ifstream

Read double values from a text file name `numbers.txt` and output their sum

```
ifstream in("numbers.txt");
double sum = 0;
while (true) {
    double x;
    in >> x;
    if (in.eof()) break;
    sum += x;
    cout << "Read " << x << '\n';
}
cout << "Sum: " << sum << '\n';
```

The input file can contain numbers separated by blank characters (e.g., spaces, tabs or line breaks) which are handled by the `>>` operator. `eof()` returns `true` when the end of the file is reached, and `>>` will fail in that case without assigning `x`.

Example - ifstream - variation

More succinct code:

```
ifstream in("numbers.txt");
double sum = 0, x;
while (in >> x) {
    sum += x;
    cout << "Read " << x << '\n';
}
cout << "Sum: " << sum << '\n';
```

Explanation: `in >> x` returns `in` (as usual) for chained calls, which can then be evaluated as a boolean expression through [operator bool](#). The result is `true` if the stream has no errors and is ready for I/O operations.

Reading line by line - example

Reads numbers line by line, and output the sum of numbers found in each line. `getline` reads an entire line onto a string, and an `istringstream` object is used to obtain the values per each line.

```
ifstream in("numbers.txt");
string line;
int line_count = 1;
while (getline(in, line)) {
    double sum = 0, x;
    istringstream iss(line);
    while(iss >> x) sum += x;
    cout << "Line " << line_count
         << " - Sum: " << sum << '\n';
    line_count++;
}
```

Line 1 - Sum: 10.2

Line 2 - Sum: 14.5

Line 3 - Sum: -2.5

Error recovery when reading data

Upon a read error, the input stream will be stuck at the file position where the error occurred. We can recover from the error by clearing the error flag using `clear()` and skipping a certain number of characters using `ignore()`.

```
int read_int() {  
    int x;  
    while (true) {  
        if (cin >> x)  
            break;  
        cin.clear(); // clear error flag  
        cin.ignore(1); // skip 1 character and try again  
    }  
    return x;  
}
```

Error recovery - variation

`ignore()` can also be used to skip all characters until a given character is found, e.g., a line break.

```
int read_int_v2() {
    int x;
    while (true) {
        if (cin >> x)
            break;
        cin.clear(); // clear error flag
        cin.ignore(std::numeric_limits<std::streamsize>::max(),
                   '\n'); // skip rest of the line
    }
    return x;
}
```

Output streams

Output streams like `fstream` and `sstream` can be used just like `ostream` objects. For instance, the “sum-by-line” program variant below outputs the sum print-outs to an output file called `sums.txt`:

```
ifstream in("numbers.txt");
ofstream out("sums.txt"); // <-- File output stream
string line;
int line_count = 1;
while (getline(in, line)) {
    double sum = 0, x;
    istringstream iss(line);
    while(iss >> x) sum += x;
    out << "Line " << line_count
        << " - Sum: " << sum << '\n';
    line_count++;
}
```