

Escuela Profesional de Ciencia de la Computación

Algoritmos y Estructuras de Datos

2020-B

# **AVL Tree**

M.Sc. Franci Suni Lopez

Universidad Nacional de San Agustín de Arequipa


M.S. Franci Suni Lopez - UNSA


fsunilo@unsa.edu.pe

1

#### Motivation

When building a binary search tree, what type of trees would we like? Example: 3, 5, 8, 20, 18, 13, 22






M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

#### Motivation

- Complete binary tree is hard to build when we allow **dynamic** insert and remove.
  - We want a tree that has the following properties
    - Tree height = O(log(N))
    - allows dynamic insert and remove with O(log(N)) time complexity.
  - The AVL tree is one of this kind of trees.



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

3

#### **AVL Tree**

- Named after inventors Adelson-Velsky and Landis.
- Two Soviet inventors, **Georgy Adelson-Velsky** and **Evgenii Landis**, who published it in their **1962** paper "An algorithm for the organization of information".
- A self-balancing binary search tree.

M.Sc. Franci Suni Lopez - UNSA


fsunilo@unsa.edu.pe

#### Balance

Balance == height(left subtree) - height(right subtree)

- zero everywhere ⇒ perfectly balanced
- small everywhere ⇒ balanced enough

Balance between -1 and 1 everywhere.



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

5

#### **AVL Tree**

Binary search tree properties


- binary tree property
- search tree property

Balance property

• balance of every node is:

$$-1 \le b \le 1$$


- result:
  - depth is  $\Theta$  (log n)



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

# An AVL Tree




M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

7

## Not AVL Trees



Note: height(empty tree) == -1


M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

# Good Insert Case: Balance Preserved

Good case: insert middle, then small, then tall

Insert(middle)
Insert(small)
Insert(tall)



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

9

# Bad Insert Case #1: Left-Left or Right-Right Imbalance

Insert(small)
Insert(middle)
Insert(tall)

BC#1 Imbalance caused by either:


Insert into left child's left subtree

• Insert into right child's right subtree

M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

## Single Rotation



Basic operation used in AVL trees:


A right child could legally have its parent as its left child.

M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

11


### General Bad Case #1



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

### Single Rotation Fixes Case #1 Imbalance



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

13

# Bad Insert Case #2: Left-Right or Right-Left Imbalance


Insert(small)
Insert(tall)

Insert(middle)

BC#2 Imbalance caused by either:

- Insert into left child's right subtree
- Insert into right child's left subtree


Will a single rotation fix this?



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

### Double Rotation




M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

15


### General Bad Case #2



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

### Double Rotation Fixes Case #2 Imbalance



Initially: insert into either X or Y unbalances tree (root balance goes to 2 or -2) "Zig zag" to pull up c – restores root height to h+1, left subtree height to h

M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

17

#### AVL Insert Algorithm


- Find spot for value
- Hang new node
- Search back up looking for imbalance
- If there is an imbalance:

case #1: Perform single rotation

case #2: Perform double rotation

• Done!


(There can only be one imbalance!)



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

## Easy Insert




M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

19

## Hard Insert (Bad Case #1)


Insert(33)



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

## Single Rotation




M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

21

## Hard Insert (Bad Case #2)






M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

### Single Rotation (oops!)




M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

23


### Double Rotation (Step #1)



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

#### Double Rotation (Step #2)



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe


25

# AVL Insert Algorithm Revisited

- Recursive
- Search downward for spot
- 2. Insert node
- Unwind stack, correcting heights
  - a. If imbalance #1, single rotate
  - b. If imbalance #2,
     double rotate

- Iterative
- Search downward for spot, stacking parent nodes
- 2. Insert node
- Unwind stack, correcting heights
  - a. If imbalance #1, single rotate and
  - b. If imbalance #2,
     double rotate and
     exit

### Deletion: Really Easy Case




M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

30

### Deletion: Pretty Easy Case




M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

## Deletion: Pretty Easy Case (cont.)

Delete(15)




M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

32

## Deletion (Hard Case #1)


Delete(12)



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

## Single Rotation on Deletion



Deletion can differ from insertion – *How?* 


M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

34

### Deletion (Hard Case)






M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

### Double Rotation on Deletion




M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

36


#### **Deletion with Propagation**



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

### Propagated Single Rotation




M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

38

### Propagated Double Rotation



M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

## AVL Deletion Algorithm

- Recursive
- Search downward for node
- 2. Delete node
- 3. Unwind, correcting heights as we go
  - a. If imbalance #1, single rotate
  - b. If imbalance #2
     (or don't care),
     double rotate

- Iterative
- Search downward for node, stacking parent nodes
- 2. Delete node
- Unwind stack, correcting heights
  - a. If imbalance #1,
     single rotate
  - b. If imbalance #2
     (or don't care)
     double rotate

40

#### **Building an AVL Tree**

Input: sequence of n keys (unordered)

19 3 4 18 7

Insert each into initially empty AVL tree

$$\sum_{i=1}^{n} \log i \le \sum_{i=1}^{n} \log n = O(n \log n)$$

But, suppose input is already sorted ...

3 4 7 18 19

M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe


## **AVL BuildTree**



#### Divide & Conquer

- Divide the problem into parts
- · Solve each part recursively
- Merge the parts into a general solution


How long does divide & conquer take?



42

# BuildTree Example





#### Thinking About AVL

#### Observations

- + Worst case height of an AVL tree is about 1.44 log n
- + Insert, Find, Delete in worst case O(log n)
- + Only one (single or double) rotation needed on insertion
- + Compatible with lazy deletion
- O(log n) rotations needed on deletion
- Height fields must be maintained (or 2-bit balance)

M.Sc. Franci Suni Lopez - UNSA

fsunilo@unsa.edu.pe

44

