

Stream Ciphers


Elements of Applied Data Security M

Alex Marchioni– alex.marchioni@unibo.it

Livia Manovi– livia.manovi@unibo.it

Stream Cipher

A stream cipher is a **symmetric key** cipher where the plaintext is encrypted (and ciphertext is decrypted) one digit at a time. A digit usually is either a bit or a byte.



Encryption (decryption) is achieved by xoring the plaintext (ciphertext) with a stream of pseudorandom digits obtained as an expansion of the key.

Tasks

1. LFSR
2. Berlekamp-Massey Algorithm
3. LFSR-based generator

Python Module

- A **module** is a `.py` file in which you can collect several definitions that you may want to use repeatedly.
- You can then **import** such definitions either into your notebook or even in other modules.


For the current assignment:

- You must collect all the functions and objects employed to implement the requested structures in a python module `streamcipher.py` following the naming conventions indicated in the following slides.

Task 1: LFSR


LFSR

In an LFSR, the output from a standard shift register is fed back into its input causing an endless cycle. The feedback bit is the result of a linear combination of the shift register content and the polynomial coefficients.




LFSR

In an LFSR, the output from a standard shift register is fed back into its input causing an endless cycle. The feedback bit is the result of a linear combination of the shift register content and the polynomial coefficients.



LFSR


In an LFSR, the output from a standard shift register is fed back into its input causing an endless cycle. The feedback bit is the result of a linear combination of the shift register content and the polynomial coefficients.



LFSR

From the block scheme:


$$\left\{ \begin{array}{l} s_j[t] = s_{j+1}[t-1], \quad j = 0, 1, \dots, m-2 \\ s_{m-1}[t] = \bigoplus_{j=0}^{m-1} p_{m-j} \otimes s_j[t-1] \\ b[t] = s_0[t] \end{array} \right.$$



LFSR


From the block scheme:

$$\left\{ \begin{array}{l} s_j[t] = s_{j+1}[t-1], \quad j = 0, 1, \dots, m-2 \\ s_{m-1}[t] = \bigoplus_{j=0}^{m-1} p_{m-j} \otimes s_j[t-1] \\ b[t] = s_0[t] \end{array} \right.$$




LFSR

From the block scheme:



LFSR


From the block scheme:



LFSR example

- length = 3
- polynomial = $x^3 + x + 1$ ($p = 0b1011$)
- initial state $0b111$


 s *b* *fb*



LFSR example

- length = 3
- polynomial = $x^3 + x + 1$ ($p = 0b1011$)
- initial state $0b111$


s	b	fb
111 (7)	1	0



LFSR example

- length = 3
- polynomial = $x^3 + x + 1$ ($p = 0b1011$)
- initial state $0b111$


s		b	fb
111	(7)	1	0
011	(3)	1	1



LFSR example

- length = 3
- polynomial = $x^3 + x + 1$ ($p = 0b1011$)
- initial state $0b111$


s		b	fb
111	(7)	1	0
011	(3)	1	1
101	(5)	1	0



LFSR example

- length = 3
- polynomial = $x^3 + x + 1$ ($p = 0b1011$)
- initial state $0b111$


s		b	fb
111	(7)	1	0
011	(3)	1	1
101	(5)	1	0
010	(2)	0	0



LFSR example


- length = 3
- polynomial = $x^3 + x + 1$ ($p = 0b1011$)
- initial state $0b111$

s	b	fb
111 (7)	1	0
011 (3)	1	1
101 (5)	1	0
010 (2)	0	0
001 (1)	1	1



LFSR example


- length = 3
- polynomial = $x^3 + x + 1$ ($p = 0b1011$)
- initial state $0b111$



<i>s</i>	<i>b</i>	<i>fb</i>
111 (7)	1	0
011 (3)	1	1
101 (5)	1	0
010 (2)	0	0
001 (1)	1	1
100 (4)	0	1

LFSR example


- length = 3
- polynomial = $x^3 + x + 1$ ($p = 0b1011$)
- initial state $0b111$



s	b	fb
111 (7)	1	0
011 (3)	1	1
101 (5)	1	0
010 (2)	0	0
001 (1)	1	1
100 (4)	0	1
110 (6)	0	1

LFSR example

- length = 3
- polynomial = $x^3 + x + 1$ ($p = 0b1011$)
- initial state $0b111$



s	b	fb
111 (7)	1	0
011 (3)	1	1
101 (5)	1	0
010 (2)	0	0
001 (1)	1	1
100 (4)	0	1
110 (6)	0	1
111 (7)	1	0

LFSR Iterable

Inputs:

- **Feedback Polynomial:**

list of integers representing the degrees of the non-zero coefficients.

Example: $[12, 6, 4, 1, 0]$ represents $P(x) = x^{12} + x^6 + x^4 + x^1 + 1$

- **LFSR state** (optional, default all bits to 1)

bytes object representing the LFSR initial state. Note that bytes are converted into bits as big-endian (most significant bit first).

Example: `b'e\xa0'` (`[0x65, 0xa0]`) represents the state 0110 0101 1010

LFSR Iterable

Attributes:

- **poly**: list of the polynomial coefficients (list of int)
- **length**: polynomial degree and length of the shift register (int)
- **state**: LFSR state (bytes)
- **output**: output bit (bool)
- **feedback**: last feedback bit (bool)

LFSR Iterable

Methods:

- **__init__**: class constructor;
- **__iter__**: necessary to be an iterable;
- **__next__**: update LFSR state and returns output bit;
- **cycle**: returns a list of bool representing the full LFSR cycle ;
- **run_steps**: execute N LFSR steps and returns the corresponding output list of bool (N is a input parameter, default N=1);
- **__str__**: return a string describing the LFSR class instance.

LFSR Iterable

```
class LFSR:
    ''' class docstring '''

    def __init__(self, poly, state=None):
        ''' constructor docstring '''
        ...
        self.poly = ...
        self.length = ...
        self.state = ...
        self.output = ...
        self.feedback = ...

    def __iter__(self):
        return self

    def __next__(self):
        ''' next docstring '''
        ...
        return self.output

    def run_steps(self, N=1):
        ''' run_steps docstring '''
        ...
        return list_of_bool

    def cycle(self, state=None):
        ''' cycle docstring '''
        ...
        return list_of_bool
```

Hints

There are several ways to implement an LFSR in Python.

The first choice to make is how to store the internal state and the polynomial. I suggest two types:

- **list of bool**: it is the most straightforward choice as it directly maps the LFSR block scheme, but bit-wise logical operation may not be as easy.
- **integer**: bit-wise logical operation, as well as bit-shift, are easy to perform on integers, while XOR of multiple bits or reversing the bit order are less straightforward.

Useful functions

- **XOR:** In Python bit-wise xor between two integers is implemented with the `^` mark. It is also implemented as function (`xor`) in the built-in module [operator](#).
Example: `xor(5,4) -> 5^4 -> 0b101^0b100 -> 0b001 -> 1`
- **reduce:** available from the built-in module [functools](#), apply a function of two arguments cumulatively to the items of an iterable so as to reduce the iterable to a single value.
Example: `reduce(xor, [True, False, True, False]) -> False`
- **compress:** available from the built-in module [itertools](#), make an iterator that filters elements from data returning only those that have a corresponding element in selectors that evaluates to True.
Example: `compress([3, 7, 5], [True, False, True]) -> [3, 5]`

Task 2: Berlekamp-Massey Algorithm

Berlekamp-Massey Algorithm

Find the shortest LFSR for a given binary sequence.

- **Inputs:** sequence of bit b of length N
- **Outputs:** feedback polynomial $P(x)$.

```
def berlekamp_massey(b):  
    ''' function docstring '''  
    # algorithm implementation  
    return poly
```

Input $b = [b_0, b_1, \dots, b_N]$

$P(x) \leftarrow 1, m \leftarrow 0$

$Q(x) \leftarrow 1, r \leftarrow 1$

For $\tau = 0, 1, \dots, N - 1$

$d \leftarrow \bigoplus_{j=0}^m p_j \otimes b[\tau - j]$

If $d = 1$ **then**

If $2m \leq \tau$ **then**

$R(x) \leftarrow P(x)$

$P(x) \leftarrow P(x) + Q(x)x^r$

$Q(x) \leftarrow R(x)$

$m \leftarrow \tau + 1 - m$

$r \leftarrow 0$

else

$P(x) \leftarrow P(x) + Q(x)x^r$

endif

endif

$r \leftarrow r + 1$

endfor

Output $P(x)$

Berlekamp-Massey Algorithm

τ	b_τ	d		$P(x)$	m	$Q(x)$	r
-	-	-		1	0	1	1
0	1	1	A	$1 + x$	1	1	1
1	0	1	B	1	1	1	2
2	1	1	A	$1 + x^2$	2	1	1
3	0	0		$1 + x^2$	2	1	2
4	0	1	A	1	3	$1 + x^2$	1
5	1	1	B	$1 + x + x^3$	3	$1 + x^2$	2
6	1	0		$1 + x + x^3$	3	$1 + x^2$	3
7	1	0		$1 + x + x^3$	3	$1 + x^2$	4

Input $b = [b_0, b_1, \dots, b_N]$

$P(x) \leftarrow 1, m \leftarrow 0$

$Q(x) \leftarrow 1, r \leftarrow 1$

For $\tau = 0, 1, \dots, N - 1$

$$d \leftarrow \bigoplus_{j=0}^m p_j \otimes b[\tau - j]$$

If $d = 1$ **then**

If $2m \leq \tau$ **then**

A

$R(x) \leftarrow P(x)$

$P(x) \leftarrow P(x) + Q(x)x^r$

$Q(x) \leftarrow R(x)$

$m \leftarrow \tau + 1 - m$

$r \leftarrow 0$

else

B

$P(x) \leftarrow P(x) + Q(x)x^r$

endif

endif

$r \leftarrow r + 1$

endfor

Output $P(x)$

Berlekamp-Massey Algorithm Task

- Implement the Berlekamp-Massey Algorithm
- Test the algorithm implementation
- Apply the Berlekamp-Massey Algorithm to the bit sequence stored in the file `binary_sequence.bin` to compute:
 - The polynomial of the shortest LFSR that can produce that sequence
 - The linear complexity of the bit sequence

Task 3: LFSR-based generator


Generator Type Assignment

- Select *one of the two* possible generators according to the procedure described below
- Procedure:
 1. Transform the **name of your group** into a bytes object (big-endian)
 2. Transform the bytes object into a sequence of booleans (big-endian)
 3. Compute the **parity bit**

Parity bit	Assigned generator
0	Shrinking Generator
1	Self-Shrinking Generator

Shrinking Generator

The shrinking generator comprises LFSR_A that produces bits and LFSR_S that selects the produced bits. Since bit selection is irregular, a FIFO is necessary for a regular output rate.



Shrinking Generator Class

- **Inputs**

- Polynomials `polyA` and `polyS` (optional, default are
 - $P_A(x) = x^5 + x^2 + 1$
 - $P_S(x) = x^3 + x + 1$
- `stateA` and `stateS` (optional, default all bits of the LFSR states at 1)

- **Attributes**


- `lfsrA`: the LFSR class instance for LFSR_A .
- `lfsrS`: the LFSR class instance for LFSR_S .
- `output`: boolean storing the last produced output bit

Shrinking Generator Task

- Implement the Shrinking Generator Class
- Testing the functionality of the implemented class
 - Test that all methods and attributes work as expected
- Decrypt the ciphertext `ciphertext_shrinking.bin` given:
 - $P_A(x) = x^{16} + x^{15} + x^{12} + x^{10} + 1$, stateA: `b'\xc5\xd7'`
 - $P_S(x) = x^{24} + x^{11} + x^5 + x^2 + 1$, stateS: `b'\x14\x84\xf8'`

Self-Shrinking Generator

The Self-Shrinking Generator is composed by a single LFSR that produce bits and selects them depending on the value of the internal state. A decimator and a FIFO are necessary for a regular output rate.



Self-Shrinking Generator Class

- **Inputs**

- Polynomial `poly` (optional, default is $P(x) = x^5 + x^2 + 1$)
- Index of the selection bit `selection_bit` (optional, default 3)
- State `state` (optional, default all bits of the LFSR state at 1)

- **Attributes**

- `lfsr`: the LFSR class instance for LFSR.
- `sbit`: integer storing the index of the selection bit.
- `output`: boolean storing the last produced output bit

Self-Shrinking Generator Task

- Implement the Self-Shrinking Generator Class
- Testing the functionality of the implemented class
 - Test that all methods and attributes work as expected
- Decrypt the ciphertext `ciphertext_selfshrinking.bin` given:
 - $P(x) = x^{32} + x^{16} + x^7 + x^2 + 1$
 - Selection bit: 4
 - state: `b'mJ\x9by'`

Deadline

Tuesday, April 23rd at 12PM (noon)