

ME315A_Lista3

Luiz Fernando Celin

Lista 3

SETUP

```
library(DBI)
library(RSQLite)

# Conecta/Cria o arquivo
con <- dbConnect(RSQLite::SQLite(), "me315.sqlite")
```

QUESTÃO 1

```
SELECT DISTINCT STATE, FEE FROM PRESERVE
```

Table 1: 4 records

STATE	FEE
AZ	3
MT	0
AZ	0
MA	0

QUESTÃO 2

```
SELECT DISTINCT DNO FROM EMPLOYEE
```

Table 2: 3 records

DNO
20
10
40

QUESTÃO 3

PRIMEIRA QUERY

```
SELECT DNO, SALARY FROM EMPLOYEE
```

Table 3: 6 records

DNO	SALARY
20	2000
10	2000
20	3000
40	500
10	400
20	9000

Nesta primeira Query puxo os valores DNO e Salary independente se forem repetidos ou não.

SEGUNTA QUERY

```
SELECT DISTINCT DNO, SALARY FROM EMPLOYEE
```

Table 4: 6 records

DNO	SALARY
20	2000
10	2000

DNO	SALARY
20	3000
40	500
10	400
20	9000

Nesta segunda Query puxamos os valores distintos. Contudo, como não à valores repetidos o banco parece o mesmo.

TERCEIRA QUERY

```
SELECT DISTINCT DNO, SALARY FROM EMPLOYEE
ORDER BY DNO, SALARY
```

Table 5: 6 records

DNO	SALARY
10	400
10	2000
20	2000
20	3000
20	9000
40	500

Na terceira, puxamos DNO e Salary em ordem de DNO, somente valores distintos.

QUESTÃO 4

```
SELECT * FROM PRESERVE
WHERE STATE = "MT" AND ACRES < 1000
```

Table 6: 2 records

PNO	PNAME	STATE	ACRES	FEE
3	DANCING PRAIRIE	MT	680	0
40	SOUTH FORK MADISON	MT	121	0

QUESTÃO 5

```
SELECT * FROM PRESERVE  
WHERE ACRES <= 15000 AND ACRES >= 1200
```

Table 7: 2 records

PNO	PNAME	STATE	ACRES	FEE
2	PINE BUTTE SWAMP	MT	15000	0
6	PAPAGONIA-SONOITA CREEK	AZ	1200	3

QUESTÃO 6

```
SELECT * FROM PRESERVE  
WHERE FEE = 0 AND ACRES >= 10000 AND STATE = "MT"
```

Table 8: 1 records

PNO	PNAME	STATE	ACRES	FEE
2	PINE BUTTE SWAMP	MT	15000	0

QUESTÃO 7

```
SELECT * FROM PRESERVE  
WHERE STATE = "MT" OR STATE = "MA"
```

Table 9: Displaying records 1 - 10

PNO	PNAME	STATE	ACRES	FEE
3	DANCING PRAIRIE	MT	680	0
40	SOUTH FORK MADISON	MT	121	0
14	MCELWAIN-OLSEN	MA	66	0
13	TATKON	MA	40	0
9	DAVID H. SMITH	MA	830	0
11	MIACOMET MOORS	MA	4	0

PNO	PNAME	STATE	ACRES	FEE
12	MOUNT PLANTAIN	MA	730	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
10	HOFT FARM	MA	90	0

QUESTÃO 8

```
SELECT * FROM PRESERVE
WHERE STATE = "MT" OR ACRES < 1000
```

Table 10: Displaying records 1 - 10

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
3	DANCING PRAIRIE	MT	680	0
40	SOUTH FORK MADISON	MT	121	0
14	MCELWAIN-OLSEN	MA	66	0
13	TATKON	MA	40	0
9	DAVID H. SMITH	MA	830	0
11	MIACOMET MOORS	MA	4	0
12	MOUNT PLANTAIN	MA	730	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0

QUESTÃO 9

```
SELECT PNO, PNAME FROM PRESERVE
WHERE FEE != 0
```

Table 11: 3 records

PNO	PNAME
5	HASSAYAMPA RIVER
80	RAMSEY CANYON
6	PAPAGONIA-SONOITA CREEK

QUESTÃO 10

```
SELECT PNO, PNAME FROM PRESERVE  
WHERE FEE != 3 AND FEE != 10
```

Table 12: Displaying records 1 - 10

PNO	PNAME
3	DANCING PRAIRIE
7	MULESHOE RANCH
40	SOUTH FORK MADISON
14	MCELWAIN-OLSEN
13	TATKON
9	DAVID H. SMITH
11	MIACOMET MOORS
12	MOUNT PLANTAIN
1	COMERTOWN PRAIRIE
2	PINE BUTTE SWAMP

QUESTÃO 11

```
SELECT * FROM PRESERVE  
WHERE (STATE = "AZ" AND FEE = 0) OR ACRES < 100
```

Table 13: 5 records

PNO	PNAME	STATE	ACRES	FEE
7	MULESHOE RANCH	AZ	49120	0
14	MCELWAIN-OLSEN	MA	66	0
13	TATKON	MA	40	0
11	MIACOMET MOORS	MA	4	0
10	HOFT FARM	MA	90	0

QUESTÃO 12

```
SELECT * FROM PRESERVE
WHERE (ACRES < 1000 AND FEE = 0) OR STATE = "AZ"
```

Table 14: Displaying records 1 - 10

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
3	DANCING PRAIRIE	MT	680	0
7	MULESHOE RANCH	AZ	49120	0
40	SOUTH FORK MADISON	MT	121	0
14	MCELWAIN-OLSEN	MA	66	0
13	TATKON	MA	40	0
9	DAVID H. SMITH	MA	830	0
11	MIACOMET MOORS	MA	4	0
12	MOUNT PLANTAIN	MA	730	0
80	RAMSEY CANYON	AZ	380	3

QUESTÃO 13

```
SELECT * FROM PRESERVE
WHERE (STATE = "MT" AND ACRES > 1000) OR FEE < 0
```

Table 15: 2 records

PNO	PNAME	STATE	ACRES	FEE
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0

QUESTÃO 14

```
SELECT * FROM PRESERVE
WHERE NOT (STATE = "MT" AND FEE = 0)
```

Table 16: Displaying records 1 - 10

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
7	MULESHOE RANCH	AZ	49120	0
14	MCELWAIN-OLSEN	MA	66	0
13	TATKON	MA	40	0
9	DAVID H. SMITH	MA	830	0
11	MIACOMET MOORS	MA	4	0
12	MOUNT PLANTAIN	MA	730	0
80	RAMSEY CANYON	AZ	380	3
10	HOFT FARM	MA	90	0
6	PAPAGONIA-SONOITA CREEK	AZ	1200	3

QUESTÃO 15

Situação 1

```
SELECT * FROM PRESERVE
WHERE STATE = 'MA' AND (ACRES > 1000 OR FEE = 0.0)
```

Table 17: 6 records

PNO	PNAME	STATE	ACRES	FEE
14	MCELWAIN-OLSEN	MA	66	0
13	TATKON	MA	40	0
9	DAVID H. SMITH	MA	830	0
11	MIACOMET MOORS	MA	4	0
12	MOUNT PLANTAIN	MA	730	0
10	HOFT FARM	MA	90	0

Situação 2

```
SELECT * FROM PRESERVE
WHERE (STATE = 'MA' AND ACRES > 1000) OR (STATE = 'MA' AND FEE = 0.0)
```

Table 18: 6 records

PNO	PNAME	STATE	ACRES	FEE
14	MCELWAIN-OLSEN	MA	66	0
13	TATKON	MA	40	0
9	DAVID H. SMITH	MA	830	0
11	MIACOMET MOORS	MA	4	0
12	MOUNT PLANTAIN	MA	730	0
10	HOFT FARM	MA	90	0

Resposta

Sim, ambos são iguais. Pensando em teoria dos conjuntos a interseção da união de 2 conjuntos é a União da interseção.

$$A \cap (B \cup C) = (A \cap B) \cup (A \cap C)$$

QUESTÃO 16 ##### Situação 1

```
SELECT * FROM PRESERVE
WHERE STATE = 'MA' OR (ACRES > 1000 AND FEE = 0.0)
```

Table 19: 9 records

PNO	PNAME	STATE	ACRES	FEE
7	MULESHOE RANCH	AZ	49120	0
14	MCELWAIN-OLSEN	MA	66	0
13	TATKON	MA	40	0
9	DAVID H. SMITH	MA	830	0
11	MIACOMET MOORS	MA	4	0
12	MOUNT PLANTAIN	MA	730	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
10	HOFT FARM	MA	90	0

Situação 2

```
SELECT * FROM PRESERVE
WHERE (STATE = 'MA' OR ACRES > 1000) AND (STATE = 'MA' OR FEE = 0.0)
```

Table 20: 9 records

PNO	PNAME	STATE	ACRES	FEE
7	MULESHOE RANCH	AZ	49120	0
14	MCELWAIN-OLSEN	MA	66	0
13	TATKON	MA	40	0
9	DAVID H. SMITH	MA	830	0
11	MIACOMET MOORS	MA	4	0
12	MOUNT PLANTAIN	MA	730	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
10	HOFT FARM	MA	90	0

Resposta

Assim como na pergunta anterior, sim são logicamente equivalentes.

$$A \cup (B \cap C) = (A \cup B) \cap (A \cup C)$$

QUESTÃO 17**Situação 1**

```
SELECT * FROM PRESERVE
WHERE NOT (ACRES < 50 AND STATE = 'MA')
```

Table 21: Displaying records 1 - 10

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
3	DANCING PRAIRIE	MT	680	0
7	MULESHOE RANCH	AZ	49120	0
40	SOUTH FORK MADISON	MT	121	0
14	MCELWAIN-OLSEN	MA	66	0
9	DAVID H. SMITH	MA	830	0
12	MOUNT PLANTAIN	MA	730	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
80	RAMSEY CANYON	AZ	380	3

Situação 2

```
SELECT * FROM PRESERVE  
WHERE NOT ACRES < 50 AND NOT STATE = 'MA'
```

Table 22: 8 records

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
3	DANCING PRAIRIE	MT	680	0
7	MULESHOE RANCH	AZ	49120	0
40	SOUTH FORK MADISON	MT	121	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
80	RAMSEY CANYON	AZ	380	3
6	PAPAGONIA-SONOITA CREEK	AZ	1200	3

Situação 3

```
SELECT * FROM PRESERVE  
WHERE ACRES >= 50 OR STATE <> 'MA'
```

Table 23: Displaying records 1 - 10

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
3	DANCING PRAIRIE	MT	680	0
7	MULESHOE RANCH	AZ	49120	0
40	SOUTH FORK MADISON	MT	121	0
14	MCELWAIN-OLSEN	MA	66	0
9	DAVID H. SMITH	MA	830	0
12	MOUNT PLANTAIN	MA	730	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
80	RAMSEY CANYON	AZ	380	3

Resposta

Neste caso, a situação 1 é equivalente à situação 3 por conta da Lei de Morgan. Mas, diferem da situação 2.

$$(A \cap B)^c = A^c \cup B^c$$

Sendo a correção para a situação 2:

```
SELECT * FROM PRESERVE
WHERE NOT ACRES < 50 OR NOT STATE = 'MA'
```

Table 24: Displaying records 1 - 10

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
3	DANCING PRAIRIE	MT	680	0
7	MULESHOE RANCH	AZ	49120	0
40	SOUTH FORK MADISON	MT	121	0
14	MCELWAIN-OLSEN	MA	66	0
9	DAVID H. SMITH	MA	830	0
12	MOUNT PLANTAIN	MA	730	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
80	RAMSEY CANYON	AZ	380	3

QUESTÃO 18

Situação 1

```
SELECT * FROM PRESERVE
WHERE NOT (ACRES < 50 OR STATE = 'MA')
```

Table 25: 8 records

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
3	DANCING PRAIRIE	MT	680	0
7	MULESHOE RANCH	AZ	49120	0
40	SOUTH FORK MADISON	MT	121	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
80	RAMSEY CANYON	AZ	380	3

PNO	PNAME	STATE	ACRES	FEE
6	PAPAGONIA-SONOITA CREEK	AZ	1200	3

Situação 2

```
SELECT * FROM PRESERVE
WHERE NOT ACRES < 50 OR NOT STATE = 'MA'
```

Table 26: Displaying records 1 - 10

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
3	DANCING PRAIRIE	MT	680	0
7	MULESHOE RANCH	AZ	49120	0
40	SOUTH FORK MADISON	MT	121	0
14	MCELWAIN-OLSEN	MA	66	0
9	DAVID H. SMITH	MA	830	0
12	MOUNT PLANTAIN	MA	730	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
80	RAMSEY CANYON	AZ	380	3

Situação 3

```
SELECT * FROM PRESERVE
WHERE NOT ACRES < 50 AND NOT STATE = 'MA'
```

Table 27: 8 records

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
3	DANCING PRAIRIE	MT	680	0
7	MULESHOE RANCH	AZ	49120	0
40	SOUTH FORK MADISON	MT	121	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
80	RAMSEY CANYON	AZ	380	3
6	PAPAGONIA-SONOITA CREEK	AZ	1200	3

Resposta

Aqui temos o mesmo problema que a questão anterior.

$$(A \cup B)^c = A^c \cap B^c$$

Sendo a correção para a situação 2:

```
SELECT * FROM PRESERVE  
WHERE NOT ACRES < 50 AND NOT STATE = 'MA'
```

Table 28: 8 records

PNO	PNAME	STATE	ACRES	FEE
5	HASSAYAMPA RIVER	AZ	660	3
3	DANCING PRAIRIE	MT	680	0
7	MULESHOE RANCH	AZ	49120	0
40	SOUTH FORK MADISON	MT	121	0
1	COMERTOWN PRAIRIE	MT	1130	0
2	PINE BUTTE SWAMP	MT	15000	0
80	RAMSEY CANYON	AZ	380	3
6	PAPAGONIA-SONOITA CREEK	AZ	1200	3

```
Sys.setenv(TZ = "America/Sao_Paulo")  
Sys.time()
```

```
[1] "2026-08-30 15:32:36 -03"
```