



# Deep Learning in Computer Vision



Alexei Manso Corrêa Machado

Pontifical Catholic University of Minas Gerais – D. Computer Science


# Convolutional Neural Networks



machinelearningguru.com


$$f[x,y] * g[x,y] = \sum_{n_1=-\infty}^{\infty} \sum_{n_2=-\infty}^{\infty} f[n_1,n_2] \cdot g[x-n_1,y-n_2]$$

# Convolutional Neural Networks




[www.ayasdi.com](http://www.ayasdi.com)


# Fully-connected layers




# Convolutional layers




# Convolutional layers



# Convolutional layers




# Convolutional layers






# Convolutional layers

If we have 6 filters (5x5x3), there will be 6 activation maps:




# Convolutional layers

A ConvNet is a sequence of convolutional layers, each followed by an activation function:





# Convolutional layers


A ConvNet is a sequence of convolutional layers, each followed by an activation function:



# Filter hierarchy




# Activation maps



# Convolution as feature extraction

bank of K filters



K feature maps




⋮



image


feature map

# Padding



- When an image  $n \times n$  is convolved by a filter  $f \times f$ , it loses rows and columns, resulting in a  $n-f+1 \times n-f+1$  image
- In order for the image to keep the same dimensions,  $p$  columns and rows must be added prior to convolution, resulting in a  $n+2p-f+1 \times n+2p-f+1$  image


# Padding






# Striding

7 x 7 Input Volume



3 x 3 Output Volume



- When an image  $n \times n$  is convolved by a filter  $f \times f$  using stride  $s$ , it loses rows and columns, resulting in a  $(n-f)/s+1 \times (n-f)/s+1$  image

# Padding and striding

- When an image  $n \times n$  is convolved by a filter  $f \times f$  using stride  $s$  and pad  $p$  the resulting image is

$$(n+2p-f)/s+1 \times (n+2p-f)/s+1$$

- In order for the image to keep original dimensions ("same" padding):

$$p = (ns - n + f - s) / 2$$

# Convolution over volumes

- A convolutional layer may receive an image with multiple channels to be convolved by multiple filters
- The number of channels of the image and the filters must be the same
- Example: Input image of **6x6x3** and **10** filters **3x3x3** resulting in a **4x4x10** output (with **p = 0**, **s = 1**)

# Convolution over volumes

- Each layer receives a volume of  $\mathbf{W}_1 \times \mathbf{H}_1 \times \mathbf{D}_1$
- Requires 4 hyperparameters:
  - Number of filters  $n_c$
  - Size of filter  $\mathbf{f}$
  - *Stride*  $\mathbf{s}$
  - *Padding*  $\mathbf{p}$
- Outputs a volume of  $\mathbf{W}_2 \times \mathbf{H}_2 \times \mathbf{D}_2$ , where:
  - $\mathbf{W}_2 = (\mathbf{W}_1 - \mathbf{f} + 2\mathbf{p})/\mathbf{s} + 1$
  - $\mathbf{H}_2 = (\mathbf{H}_1 - \mathbf{f} + 2\mathbf{p})/\mathbf{s} + 1$
  - $\mathbf{D}_2 = n_c$
- Must compute  $\mathbf{f} \times \mathbf{f} \times \mathbf{D}_1$  weights per filter, a total of  $\mathbf{f} \times \mathbf{f} \times \mathbf{D}_1 \times n_c$  weights and  $n_c$  *biases*
- In the output volume, the  $d$ -th slice of size  $\mathbf{W}_2 \times \mathbf{H}_2$  is the result of the convolution between the  $d$ -th filter and the image with *stride*  $\mathbf{s}$ , and applying an offset related to the  $d$ -th *bias*

# Summary of notation

$f[l]$  = filter size

$p[l]$  = padding

$s[l]$  = stride

$nc[l]$  = number of filters

Input:  $n[l-1] \times n[l-1] \times nc[l-1]$       **Or**       $nH[l-1] \times nW[l-1] \times nc[l-1]$

Output:  $n[l] \times n[l] \times nc[l]$       **Or**       $nH[l] \times nW[l] \times nc[l]$

Where  $n[l] = (n[l-1] + 2p[l] - f[l] / s[l]) + 1$

Each filter is:  $f[l] \times f[l] \times nc[l-1]$

Activations:  $a[l]$  is  $nH[l] \times nW[l] \times nc[l]$

$A[l]$  is  $m \times nH[l] \times nW[l] \times nc[l]$

Weights:  $f[l] * f[l] * nc[l-1] * nc[l]$

bias:  $(1, 1, 1, nc[l])$

# Forward propagation


- Convolve the filters with the image
- Add a bias to the output of each filter
- Apply ReLU to the result

# Forward propagation

## Example:


- Convolve the filters with the image:
  - Input image: **6x6x3** ( $a_0$ )
  - 10 filters: **3x3x3** ( $W_1$ )
  - Result: **4x4x10** ( $W_1 a_0$ )
- Add a bias to the output of each filter
  - **b**, **10x1**: image **4x4x10** ( $W_1 a_0 + b$ )
- Apply ReLU to the result
  - image **4x4x10** ( $A_1 = \text{ReLU}(W_1 a_0 + b)$ )
- Number of parameters: **(3x3x3x10) + 10 = 280**

# Example of ConvNet





# Pooling layers



# Pooling layers


- In addition to the convolutional layers, CNNs usually use pooling layers to
  - Reduce the size of entries
  - Speed up computation
  - Make some detected features more robust
- Pooling layers have no parameters to learn!

# Max pooling layer

1	3	2	1
2	9	1	1
1	3	2	3
5	6	1	2



**Max pooling** says that if a feature is detected anywhere in the filter, keep it high to the next layer

# Average pooling layer




**Average pooling** takes the average of values and is less used than max pooling

# Summary: CNN pipeline




Input




Feature Map


# Summary: CNN pipeline




**ReLU**  
 $\max(0, x)$




**Leaky ReLU**  
 $\max(0.1x, x)$




**ELU**  
$$\begin{cases} x & x \geq 0 \\ \alpha(e^x - 1) & x < 0 \end{cases}$$



# Summary: CNN pipeline



# Example of CNN (LeNet-5)





# References and acknowledgements

Some of these slides were inspired or adapted from courses and presentations given by Andrew Ng, Camila Laranjeira, Fei-Fei Li, Flávio Figueiredo, Hugo Oliveira, Jefersson dos Santos, Justin Johnson, Keiller Nogueira, Pedro Olmo, Renato Assunção, Serena Yeung.

Reference courses include *Machine Learning* and *Deep Learning* CS230 and CS231 from Stanford University, *Deep Learning* and *Hands-on Deep Learning* from UFMG, *Deep Learning* CS498 from Un. Of Illinois.