

t depends on what kind of YAML file it is.

If it's a Kubernetes manifest (Deployment, Pod, Service, etc.)

Apply it to the cluster:

```
kubectl apply -f filename.yaml
```

For example:

```
kubectl apply -f deployment.yaml
```

Check the resources:

```
kubectl get all
```

Delete them later:

```
kubectl delete -f deployment.yaml
```

If it's a Podman-generated Kubernetes YAML

Run it with Podman:

```
podman kube play filename.yaml
```

Example:

```
podman kube play pod.yaml
```

Remove it:

```
podman kube play --down pod.yaml
```

If it's a Docker Compose / Podman Compose YAML

Start the stack:

```
podman-compose up -d
```

or

```
podman compose up -d
```

Stop it:

```
podman-compose down
```

Before applying (recommended)

Validate the manifest:

```
kubectl apply --dry-run=server -f filename.yaml
```

Or just inspect it:

```
cat filename.yaml
```

For your exam

Remember these three commands:

YAML type	Run command
Kubernetes manifest	<code>kubectl apply -f file.yaml</code>
Podman Kubernetes YAML	<code>podman kube play file.yaml</code>
Compose YAML	<code>podman-compose up -d</code>

If you upload your YAML file, I can tell you **exactly which command** to use and check whether the file is correct before you run it.