

Discrete Algebraic Structures

WiSe 2025/2026

Prof. Dr. Antoine Wiehe
Research Group for Theoretical Computer Science



- If you are registered for a tutorial but are not attending, please unregister!
- 16 points not necessary for students registered in WiSe 2023
- Use of LLMs for the weekly quiz is strictly forbidden

- If you are registered for a tutorial but are not attending, please unregister!
- 16 points not necessary for students registered in WiSe 2023
- Use of LLMs for the weekly quiz is strictly forbidden
Be careful of the **blackboxing**/*vibe coding* phenomenon!

- If you are registered for a tutorial but are not attending, please unregister!
- 16 points not necessary for students registered in WiSe 2023
- Use of LLMs for the weekly quiz is strictly forbidden
Be careful of the **blackboxing**/*vibe coding* phenomenon!

Studienleistungen \subseteq official examinations
Use of LLM \subseteq cheating

\implies Use of LLM during quiz \subseteq cheating during official examination

Allgemeine Studien- und Prüfungsordnung:

§ 25b Deception and breach of order

- (1) 'If the student attempts to influence the result of the examination or coursework by deception, in particular by using unauthorized aids, the examination or coursework in question will be graded as "fail" (5.0).

- If you are registered for a tutorial but are not attending, please unregister!
- 16 points not necessary for students registered in WiSe 2023
- Use of LLMs for the weekly quiz is strictly forbidden
Be careful of the **blackboxing**/*vibe coding* phenomenon!

Studienleistungen \subseteq official examinations
Use of LLM \subseteq cheating

\Rightarrow Use of LLM during quiz \subseteq cheating during official examination

$SL \subseteq Exam$

$LLM \subseteq Cheat$

$\Rightarrow SL \cap LLM \subseteq Exam \cap Cheat$

Allgemeine Studien- und Prüfungsordnung:

§ 25b Deception and breach of order

- (1) 'If the student attempts to influence the result of the examination or coursework by deception, in particular by using unauthorized aids, the examination or coursework in question will be graded as "fail" (5.0).

Sets


- Definition of $\cap, \cup, \times, \setminus, \Delta, \mathcal{P}$
- How to prove $S \subseteq T$
- How to prove $S = T$
(prove $S \subseteq T$ and $T \subseteq S$)

Functions


- Definition; be able to determine if a given set $f \subseteq A \times B$ is a function or not
- Properties of functions: **injectivity**, **surjectivity**, **bijectivity**
- Composition of functions
- Identity function
- Inverses

Logic


- Recognize legal formulas of propositional/predicate logic
- How to compute truth table of a propositional formula
- From a truth table, compute a corresponding formula
- Be able to determine logical equivalences between formulas
- Know the valid ways to prove an implication $\varphi \Rightarrow \psi$
- Know how to compute $\neg\varphi$



- We know functions $A \rightarrow B$



- We know functions $A \rightarrow B$



- In many applications, we want to express a relationship between things that is *not* a function


1 input \longrightarrow multiple outputs

movie \longrightarrow directors



book \longrightarrow authors

x \longrightarrow a square root of x


- We know functions $A \rightarrow B$



- In many applications, we want to express a relationship between things that is *not* a function



- We know functions $A \rightarrow B$



- In many applications, we want to express a relationship between things that is *not* a function

1 input \longrightarrow multiple outputs

movie \longrightarrow directors



book \longrightarrow authors

x \longrightarrow a square root of x

1 input \longrightarrow 0 or 1 output

element of an array \longrightarrow next element

x \longrightarrow $1/x$




Definition. A function $f: A \rightarrow B$ is a set $f \subseteq A \times B$ such that **for every** $a \in A$, there exists a **unique** $b \in B$ such that $(a, b) \in f$.

Definition. A function $f: A \rightarrow B$ is a set $f \subseteq A \times B$ such that ~~for every $a \in A$, there exists a~~ **unique** $b \in B$ such that $(a, b) \in f$.

Definition. A ~~function~~ **binary relation** R is a set $R \subseteq A \times B$ ~~such that for every~~
 ~~$a \in A$, there exists a~~ **unique** ~~$b \in B$ such that $(a, b) \in f$.~~


Definition. A **binary relation** R is a set $R \subseteq A \times B$.

Definition. A **binary relation** R is a set $R \subseteq A \times B$.



$R \subseteq \mathbb{R} \times \mathbb{R}$
a relation that is not a function

Definition. A **binary relation** R is a set $R \subseteq A \times B$.



$\{(\text{Max}, \text{Climbing}), (\text{Maria}, \text{Yoga}), (\text{Philipp}, \text{Bouldering}), \dots\}$

Definition. A **binary relation** R is a set $R \subseteq A \times B$.

- Most common way of representing structured information

Definition. A **binary relation** R is a set $R \subseteq A \times B$.

- Most common way of representing structured information
- Every database probably contains a binary relation somewhere

Subscriptions \subseteq Accounts \times Channels Birthdate \subseteq Accounts $\times \mathbb{N}$ Teaches \subseteq Professors \times Courses

Definition. A **binary relation** R is a set $R \subseteq A \times B$.

- Most common way of representing structured information
- Every database probably contains a binary relation somewhere

Subscriptions \subseteq Accounts \times Channels Birthdate \subseteq Accounts $\times \mathbb{N}$ Teaches \subseteq Professors \times Courses

One can also put more data together:

Definition. A **relation** on A_1, \dots, A_n is a set $R \subseteq A_1 \times A_2 \times \dots \times A_n$.

Definition. A **binary relation** R is a set $R \subseteq A \times B$.

- Most common way of representing structured information
- Every database probably contains a binary relation somewhere


Subscriptions \subseteq Accounts \times Channels Birthdate \subseteq Accounts $\times \mathbb{N}$ Teaches \subseteq Professors \times Courses

One can also put more data together:

Definition. A **relation** on A_1, \dots, A_n is a set $R \subseteq A_1 \times A_2 \times \dots \times A_n$.

- In data science: the sets A_1, \dots, A_n are the **features**, $R \subseteq A_1 \times \dots \times A_n$ is the dataset

Iris data set $\subseteq \mathbb{R} \times \mathbb{R} \times \mathbb{R} \times \mathbb{R} \times \{\text{l. setosa, l. virginica, l. versicolor}\}$



Definition. A **binary relation** R is a set $R \subseteq A \times B$.

- Most common way of representing structured information
- Every database probably contains a binary relation somewhere

Subscriptions \subseteq Accounts \times Channels Birthdate \subseteq Accounts $\times \mathbb{N}$ Teaches \subseteq Professors \times Courses

One can also put more data together:

Definition. A **relation** on A_1, \dots, A_n is a set $R \subseteq A_1 \times A_2 \times \dots \times A_n$.

- In data science: the sets A_1, \dots, A_n are the **features**, $R \subseteq A_1 \times \dots \times A_n$ is the dataset

Iris data set $\subseteq \mathbb{R} \times \mathbb{R} \times \mathbb{R} \times \mathbb{R} \times \{\text{l. setosa, l. virginica, l. versicolor}\}$

YellowCab \subseteq DateTime \times DateTime $\times \mathbb{N} \times \mathbb{Q}$

Definition. A **binary relation** R is a set $R \subseteq A \times B$.

- Most common way of representing structured information
- Every database probably contains a binary relation somewhere

Subscriptions \subseteq Accounts \times Channels Birthdate \subseteq Accounts $\times \mathbb{N}$ Teaches \subseteq Professors \times Courses

One can also put more data together:

Definition. A **relation** on A_1, \dots, A_n is a set $R \subseteq A_1 \times A_2 \times \dots \times A_n$.

- In data science: the sets A_1, \dots, A_n are the **features**, $R \subseteq A_1 \times \dots \times A_n$ is the dataset

Iris data set $\subseteq \mathbb{R} \times \mathbb{R} \times \mathbb{R} \times \mathbb{R} \times \{\text{l. setosa, l. virginica, l. versicolor}\}$

YellowCab \subseteq DateTime \times DateTime $\times \mathbb{N} \times \mathbb{Q}$

- In computer science: many relations together = **relational database**

Movies $\subseteq \mathbb{N} \times \text{String} \times \mathbb{N} \times \dots$

Directors $\subseteq \mathbb{N} \times \text{String} \times \dots$


Directed $\subseteq \mathbb{N} \times \mathbb{N}$

Knowledge graphs:

- semantic Web: representing information on the Web in a **structured** way
- SPARQL query language


Knowledge graphs:

- semantic Web: representing information on the Web in a **structured** way
- SPARQL query language




Knowledge graphs:

- semantic Web: representing information on the Web in a **structured** way
- SPARQL query language



Knowledge graphs:

- semantic Web: representing information on the Web in a **structured** way
- SPARQL query language



Very often:

- relations are binary $R \subseteq A \times B$
- $A = B$

Very often:


- relations are binary $R \subseteq A \times B$
- $A = B$

Definition. A relation $R \subseteq A \times A$ is called a **directed graph**.
The elements of A are the **vertices** and the elements of R are the **edges**.

Very often:

- relations are binary $R \subseteq A \times B$
- $A = B$

Definition. A relation $R \subseteq A \times A$ is called a **directed graph**.
The elements of A are the **vertices** and the elements of R are the **edges**.



Algebraic properties of relations

Algebra: study of **operations** and **equations** on *stuff*

Algebra: study of **operations** and **equations** on *stuff*

Numbers: $+$, \times , $1/x$, 1 , 0

Matrices: $+$, \times , M^{-1} , I_n , 0

Algebra: study of **operations** and **equations** on *stuff*

Numbers: $+$, \times , $1/x$, 1 , 0

Matrices: $+$, \times , M^{-1} , I_n , 0

Sets: \cap , \cup , \times , Δ , \emptyset , \dots

Functions: \circ , f^{-1} , Id_A

Algebra: study of **operations** and **equations** on *stuff*

Numbers: $+$, \times , $1/x$, 1 , 0

Matrices: $+$, \times , M^{-1} , I_n , 0

Sets: \cap , \cup , \times , Δ , \emptyset , \dots

Functions: \circ , f^{-1} , Id_A

Booleans: \wedge , \vee , \Rightarrow , \neg , \top , \perp

Algebra: study of **operations** and **equations** on *stuff*

Numbers: $+$, \times , $1/x$, 1 , 0

Matrices: $+$, \times , M^{-1} , I_n , 0

Sets: \cap , \cup , \times , Δ , \emptyset , \dots

Functions: \circ , f^{-1} , Id_A

Booleans: \wedge , \vee , \Rightarrow , \neg , \top , \perp

Relations: ?

Algebra: study of **operations** and **equations** on *stuff*

Number theory

Numbers: $+$, \times , $1/x$, 1 , 0

Matrices: $+$, \times , M^{-1} , I_n , 0

Linear algebra

Sets: \cap , \cup , \times , Δ , \emptyset , \dots

Functions: \circ , f^{-1} , Id_A


Boolean algebra

Booleans: \wedge , \vee , \Rightarrow , \neg , \top , \perp


Relations: ?

Relational algebra

$R \subseteq A \times B$




$S \subseteq B \times C$




$$R \subseteq A \times B$$


$$S \subseteq B \times C$$



1. Glue the potatoes together




1. Glue the potatoes together
2. Compute paths from A to C




1. Glue the potatoes together
2. Compute paths from A to C
3. Forget about B

Definition. Let $R \subseteq A \times B$ and $S \subseteq B \times C$. The **composition** is defined by $S \circ R = \{(a, c) \in A \times C \mid \exists b \in B ((a, b) \in R \wedge (b, c) \in S)\}$.



1. Glue the potatoes together
2. Compute paths from A to C
3. Forget about B


Definition. Let $R \subseteq A \times B$ and $S \subseteq B \times C$. The **composition** is defined by $S \circ R = \{(a, c) \in A \times C \mid \exists b \in B ((a, b) \in R \wedge (b, c) \in S)\}$.



Compute the composition of the given relations. Which pairs does it contain?




Given $R \subseteq A \times B$, can one find a relation X on $B \times B$ such that $X \circ R = R$?



Given $R \subseteq A \times B$, can one find a relation X on $B \times B$ such that $X \circ R = R$?


Theorem. Let $\text{Id}_B = \{(b, b) \in B \times B\}$. For all $R \subseteq A \times B$, we have $\text{Id}_B \circ R = R$ and $R \circ \text{Id}_A = R$.



Given $R \subseteq A \times B$, can one find a relation X on $B \times B$ such that $X \circ R = R$?

Theorem. Let $\text{Id}_B = \{(b, b) \in B \times B\}$. For all $R \subseteq A \times B$, we have $\text{Id}_B \circ R = R$ and $R \circ \text{Id}_A = R$.


This is actually the
function we already know!
 $\text{Id}_B: B \rightarrow B, \text{Id}_B(x) = x$.



Given $R \subseteq A \times B$, can one find a relation X on $B \times B$ such that $X \circ R = R$?

Theorem. Let $\text{Id}_B = \{(b, b) \in B \times B\}$. For all $R \subseteq A \times B$, we have $\text{Id}_B \circ R = R$ and $R \circ \text{Id}_A = R$.


Given $R \subseteq A \times B$, is there an inverse? A $X \subseteq B \times A$ such that $S \circ X = \text{Id}_B$ and $X \circ S = \text{Id}_A$?



Given $R \subseteq A \times B$, can one find a relation X on $B \times B$ such that $X \circ R = R$?

Theorem. Let $\text{Id}_B = \{(b, b) \in B \times B\}$. For all $R \subseteq A \times B$, we have $\text{Id}_B \circ R = R$ and $R \circ \text{Id}_A = R$.

Given $R \subseteq A \times B$, is there an inverse? A $X \subseteq B \times A$ such that $S \circ X = \text{Id}_B$ and $X \circ S = \text{Id}_A$?



Exercise: which relations have such an inverse?

Given $R \subseteq A \times B$, can one find a relation X on $B \times B$ such that $X \circ R = R$?


Theorem. Let $\text{Id}_B = \{(b, b) \in B \times B\}$. For all $R \subseteq A \times B$, we have $\text{Id}_B \circ R = R$ and $R \circ \text{Id}_A = R$.

Given $R \subseteq A \times B$, is there an inverse? A $X \subseteq B \times A$ such that $S \circ X = \text{Id}_B$ and $X \circ S = \text{Id}_A$?

No, but:

Definition. Let $R \subseteq A \times B$. The **transpose** of R is

$$R^T = \{(b, a) \in B \times A \mid (a, b) \in R\}.$$



Given $R \subseteq A \times B$, can one find a relation X on $B \times B$ such that $X \circ R = R$?

Theorem. Let $\text{Id}_B = \{(b, b) \in B \times B\}$. For all $R \subseteq A \times B$, we have $\text{Id}_B \circ R = R$ and $R \circ \text{Id}_A = R$.



Given $R \subseteq A \times B$, is there an inverse? A $X \subseteq B \times A$ such that $S \circ X = \text{Id}_B$ and $X \circ S = \text{Id}_A$?

No, but:

Definition. Let $R \subseteq A \times B$. The **transpose** of R is

$$R^T = \{(b, a) \in B \times A \mid (a, b) \in R\}.$$

- $\text{isChildOf} \subseteq \text{People} \times \text{People}$
 $\text{isChildOf}^T \subseteq \text{People} \times \text{People}$



Given $R \subseteq A \times B$, can one find a relation X on $B \times B$ such that $X \circ R = R$?

Theorem. Let $\text{Id}_B = \{(b, b) \in B \times B\}$. For all $R \subseteq A \times B$, we have $\text{Id}_B \circ R = R$ and $R \circ \text{Id}_A = R$.



Given $R \subseteq A \times B$, is there an inverse? A $X \subseteq B \times A$ such that $S \circ X = \text{Id}_B$ and $X \circ S = \text{Id}_A$?

No, but:

Definition. Let $R \subseteq A \times B$. The **transpose** of R is

$$R^T = \{(b, a) \in B \times A \mid (a, b) \in R\}.$$

- $\text{isChildOf} \subseteq \text{People} \times \text{People}$
 $\text{isChildOf}^T \subseteq \text{People} \times \text{People}$
- $\text{isSiblingOf} \subseteq \text{People} \times \text{People}$
 $\text{isSiblingOf}^T = ?$



Given $R \subseteq A \times B$, can one find a relation X on $B \times B$ such that $X \circ R = R$?

Theorem. Let $\text{Id}_B = \{(b, b) \in B \times B\}$. For all $R \subseteq A \times B$, we have $\text{Id}_B \circ R = R$ and $R \circ \text{Id}_A = R$.

Given $R \subseteq A \times B$, is there an inverse? A $X \subseteq B \times A$ such that $S \circ X = \text{Id}_B$ and $X \circ S = \text{Id}_A$?



No, but:

Definition. Let $R \subseteq A \times B$. The **transpose** of R is

$$R^T = \{(b, a) \in B \times A \mid (a, b) \in R\}.$$

- $\text{isChildOf} \subseteq \text{People} \times \text{People}$
 $\text{isChildOf}^T \subseteq \text{People} \times \text{People}$
- $\text{isSiblingOf} \subseteq \text{People} \times \text{People}$
 $\text{isSiblingOf}^T = ?$

Remark. It is **not true** that $R \circ R^T = \text{Id}_B$ holds in general!
 But **if** R has an inverse, then R^T is **the** inverse.



Algebra: study of **operations** and **equations** on *stuff*

Number theory

Numbers: $+, \times, 1/x, 1, 0$
 Matrices: $+, \times, M^{-1}, I, 0$

Linear algebra


Sets: $\cap, \cup, \times, \Delta, \emptyset, \dots$
 Functions: $\circ, f^{-1}, \text{Id}_A$

Boolean algebra

Booleans: $\wedge, \vee, \Rightarrow, \neg, \top, \perp$
 Relations: $\circ, R^T, \text{Id}, \cup, \cap, \times, \dots$


Relational algebra

Properties of directed graphs




Definition. A relation $R \subseteq A \times A$ is:

- **reflexive**: if for all $a \in A$, $(a, a) \in R$
- **antireflexive**: if for all $a \in A$, $(a, a) \notin R$
- **symmetric**: if for all $a, b \in A$, if $(a, b) \in R$, then $(b, a) \in R$
- **antisymmetric**: if for all $a, b \in A$, if $(a, b) \in R$ and $a \neq b$ then $(b, a) \notin R$
- **transitive**: if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.



Definition. A relation $R \subseteq A \times A$ is:


- **reflexive**: if for all $a \in A$, $(a, a) \in R$
- **antireflexive**: if for all $a \in A$, $(a, a) \notin R$



Definition. A relation $R \subseteq A \times A$ is:

- **reflexive**: if for all $a \in A$, $(a, a) \in R$
- **antireflexive**: if for all $a \in A$, $(a, a) \notin R$


Examples. $x \leq y$, $x = y$



Definition. A relation $R \subseteq A \times A$ is:


- **reflexive**: if for all $a \in A$, $(a, a) \in R$
- **antireflexive**: if for all $a \in A$, $(a, a) \notin R$

Examples. $x < y$, $x \neq y$, "is child of"



Definition. A relation $R \subseteq A \times A$ is:


- **symmetric**: if for all $a, b \in A$, if $(a, b) \in R$, then $(b, a) \in R$
- **antisymmetric**: if for all $a, b \in A$, if $(a, b) \in R$ and $a \neq b$ then $(b, a) \notin R$



Definition. A relation $R \subseteq A \times A$ is:

- **symmetric**: if for all $a, b \in A$, if $(a, b) \in R$, then $(b, a) \in R$
- **antisymmetric**: if for all $a, b \in A$, if $(a, b) \in R$ and $a \neq b$ then $(b, a) \notin R$


Examples. $x = y$, “is sibling of”



Definition. A relation $R \subseteq A \times A$ is:


- **symmetric**: if for all $a, b \in A$, if $(a, b) \in R$, then $(b, a) \in R$
- **antisymmetric**: if for all $a, b \in A$, if $(a, b) \in R$ and $a \neq b$ then $(b, a) \notin R$

Examples. $x < y$, “is child of”




Definition. A relation $R \subseteq A \times A$ is:

- **transitive**: if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.



Definition. A relation $R \subseteq A \times A$ is:


- **transitive**: if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.




Definition. A relation $R \subseteq A \times A$ is:

- **transitive:** if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.

Examples. $x < y$, $x = y$, “ x is an ancestor of y ”





Idea of “closure”: take something that does **not** satisfy a property, and make it bigger until it does



Idea of “closure”: take something that does **not** satisfy a property, and make it bigger until it does


Reflexive closure




Reflexive closure of $R = R \cup \text{Id}_A$

Idea of “closure”: take something that does **not** satisfy a property, and make it bigger until it does


Reflexive closure



Reflexive closure of $R = R \cup \text{Id}_A$




Symmetric closure




Symmetric closure of $R = R \cup R^T$

Idea of “closure”: take something that does **not** satisfy a property, and make it bigger until it does


Reflexive closure



Reflexive closure of $R = R \cup \text{Id}_A$




Symmetric closure



Symmetric closure of $R = R \cup R^T$


Transitive closure




Transitive closure of $R = R \cup (R \circ R) \cup (R \circ R \circ R) \cup \dots$

Idea of “closure”: take something that does **not** satisfy a property, and make it bigger until it does


Reflexive closure



Reflexive closure of $R = R \cup \text{Id}_A$




Symmetric closure





Symmetric closure of $R = R \cup R^T$

Transitive closure





Transitive closure of $R = R \cup (R \circ R) \cup (R \circ R \circ R) \cup \dots$

if $(a, b), (b, c), (c, d) \in R$, then (a, d) in the transitive closure





Reflexive closure of $R = R \cup \text{Id}_A$

```
def reflexive_closure(A, R):
    T = R.copy() # make a copy of R
    # ???
    # ???
    return T
```





Reflexive closure of $R = R \cup \text{Id}_A$

```
def reflexive_closure(A, R):  
    T = R.copy() # make a copy of R  
    for a in A:  
        T.add((a,a))  
    return T
```



Symmetric closure of $R = R \cup R^T$

```
def symmetric_closure(R):  
    T = R.copy() # make a copy of R  
    # ???  
    # ???  
    return T
```





Symmetric closure of $R = R \cup R^T$

```
def symmetric_closure(R):
    T = R.copy() # make a copy of R
    for (a,b) in R:
        T.add((b,a))
    return T
```


Definition. A relation $R \subseteq A \times A$ is:

- **transitive**: if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.




Definition. A relation $R \subseteq A \times A$ is:

- **transitive:** if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.




Definition. A relation $R \subseteq A \times A$ is:

- **transitive:** if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.



Definition. A relation $R \subseteq A \times A$ is:


- **transitive**: if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.



$$T = R \cup (R \circ R)$$

Definition. A relation $R \subseteq A \times A$ is:

- **transitive**: if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.




$$T = R \cup (R \circ R)$$

Definition. A relation $R \subseteq A \times A$ is:

- **transitive:** if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.

Question. Is T transitive?

$$T = R \cup (R \circ R)$$




Definition. A relation $R \subseteq A \times A$ is:

- **transitive:** if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.


Question. Is T transitive?

$$T = R \cup (R \circ R)$$



Definition. A relation $R \subseteq A \times A$ is:


- **transitive:** if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.




$$T = R \cup (R \circ R) \cup (R \circ R \circ R)$$

Definition. A relation $R \subseteq A \times A$ is:


- **transitive**: if for all $a, b, c \in A$, if $(a, b) \in R$ and $(b, c) \in R$ then $(a, c) \in R$.



$$T = R \cup (R \circ R) \cup (R \circ R \circ R) \cup \dots$$





Transitive closure




$$\text{Transitive closure of } R = R \cup (R \circ R) \cup (R \circ R \circ R) \cup \dots$$

```
def transitive_closure(R):
    T = R.copy()
    keepGoing = True
    while keepGoing:
        ???
        ???
        ???
        ???
        ???
        ???
    return T
```

Write code that from R , computes all pairs (a, b) such that there is a *path* from a to b






Transitive closure



Transitive closure of $R =$
 $R \cup (R \circ R) \cup (R \circ R \circ R) \cup \dots$

```
def transitive_closure(R):
    T = R.copy()
    keepGoing = True
    while keepGoing:
        keepGoing = False
        for (a,b) in T:
            for (c,d) in R:
                if b==c and (a,d) not in T:
                    T.add((a,d))
                    keepGoing = True
    return T
```



Transitive closure of $R = R \cup (R \circ R) \cup (R \circ R \circ R) \cup \dots$

Compute the transitive closure of $\{(0, 1), (0, 2), (1, 4), (2, 4), (0, 3)\}$:

- $\{(0, 4)\}$
- $\{(0, 1), (0, 2), (1, 4), (2, 4), (0, 3), (0, 4)\}$
- $\{(0, 1), (0, 2), (1, 4), (2, 4), (0, 3), (1, 2)\}$
- $\{(0, 1), (0, 2), (1, 4), (2, 4), (0, 3), (3, 4)\}$



1. Draw the relation as a graph (how many vertices?, how many edges?)
2. Add the missing edges
3. Then compare your solution to the given solutions

- What a relation is
- How to draw a relation $R \subseteq A \times B$
- How to compute the composition and transpose of binary relations
- The basic properties
(anti)reflexivity, (anti)symmetry, transitivity
- How to compute the closures