

Package ‘psychtoolbox’

March 3, 2024

Title Tools for psychology research and psychometrics

Version 0.0.1

Description This package contains functions helping to analyse psychological data.

License CC BY 4.0

URL <https://gitlab.com/lukas.novak/psychtoolbox>

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Imports coin,
docextractr,
dplyr,
equaltestMI,
foreign,
insight,
lavaan,
magrittr,
rmarkdown,
rstatix,
stats,
tidyr,
expss,
stringr,
tidyselect,
vctrs,
purrr,
reshape2,
janitor,
broom,
car

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Depends R (>= 2.10)

R topics documented:

clin_sig_chang	2
lasy.lin.reg	3
lasy.log.reg	5
mitab	6
mult.g.comp	8
paq.validation.study	9
RCI	11
small_boot_table	12
two.g.comp	14
word2pdf	15

Index	16
--------------	-----------

clin_sig_chang	<i>Clinically significant change</i>
----------------	--------------------------------------

Description

This easy function calculates Clinically significant change (clinical cut-off scores) as defined by Jacobson and Truax (1991).

Usage

```
clin_sig_chang(SD_0, SD_1, M_1, M_0)
```

Arguments

SD_0	standard deviation of the non-clinical population
SD_1	standard deviation of the clinical population
M_1	mean of the clinical population
M_0	mean of the non-clinical population

Format

numeric vector of values

Details

This function computes cut-off score differentiating between the clinical and non-clinical population based on the Jacobson and Truax (1991) formula (p. 13). The mathematical formula can be also found in Biescad & Timulak(2014, p. 150).

Value

numeric vector

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

Jacobson, N. S., & Truax, P. (1991). Clinical significance: A statistical approach to defining meaningful change in psychotherapy research. *Journal of Consulting and Clinical Psychology*, 59(1), 12-19, DOI: <https://doi.org/10.1037/0022-006X.59.1.12>

Matus Biescad & Ladislav Timulak (2014). Measuring psychotherapy outcomes in routine practice: Examining Slovak versions of three commonly used outcome instruments, *European Journal of Psychotherapy & Counselling*, 16:2, 140-162, DOI: <https://doi.org/10.1080/13642537.2014.895772>

See Also

[RCI\(\)](#) function for calculation of the Reliable Change Index

Examples

```
clin.cut.off=clin_sig_chang(SD_0 = 3.5,
                           SD_1 = 2.1,
                           M_0 = 4.2,
                           M_1 = 12.1)

clin.cut.off
```

lasy.lin.reg

Lasy linear regression function

Description

This function performs linear regression and print results in tibble output. This function aims to provide the results of the regression analysis in the format, which is frequently desired in academic journals.

Usage

```
lasy.lin.reg(
  independent.var,
  dependent.var,
  print.cov = FALSE,
  Z_score_independent = FALSE,
  check_multicollinearity = TRUE,
  covariates = NULL,
  data
)
```

Arguments

independent.var	independent variable/s
dependent.var	dependent variable/s
print.cov	Print effect of covariates, default is FALSE
Z_score_independent	Should independent variables be z-scored? Default is FALSE


```
data = data.PAQ,  
print.cov = FALSE)  
  
print(lin.reg.output)
```

`lasy.log.reg`*Lasy logistic regression function*

Description

This function performs logistic regression and print results in tibble output. This function aims to provide the results of the regression analysis in the format, which is frequently desired in academic journals.

Usage

```
lasy.log.reg(  
  independent.var,  
  dependent.var,  
  print.cov = FALSE,  
  covariates = NULL,  
  check_multicollinearity = TRUE,  
  data  
)
```

Arguments

<code>independent.var</code>	independent variable/s
<code>dependent.var</code>	dependent variable/s
<code>print.cov</code>	Print effect of covariates, default is FALSE
<code>covariates</code>	covariates to be included in a model
<code>check_multicollinearity</code>	Should multicollinearity assumption be checked? Default is TRUE
<code>data</code>	data frame or tibble object

Format

An object of class "tibble"

Details

Currently, this function does not provide model fit indicators such as AIC or BIC.

Value

data frame

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

- Welch, B. L. (1947). "The generalization of "Student's" problem when several different population variances are involved". *Biometrika*. 34 (1–2): 28–35.
- Wilcoxon, F., Individual Comparisons by Ranking Methods, *Biometrics Bulletin*, Vol. 1, 1945, pp. 80–83. DOI:10.2307/3001968
- Dunn, O. J. (1961) Multiple comparisons among means. *Journal of the American Statistical Association*. 56, 52–64.
- Games, P. A., Keselman, H. J., & Clinch, J. J. Tests for homogeneity of variance in factorial designs. *Psychological Bulletin*, 86, 978–984

Examples

```
# data loading
data(paq.validation.study)
regress.output <- lasy.log.reg(independent.var = c("TEQ", "PAQ"),
                              covariates = c("Age"),
                              dependent.var = c("econom_stat_dich",
                                                  "family_status",
                                                  "edu_dich"),
                              data = paq.validation.study)

print(regress.output)
```

mitab

Measurement invariance table

Description

Measurement invariance table

Usage

```
mitab(
  group1_nam,
  group2_nam,
  ordered,
  model,
  data,
  std.lv,
  meanstructure,
  group,
  yes_no_results,
  estimator,
  robust = FALSE,
  cfi.difference = TRUE,
  rmsea.difference = TRUE,
  ...
)
```

Arguments

group1_nam	name of the first group
group2_nam	name of the second group
ordered	logical, if set to TRUE items will be treated as ordered variables
model	lavaan model to test
data	data frame or tibble
std.lv	logical, if TRUE than standardized loadings are stored in temporal output
meanstructure	logical, if TRUE than model with meanstructure is estimated
group	name of grouping variable
yes_no_results	logical, if TRUE than lasy output indicating difference between models is added, currently working only based on CFI and RMSEA
estimator	name of estimator to be used during fitting procedure
robust	logical, if TRUE, than robust results are printed, working only with estimators providing robust results (e.g. MLR or DWLS)
cfi.difference	logical, if TRUE, delta of the CFI is printed in output
rmsea.difference	logical, if TRUE, delta of RMSEA is printed in output
...	optional arguments for CFA function

Format

An object of class "tibble"

Details

This function creates table with the key output from measurement invariance testing.

Value

data frame

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

Myles Hollander and Douglas A. Wolfe (1973). Nonparametric Statistical Methods. New York: John Wiley & Sons. Pages 27–33 (one-sample), 68–75 (two-sample). Or second edition (1999).

Examples

```
# The famous Holzinger and Swineford (1939) example
HS.model <- ' visual  =~ x1 + x2 + x3
textual =~ x4 + x5 + x6
speed   =~ x7 + x8 + x9 '

library(lavaan)
dat <- HolzingerSwineford1939
res.tab.mi <- mitab(
```

```

group1_nam = "Grant-White",
group2_nam = "Pasteur",
ordered = FALSE,
model = HS.model,
data = dat,
std.lv = TRUE,
meanstructure = TRUE,
group = "school",
yes_no_results = TRUE,
estimator = "MLR",
robust = TRUE,
cfi.difference = TRUE,
rmsea.difference = TRUE
)

print(res.tab.mi)

```

mult.g.comp

Robust multi-group comparison

Description

This function allows to compare multiple groups in multiple outcome variables with violated parametric assumptions.

Usage

```

mult.g.comp(
  df,
  outcome.var,
  groups,
  desc_only = FALSE,
  short_results = TRUE,
  remove_missings = FALSE,
  percent_decimals = 2
)

```

Arguments

df	data frame or tibble object
outcome.var	continuous variable/s
groups	grouping variable/s
desc_only	print only descriptive statistics, default is FALSE
short_results	prints only significance stars without numerical results, default is TRUE
remove_missings	remove missing values from a table, default is FALSE
percent_decimals	number of decimals used to round percentages, default is 2

Format

An object of class "tibble"

Details

Currently, this function does not report effect size from post-hoc tests.

Two group comparison:

If there is less than three groups, the Welch test or the Wilcoxon test depending on data distribution.

Three and more groups comparison:

If more than two groups are present in data, the Dunn test or Games-Howell test is performed.

Value

data frame

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

Welch, B. L. (1947). "The generalization of "Student's" problem when several different population variances are involved". *Biometrika*. 34 (1–2): 28–35.

Wilcoxon, F., Individual Comparisons by Ranking Methods, *Biometrics Bulletin*, Vol. 1, 1945, pp. 80–83. DOI:10.2307/3001968

Dunn, O. J. (1961) Multiple comparisons among means. *Journal of the American Statistical Association*. 56, 52–64.

Games, P. A., Keselman, H. J., & Clinch, J. J. Tests for homogeneity of variance in factorial designs. *Psychological Bulletin*, 86, 978–984

Examples

```
# data loading
tab.1=mult.g.comp(df = paq.validation.study, outcome.var = c("PAQ", "G_DIF", "G_DDF", "G_EOT"),
groups = c("economical_status",
           "Gender",
           "education",
           "family_status"))
# printing the output
print(tab.1)
```

paq.validation.study *paq.validation.study*

Description

This dataset contains data which were used for validation of the Perth Alexithymia Questionnaire in the Czech Republic.

Usage

```
paq.validation.study
```

Format

A data frame with 848 rows and 53 variables:

P_DIF double COLUMN_DESCRIPTION
 P_DDF double COLUMN_DESCRIPTION
 P_DAF double COLUMN_DESCRIPTION
 N_DIF double COLUMN_DESCRIPTION
 N_DDF double COLUMN_DESCRIPTION
 N_DAF double COLUMN_DESCRIPTION
 G_EOT double COLUMN_DESCRIPTION
 G_DIF double COLUMN_DESCRIPTION
 G_DDF double COLUMN_DESCRIPTION
 G_DAF double COLUMN_DESCRIPTION
 family_status integer COLUMN_DESCRIPTION
 Gender integer COLUMN_DESCRIPTION
 TEQ_1 double COLUMN_DESCRIPTION
 TEQ_3 double COLUMN_DESCRIPTION
 TEQ_5 double COLUMN_DESCRIPTION
 TEQ_16 double COLUMN_DESCRIPTION
 TEQ_CON_2 double COLUMN_DESCRIPTION
 TEQ_CON_4 double COLUMN_DESCRIPTION
 TEQ_CON_14 double COLUMN_DESCRIPTION
 TEQ double COLUMN_DESCRIPTION
 Age double COLUMN_DESCRIPTION
 age_group double COLUMN_DESCRIPTION
 age.quality double COLUMN_DESCRIPTION
 ethnicity integer COLUMN_DESCRIPTION
 education integer COLUMN_DESCRIPTION
 economical_status integer COLUMN_DESCRIPTION
 PAQ_1 double COLUMN_DESCRIPTION
 PAQ_2 double COLUMN_DESCRIPTION
 PAQ_3 double COLUMN_DESCRIPTION
 PAQ_4 double COLUMN_DESCRIPTION
 PAQ_5 double COLUMN_DESCRIPTION
 PAQ_6 double COLUMN_DESCRIPTION
 PAQ_7 double COLUMN_DESCRIPTION
 PAQ_8 double COLUMN_DESCRIPTION
 PAQ_9 double COLUMN_DESCRIPTION
 PAQ_10 double COLUMN_DESCRIPTION
 PAQ_11 double COLUMN_DESCRIPTION
 PAQ_12 double COLUMN_DESCRIPTION

```

PAQ_13 double COLUMN_DESCRIPTION
PAQ_14 double COLUMN_DESCRIPTION
PAQ_15 double COLUMN_DESCRIPTION
PAQ_16 double COLUMN_DESCRIPTION
PAQ_17 double COLUMN_DESCRIPTION
PAQ_18 double COLUMN_DESCRIPTION
PAQ_19 double COLUMN_DESCRIPTION
PAQ_20 double COLUMN_DESCRIPTION
PAQ_21 double COLUMN_DESCRIPTION
PAQ_22 double COLUMN_DESCRIPTION
PAQ_23 double COLUMN_DESCRIPTION
PAQ_24 double COLUMN_DESCRIPTION
PAQ double COLUMN_DESCRIPTION
edu_dich integer COLUMN_DESCRIPTION
econom_stat_dich integer COLUMN_DESCRIPTION

```

dichotomization of variables

```

paq.validation.study <- paq.validation.study %>% dplyr::mutate(edu_dich = as.factor(ifelse( educa-
tion == "University master or higher", "University", "lower_edu" )), econom_stat_dich = as.factor(ifelse(
economical_status == "Student", "Student", "non_student" )))

```

RCI	<i>Reliable Change Index (RCI)</i>
-----	------------------------------------

Description

This function calculates Reliable Change Index (RCI) as modified by Wiger and Solberg (2001, p.148).

Usage

```
RCI(SD_0, test.ret.rel)
```

Arguments

SD_0	standard deviation of the non-clinical population
test.ret.rel	test-retest reliability of the instrument

Format

numeric vector of values

Details

This function computes value corresponding to "the minimum amount of change that could not be attributed to the error of measurement" (Biescad & Timulak, 2014, p. 150). If score change from before to post treatment is lower than value resulting from this function, than change in client score can not be attributed to the effectiveness of the therapy but rather other factors such as a measurement error (Biescad & Timulak, 2014). This function is a result of modification of the original Jacobson and Truax (1991) formula by Wiger and Solberg (2001, p.148).

Value

numeric vector

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

Jacobson, N. S., & Truax, P. (1991). Clinical significance: A statistical approach to defining meaningful change in psychotherapy research. *Journal of Consulting and Clinical Psychology*, 59(1), 12-19, DOI: <https://doi.org/10.1037/0022-006X.59.1.12>

Matus Biescad & Ladislav Timulak (2014). Measuring psychotherapy outcomes in routine practice: Examining Slovak versions of three commonly used outcome instruments, *European Journal of Psychotherapy & Counselling*, 16:2, 140-162, DOI: <https://doi.org/10.1080/13642537.2014.895772>

Wiger, D. E., & Solberg, K. B. (2001). *Tracking Mental Health Outcomes: A Therapist's Guide to Measuring Client Progress, Analyzing Data, and Improving Your Practice* (1., Vol. 2001). Wiley.

See Also

[clin_sig_chang\(\)](#) function for calculation of the clinical cut-off scores

Examples

```
re.ch.in = RCI(SD_0 = 4.87, test.ret.rel = 0.66)
re.ch.in
```

small_boot_table

Summarizing Bootstrapped Network Estimates from 'bootnet'

Description

Summarizing Bootstrapped Network Estimates from 'bootnet'

Usage

```
small_boot_table(bootnet_output, predict_function_output = NULL)
```

Arguments

`bootnet_output` output from the 'bootnet' package after bootstrapping network analysis.
`predict_function_output`
optional, output from a predictability analysis function.

Format

An object of class "tibble".

Details

This function provides a convenient summary of bootstrapped network estimates from the 'bootnet' package, including edge weights and their confidence intervals. Optionally, it can also include node predictability metrics if provided. It is tailored to enhance the usability of 'bootnet' output by summarizing critical metrics in a concise format.

Value

A tibble summarizing edge weights and, optionally, node predictability.

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

Epskamp, S., Borsboom, D., & Fried, E. I. (2018). Network analysis: An integrative approach to the structure of psychopathology. *Annual review of clinical psychology*, 14, 91-121.

Examples

```
# Load required package
library(bootnet)

# Simulate data using base R
set.seed(123)
Sigma <- matrix(0.5, nrow = 5, ncol = 5) + diag(0.5, 5)
chol_decomp <- chol(Sigma)
z <- matrix(rnorm(100 * 5), nrow = 100, ncol = 5)
sim_data <- z %*% chol_decomp
sim_data_df <- as.data.frame(sim_data)

# Estimate a network using 'EBICglasso'
estimate <- bootnet::estimateNetwork(sim_data_df, default = "EBICglasso")

# Perform bootstrapping on the estimated network
boot_results <- bootnet::bootnet(estimate, nBoots = 100, nCores = 1)

# Summarize the bootstrapped network
summary <- small_boot_table(bootnet_output = boot_results)
print(summary)
```

`two.g.comp`*Automatic two-groups comparison*

Description

Automatic two-groups comparison

Usage

```
two.g.comp(df, y, group.var)
```

Arguments

<code>df</code>	data frame or tibble with one socio-demographic variable and one continuous variable
<code>y</code>	continuous variable
<code>group.var</code>	binary grouping variable

Format

An object of class "tibble"

Details

This function computes either Wilcoxon test or t-test depending on whether homogeneity of variances assumption is met or not.

Value

data frame

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

Myles Hollander and Douglas A. Wolfe (1973). Nonparametric Statistical Methods. New York: John Wiley & Sons. Pages 27–33 (one-sample), 68–75 (two-sample). Or second edition (1999).

Examples

```
Sex = rbinom(1:100, size = 0:1, prob = .5)
test.dat = data.frame(cbind(Sex), Empathy = ifelse(Sex == 0,
                                                    rnorm(n = 1:100, mean = 50, sd = 10),
                                                    rnorm(n = 1:100, mean = 10, sd = 25)))

# running the function
two.g.comp.out.EC = two.g.comp(df = test.dat, y = "Empathy", group.var = "Sex")
# printing the output
print(two.g.comp.out.EC)
```

`word2pdf`*word to pdf*

Description

Conversion of word document to pdf using either R Markdown package or Libre office. The latter represents higher quality approach - in general.

Usage

```
word2pdf(imp_file, out_file)
```

Arguments

<code>imp_file</code>	name of the word document to convert - without docx suffix
<code>out_file</code>	name of output pdf file without - without pdf suffix

Format

An object of class "pdf"

Details

this function is currently running only on windows

Value

pdf file

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

Examples

```
# example from word do pdf
#word2pdf(imp_file = "example.docx",out_file = "example1.pdf")
```

Index

- * **'bootnet'**
 - small_boot_table, [12](#)
- * **Dunn-test**
 - mult.g.comp, [8](#)
- * **Games-Howell**
 - mult.g.comp, [8](#)
- * **MI,**
 - mitab, [6](#)
- * **Wilcoxon**
 - two.g.comp, [14](#)
- * **analysis,**
 - small_boot_table, [12](#)
- * **a**
 - mitab, [6](#)
- * **bootstrapping,**
 - small_boot_table, [12](#)
- * **comparison,**
 - two.g.comp, [14](#)
- * **datasets**
 - paq.validation.study, [9](#)
- * **equivalence,**
 - mitab, [6](#)
- * **group**
 - two.g.comp, [14](#)
- * **invariance**
 - mitab, [6](#)
- * **linear-regression**
 - lasy.lin.reg, [3](#)
- * **logistic-regression**
 - lasy.log.reg, [5](#)
- * **measurement**
 - mitab, [6](#)
- * **multiple-groups**
 - mult.g.comp, [8](#)
- * **network**
 - small_boot_table, [12](#)
- * **of**
 - mitab, [6](#)
- * **pdf,word**
 - word2pdf, [15](#)
- * **test,**
 - mult.g.comp, [8](#)
- * **testing,**
 - mult.g.comp, [8](#)
- * **test**
 - two.g.comp, [14](#)
- * **two**
 - two.g.comp, [14](#)
- clin_sig_chang, [2](#)
- clin_sig_chang(), [12](#)
- lasy.lin.reg, [3](#)
- lasy.log.reg, [5](#)
- mitab, [6](#)
- mult.g.comp, [8](#)
- paq.validation.study, [9](#)
- RCI, [11](#)
- RCI(), [3](#)
- small_boot_table, [12](#)
- two.g.comp, [14](#)
- word2pdf, [15](#)