

Package ‘psychtoolbox’

August 18, 2022

Title Tools for psychology and psychometrics

Version 0.0.0.9000

Description This package contains functions helping to analyse psychological data.

License CC BY 4.0

URL <https://gitlab.com/lukas.novak/psychtoolbox>

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.0

Imports coin,
docextractr,
dplyr,
foreign,
magrittr,
rmarkdown,
rstatix,
stats,
tidyr,
expss,
insight,
stringr,
tidyselect,
vctrs,
purrr,
reshape2,
janitor,
broom

Suggests testthat (>= 3.0.0)

Config/testthat/edition 3

Depends R (>= 2.10)

R topics documented:

clin_sig_chang	2
dat	3

lasy.log.reg	4
mult.g.comp	5
paq.validation.study	7
RCI	8
two.g.comp	10
word2pdf	11
Index	12

clin_sig_chang	<i>Clinically significant change</i>
----------------	--------------------------------------

Description

This easy function calculates Clinically significant change (clinical cut-off scores) as defined by Jacobson and Truax (1991).

Usage

```
clin_sig_chang(SD_0, SD_1, M_1, M_0)
```

Arguments

SD_0	standard deviation of the non-clinical population
SD_1	standard deviation of the clinical population
M_1	mean of the clinical population
M_0	mean of the non-clinical population

Format

numeric vector of values

Details

This function computes cut-off score differentiating between the clinical and non-clinical population based on the Jacobson and Truax (1991) formula (p. 13). The mathematical formula can be also found in Biescad & Timulak(2014, p. 150).

Value

numeric vector

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

Jacobson, N. S., & Truax, P. (1991). Clinical significance: A statistical approach to defining meaningful change in psychotherapy research. *Journal of Consulting and Clinical Psychology*, 59(1), 12-19, DOI: <https://doi.org/10.1037/0022-006X.59.1.12>

Matus Biescad & Ladislav Timulak (2014). Measuring psychotherapy outcomes in routine practice: Examining Slovak versions of three commonly used outcome instruments, *European Journal of Psychotherapy & Counselling*, 16:2, 140-162, DOI: <https://doi.org/10.1080/13642537.2014.895772>

See Also

[RCI\(\)](#) function for calculation of the Reliable Change Index

Examples

```
clin.cut.off=clin_sig_chang(SD_0 = 3.5,  
                           SD_1 = 2.1,  
                           M_0 = 4.2,  
                           M_1 = 12.1)  
clin.cut.off
```

dat	<i>IRI validation dataset</i>
-----	-------------------------------

Description

This dataset consists the two variables which were used in the study examining psychometric properties of the Interpersonal Reactivity Index.

Usage

dat

Format

A data frame with 835 rows and 2 variables:

Gender integer COLUMN_DESCRIPTION

IRI_EC double COLUMN_DESCRIPTION

Details

DETAILS

lasy.log.reg	<i>Lasy logistic regression function</i>
--------------	--

Description

This function performs logistic regression and print results in tibble output. This function aims to provide the results of the regression analysis in the format, which is frequently desired in academic journals

Usage

```
lasy.log.reg(  
  independent.var,  
  dependent.var,  
  covariates,  
  print.cov = FALSE,  
  data  
)
```

Arguments

independent.var	independent variable/s
dependent.var	dependent variable/s
covariates	covariates to be included in a model
print.cov	Print effect of covariates, default is FALSE
data	data frame or tibble object

Format

An object of class "tibble"

Details

Currently, this function does not provide model fit indicators such as AIC or BIC

Value

data frame

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

- Welch, B. L. (1947). "The generalization of "Student's" problem when several different population variances are involved". *Biometrika*. 34 (1–2): 28–35.
- Wilcoxon, F., Individual Comparisons by Ranking Methods, *Biometrics Bulletin*, Vol. 1, 1945, pp. 80–83. DOI:10.2307/3001968
- Dunn, O. J. (1961) Multiple comparisons among means. *Journal of the American Statistical Association*. 56, 52–64.
- Games, P. A., Keselman, H. J., & Clinch, J. J. Tests for homogeneity of variance in factorial designs. *Psychological Bulletin*, 86, 978–984

Examples

```
# data loading
data(paq.validation.study)
# dichotomization of variables
paq.validation.study <- paq.validation.study %>%
  dplyr::mutate(edu_dich = as.factor(ifelse(
    education == "University master or higher",
    "University", "lower_edu"
  )),
  econom_stat_dich = as.factor(ifelse(
    economical_status == "Student",
    "Student", "non_student"
  )))

# dichotomization of variables
regress.output <- lasy.log.reg(independent.var = c("TEQ", "PAQ", "G_EOT", "G_DDF"),
  covariates = c("Age"),
  dependent.var = c("econom_stat_dich",
    "family_status",
    "edu_dich"),
  data = "paq.validation.study")

print(regress.output)
```

mult.g.comp

Robust multi-group comparison

Description

This function allows to compare multiple groups in multiple outcome variables with violated parametric assumptions.

Usage

```
mult.g.comp(df, outcome.var, groups)
```

Arguments

df	data frame or tibble object
outcome.var	continuous variable/s
groups	grouping variable/s

Format

An object of class "tibble"

Details

Currently, this function does not use para

Two group comparison:

If there is less than three groups, the Welch test or the Wilcoxon test depending on data distribution.

Three and more groups comparison:

If more than two groups are present in data, the Dunn test or Games-Howell test is performed.

Value

data frame

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

Welch, B. L. (1947). "The generalization of "Student's" problem when several different population variances are involved". *Biometrika*. 34 (1–2): 28–35.

Wilcoxon, F., Individual Comparisons by Ranking Methods, *Biometrics Bulletin*, Vol. 1, 1945, pp. 80–83. DOI:10.2307/3001968

Dunn, O. J. (1961) Multiple comparisons among means. *Journal of the American Statistical Association*. 56, 52–64.

Games, P. A., Keselman, H. J., & Clinch, J. J. Tests for homogeneity of variance in factorial designs. *Psychological Bulletin*, 86, 978–984

Examples

```
# data loading
data(dat)
tab.1=mult.g.comp(df = paq.validation.study, outcome.var = c("PAQ", "G_DIF", "G_DDF", "G_EOT"),
groups = c("economical_status",
           "Gender",
           "education",
           "family_status"))
# printing the output
print(tab.1)
```

paq.validation.study *paq.validation.study*

Description

This dataset contains data which were used for validation of the Perth Alexithymia Questionnaire in the Czech Republic.

Usage

paq.validation.study

Format

A data frame with 848 rows and 53 variables:

P_DIF double COLUMN_DESCRIPTION
 P_DDF double COLUMN_DESCRIPTION
 P_DAF double COLUMN_DESCRIPTION
 N_DIF double COLUMN_DESCRIPTION
 N_DDF double COLUMN_DESCRIPTION
 N_DAF double COLUMN_DESCRIPTION
 G_EOT double COLUMN_DESCRIPTION
 G_DIF double COLUMN_DESCRIPTION
 G_DDF double COLUMN_DESCRIPTION
 G_DAF double COLUMN_DESCRIPTION
 family_status integer COLUMN_DESCRIPTION
 Gender integer COLUMN_DESCRIPTION
 TEQ_1 double COLUMN_DESCRIPTION
 TEQ_3 double COLUMN_DESCRIPTION
 TEQ_5 double COLUMN_DESCRIPTION
 TEQ_16 double COLUMN_DESCRIPTION
 TEQ_CON_2 double COLUMN_DESCRIPTION
 TEQ_CON_4 double COLUMN_DESCRIPTION
 TEQ_CON_14 double COLUMN_DESCRIPTION
 TEQ double COLUMN_DESCRIPTION
 Age double COLUMN_DESCRIPTION
 age_group double COLUMN_DESCRIPTION
 age.quality double COLUMN_DESCRIPTION
 ethnicity integer COLUMN_DESCRIPTION
 education integer COLUMN_DESCRIPTION
 economical_status integer COLUMN_DESCRIPTION
 PAQ_1 double COLUMN_DESCRIPTION

```

PAQ_2 double COLUMN_DESCRIPTION
PAQ_3 double COLUMN_DESCRIPTION
PAQ_4 double COLUMN_DESCRIPTION
PAQ_5 double COLUMN_DESCRIPTION
PAQ_6 double COLUMN_DESCRIPTION
PAQ_7 double COLUMN_DESCRIPTION
PAQ_8 double COLUMN_DESCRIPTION
PAQ_9 double COLUMN_DESCRIPTION
PAQ_10 double COLUMN_DESCRIPTION
PAQ_11 double COLUMN_DESCRIPTION
PAQ_12 double COLUMN_DESCRIPTION
PAQ_13 double COLUMN_DESCRIPTION
PAQ_14 double COLUMN_DESCRIPTION
PAQ_15 double COLUMN_DESCRIPTION
PAQ_16 double COLUMN_DESCRIPTION
PAQ_17 double COLUMN_DESCRIPTION
PAQ_18 double COLUMN_DESCRIPTION
PAQ_19 double COLUMN_DESCRIPTION
PAQ_20 double COLUMN_DESCRIPTION
PAQ_21 double COLUMN_DESCRIPTION
PAQ_22 double COLUMN_DESCRIPTION
PAQ_23 double COLUMN_DESCRIPTION
PAQ_24 double COLUMN_DESCRIPTION
PAQ double COLUMN_DESCRIPTION
edu_dich integer COLUMN_DESCRIPTION
econom_stat_dich integer COLUMN_DESCRIPTION

```

Details

DETAILS

RCI	<i>Reliable Change Index (RCI)</i>
-----	------------------------------------

Description

This function calculates Reliable Change Index (RCI) as modified by Wiger and Solberg (2001, p.148).

Usage

```
RCI(SD_0, test.ret.rel)
```


Arguments

SD_0 standard deviation of the non-clinical population
test.ret.rel test-retest reliability of the instrument

Format

numeric vector of values

Details

This function computes value corresponding to "the minimum amount of change that could not be attributed to the error of measurement" (Biescad & Timulak, 2014, p. 150). If score change from before to post treatment is lower than value resulting from this function, then change in client score can not be attributed to the effectiveness of the therapy but rather other factors such as a measurement error (Biescad & Timulak, 2014). This function is a result of modification of the original Jacobson and Truax (1991) formula by Wiger and Solberg (2001, p.148).

Value

numeric vector

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

Jacobson, N. S., & Truax, P. (1991). Clinical significance: A statistical approach to defining meaningful change in psychotherapy research. *Journal of Consulting and Clinical Psychology*, 59(1), 12-19, DOI: <https://doi.org/10.1037/0022-006X.59.1.12>

Matus Biescad & Ladislav Timulak (2014). Measuring psychotherapy outcomes in routine practice: Examining Slovak versions of three commonly used outcome instruments, *European Journal of Psychotherapy & Counselling*, 16:2, 140-162, DOI: <https://doi.org/10.1080/13642537.2014.895772>

See Also

[clin_sig_chang\(\)](#) function for calculation of the clinical cut-off scores

Examples

```
re.ch.in = RCI(SD_0 = 4.87, test.ret.rel = 0.66)
re.ch.in
```

`two.g.comp`*Automatic two-groups comparison*

Description

Automatic two-groups comparison

Usage

```
two.g.comp(df, y, group.var)
```

Arguments

<code>df</code>	data frame or tibble with one socio-demographic variable and one continuous variable
<code>y</code>	continuous variable
<code>group.var</code>	binary grouping variable

Format

An object of class "tibble"

Details

This function computes either Wilcoxon test or t-test depending on whether homogeneity of variances assumption is met or not.

Value

data frame

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

References

Myles Hollander and Douglas A. Wolfe (1973). Nonparametric Statistical Methods. New York: John Wiley & Sons. Pages 27–33 (one-sample), 68–75 (two-sample). Or second edition (1999).

Examples

```
# data loading
data(dat)
# running the function
two.g.comp.out.EC = two.g.comp(df = dat, y = "IRI_EC", group.var = "Gender")
# printing the output
print(two.g.comp.out.EC)
```

`word2pdf`*word to pdf*

Description

Conversion of word document to pdf using either R Markdown package or Libre office. The latter represents higher quality approach - in general.

Usage

```
word2pdf(imp_file, out_file)
```

Arguments

<code>imp_file</code>	name of the word document to convert - without docx suffix
<code>out_file</code>	name of output pdf file without - without pdf suffix

Format

An object of class "pdf"

Details

this function is currently running only on windows

Value

pdf file

Author(s)

Lukas Novak, <lukasjirinovak@gmail.com>

Examples

```
# example from word do pdf
#word2pdf(imp_file = "example.docx",out_file = "example1.pdf")
```

Index

- * **Wilcoxon**
 - two.g.comp, [10](#)
- * **comparison,**
 - two.g.comp, [10](#)
- * **datasets,**
 - two.g.comp, [10](#)
- * **datasets**
 - dat, [3](#)
 - paq.validation.study, [7](#)
- * **group**
 - two.g.comp, [10](#)
- * **pdf,word**
 - word2pdf, [11](#)
- * **test**
 - two.g.comp, [10](#)
- * **two**
 - two.g.comp, [10](#)
- clin_sig_chang, [2](#)
- clin_sig_chang(), [9](#)
- dat, [3](#)
- lasy.log.reg, [4](#)
- mult.g.comp, [5](#)
- paq.validation.study, [7](#)
- RCI, [8](#)
- RCI(), [3](#)
- two.g.comp, [10](#)
- word2pdf, [11](#)