

# hu-berlin-bundle

Documents and Documentations for  $\text{\LaTeX}$  at the  
Humboldt-Universität zu Berlin (unofficial)

»Documentation must be regarded as an integral part of the process of design and coding. A good programming language will encourage and assist the programmer to write clear, self-documenting code, and even perhaps to develop and display a pleasant style of writing.«  
[3, p. 195]

# Contents

<b>1</b>	<b>Introduction—3</b>
1.1	Installation of the bundle—3
1.2	Changelog—3
1.2.1	v1.0.9 (2021/01/10)—3
1.2.2	v1.0.8 (2020/10/30)—3
1.2.3	v1.0.7 (2020/10/29)—4
1.2.4	v1.0.6 (2020-10-22)—4
1.2.5	v1.0.5 (2020-04-28)—4
1.2.6	v1.0.4 (2019-12-19)—4
1.2.7	v1.0.3 (2019-06-26)—4
1.2.8	v1.0.2 (2019-06-22)—4
1.2.9	v1.0.1 (2019-06-21)—4
1.2.10	v1.0.0 (2019-06-21)—4
1.3	Copyright—4
1.3.1	Boilerplate / markdown-template—5
<b>2</b>	<b>Preamble—6</b>
<b>I</b>	<b>GUIDELINE FOR USERS</b>
<b>3</b>	<b>Letter—8</b>
3.1	.lco-file—8
3.2	.tex-file—10
3.3	Letter from markdown—12
<b>II</b>	<b>GUIDE FOR CODERS</b>
<b>4</b>	<b>hu-berlin-base-package—15</b>
<b>5</b>	<b>Letter—16</b>
<b>6</b>	<b>Boilerplate / Template for letters—24</b>
<b>7</b>	<b>Documentation preamble &lt;style&gt;—26</b>
<b>III</b>	<b>EXAMPLE FILES</b>
<b>8</b>	<b>Letter—43</b>
8.1	From .tex—43
8.2	From .md—45

# 1 Introduction

With this (unofficial) bundle you have several documents which are designed according to the corporate design of the Humboldt-Universität zu Berlin.

Following documents or documentclasses are available:

- **letter** (hu-berlin-letter.cls); via .tex and .md
- **base package** (hu-berlin-base.sty)

## 1.1 Installation of the bundle

hu-berlin is part of the distributions [MiKTeX](#) and [TeXLive](#) – thus, you can easily install it using the respective package manager. If you would like to install hu-berlin-bundle into your local folder manually, do the following: Go to your terminal, browse to the folder of this bundle and run

```
make install
```

If you are using macOS you might be asked for your user account password for the installation.

Further options of this makefile are:

- **clean**: deletes all unnecessary files
- **cleanbundle**: deletes all files except .dtx, .md. You will get the plain version of this bundle. This might be helpful if you send the bundle to someone else.
- **ctan**: this will create a zip file which can be used to send to CTAN.
- **files**: will only create the files from the .dtx-scratch.
- **uninstall**: will erase the locally installed files.

This bundle is constantly updated. For hints, errors or suggestions use the GitHub repository <https://github.com/LukasCBossert/hu-berlin-bundle>.

## 1.2 Changelog

All notable changes to this project will be documented in the [README.md](#). This project **does not** adhere to [Semantic Versioning](#). The markdown syntax is inspired by the conventions proposed by [keepachangelog.com](#).

### 1.2.1 v1.0.9 (2021/01/10)

- (letter) making everything multi-lingual (at least German and English); German is default language. You can load English e.g. by `documentclass[english]{hu-berlin-letter}` (addresses [issue No. 3](#))

### 1.2.2 v1.0.8 (2020/10/30)

- (letter) replacing actual logo with a dummy text (due to possible copyright conflicts). The correct logo has to be called `hu-berlin-logo.pdf` and needs to be put somewhere

in PATH so it will be found. If such file cannot be found a dummy text will be taken instead ('Humboldt-Universität zu Berlin')

### 1.2.3 v1.0.7 (2020/10/29)

- (letter) fixed missing `\removerefferfields`
- (letter) added missing suffix for hu-logo (`.pdf`)

### 1.2.4 v1.0.6 (2020-10-22)

- (letter) changed address separator
- (letter) fixed empty minipage when no metadata given
- (letter) changed default backaddress

### 1.2.5 v1.0.5 (2020-04-28)

- (general) Changed logo format to `.pdf`
- (letter) Changed `\ifkomavareempty` to `\ifkomavareempty`, fixes [github-issue nr. 1](#)

### 1.2.6 v1.0.4 (2019-12-19)

- Added `hu-berlin-base.sty` as a package which contains all relevant code for documents and documentclasses of the bundle.

### 1.2.7 v1.0.3 (2019-06-26)

- Changed the main font for compatibility with UNIX-systems (TeX Gyre Heros instead of Verdana).

### 1.2.8 v1.0.2 (2019-06-22)

Renaming files for CTAN compatability.

### 1.2.9 v1.0.1 (2019-06-21)

Internal changes for publishing. Still one documentclass for a letter.

### 1.2.10 v1.0.0 (2019-06-21)

First release with a documentclass for letter.

## 1.3 Copyright

Various parts of this bundle have different copyrights. If not otherwise stated the copyright is [The LaTeX project public license \(LPPL\)](#), version 1.3c

### 1.3.1 Boilerplate / markdown-template

The template for the markdown conversion, forked from the pandoc-templates and [JensErat pandoc-scrilttr2](#) is dual-licensed, under both the GPL (v2 or higher, same as pandoc) and the BSD 3-clause license (included below).

---

Copyright (c) 2014, John MacFarlane Copyright (c) 2014, Jens Erat All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of John MacFarlane nor the names of other contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

## 2 Preamble

This bundle consists of various files which are either generated by the core file (`.dtx`) or are part of the basic structure of this bundle. You can easily pick up the basic file structure from [fig. 2.1](#).

```

hu-berlin-bundle
├── hu-berlin-bundle.dtx ..... code and documentation
├── hu-berlin-bundle.pdf ..... documentation
├── hu-berlin-base.sty ..... basic components of the bundle
├── hu-berlin-letter-example-lualatex.tex ..... letter
├── hu-berlin-letter-example.lco ..... datafile for letter
├── hu-berlin-letter-example-lualatex.pdf ..... letter
├── hu-berlin-letter-example-markdown.pdf .... converted letter from markdown
├── hu-berlin-letter-example-markdown.md ..... example markdown file
├── hu-berlin-letter-template.latex ..... template for conversion
├── img ..... folder for images
│   └── texografie-logo.pdf ..... logo of maintainer
├── makefile ..... makefile to generate all required files
└── README.md ..... README file with information on installation

```

Figure 2.1: Structure of `hu-berlin` bundle

When you run the `makefile` you get all these various files described above.

A large, light gray, serif capital letter 'I' is centered vertically and horizontally on the page. It serves as a background element for the title.

# Guideline for Users

1 `\example`

## 3 Letter

We give an example on how to create a letter.

### 3.1 `.lco`-file

2 `\lco`

This is the file you load into your `.tex` letter. The information you provide here do normally not change from letter to letter. That's why we put it in a separate file.

The first line should provide this information.

3 `\ProvidesFile{hu-berlin-letter-example.lco}`

Now we set up the personal data.

We start with the name of the sender.

4 `\setkomavar{fromname}`

you can also write the position of this person in brackets, this is optional; [`\position`]

5 `[Wissenschaftlicher Mitarbeiter]`

But you need to give a name:

6 `{Dr. Max Mustermann}`

The mail address

7 `\setkomavar{fromemail}{max.mustermann@hu-berlin.de}`

For phone and fax number you only need to type the last digits.

8 `\setkomavar{fromphone}{1234}`

If you don't have a fax (or a phone), leave it empty. Do *not* delete it.

9 `\setkomavar{fromfax}{5678}`

And finally the URL.

10 `\setkomavar{fromurl}{www.hu-berlin.de}`

If your backaddress is too long – it will be set up automatically – you can redefine it.

11 `%% \setkomavar{backaddress}{HU Berlin\\`

12 `%% Unter den Linden 6\\`

13 `%% D-10099 Berlin}`

Selfexplaining: the faculty.

14 `\setkomavar{faculty}{%`

15 `Philosophische Fakultät`

16 `}`

17 `\setkomavar{institute}{%`



```

18 \mbox{Institut für Briefvorlagen}
19 }

20 \setkomavar{institute.additional}{Here you can add more text.}

21 \setkomavar{institute.head}[Dekanin]{Prof. Dr. Maike Musterfrau}

22 \setkomavar{institute.head.mail}{maike.musterfrau@hu-berlin.de}

23 \setkomavar{office}{%
24   Mohrenstraße 40/41\\
25   Zimmer X\\
26   D-10117 Berlin}

27 \setkomavar{connections}{U Bahnhof Hausvogteiplatz (U2)}

28 \setkomavar{accessibility}{Hausvogteiplatz}

29 \setkomavar{signature}{%
30   \usekomavar{institute.head} --
31   \usekomavar{fromname}
32 }
33 </lco>

```

## Example 1

```

1 \ProvidesFile{hu-berlin-letter-example.lco}
2 \setkomavar{fromname}
3   [Wissenschaftlicher Mitarbeiter]
4   {Dr. Max Mustermann}
5 \setkomavar{fromemail}{max.mustermann@hu-berlin.de}
6 \setkomavar{fromphone}{1234}
7 \setkomavar{fromfax}{5678}
8 \setkomavar{fromurl}{www.hu-berlin.de}
9 %% \setkomavar{backaddress}{HU Berlin\\
10 %% Unter den Linden 6\\
11 %% D-10099 Berlin}
12 \setkomavar{faculty}{%
13 Philosophische Fakultät
14 }
15 \setkomavar{institute}{%
16   \mbox{Institut für Briefvorlagen}
17 }
18 \setkomavar{institute.additional}{Here you can add more text.}
19 \setkomavar{institute.head}[Dekanin]{Prof. Dr. Maike
20   Musterfrau}
21 \setkomavar{institute.head.mail}{maike.musterfrau@hu-berlin.de}
22 \setkomavar{office}{%
23   Mohrenstraße 40/41\\
24   Zimmer X\\
25   D-10117 Berlin}
26 \setkomavar{connections}{U Bahnhof Hausvogteiplatz (U2)}
27 \setkomavar{accessibility}{Hausvogteiplatz}
28 \setkomavar{signature}{%
29   \usekomavar{institute.head} --
30   \usekomavar{fromname}

```

```

30 }
31 %%

```

### 3.2 .tex-file

```

34 \let*letter)

35 \documentclass{hu-berlin-letter}

```

Now we load the personal data-file which has the ending .lco.

```

36 \LoadLetterOption{hu-berlin-letter-example}

```

If you have the HU font installed on your computer, you can load it, too:

```

37 % \setmainfont[%
38 %     BoldFont=ScalaSans-BoldLF,
39 %     Numbers=OldStyle]{ScalaSans-RegularLF}

```

Now following the reference information

```

40 \setkomavar{myref}{}
41 \setkomavar{yourref}{}
42 \setkomavar{yourmail}{}
43 \setkomavar{customer}{}
44 \setkomavar{invoice}{}
45 \setkomavar{subject}{Betreff}
46 \usepackage{blindtext}

```

We close the preamble and start the letter

```

47 \begin{document}

```

The address is written as `{\address}`

```

48 \begin{letter}{%
49     Erika Musterfrau\par
50     Musterweg 43\par
51     56789 Musterhausen%

```

Closing now again.

```

52 }

53 \opening{Sehr geehrte Frau Musterfrau,}

```

This is just some blindtext.

```

54 \blindtext[2]
55 \clearpage
56 \blindtext

```

Closing letter

```
57 \closing{Mit freundlichen Grüßen}
```

If you still have something to say/write.

```
58 \ps PS: \dots
```

Any amendment.

```
59 \encl{%
60   Anlage 1\\
61   Anlage 2%
62 }
```

This is the distribution

```
63 \cc{%
64   Verteiler 1\\
65   Verteiler 2%
66 }
```

That's it. Done.

```
67 \end{letter}
68 \end{document}
```

And how does a example letter looks like?

Example 2

```
1  \documentclass{hu-berlin-letter}
2  \LoadLetterOption{hu-berlin-letter-example}
3  \setkomavar{myref}{}
4  \setkomavar{yourref}{}
5  \setkomavar{yourmail}{}
6  \setkomavar{customer}{}
7  \setkomavar{invoice}{}
8  \setkomavar{subject}{Betreff}
9  \usepackage{blindtext}
10 \begin{document}
11 \begin{letter}{%
12   Erika Musterfrau\par
13   Musterweg 43\par
14   56789 Musterhausen%
15 }
16 \opening{Sehr geehrte Frau Musterfrau,}
17 \blindtext[2]
18 \clearpage
19 \blindtext
20 \closing{Mit freundlichen Grüßen}
21 \ps PS: \dots
22 \encl{%
23   Anlage 1\\
24   Anlage 2%
25 }
26 \cc{%
27   Verteiler 1\\
28   Verteiler 2%
29 }
30 \end{letter}
31 \end{document}
```

69 `</letter>`

### 3.3 Letter from markdown

70 `<{*letter-md>`

You need to have `pandoc` installed on your computer. To create letters via markdown and `pandoc` run from the command line:

**!** `pandoc -pdf-engine=lualatex -template hu-berlin-letter-template.latex -o YOUR-FILE.pdf YOUR-FILE.md`

The `.md` file needs a section with metadata.

It starts and ends with three `---`. All necessary metadata information are listed inbetween.

71 `---`

72 `documentclass: hu-berlin-letter`

The following will load the `.lco`-file, you replace that with the name of your `.lco`-file.

73 `sender: hu-berlin-letter-example`

You should also tell a short subject

74 `subject: Short description`

And if you want to have a different language, define it now. You can choose between German (default) and English.

75 `lang: english`

The information for the addressee has to be written like this:

76 `addressee:`

77 `- Alexander von Humboldt`

78 `- Unter den Linden 6`

79 `- 10099 Berlin`

80 `---`

You find a list with possible options for this metadata information header below.

Now the content of your letter

81 `Thank you very much for your letter.`

Let's see how this example file looks like:

## Example 3

```
1 ---
2 documentclass: hu-berlin-letter
3 sender: hu-berlin-letter-example
4 subject: Short description
5 lang: english
6 addressee:
7 - Alexander von Humboldt
8 - Unter den Linden 6
9 - 10099 Berlin
10 ---
11 Thank you very much for your letter.
```

82 `</letter-md>`

Here we close the example files.

83 `</example>`



## Guide for Coders

1 `\*sty`

## 4 hu-berlin-base-package

2 `\*base`

Since we do want to compile with Lua<sup>A</sup>T<sub>E</sub>X, we make sure that it will be compilable only with that.

3 `\RequirePackage{ifluatex, luatex85}`

Now a fix.<sup>1</sup>

4 `\ifx\directlua\relax`

5 `\let\directlua\UnDeFiNeD`

6 `\fi`

7 `\ifluatex`

8 `\else`

9 `\GenericError{hu-berlin}%`

10 `{Please use 'LuaLaTeX' as Compiler.^^J I abort here.}`

11 `\fi`

We do not need many packages. The ones we need are loaded now.

12 `\RequirePackage[english,ngerman]{babel}`

Common package for handling figures is **graphicx** [1].

13 `\RequirePackage{graphicx}`

For loading fonts.

14 `\RequirePackage{fontspec}`

Actually the corporate design says that the font Verdana should be used. But since this font is not included in UNIX-systems we use a derivative.

15 `\setmainfont{TeX Gyre Heros}`

If you have Verdana on your system you can uncomment the following line.

16 `% \setmainfont{Verdana}`

For the wheelchair symbol we load **marvosym** [2]

17 `\RequirePackage{marvosym}`

And we define various colors from the corporate design manual.

18 `\RequirePackage{xcolor}`

19 `\definecolor{hu-berlin-blue}{RGB}{0,65,137}`

20 `\definecolor{hu-berlin-green}{RGB}{150,190,20}`

21 `\definecolor{hu-berlin-grey}{RGB}{169,169,169}`

22 `\definecolor{hu-berlin-brown}{RGB}{82,79,60}`

<sup>1</sup> <https://tex.stackexchange.com/a/75065>

```
23 \definecolor{hu-berlin-red}{RGB}{180,0,0}
```

That's all for the base package, so we close it.

```
24 </base>
```

```
25 </sty>
```

```
26 <*cls>
```

## 5 Letter

```
27 <*letter>
```

We load **scrlettr2** [5] which is the documentclass for letters. Furthermore we set up some options. The default language is German. But all strings are also available for English. You can load English as option to the documentclass.

```
28 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{scrlettr2}}
```

```
29 \DeclareOption{english}{\PassOptionsToPackage{ngerman,main=english}{babel}}
```

```
30 \DeclareOption{ngerman}{\PassOptionsToPackage{ngerman}{babel}}
```

```
31 \ExecuteOptions{ngerman}
```

```
32 \ProcessOptions\relax
```

Now the documentclass itself.

```
33 \LoadClass[%
```

```
34   fontsize=10pt,
```

```
35   version=last,
```

If there is anything to debug, you can enable visualize

```
36   % visualize
```

```
37 ]{scrlettr2}
```

For debugging also uncomment the `\showfields{<fields>}` command.

```
38 % \showfields{head, address, location, refile, foot}
```

Since all common and basic features of the bundle are located in a separate package we load that first.

```
39 \RequirePackage{hu-berlin-base}
```

To get the HU logo on the second and following pages we load **scrlayer-scrpage** [4].<sup>1</sup>

```
40 \RequirePackage{scrlayer-scrpage}
```

```
41 \clearpaairofpagestyles
```

```
42 \DeclareNewLayer[
```

```
43   foreground,
```

```
44   voffset=\useplength{firstheadvpos},
```

```
45   hoffset=\useplength{firstheadhpos},
```

<sup>1</sup> <https://tex.stackexchange.com/a/495258/98739>



```

46 width=\useplength{firstheadwidth},
47 mode=picture,
48 contents=\putUL{\raisebox{-\height}{\usekomavar{firsthead}}}{\likefirstpage.head}
49 ]{\likefirstpage.head}
50 \AddLayersToPageStyle{scrheadings}{\likefirstpage.head}
51 \DeclareNewLayer[
52 foreground,
53 align=r,
54 voffset=\useplength{locvpos},
55 hoffset=\paperwidth-\useplength{lochpos},
56 width=\useplength{locwidth},
57 height=\useplength{locheight},
58 contents=\usekomavar{nextlocation},
59 %pretoccontents=\layercontentsmeasure% to show the position of the layer
60 ]{\likefirstpage.loc}
61 \AddLayersToPageStyle{scrheadings}{\likefirstpage.head,\likefirstpage.loc}

```

Now we apply the code for following pages.

```

62 \newkomavar{nextlocation}
63 \setkomavar{nextlocation}{%
64   \raggedright
65   \fontsize{7}{8.5}\selectfont
66   \pagemark
67 }

```

For better adjustments of the layout we load **geometry** [9].

```

68 \RequirePackage{geometry}
69 \geometry{%
70   a4paper
71   ,left           =25mm
72   ,bottom         =16mm
73   ,foot           =4mm
74   ,top            =77mm
75   ,headheight     =15pt
76   ,textwidth      =117mm
77   ,marginparsep   =0mm
78   ,marginparwidth =0mm
79 }

```

Main Text and signature should be raggedright.

```

80 \renewcommand*{\raggedsignature}{\raggedright}
81 \raggedright

```

We also want to put the enclosures at the bottom of the page.<sup>2</sup>

```

82 \def\stopletter{}
83 \let\enclold\encl
84 \renewcommand\encl[1]{\vskip0ptplus1filll\enclold{#1}}

```

<sup>2</sup> <https://tex.stackexchange.com/questions/77991/put-the-encl-at-the-bottom-of-the-page-lettre-cl>

We define new komavars and we make it for German and for English as well.

```

85 \providcaptionname{english}{\hubCCseparator}{Copy to}
86 \providcaptionname{english}{\hubEnclSeparator}{Attachment}
87 \providcaptionname{english}{\hubMyRef}{Reference:}
88 \providcaptionname{english}{\hubFromName}{Clerk:}
89 \providcaptionname{english}{\hubDate}{Date:}
90 \providcaptionname{english}{\hubAddress}{Postal address:}
91 \providcaptionname{english}{\hubConnections}{Public transport:}
92 \providcaptionname{english}{\hubOffice}{Office:}
93 \providcaptionname{english}{\hubBank}{Bank:}
94 \providcaptionname{english}{\hubOfficeHours}{Consultation hours:}
95 \providcaptionname{english}{\hubAccessibility}{Entrance:}

```

Now for German.

```

96 \providcaptionname{ngerman}{\hubCCseparator}{Kopie an}
97 \providcaptionname{ngerman}{\hubEnclSeparator}{Anlage}
98 \providcaptionname{ngerman}{\hubMyRef}{Geschäftszeichen:}
99 \providcaptionname{ngerman}{\hubFromName}{Bearbeiter:}
100 \providcaptionname{ngerman}{\hubDate}{Datum:}
101 \providcaptionname{ngerman}{\hubAddress}{Postanschrift:}
102 \providcaptionname{ngerman}{\hubConnections}{Verkehrsverbindungen:}
103 \providcaptionname{ngerman}{\hubOffice}{Sitz:}
104 \providcaptionname{ngerman}{\hubBank}{Bank:}
105 \providcaptionname{ngerman}{\hubOfficeHours}{Sprechzeiten:}
106 \providcaptionname{ngerman}{\hubAccessibility}{Eingang:}

```

First the possibility to name the faculty,

```

107 \newkomavar{faculty}
108 \newkomafont{faculty}{\bfseries\fontsize{8.5}{10}\selectfont}

```

then the institute

```

109 \newkomavar{institute}
110 \newkomafont{institute}{\fontsize{8.5}{10}\selectfont}

```

and further fields for information.

```

111 \newkomavar{institute.additional}

```

We pass the name of the head of the institute.

```

112 \newkomafont{institute.head}{\bfseries}
113 \newkomavar{institute.head}%

```

Its position will be written as the optional argument.

There is even the possibility to print the email-address onto the letter.

```

114 \newkomavar{institute.head.mail}%

```

Since there are many buildings with offices we tell where to find the sender

```

115 \newkomavar{office}
116 \setkomavar*{office}{\hubOffice}

```

and how to get there.

```

117 \newkomavar{connections}

```

```
118 \setkomavar*{connections}{\hubConnections}
```

Furthermore we inform about office hours

```
119 \newkomavar{officehours}
120 \setkomavar*{officehours}{\hubOfficeHours}
```

and if there is accessibility for wheelchairs etc.

```
121 \newkomavar{accessibility}
122 \setkomavar*{accessibility}{\large\reflectbox{\Wheelchair}} \hubAccessibilit

123 \newkomavar{bank}
124 \setkomavar*{bank}{\hubBank}
125 \setkomavar{bank}{Deutsche Bank PGK AG}
126 \newkomavar{IBAN}
127 \setkomavar{IBAN}{\mbox{IBAN DE95 1007 0848 0512 6206 01}}
128 \newkomavar{BIC}
129 \setkomavar{BIC}{BIC DEUTDEDB110}
```

Now we set the location field, which is the section on the right with additional information:

```
130 \setkomavar{location}{%}
```

First anything regarding the font

```
131 \raggedright
132 \fontsize{7}{8.5}\selectfont
133 % \begin{macrocode}
134 % and for the section of faculty, institute etc. we use \env{minipage}
135 % \begin{macrocode}
136 \begin{minipage}[t][64mm]{\useplength{locwidth}}
```

then the faculty

```
137 \Ifkomavareempty{faculty}
```

This is a fake space to avoid any trouble if no custom metadata are given.

```
138 {\hspace*{1em}}
139 {\usekomafont{faculty}%
140 \usekomavar{faculty}\\[1\baselineskip]}
```

and the institute.

```
141 \Ifkomavareempty{institute}
142 {}
143 {\usekomafont{institute}\usekomavar{institute}\\[1\baselineskip]}
```

Now anything else regarding the institute.

```
144 \Ifkomavareempty{institute.additional}
145 {}
146 {\usekomavar{institute.additional}\\[1\baselineskip]}
```

What follows is the head of institute and its position name.

```
147 \Ifkomavareempty{institute.head}
148 {}
149 {\usekomafont{institute.head}%
150 \usekomavar{institute.head}}\\%
```

```
151 \usekomavar*{institute.head}}
```

We close this section and the minipage.

```
152 \end{minipage}
```

Let's turn to further information.

For example date:

```
153 \textbf{\usekomavar*{date}}\\
154 \usekomavar{date}\par
```

and the sender of the letter.

```
155 \Ifkomavareempty{fromname}
156 {}
157 {\textbf{\usekomavar*{fromname}}}\\
158 \usekomavar{fromname}\par}
```

And the reference of correspondence.

```
159 \Ifkomavareempty{myref}
160 {}
161 {\textbf{\usekomavar*{myref}}}\\
162 \usekomavar{myref}\par}
```

To complete this template we provide the possibility to name further reference fields.

```
163 \Ifkomavareempty{yourref}
164 {}
165 {\textbf{\usekomavar*{yourref}}}\\
166 \usekomavar{yourref}\par}

167 \Ifkomavareempty{yourmail}
168 {}
169 {\textbf{\usekomavar*{yourmail}}}\\
170 \usekomavar{yourmail}\par}
```

```
171 \Ifkomavareempty{customer}
172 {}
173 {\textbf{\usekomavar*{customer}}}\\
174 \usekomavar{customer}\par}
```

```
175 \Ifkomavareempty{invoice}
176 {}
177 {\textbf{\usekomavar*{invoice}}}\\
178 \usekomavar{invoice}\par}
```

```
179 \textbf{\usekomavar*{fromaddress}}\\
180 \usekomavar{fromaddress}
181 \Ifkomavareempty{fromphone}
182 {\par}
183 {\\\usekomavar*{fromphone}\usekomavar{fromphone}}
184 \Ifkomavareempty{fromfax}
185 {\par}
186 {\\\}}
```

```

187 \Ifkomavareempty{fromfax}
188 {}
189 {\usekomavar*{fromfax}\usekomavar{fromfax}\par}

```

#### Next, emails and url:

```

190 \Ifkomavareempty{institute.head.mail}
191 {}
192 {\usekomavar{institute.head.mail}
193 \Ifkomavareempty{fromemail}
194 {\Ifkomavareempty{fromurl}
195 {\par}
196 {\}}
197 {\}}

198 \Ifkomavareempty{fromemail}
199 {}
200 {\usekomavar{fromemail}
201 \Ifkomavareempty{fromurl}
202 {\par}
203 {\}}

204 \Ifkomavareempty{fromurl}
205 {}
206 {\usekomavar{fromurl}\par}

```

#### Now the actual location of the sender

```

207 \Ifkomavareempty{office}
208 {}
209 {\textbf{\usekomavar*{office}}}\
210 \usekomavar{office}\par}

```

#### The last information section should be pinned to the bottom.

```

211 \vfill

```

#### Inform your addressee about the connection possibilities.

```

212 \Ifkomavareempty{connections}
213 {}
214 {\textbf{\usekomavar*{connections}}}\
215 \usekomavar{connections}\par}

216 \Ifkomavareempty{officehours}
217 {}
218 {\textbf{\usekomavar*{officehours}}}\
219 \usekomavar{officehours}\par}

```

#### If there is a barrier free entrance, tell it.

```

220 \Ifkomavareempty{accessibility}
221 {}
222 {\textbf{\usekomavar*{accessibility}}}\
223 \usekomavar{accessibility}\par}

```

And last the bank connection

```
224 \Ifkomavareempty{bank}
225   {}
226   {\textbf{\usekomavar*{bank}}}\
227   \usekomavar{bank}\
228   \usekomavar{IBAN}\
229   \usekomavar{BIC}
230 }
```

Finally we close `\setkomavar{<location>}`

```
231 }
```

To fulfill the Corporate Design rules we adjust a few things.

```
232 \KOMAOptions{%
233   numericaldate =true
234   ,refline      =nodate
235   ,backaddress  =plain
236   ,parskip      =half-
237 }
```

Getting rid of all other fields and their default position.

```
238 \removereffield
```

Redefining length.

```
239 \setlength{refvpos}{110mm}
240 \setlength{refaftervskip}{0pt}
241 \setlength{toaddrhpos}{25mm}
242 \setlength{firstheadhpos}{\uselength{toaddrhpos}}
243 \setlength{lochpos}{15mm}
244 \setlength{locvpos}{\uselength{toaddrvpos}}
245 \addtoplength{locvpos}{.75\baselineskip}
246 \setlength{locwidth}{45mm}
247 \setlength{locheight}{232mm}
```

Now resetting or pre-defining some variables.

First we set the head of the first page, which is the logo. Be sure that you have the right using it! Everything regarding the logo is defined in the corporate design guidelines.<sup>3</sup> You need to have the actual logo of the Humboldt-Universität zu Berlin which has to be called `hu-berlin-logo.pdf`. It can be downloaded here: <http://zope.hu-berlin.de/hu-intern/design/downloads/logo> If this logo is not found a replacement text is shown instead.

```
248 \setkomavar{firsthead}{%
249 \IfFileExists{hu-berlin-logo.pdf}
250   {\includegraphics[width=145mm]{hu-berlin-logo.pdf}}
251   {\vspace*{2em}\hfil\scshape [humboldt-universität zu berlin]}}%
252 }

253 \setkomavar{backaddressseparator}{~\textbar~}
```

<sup>3</sup> <https://www.hu-berlin.de/de/hu-intern/design/basiselemente/leitfaden-corporate-design-hu.pdf>

```

254 \setkomavar{fromphone}{0000}
255 \setkomavar*{fromphone}{Telefon +49 [30] 2093-}

256 \setkomavar{fromfax}{0000}
257 \setkomavar*{fromfax}{Telefax +49 [30] 2093-}

258 \setkomavar*{fromaddress}{\hubAddress}
259 \setkomavar{fromaddress}{%
260   Humboldt-Universität zu Berlin\\
261   Unter den Linden 6\\
262   D-10099 Berlin}

```

The default backaddress is slightly changed:

```

263 \setkomavar{backaddress}{%
264   Humboldt-Universität zu Berlin\\
265   UdL 6\\
266   D-10099 Berlin}

267 \setkomavar*{date}{\hubDate}

268 \setkomavar*{fromname}{\hubFromName}

269 \setkomavar*{myref}{\hubMyRef}

270 \setkomavar*{enclseparator}{\hubEnclSeparator}

271 \setkomavar*{ccseparator}{\hubCCseparator}

272 % \RequirePackage{hyperref}
273 % \AtBeginDocument{ {
274 %   \usekomavar[\def\author]{fromname}
275 %   \usekomavar[\def\subject]{subject}
276 %   \hypersetup{%
277 %     pdftitle           = {\subject},
278 %     pdfauthor          = {\author},
279 %     pdfsubject         = {\subject},
280 %     pdfkeywords        = {\author, \subject},
281 %     pdflang            = de,
282 %     pdfdisplaydoctitle = true,
283 %     colorlinks         = true,
284 %     plainpages         = false,
285 %     hypertextnames     = false,
286 %     unicode,
287 %   }
288 % } }

289 </letter>

290 </cls>

291 <*template>

```

## 6 Boilerplate / Template for letters

292 `\letter-md`

Defining the documentclass and the language, too.

```
293 \documentclass[
294 $if(lang)$lang$endif$
295 ]{hu-berlin-letter}
```

We predefine two variables.

```
296 \newkomavar{opening}
297 \newkomavar{closing}
298 \setkomavar{opening}{Sehr geehrte Damen und Herren}
299 \setkomavar{closing}{Mit freundlichen Grüßen}

300 $for(letteroption)$
301 \LoadLetterOption{$letteroption$}
302 $endfor$
303 $if(sender)$\LoadLetterOption{$sender$}$endif$
304 $if(addresseeimage)$\setkomavar{addresseeimage}{$addresseeimage$}$endif$
305 $if(backaddress)$\setkomavar{backaddress}{$backaddress$}\KOMAOPTIONS{backad
306 $if(fromalign)$\KOMAOPTIONS{fromalign=$fromalign$}$endif$
307 $if(customer)$\setkomavar{customer}{$customer$}$endif$
308 $if(date)$\setkomavar{date}{$date$}$endif$
309 $if(fromaddress)$\setkomavar{fromaddress}{$fromaddress$}$endif$
310 $if(frombank)$\setkomavar{frombank}{$frombank$}$endif$
311 $if(fromemail)$\setkomavar{fromemail}{$fromemail$}\KOMAOPTIONS{fromemail=true
312 $if(fromfax)$\setkomavar{fromfax}{$fromfax$}\KOMAOPTIONS{fromfax=true}$endi
313 $if(fromlogo)$\setkomavar{fromlogo}{$fromlogo$}\KOMAOPTIONS{fromlogo=true}$S
314 $if(frommobilephone)$\setkomavar{frommobilephone}{$frommobilephone$}\KOMAOPT
315 $if(fromname)$\setkomavar{fromname}{$fromname$}$endif$
316 $if(fromphone)$\setkomavar{fromphone}{$fromphone$}\KOMAOPTIONS{fromphone=tru
317 $if(fromurl)$\setkomavar{fromurl}{$fromurl$}\KOMAOPTIONS{fromurl=true}$endi
318 $if(fromzipcode)$\setkomavar{fromzipcode}{$fromzipcode$}$endif$
319 $if(invoice)$\setkomavar{invoice}{$invoice$}$endif$
320 $if(location)$\setkomavar{location}{$location$}$endif$
321 $if(myref)$\setkomavar{myref}{$myref$}$endif$
322 $if(myrefname)$\setkomavar*{myref}{$myrefname$}$endif$
323 $if(place)$\setkomavar{place}{$place$}$endif$
324 $if(PPcode)$\setkomavar{PPcode}{$PPcode$}$endif$
325 $if(signature)$\setkomavar{signature}{$signature$}$endif$
326 $if(specialmail)$\setkomavar{specialmail}{$specialmail$}$endif$
327 $if(subject)$\setkomavar{subject}{$subject$}$endif$
328 $if(title)$\setkomavar{title}{$title$}$endif$
```



```

329 $if(yourmail)$\setkomavar{yourmail}{${yourmail$}}$endif$
330 $if(yourref)$\setkomavar{yourref}{${yourref$}}$endif$
331 $if(opening)$\setkomavar{opening}{${opening$}}$endif$
332 $if(closing)$\setkomavar{closing}{${closing$}}$endif$
333 $if(firstfoot)$\setkomavar{firstfoot}{${firstfoot$}}$endif$

```

Ok, let's sum up the possible options you can use to pass data to the letter:

- addresseeimage
- backaddress
- customer
- date
- fromaddress
- frombank
- fromemail
- fromfax
- fromlogo
- frommobilephone
- fromname
- fromphone
- fromurl
- fromzipcode
- invoice
- location
- myref
- myrefname
- place
- PPcode
- signature
- specialmail
- subject
- title
- yourmail
- yourref
- opening
- closing
- firstfoot

Sometimes you might not have an addressee – we are checking this, too.

```

334 $if(addressee)$
335 $else$
336 \KOMAOPTIONS{addrfield=false}
337 $endif$

```

Now the actual content of the letter

```

338 \begin{document}
339 \begin{letter}{%
340 $for(addressee)$
341 $addressee$$sep$\\

```

```

342 $endfor$
343 }
344 $for(include-before)$
345 $include-before$
346 $endfor$
347 \opening{\usekomavar{opening}}
348 $body$
349 \closing{\usekomavar{closing}}
350 $if(ps)$\ps{$ps$}$endif$
351 $if(encl)$\encl{$encl$}$endif$
352 $for(include-after)$$include-after$$endfor$
353 \end{letter}
354 \end{document}

355 </letter-md>
356 </template>

```

## 7 Documentation preamble <style>

```

357 <*sty>
358 <*style>
359 \makeatletter
360 \addtolength\marginparwidth{-40pt}
361 \addtolength\marginparsep{4mm}
362 \addtolength\oddsidemargin{-20pt}
363 \addtolength\evensidemargin{-20pt}
364 \let\PrintDescribeMacro=\@gobble
365 \let\PrintDescribeEnv=\@gobble
366 % \def\Describe@Macro#1{\endgroup
367 %     %\marginnote{\PrintDescribeMacro{#1}}%
368 %     \SpecialUsageIndex{#1}\@esphack\ignorespaces%
369 %     }
370 % \def\Describe@Env#1{\endgroup
371 %     %\marginnote{\PrintDescribeEnv{#1}}%
372 %     \SpecialEnvIndex{#1}\@esphack\ignorespaces%
373 %     }
374 \makeatother
375 \AtBeginDocument{\normalmarginpar}
376 \setlength\MacrocodeTopsep{.5\baselineskip}
377 \setlength\MacroIndent{6mm}
378
379
380 \RequirePackage{luatexbase}

```

```

381 \RequirePackage[ngerman,english]{babel}
382 \RequirePackage{calc}
383
384 \RequirePackage[
385   paper      = a4paper, % - use A4 paper size
386   foot       = 2cm,
387   inner      = 3cm, % - total body: left margin (odd pages)
388   top        = 3cm, % - total body: top margin
389   outer      = 3cm, % - total body: right margin (odd pages)
390   bottom     = 3cm, % - total body: bottom margin
391   marginparwidth = 2cm, % - width for side note
392   marginparsep = .5cm, % - space between notes and body text (content)
393 % showframe,
394 ]{geometry}
395
396 \newlength\fullwidth
397 \setlength\fullwidth{\textwidth+\marginparwidth+\marginparsep}
398
399 \KOMAOptions{
400 numbers      = noenddot,
401 }
402 \AtBeginDocument{
403   \KOMAOptions{
404 % headwidth  = {\fullwidth},
405 % footwidth  = {\fullwidth},
406 footheight = 20pt,
407 headheight = 29pt,
408 captions    = tableheading,
409 }}
410
411
412
413 \title{\huberlintitle}
414 %\subtitle{\huberlinsubtitle}
415 \author{\huberlinauthor}
416 \date{\Version}
417
418
419 %---- Required Packages
420 \RequirePackage{ifluatex,luatex85}
421 \ifx\directlua\relax
422   \let\directlua\UnDeFiNeD
423 \fi
424 \ifluatex
425 \else
426 \GenericError{hu-berlin}%
427 {Please use 'LuaLaTeX' as Compiler.^^J I abort here.}

```

428 \fi

For fonts we load the package **fontspec** [8] which has almost no limits handling font-stuff.

```
429 \RequirePackage{fontspec}

430 \RequirePackage[mono=false]{libertine}
431 \RequirePackage{amssymb}
432
433 \defaultfontfeatures{%
434   Ligatures = TeX
435 }
```

For fonts we use the available TeX Gyre Pagella as main font.<sup>1</sup>

```
436 \setmainfont[%
437   Ligatures = TeX
438   ,Numbers   = OldStyle]{TeX Gyre Pagella}
```

And we declare also the other fonts, too.

```
439 \setmonofont[%
440   Scale=1
441 ]{TeX Gyre Cursor}
442 \setsansfont[%
443   ,LetterSpace = .8
444 ]{TeX Gyre Adventor-Regular}
445 \linespread{1.05}

446
447
448
449 \RequirePackage{marginnote}
450 \renewcommand*{\marginfont}{%
451   \rule{0pt}{0.7\baselineskip}%
452   \footnotesize%
453   \color{hu-berlin-brown}}
454
455 \RequirePackage[
456   german = guillemets,
457   style   = german,
458 ]{csquotes}
459
460 \RequirePackage{enumitem}
461 \setlist{
462   nosep,
463   % itemindent=1em,
464   % labelindent=0.5\parindent,
465   leftmargin=*}
466 \newlist{tabitemize}{itemize}{2}% neue Listenumgebung
467 \setlist{tabitemize}{%
```

<sup>1</sup> <http://www.gust.org.pl/projects/e-foundry/tex-gyre>

```

468 nose,
469 leftmargin=*
470 }
471 \setlist[tabitemize,1]{label=\labelitemi}
472 \setlist[tabitemize,2]{label=\labelitemii}
473
474
475 \clubpenalty=10000 % prevent single lines at the beginning of a paragraph
476 \widowpenalty=10000 % prevent single lines at the end of a paragraph (Huren
477 \displaywidowpenalty=10000 %
478
479 \RequirePackage{pdfpages}
480 \RequirePackage{biblatex}
481 \addbibresource{\jobname-bibliography.bib}
482 \addbibresource{\jobname-ctan.bib}
483 \RequirePackage{ccicons} %creative commons
484 \RequirePackage{xparse}
485 \RequirePackage{ragged2e}
486 \RequirePackage{microtype}
487 \RequirePackage{xspace}
488 \RequirePackage{graphicx}
489 \graphicspath{{img/}}

490 \RequirePackage{etoolbox}
491 %https://tex.stackexchange.com/a/235881/98739
492 \AfterEndPreamble{%
493   \maketitle
494   \renewcommand\MacroFont{\ttfamily}
495   \renewcommand\AltMacroFont{\ttfamily\linespread{.8}}% slanted verbatim
496 }
497
498 % https://tex.stackexchange.com/a/401466/98739
499 \makeatletter
500 \renewcommand*{\maketitle}{%
501   % taken and shortened from /usr/share/texmf/tex/latex/koma-script/scrartcl
502   \begin{titlepage}
503     \newgeometry{left=3cm, right=3cm, top=1.5cm, bottom=2cm}
504     \global\@topnum=\z@
505     \setparsizes{\z@}{\z@}{\z@\@plus 1fil}\par@updaterelative
506     \null
507     {\large\@author\hfill \href{mailto:lukas@texografie.de}{lukas@texografie.de}
508     \vskip 10em%
509     {\begin{center}\color{hu-berlin-blue}
510     {\fontsize{50}{55}\selectfont\huberlinshort{} \par\vskip .5em%
511     \Large\sffamily\@title}\par
512     \vskip .5em
513     \end{center}}}%

```

```

514 {\ifx\@subtitle\@empty\else\usekomafont{subtitle}\@subtitle\par\fi}%
515 \null\vskip 5em%
516 \blockcquote[195]{Hoare1973}{Documentation must be regarded as an integral p
517 A good programming language will encourage and assist the programmer to wr
518 self-documenting code,
519 and even perhaps to develop
520 and display a pleasant style
521 of writing.}
522 \null\vfill
523 {\usekomafont{subtitle}{\@date \hfill
524 \includegraphics[width=4cm]{img/texografie-logo.pdf}\}\}%
525 \par
526 \vskip 0em
527 \restoregeometry
528 \end{titlepage}
529 }%
530 \makeatother
531
532 \RequirePackage{xcolor}
533 \definecolor{hu-berlin-blue}{RGB}{0,65,137} % HEX 004189
534 \definecolor{hu-berlin-green}{RGB}{150,190,20} % HEX 93C11A % Topoi
535 \definecolor{hu-berlin-grey}{RGB}{169,169,169}
536 \definecolor{hu-berlin-brown}{RGB}{82,79,60}
537 \definecolor{hu-berlin-red}{RGB}{180,0,0}
538
539
540 \RequirePackage{dirtree}
541 \renewcommand*{DTstylecomment}{%
542 \color{hu-berlin-grey}%
543 \footnotesize%
544 \sffamily}
545 \renewcommand*{DTstyle}{%
546 \ttfamily%
547 \small%
548 }
549
550 \RequirePackage[
551 markcase = noupper,
552 footsepline = .5pt,
553 % headsepline = .5pt,
554 autooneside = false,% use left and right marks with a onesided document
555 automark,% set \leftmark and \rightmark automatically by *\section and \s
556 draft = false,
557 ]{scrlayer-scrpage}
558
559 \pagestyle{scrheadings}
560 \clearscrheadfoot

```

```

561 \rofoot*{\thepage}
562 \lofoot*{\textcolor{hu-berlin-blue}{\huberlintitle}\ \vrule\ \textcolor{hu-
    berlin-brown}{\huberlinsubtitle}}
563 \rohead*{hu-berlin-bundle}
564 \lohead*{Version: \Version}

565 % https://tex.stackexchange.com/a/352925/98739
566 \newcommand*\partnumber{}
567 \DeclareNewLayer[
568   background,
569   textarea,
570   addwidth=\marginparsep+\marginparwidth,
571   mode=picture,
572   contents={%
573 \putC{\makebox[0pt][c]{\raisebox{-.5\height}{\scalebox{50}{\textcolor{black}
574   }}}
575 ]{\partnumber}
576 \DeclareNewPageStyleByLayers{part}{\partnumber}
577 \renewcommand\partpagestyle{part}
578 \renewcommand*\{\partformat}{\gdef\partnumber{\thepart}}
579
580 % only a dirty workaround for the part title
581 \newcommand*\changedpartwidth[1]{%
582   \makebox[\linewidth][l]{%
583 \parbox{\dimexpr\textwidth+\marginparsep+\marginparwidth\relax}{\raggedpart
584   }}%
585 }
586 % add \changedpartwidth as last command to the settings for font element pa
587 \addtokomafont{part}{\Huge\changedpartwidth}
588
589
590
591 %-https://tex.stackexchange.com/a/339516/98739 | https://tex.stackexchange.
592 % footnotes in the footer:
593 \deffootnote%
594   %[\normalparindent]%<width of mark>
595   {0.0cm}%<indent of footnote text>
596   {\normalparindent}%<paragraph indent in the footnote text>
597   {\makebox[\normalparindent][r]%
598   {\thefootnotemark\hspace*{3pt}}}%<definition of mark>
599 \newlength{\normalparindent}
600 \AtBeginDocument{\setlength{\normalparindent}{\parindent}}
601 \setfootnoterule{0pt}% Kein Fußnotenstrich
602 %\setfootnoterule[<height>]{<length>}
603

```

This will put the numbers of the chapters and sections into the margin.

```

604 \renewcommand\sectionlinesformat[4]{%

```

```

605 \makebox[0pt][r]{#3}#4%
606 }

607 \RequirePackage{url}
608 % \urlstyle{same}
609
610 \setkomafont{title}{\sffamily\color{hu-berlin-blue}\flushleft\bfseries}
611 \setkomafont{disposition}{\color{hu-berlin-brown}\sffamily\bfseries\large}
612 \setkomafont{section}{\usekomafont{disposition}}
613 \setkomafont{subsection}{\usekomafont{disposition}}
614 \setkomafont{subsubsection}{\usekomafont{disposition}}
615 % \setkomafont{paragraph}{\bfseries}
616 % \setkomafont{subsubsection}{\sffamilybold}
617 \setkomafont{subtitle}{\large\color{hu-berlin-brown}\sffamily\flushleft}
618 \setkomafont{pageheadfoot}{\footnotesize\sffamily\color{hu-berlin-
  grey}}
619 \setkomafont{descriptionlabel}{\bfseries}
620 \setkomafont{footnotelabel}{\bfseries}
621 \addtokomafont{titlehead}{\flushright}
622 % \setkomafont{headsepline}{\color{hu-berlin-blue}}
623 % \setkomafont{marginnote}{\MakeUppercase\color{hu-berlin-brown}}
624 \addtokomafont{caption}{\scriptsize}
625 \setkomafont{captionlabel}{\bfseries\sffamily}
626 \setkomafont{subject}{\bfseries\sffamily}
627 \setcapindent{0pt}
628
629 \raggedbottom
630
631 \RequirePackage{listings}
632 \PassOptionsToPackage{final}{listings}
633 \RequirePackage[%
634   skins
635   , listings
636   , breakable
637   , xparse
638   , documentation
639 ]{tcolorbox}
640 \lstMakeShortInline[language=TeX,basicstyle=\ttfamily]

```

Following we load **hyperxmp** [7] and **hyperref** [6] for PDF-meta data and interactive linked text.

```

641 \RequirePackage{hyperxmp}
642 \RequirePackage{hyperref}
643 \hypersetup{% setup the hyperref-package options
644   unicode      = true,
645   pdfauthor     = {hu-berlin}, % - author (PDF meta)
646   pdfauthortitle = {},
647   pdfcopyright  = {Copyright (c) \the\year . All rights reserved.},

```



```

648 pdfhighlight      = /N,
649 pdfdisplaydoctitle = true,
650 pdflang           = {}, %de en
651 pdfcaptionwriter   = {Lukas C. Bossert},
652 pdfkeywords        = {hu-berlin},
653 pdfencoding        = auto,
654 pdfproducer        = {hu-berlin with LuaLaTeX},
655 bookmarksnumbered  = true,
656 bookmarksopenlevel = 2,
657 bookmarksopen      = true,
658 bookmarksdepth     = 3,
659 colorlinks         = true,      %Colours links instead of ugly boxes
660 urlcolor           = hu-berlin-blue, %Colour for external hyperlinks
661 linkcolor          = black,      %Colour of internal links
662 citecolor          = black,      %Colour of citations
663 linktoc            = page,
664 pdfborder          = {0 0 0},
665 breaklinks         = true,      %allow line break inside links
666 final
667 }
668 \RequirePackage{bookmark}
669
670 \RequirePackage[
671   sort,
672   nameinlink,
673   compress,
674   ngerman, english
675 ]{cleveref}
676
677
678 %---- newcommands
679 \newcommand{\TeXografie}{Lukas C. Bossert
680   (www.texografie.de) }
681 \newcommand\huberlin{\huberlintitle\xspace}
682
683
684 \newcommand\huberlinFolder{%
685   \begingroup%
686   \normalfont%
687   \color{hu-berlin-blue}%
688   % \faFolderOpen% taken from fontawesome
689   \hspace{.3em}%
690   \endgroup}
691
692
693
694 \RedeclareSectionCommands[

```

```

695   tocraggedpagenumber,
696   toclinefill=\tocpageseparator,
697   tocindent=0em,
698   tocnumwidth=4em,
699   tocpagenumberbox=\tocpagenumberbox% <- added
700 %   tocpagenumberformat=\textsf,
701 ]{chapter, section, subsection, subsubsection, paragraph}
702
703 \newcommand\tocgobble[1]{}% <- added
704 \newcommand\tocpageseparator{\footnotesize\,\mbox{---}\,}
705 \newcommand\tocpagenumberbox[1]{\mbox{#1}}% <- added
706 \KOMAoptions{toc=indentunnumbered}
707
708 \RedeclareSectionCommand[
709 %   tocbeforeskip=1.25em plus 1pt
710   ,tocentryformat=\large\scshape%
711   ,tocindent=0em
712   ,tocnumwidth=4em
713   ,tocpagenumberbox=\tocgobble% <- added
714 ]{part}
715 %\addtokomafont{partentry}{\scshape\sffamily\bfseries}
716
717 \RedeclareSectionCommand[%
718 %   ,beforeskip=1.15em plus 1pt%
719 ,tocentryformat=\textbf%
720 %   ,toclinefill={\TOCLineLeaderFill}%\TOCLineLeaderFill[\textbf{.}]
721 ]{chapter}
722
723
724
725
726 \newtcolorbox{example}[1][]{
727   breakable,
728   top=5pt,
729   bottom=5pt,
730   colback=hu-berlin-blue!10,
731   colframe=hu-berlin-blue,
732   left=5pt,
733   right=5pt,
734   sharp corners,
735   boxrule=0pt,
736   bottomrule=2pt,
737   toprule=2pt,
738   enhanced jigsaw,
739   lefttitle=0pt,
740   coltitle=white,
741   fonttitle=\bfseries,

```

```

742 fontupper=\small,%\ttfamily,
743 % colbacktitle=hu-berlin-blue!20
744 #1,
745 }
746
747 % Replace the squat-u symbol for spaces
748 % https://tex.stackexchange.com/a/488123/98739
749 \makeatletter
750 \def\lst@visiblespace{\lst@ttfamily{\char32}$\textcolor{hu-berlin-
    grey}{\cdot}$}
751 \makeatother
752
753
754 \lstset{%
755   basicstyle = \linespread{0.7}\ttfamily
756   ,breaklines = true
757   ,breakatwhitespace
758   ,alsoletter=\\{\}\*\{[\]\-
759   ,showstringspaces=true
760 }
761
762 \lstdefinestyle{hu-berlinlistingstyledef}{%
763   tabsize      = 4,
764   breaklines    = true,
765   breakatwhitespace = true,
766   postbreak=\mbox{$\hookrightarrow$},
767   %keepspace    = true,
768   escapeinside = {(*@}{@*)},
769   moredelim    = {[is][\ttfamily\bfseries\color{hu-berlin-blue}]{|}{|}},
770   moredelim    = {[is][\ttfamily\bfseries\color{hu-berlin-blue}]{|1}{1|}},
771   moredelim    = {[is][\ttfamily\bfseries\color{hu-berlin-red}]{|2}{2|}},
772   aboveskip=0pt,
773   belowskip=0pt,
774   captionpos=b,
775   resetmargins=true,
776   sensitive=true,
777   upquote=true,
778   showspaces=true,
779   showtabs=true,
780   tab=\textcolor{hu-berlin-grey}{\rightarrowfill},
781   %numbers=left,
782   %numberstyle=\footnotesize\ttfamily\color{hu-berlin-grey},
783   comment      = [l]{\%},
784   commentstyle = \footnotesize\color{hu-berlin-grey}\addfontfeature{LetterSp
785   % deletecomment = [l]{\%<}
786   % morecomment  = [l][\nullfont]{\%<},
787   % deletecomment = [is]{\%<}{>},

```

```

788 }
789
790 \lstdefinestyle{hu-berlinlistingstyle}{%
791   language   = {TeX},
792   style      = {hu-berlinlistingstyledef},
793 }
794
795
796
797
798
799
800 \tcbset{%
801 hu-berlinstyle/.style={%
802   enhanced,
803   before skip=2mm,
804   after skip=3mm,
805   boxrule=0.7pt,
806   left=2mm,
807   right=2mm,
808   top=2mm,
809   bottom=2mm,
810   sharp corners,
811   colback=white,
812   colbacklower=white,
813   % fonttitle=\sffamily\bfseries,
814   breakable,
815   %before skip=\baselineskip,
816   coltitle=white,
817   colbacktitle=hu-berlin-blue!50!black,
818   fonttitle=\bfseries\sffamily\footnotesize,
819   % before upper={\mynote{\thetcbcounter}},
820   title={\hfill{Example \thetcbcounter}},
821 },
822 codecomment/.style={%
823   listing outside comment,%
824   boxrule=0pt,
825   colback=white,
826 }
827 }
828
829 \newtcolorbox{warning}[1][]{
830   enhanced,
831   before skip=2mm,
832   after skip=3mm,
833   boxrule=0.7pt,
834   left=5mm,

```

```

835 right=2mm,
836 top=2mm,
837 bottom=2mm,
838 colback=white,
839 colframe=yellow!20!black,
840 sharp corners,
841 rounded corners=southeast,
842 arc is angular,
843 arc=3mm,
844 underlay={%
845 \path[fill=hu-berlin-grey!80!black] ([yshift=3mm]interior.south east)--
      ++(-0.4,-0.1)--++(0.1,-0.2);
846 \path[draw=hu-berlin-grey,shorten <=-0.05mm,shorten >=-0.05mm] ([yshift=3mm]
      ++(-0.4,-0.1)--++(0.1,-0.2);
847 \path[fill=red!50!black,draw=none] (interior.south west) rectangle node[white]
848 },
849 drop fuzzy shadow,
850 #1
851 }
852
853 \newtcblisting[%
854 auto counter,
855 crefname = {example}{examples},
856 Crefname = {Example}{Examples},
857 ]{codetext}[2][]{%
858 hu-berlinstyle,
859 % side text,
860 rounded corners=northeast,
861 arc=6mm,
862 listing style=hu-berlinlistingstyle,
863 label = #2,
864 #1,
865 }
866
867 \newtcblisting[%
868 use counter from=codetext,
869 crefname={code example}{code examples},
870 Crefname={Code example}{Code examples}%
871 ]{code}[2][]{%
872 hu-berlinstyle,
873 rounded corners=southeast,
874 arc=6mm,
875 listing only,
876 listing style=hu-berlinlistingstyle,
877 label = #2,
878 #1,
879 }

```

```

880
881
882 \DeclareTCBInputListing[%
883   use counter from=codetext,
884   crefname={code example}{code examples},
885   Crefname={Code example}{Code examples}%
886 ]{\huberlinlisting}{ O{} m }{%
887   hu-berlinstyle,
888   listing file={#2},
889   listing only,
890   listing style=hu-berlinlistingstyle,
891   #1,
892 }
893
894 \makeatletter
895 \newrobustcmd*{\fnurl}[1][\hyper@normalise\ltd@fnurl{#1}]
896 \def\ltd@fnurl#1#2{\footnote{#1\hyper@linkurl{\Hurl{#2}}{#2}}}
897 \makeatother

```

The first command is used to reference packages with: `\pkg{<package name>}`.<sup>2</sup> The name of the package is linked to its entry on CTAN and referenced to the bibliography in the end of this documentation.

```

898 \RequirePackage{newfile}
899 \newoutputstream{pkglist}

900 \NewDocumentCommand{\pkg}{om}{%
901   \IfNoValueTF{#1}
902   {\lowercase{\href{http://www.ctan.org/pkg/#2}}{\textbf{#2}}}
903   {\lowercase{\href{http://www.ctan.org/pkg/#1-#2}}{\textbf{#2}}}%
904   \space\cite{#2}%
905   \addtostream{pkglist}{#2}}

906 \newrobustcmd*{\lit}[1]{\textsf{#1}}
907 \newrobustcmd*{\Code}[1]{\texttt{#1}}
908 \newrobustcmd*{\tex}{\TeX}
909 \newrobustcmd*{\etex}{\mbox{e-TeX}}
910 \newrobustcmd*{\pdftex}{pdf\-\tex}
911 \newrobustcmd*{\xetex}{Xe\-\tex}
912 \newrobustcmd*{\luatex}{Lua\-\tex}
913 \newrobustcmd*{\latex}{\LaTeX}%{La\kern-0.07em TeX}
914 \newrobustcmd*{\pdflatex}{pdf\-\latex}
915 \newrobustcmd*{\xelatex}{Xe\-\latex}
916 \newrobustcmd*{\lualatex}{Lua\-\latex}
917 \newrobustcmd*{\miktex}{Mik\-\tex}
918 \newrobustcmd*{\texlive}{\tex~live}
919 \newrobustcmd*{\bibtex}{Bib\kern-0.07em TeX}

```

<sup>2</sup> Do not forget to insert the name of the package into the makefile in the definition of PKG.

```

920 \newrobustcmd*{\lppl}{\latex{} Project Public License}
921 \newrobustcmd*{\pdf}{{PDF}}
922 \newrobustcmd*{\md}{{Markdown}}
923 \newrobustcmd*{\utf}{\mbox{{UTF}-8}}
924 % no \mbox here, we may have to break things
925 \newrobustcmd*{\bibfield}[1]{\Code{#1}}
926 \newrobustcmd*{\opt}[1]{\Code{#1}}
927 \newrobustcmd*{\bibmacro}[1]{\Code{#1}}
928 \newrobustcmd*{\bibtype}[1]{\Code{@#1}}
929 %\renewrobustcmd*{\cmd}[1]{\Code{\textbackslash #1}}
930 \renewrobustcmd\meta[1]{\normalfont\texttriangle\itshape#1\}{\texttriangle}
931
932 % directly taken from ltxdoc.dtx
933 \renewrobustcmd\marg[1]{%
934   {\ttfamily\textcolor{hu-berlin-red}{\{}}}%
935   \meta{#1}%
936   {\ttfamily\textcolor{hu-berlin-red}{\}}}%
937 }
938
939 \renewrobustcmd\oarg[1]{%
940   {\ttfamily\textcolor{hu-berlin-green}{[]}}%
941   \meta{#1}%
942   {\ttfamily\textcolor{hu-berlin-green}{[]}}}%
943 }
944
945 % adapted from listings.dtx (lstdoc.sty)
946 \renewrobustcmd\cmd[1]{%
947   \texttt{\color{hu-berlin-blue}\textbackslash string#1}\xspace%
948 }
949
950 \newrobustcmd\env[2][]{%
951   \texttt{%
952     \color{hu-berlin-blue}%
953     \textbackslash begin\{\string#2\}#1}%
954     \ldots
955     \texttt{%
956       \color{hu-berlin-blue}%
957       \textbackslash end\{\string#2\}}%
958     \xspace}

```

For a common layout of the parameter style to identify code of the different documents, files and packages we use `\param{<name of the parameter>}`.

```

959 \newcommand\param[1]{%
960   \begingroup%
961   \normalfont%
962   \ttfamily%
963   \bfseries%

```

```

964 \textless%
965 #1%
966 \ttfamily%
967 \bfseries%
968 \textgreater%
969 \endgroup}

970 \pdfstringdefDisableCommands{%
971 \def\lstinline#1{<#1>}
972 \def\tex{TeX}%
973 \def\etex{e-TeX}%
974 \def\xetex{XeTeX}%
975 \def\latex{LaTeX}%
976 \def\xelatex{XeLaTeX}%
977 \def\bibtex{BibTeX}%
978 \def\lppl{LaTeX Project Public License}%
979 \def\pdf{PDF}%
980 \def\utf{UTF-8}%
981 \def\\{\}%
982 \def\texttt#1{<#1>}%
983 \def\marg#1{\{#1\}}%
984 \def\oarg#1{[#1]}%
985 \def\color#1#2{}%
986 \def\env#1{<#1>}
987 \def\cmd#1{#1}
988 }
989 % https://tex.stackexchange.com/a/24067/98739
990 \makeatletter
991 \patchcmd{\scr@startchapter}{\if@openright\cleardoublepage\else\clearpage\fi}{}{}{}
992 \makeatother
993 %
994 \RequirePackage[tightLists=false]{markdown}
995 \markdownSetup{rendererPrototypes={%
996 link = {\href{#3}{#1}}}%
997 }}
998 \</style>

999 \</sty>

```

## References

- [1] David Carlisle and The LaTeX Team. *The Graphicx package. Enhanced support for graphics.* Version 1.2b. Sept. 9, 2020. URL: <http://www.ctan.org/pkg/graphicx> (visited on 01/31/2021).
- [2] Thomas Henlich, Martin Vogel, and Mojca Miklavc. *The Marvosym package. Martin Vogel's Symbols (marvosym) font.* Version 2.2a. URL: <http://www.marvosym.de> (visited on 01/31/2021).



- [3] Charles Antony Richard Hoare. »Hints on programming language design«. In: *Computer Systems Reliability*. Ed. by C. Bunyan. State of the Art Report 20. 1973, pp. 193–216. URL: <http://flint.cs.yale.edu/cs428/doc/HintsPL.pdf> (visited on 09/06/2018).
- [4] Markus Kohm. *The Scrlayer-scrpage package. Define and manage page styles*. Version 3.32. URL: <http://www.komascript.de/> (visited on 01/31/2021).
- [5] Markus Kohm. *The Scrlltr2 package. Koma-Script 'letter' class*. Version 3.30. Apr. 19, 2020. URL: <http://www.komascript.de/> (visited on 01/31/2021).
- [6] Heiko Oberdiek, Sebastian Rahtz, and The LaTeX Team. *The Hyperref package. Extensive support for hypertext in LaTeX*. Version 7.00e. May 15, 2020. URL: <https://github.com/latex3/hyperref> (visited on 01/31/2021).
- [7] Scott Pakin. *The Hyperxmp package. Embed XMP metadata within a LaTeX document*. Version 5.9. Nov. 22, 2020. URL: <http://www.ctan.org/pkg/hyperxmp> (visited on 01/31/2021).
- [8] Will Robertson. *The Fontspec package. Advanced font selection in XeLaTeX and LuaLaTeX*. Version 2.7i. URL: <http://www.ctan.org/pkg/fontspec> (visited on 01/31/2021).
- [9] Hideo Umeki and David Carlisle. *The Geometry package. Flexible and complete interface to document dimensions*. Version 5.9. Jan. 2, 2020. URL: <http://www.ctan.org/pkg/geometry> (visited on 01/31/2021).



Example files

## 8 Letter

### 8.1 From `.tex`

[HUMBOLDT-UNIVERSITÄT ZU BERLIN]

[HUMBOLDT-UNIVERSITÄT ZU BERLIN]

Seite 2

Humboldt-Universität zu Berlin | Udl. 6 | D-10099 Berlin

Erika Musterfrau  
Musterweg 43  
56789 Musterhausen

**Betreff**

Sehr geehrte Frau Musterfrau,

Dies hier ist ein Blindtext zum Testen von Textausgaben. Wer diesen Text liest, ist selbst schuld. Der Text gibt lediglich den Grauwert der Schrift an. Ist das wirklich so? Ist es gleichgültig, ob ich schreibe: „Dies ist ein Blindtext“ oder „Huardest gefburn“? Kjift – mitnichten! Ein Blindtext bietet mir wichtige Informationen. An ihm messe ich die Lesbarkeit einer Schrift, ihre Anmutung, wie harmonisch die Figuren zueinander stehen und prüfe, wie breit oder schmal sie läuft. Ein Blindtext sollte möglichst viele verschiedene Buchstaben enthalten und in der Originalsprache gesetzt sein. Er muss keinen Sinn ergeben, sollte aber lesbar sein. Fremdsprachige Texte wie „Lorem ipsum“ dienen nicht dem eigentlichen Zweck, da sie eine falsche Anmutung vermitteln. Dies hier ist ein Blindtext zum Testen von Textausgaben. Wer diesen Text liest, ist selbst schuld. Der Text gibt lediglich den Grauwert der Schrift an. Ist das wirklich so? Ist es gleichgültig, ob ich schreibe: „Dies ist ein Blindtext“ oder „Huardest gefburn“? Kjift – mitnichten! Ein Blindtext bietet mir wichtige Informationen. An ihm messe ich die Lesbarkeit einer Schrift, ihre Anmutung, wie harmonisch die Figuren zueinander stehen und prüfe, wie breit oder schmal sie läuft. Ein Blindtext sollte möglichst viele verschiedene Buchstaben enthalten und in der Originalsprache gesetzt sein. Er muss keinen Sinn ergeben, sollte aber lesbar sein. Fremdsprachige Texte wie „Lorem ipsum“ dienen nicht dem eigentlichen Zweck, da sie eine falsche Anmutung vermitteln.

**Philosophische Fakultät**  
**Institut für Briefvorlagen**  
**Here you can add more text.**  
**Prof. Dr. Maike Musterfrau**  
**Dekanin**

**Datum:**  
31.1.2021  
**Wissenschaftlicher Mitarbeiter**  
Dr. Max Mustermann  
**Postanschrift:**  
Humboldt-Universität zu Berlin  
Unter den Linden 6  
D-10099 Berlin  
Telefon +49 (30) 2093-1234  
Telefax +49 (30) 2093-5678  
maike.musterfrau@hu-berlin.de  
max.mustermann@hu-berlin.de  
www.hu-berlin.de  
**Sitz:**  
Mötenstraße 40/41  
Zimmer X  
D-10117 Berlin

**Verkehrsverbindungen:**  
U Bahnhof Hausvogteiplatz (U2)  
**Eingang:**  
Hausvogteiplatz  
**Bank:**  
Deutsche Bank PGK AG  
IBAN DE95 1007 0648 0512 6206 01  
BIC DEUTDE33110

Dies hier ist ein Blindtext zum Testen von Textausgaben. Wer diesen Text liest, ist selbst schuld. Der Text gibt lediglich den Grauwert der Schrift an. Ist das wirklich so? Ist es gleichgültig, ob ich schreibe: „Dies ist ein Blindtext“ oder „Huardest gefburn“? Kjift – mitnichten! Ein Blindtext bietet mir wichtige Informationen. An ihm messe ich die Lesbarkeit einer Schrift, ihre Anmutung, wie harmonisch die Figuren zueinander stehen und prüfe, wie breit oder schmal sie läuft. Ein Blindtext sollte möglichst viele verschiedene Buchstaben enthalten und in der Originalsprache gesetzt sein. Er muss keinen Sinn ergeben, sollte aber lesbar sein. Fremdsprachige Texte wie „Lorem ipsum“ dienen nicht dem eigentlichen Zweck, da sie eine falsche Anmutung vermitteln.

Mit freundlichen Grüßen  
  
Prof. Dr. Maike Musterfrau – Dr. Max Mustermann  
  
PS: ...

Anlage: Anlage 1  
Anlage 2  
Kopie an: Verteiler 1  
Verteiler 2

## 8.2 From `.md`

[HUMBOLDT-UNIVERSITÄT ZU BERLIN]

Humboldt-Universität zu Berlin | Udl. 6 | D-10099 Berlin

Alexander von Humboldt  
Unter den Linden 6  
10099 Berlin

Philosophische Fakultät  
Institut für Briefvorlagen

Here you can add more text.

Prof. Dr. Maike Musterfrau  
Dekanin

Short description

Sehr geehrte Damen und Herren

Thank you very much for your letter.

Mit freundlichen Grüßen

Prof. Dr. Maike Musterfrau – Dr. Max Mustermann

Date:  
31/1/2021

Wissenschaftlicher Mitarbeiter  
Dr. Max Mustermann

Postal address:  
Humboldt-Universität zu Berlin  
Unter den Linden 6  
D-10099 Berlin  
Telefon +49 [30] 2093-1234  
Telefax +49 [30] 2093-5678  
mai.k.e.m.u.s.t.e.r.f.r.a.u@h.u-berlin.de  
m.a.x.m.u.s.t.e.r.m.a.n.n@h.u-berlin.de  
www.h.u-berlin.de

Office:  
Möhrrenstraße 40/41  
Zimmer X  
D-10117 Berlin

Public transport:  
U Bahnhof Hausvogteiplatz (U2)

Entrance:  
Hausvogteiplatz

Bank:  
Deutsche Bank PGK AG  
IBAN DE95 1007 0648 0512 6206 01  
BIC DEUTDE33HAN

Documents and Documentations for  $\text{\LaTeX}$  at the Humboldt-Universität zu Berlin (unofficial) | For Authors and Developers

46