

Compare Go Parallel Programming with Python

by Lukas Kiederle

Table of Contents

1. [Motivation](#)
2. [The Raft cluster](#)
3. [The Raft cluster implemented](#)
4. [Conclusion](#)
5. [Sources](#)

Motivation

The problem of having spread data over multiple networks is currently omnipresent. For example databases like [Elastic Search](#) or [Docker Swarm](#) need to deal with this efficiently in order to work reliable.

This paper is going to reflect the technical differences between go and python when building a simulated cluster which contains its status within all of its nodes. This is accomplished with the Raft algorithm which was introduced by Diego Ongaro and John Ousterhou in 2014.

The Raft algorithm

Raft is an understandable distributed consensus algorithm. It was created based on the consensus algorithm [paxos](#). The key goal was to develop an alternative for paxos which is much easier to understand and programmable.

Raft has been proven to be as efficient as paxos but is structured differently. Diego Ongaro also claimed in his paper that Raft is more understandable for students which was verified by a study.

The following chapters describe the Raft algorithm in detail. There will also be a comparison of an implementation in **go** and **python**.

Which problem does Raft solve?

First of all there is a node. A node can store a single value. A client now sends a request to the server(this one node). Coming to an agreement which is the new state is easy. The node just updates its value. But what about having multiple nodes that should contain the same state? How are these nodes finding a consensus?

What are the Raft Basics?

In order to have a working cluster, multiple nodes are needed which know each other. A node can be in one of these three states: FOLLOWER, CANDIDATE or LEADER. FOLLOWER is the starting state for every node. If FOLLOWER-nodes don't hear in a specific time from a LEADER they can become CANDIDATE.

The CANDIDATE requests votes from each other node in the cluster. Every node will answer with their vote. The CANDIDATE becomes the leader if it gets the majority of votes. This process is called leader election. It is described in the next chapter in detail.

The cluster is now in a correct state. This includes having exactly one leader and the majority of nodes being reachable for the leader-node.

All incoming changes to the system now go through the leader-node. Its job is to inform all of his available follower-nodes with the new state. This is accomplished with a 2-phase commit.

The 2-Phase commit

A node can represent one value. It also has an invisible log.

When a leader node sends a status update to all of his followers, the state change is added as an entry in the node's invisible log. The node replies that it stored the value. The leader waits until the majority of nodes have stored the change. If he gets enough responses in a specific time, he sets his state to the new value. Afterwards all other nodes get the info to change to the new state which was saved in the log previously.

The cluster now has come to consensus or agreement about the system state. This is called **log replication**.

What is a leader election in depth?

In Raft there are two timeout settings which control elections. One of them is the election timeout. The election timeout is the amount of time for a follower-node waits until becoming a candidate.

After the election timeout a follower-node becomes a candidate and starts an election term. It then votes for itself and requests votes from all other nodes. If the receiving node hasn't voted yet in this term then it votes for the candidate and the node resets its election timeout. As soon as a candidate-node has more than half of the clusters votes it becomes the leader.

The leader-node begins to send out Append Entries messages to all of its followers. These messages are sent in time periods specified by the heartbeat timeout. Every follower-node responds to every Append Entries message it receives. The leaders tenure will continue until a follower stops receiving heartbeats and becomes a candidate.

Stopping or loosing a leader in an already working cluster ends in a reelection. Only one node can be elected to a leader per term. In order to prevent having multiple candidates at the same time every node has randomized and therefore different election timer times. Otherwise an election could result in a draw. This would just trigger a reelection afterwards but cost additional time. One more important thing is that the election timer of every node always takes longer than the heartbeat timer. Otherwise a node would start an election a healthy cluster which makes no sense.

Basic parallel processing

In order to implement the raft algorithm properly parallelism is need as a base. This chapter explain the differences of golang and python when it comes to parallel processing.

Goroutines:

A "thread" in golang is called goroutine. This is not the same as a normal parallel processing. A goroutine can be processed concurrently by every statement or about every line of code. In other languages like java the program can only execute whole functions parallel. This results in a finer way of parallelism and better performance. Overall a pc can execute much more goroutines than normal threads because of this slight cutting of the code to be executed parallel.

Making a "thread" by can be easily done by writing the **go** keyword in front of a function like displayed in the following example.

```
package main

import (
    "fmt"
)

func main() {
    a, b := 1, 2

    go func() {
        b = a * b
    }()

    a = b * b

    fmt.Printf("a = %d, b = %d\n", a, b)
}
```

Depending on which task is being executed first, `a = b * b` or the `go func()` the result will differ. Possible results are: **a = 4, b = 8** or **a = 4, b = 2**. This is called asynchronous execution.

To execute goroutines synchronous golang uses channels. In the following example almost the same code is being shown but returning a consistent result.

```
package main

import (
    "fmt"
)

func main() {
    a, b := 1, 2

    operationDone := make(chan bool)
    go func() {
        b = a * b

        operationDone <- true //or false
    }()

    <-operationDone

    a = b * b

    fmt.Printf("a = %d, b = %d\n", a, b)
}
```

With the channel `operationDone` and the `go func()` writing a bool into `operationDone` the program is able to wait at the call `<-operationDone` for an element which is saved in `operationDone` (Like a queue). As soon as `<-operationDone` has a value the program goes ahead.

Python parallel programming:

In python parallel programming is done with threads. For this python offers a **Thread**-Class. A class which can be used as thread looks like the following code block.

```
from threading import Thread

class ServerThread(Thread):

    def __init__(self, counter):
        Thread.__init__(self)
        self.counter = counter

    def run(self):
        try:
            for i in range(0, self.counter):
                print(i)
        finally:
            print("Thread finished")
```

```
from src.server.serverThread import ServerThread

if __name__ == '__main__':

    for x in range(8):
        server = ServerThread(x)
        server.start()
        # wait for the thread to terminate
        server.join()
```

This thread is a class which has a run function that counts down one by one from a given value and prints every new decrement in the console. Once it has reached 0 the thread finishes and stops itself.

To be able to call the threads synchronous like go lang does with channels, python uses the `.join()`-method.

The raft algorithm implemented

In the following tables are the essential components of a raft implementation described shortly. This shows a quick overview about what to implement before digging into the real implementation.

Name of class/structure	Description
State machine	Used for the 3 states of a node.
Replicated Log	Used for saving values in a node.
Node	Represents a node.
Timer	Used for election and heartbeat timeouts in a concurrent environment.
Cluster	Clusters multiple nodes together.

Node implementation

Name of functionality	Description
request votes	Used for requesting votes from every other node in the cluster in an election .
append entries	Used for updating the nodes value.
election	Functionality which is used the whole election process.
heartbeat	Functionality which is used for heartbeat messages.

Custom timer implementation in python because of this code:

```
def run(self):
    self.finished.wait(self.interval)
    if not self.finished.is_set():
        self.function(*self.args, **self.kwargs)
    self.finished.set()
```

Execute election in go

```
func (n *Node) executeElection() bool {
    n.log("-> Election")
    n.votedFor = &n.id // vote for ourself

    var wg sync.WaitGroup
    nodes := n.cluster.GetRemoteFollowers(n.id)
    votes := make([]bool, len(nodes))
    wg.Add(len(nodes))
    for i, rpcIf := range nodes {
        go func(w *sync.WaitGroup, i int, rpcIf NodeRPC) {
            term, ok := rpcIf.RequestVote(n.currentTerm, n.id, 0, 0)
            if term > n.currentTerm {
                // todo
            }
            votes[i] = ok
            w.Done()
        }(&wg, i, rpcIf)
    }
}
```

```

wg.Wait() // wait until all nodes have voted

// Count votes
nbrOfVotes := 1 // master votes for itself!
for _, vote := range votes {
    if vote {
        nbrOfVotes++
    }
}
// If more than 50% respond with true - The election was won!
electionWon := nbrOfVotes >= len(n.cluster.allNodes)/2+1
n.log(fmt.Sprintf("<- Election: %v", electionWon))
return electionWon
}

```

Execute election in python

```

def execute_election(self):
    print("<- Election")
    self.votedFor = self.id # vote for yourself

    # used for thread sync
    wg = WaitGroup()

    nodes = self.cluster.get_remote_followers(self.id)
    votes = []

    # amount of threads to wait for
    wg.add(len(nodes))

    # this function calls the request_vote from all other known nodes in the
    # cluster
    def request_votes():
        term, ok = node.request_vote(self.current_term, self.id, 0, 0)
        if term > self.current_term:
            # not needed
            pass
        votes.append(ok)
        wg.done()

    for i, node in enumerate(nodes):
        Thread(target=request_votes).start()

    wg.wait()

    number_of_votes = 1 # Master votes for himself
    for vote in votes:
        if vote: # if the person voted for me:
            number_of_votes += 1

    # check if over half of the cluster is alive and about to have a new
    # master
    election_won = number_of_votes > len(self.cluster.allNodes) / 2

    print('<- Election:' + str(election_won))

    return election_won

```

WaitGroup in Python

```
import threading

class WaitGroup(object):

    def __init__(self):
        self.count = 0
        self.cv = threading.Condition()

    # add amount of processes
    def add(self, n):
        self.cv.acquire()
        self.count += n
        self.cv.release()

    # call out that a process stopped
    def done(self):
        self.cv.acquire()
        self.count -= 1
        if self.count == 0:
            self.cv.notify_all()
        self.cv.release()

    # wait for all processes to be done
    def wait(self):
        self.cv.acquire()
        while self.count > 0:
            self.cv.wait()
        self.cv.release()
```

to compare:

- statemachine, cluster is the same in go and python
 - same code
 - complexity
 - Python uses classes
 - Go uses structures
- python doesn't use interfaces -> also difference in statemachine and cluster
- node:
 - the sourcecode is about the same in both languages with different syntax
 - both languages need custom implementation for threadable timers
 - python needs a custom implementation for wait groups
 - **defer** in go is the same as **with** in python
 - present custom timer in python
 - present waiting group implementation in python
 - compare go vs python execute election



Differences

Conclusion

In conclusion ...

- Comparison code length
 - Code complexity
 - Python is much easier to program
 - the code is the same except of classes/structures and channels/threads
 - python threads are much slower than goroutines
- see: <https://madeddu.xyz/posts/go-py-benchmark/>

Sources

- <https://pragmacoders.com/blog/multithreading-in-go-a-tutorial>
- <https://www.geeksforgeeks.org/multithreading-in-python-set-2-synchronization/>
- <https://github.com/jweigend/concepts-of-programming-languages>
- <https://www.elastic.co/de/>
- <https://Raft.github.io/Raft.pdf>
- <http://theseconlivesofdata.com/Raft/>
- <https://lamport.azurewebsites.net/pubs/lamport-paxos.pdf>
- <https://madeddu.xyz/posts/go-py-benchmark/>
- <https://gist.github.com/pteichman/84b92ae7cef0ab98f5a8>