Proceedings of the 7th International Conference on Intelligent Sustainable Systems (ICISS-2025)
IEEE Xplore Part Number: CFP25M19-ART; ISBN: 979-8-3315-2243-8

2025 7th International Conference on Intelligent Sustainable Systems (ICISS) | 979-8-3315-2243-8/25/$31.00 ©2025 IEEE | DOI: 10.1109/ICISS63372.2025.11076262

Quantum-Enhanced Sentiment Analysis: Bridging NLP and Quantum Computing for Superior Text Classification

1st Boopalamani J 2nd Pranav Raj S 3rd Dr. Prasanna Kumar
Dept of Computer Science and Engineering
Amrita School of Computing
Amrita Vishwa Vidyapeetham
Chennai, India
1st boopalamani2003@gmail.com 2nd pranavmozart1207@gmail.com 3rd r_prasannakumar@ch.amrita.edu

***Abstract*—This research introduces a new paradigm for sentiment analysis on patient medication reviews through the application of quantum computing to improve machine learning models. A pre-existing dataset of medication reviews from the UCI Machine Learning repository was utilized, involving Quantum Natural Language Processing (QNLP) techniques, namely the application of quantum embeddings produced by quantum circuits to improve the performance of sentiment classification. Experimental findings indicate that improved models through quantum techniques, like the Quantum Random Forest, outperform conventional models in terms of accuracy and precision. These improvements are ascribed to quantum embeddings' capacity to efficiently represent complex linguistic patterns in high-dimensional data. Additionally, the study uses robust validation techniques including performance benchmarking and cross-validation to guarantee reliability. Through a scalable and context-aware framework for natural language comprehension, this study highlights the revolutionary potential of QNLP in improving sentiment analysis in the healthcare industry.**

***Index Terms*—Quantum Natural Language Processing (QNLP), Sentiment Analysis, Classical NLP Models, Text Classification, Lambeq Framework**

I. Introduction

In natural language processing (NLP), sentiment analysis is an important task meant to identify attitudes, emotions, and feelings in text data. Its uses cover social media, e-commerce, and healthcare, where user comments forms a significant part of the information guiding decisions. In the healthcare industry, patient drug reviews help to ascertain the general level of satisfaction of patients as well as provide information on the efficacy and adverse effects of drugs. Medical experts and the pharmaceutical companies benefit from this knowledge in optimizing therapies and enhancing patient care. Deep learning models such as Long Short-Term Memory (LSTM) networks and Convolutional Neural Networks (CNN) and conventional machine learning methods include Support Vector Machines (SVM), Random Forest (RF), and Decision Tree (DT) [1] usually define conventional sentiment analysis methodologies. Although useful, these approaches can neglect the complexity of high-dimensional, context-aware, and sophisticated textual information. Less feasible in contexts with limited resources, traditional models likewise rely mostly on vast amounts of tagged data and great computer capability.

Advancements in quantum computing have provided new opportunities for sentiment analysis, notably through Quantum Natural Language Processing (QNLP). QNLP encodes linguistic knowledge in high-dimensional quantum states utilizing fundamental quantum principles such as superposition and entanglement. QNLP provides an enhanced method for embedding contextual dependencies and semantic connections in textual material through the incorporation of quantum computing techniques. Recent studies have revealed that quantum embeddings where textual information is stored into quantum circuits have the capacity to enhance feature representations used in sentiment categorization [2]. Lambeq and other quantum models have made it feasible to map textual data into quantum states, hence allowing classical models to include quantum-processed elements for improved predictive performance [3].

This work introduces a hybrid quantum-classical sentiment analysis approach to enhance classification by integrating quantum embeddings with classical machine learning models. This method enables the extraction of subtle language patterns that are challenging to identify using traditional NLP techniques by representing textual input in quantum feature spaces. The drawbacks of traditional sentiment analysis methods, which usually rely heavily on feature engineering and fail to manage highly nonlinear relationships in textual data, inspire our work mostly. This work aims to show by using quantum embeddings how quantum-supremacy models more especially, Quantum Random Forest and Quantum Decision Tree may perform better in sentiment classification tasks. This research is needed since, especially in high-stakes applications like healthcare sentiment analysis, more accurate and reliable sentiment classification algorithms are becoming increasingly important.

One of the main aspects of this work is a thorough discussion of NLP operations inside the sentiment categorization pipeline. Raw text is turned into numerical data suitable for classical as well as quantum processing by text preparation in terms of tokenizing, stopword removal, stemming, lemma-

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:09:43 UTC from IEEE Xplore. Restrictions apply.

tization, and TF-IDF vectorization. Such preprocessing helps obtained characteristics to be maximized for next quantum embedding and classification. Furthermore, the research tackles the problem of model dependability by means of strict validation techniques including cross-valuation and comparative benchmarking with existing models, therefore guaranteeing that quantum-enhanced models continually outperform traditional approaches.

Furthermore emphasized in the research is the need of result validation by means of a detailed comparison between quantum and classical models. Transparency and repeatability are emphasized by thorough discussion of experimental setup including dataset splitting, hyperparameter adjustment, accuracy, precision, recall, and F1-score. Furthermore underlined to overcome the issue of practical application of quantum-boosted models is the need of testing simulation tools and cross validation of data. The study also addresses how quantum embeddings enhance sentiment classification models by means of better feature representations and deeper semantic implications, so integrating quantum concepts into traditional NLP procedures [4].

This research will create a new standard for sentiment analysis by combining conventional NLP methods with the unique capabilities of quantum computing under the help of QNLP. In sectors where precision and context comprehension at high accuracy levels are indispensible, the quantum-classical hybrid strategy proposed here provides a scalable and efficient method for sentiment classification augmentation. Improved technology in the quantum computing platform will enable further use of QNLP to further develop advances in NLP to the point that sentiment analysis will get ever more strong and reliable for challenging real-life scenarios.

II. Litrature Review

From conventional techniques to machine learning, then on deep learning, and most recently with the use of quantum-inspired approaches, sentiment analysis has developed from its inception. Depending on conventional machine learning algorithms, Support Vector Machines (SVM), Random Forest (RF), and Decision Trees (DT) using feature extraction techniques such Bag of Words (BoW) and Term Frequency-Inverse Document Frequency (TF-IDF) convert text-based data into a numerical representation mostly. These methods sometimes run into difficulties even if their proven performance with structured data due of complex language patterns including idioms, sarcasm, and context-dependent expressions [5]. This is especially true when handling massive textual data sets. Deep learning methods such CNN and Long Short-Term Memory (LSTM) networks have developed out of the constraints of traditional models in controlling semantic interdependencies. These methods have tremendously improved sentiment analysis by their ability to learn hierarchical elements of text and sequential dependencies. Despite their excellent accuracy, deep learning models require large volumes of labeled data and significant processing capacity, which makes their deployment in low-resource and real-time environments somewhat difficult [6].

Transformer-based models such as BERT and GPT have revolutionized sentiment analysis by including contextual links between words, hence augmenting attention mechanisms. By improving contextual knowledge and sentiment analysis accuracy, these models have produced fresh discoveries in applications of natural language processing. Still, they are predicated on computationally complicated structures and big pre-trained models that suffer with scalability. Furthermore, conventional deep learning models find it challenging to manage high-dimensional, nonlinear interactions between textual components, thereby making it more difficult to acquire significant semantic representations from text data [7]. Given these constraints, scientists have concentrated on quantum computing as a possible substitute to raise the emotion classification performance.

Quantum natural language processing (QNLP), an emerging field, employs concepts from quantum computing to perform natural language processing tasks. This field employs quantum superposition and entanglement to encapsulate language data into high-dimensional Hilbert spaces, hence achieving superior semantic links compared to conventional approaches. Early QNLP research has shown that by preserving complex language patterns often not preserved by standard feature extraction methods, quantum embeddings which translate text data into quantum circuits offer superior sentiment analysis [8]. Recent studies have started to address the joint employment of quantum aided feature representations with traditional models to enable integrated strategies using the strength of both. Lambeq and other quantum systems provide means to express natural language in quantum circuits, therefore enabling the use of quantum machine learning to natural language processing [9].

Sentiment analysis has seen effective results when classical machine learning and quantum computing are combined. Classifiers supplemented with quantum techniques, such as Quantum Random Forest and Quantum Decision Tree, demonstrate superior accuracy and stability when compared to classical classifiers according a comparative examination of both models. Quantum models are more suited for activities requiring thorough contextual analysis since studies have demonstrated they can use quantum feature spaces to detect complicated language patterns [10]. Research on the utilization of quantum kernel methods in natural language processing has demonstrated that embeddings including quantum mechanics enhance classification accuracy through increased feature expressiveness. [11]. Furthermore, experimental results show that hybrid models integrating both quantum and classical approaches can overcome some of the drawbacks inherent in conventional deep learning systems, including computational inefficiencies and overdependence on extensive labeled datasets.

Although their application presents certain difficulties, quantum-aided models offer great promise. The efficiency of quantum models mostly relies on quantum encoding methods and the quality of quantum circuits for specific natural lan-

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:09:43 UTC from IEEE Xplore. Restrictions apply.

guage processing applications. Although quantum embeddings are strong at preserving syntactic and semantic links, some research show that they can be further modified to improve effective processing of vast sentiment classification datasets [12]. Comparative research on quantum-enhanced models versus conventional baselines is another main focus of QNLP. Recent literature's experimental results highlight the requirement of thorough benchmarking to guarantee that quantum models offer a real benefit over conventional deep learning methods [13]. To enable QNLP more relevant to real-world practical sentiment analysis scenarios in real environments, this calls for the exploration of simulation frameworks, hybrid modeling approaches, and quantum circuit architecture advances.

Apart from improving performance, another crucial field of investigation is scalability of quantum-enabled models. Because of the lack of large-scale quantum computing equipment, quantum algorithms nowadays are simulation-dependent. Nevertheless, the developments in quantum computing technology make the possibility for NLP operations on actual quantum processors increasingly feasible. Recent studies imply that hybrid quantum-classical training approaches and variational quantum circuits have great possibilities to bridge quantum and classical NLP models [14]. Future research should focus on solving the scalability problems by means of more efficient hybrid learning structures, noise-robust quantum algorithms, and simplifying of quantum circuit designs.

Finally, the body of research on sentiment analysis has evolved from traditional machine learning approaches to advanced deep learning techniques and, more lately, from quantum computing-based approaches. Although deep learning and classical models offer good baselines for NLP, they struggle with managing high-dimensional language interactions and need great computational capability. By allowing quantum-enhanced feature representations to enhance sentiment classification performance, quantum computing presents a fresh cure to such a challenge. Although present QNLP research is still in its infancy, first findings show that quantum-enhanced models have the ability to keep advancing sentiment analysis by more efficient detection of complex semantic linkages. The junction of QNLP with conventional NLP methods will change the sentiment analysis paradigm as quantum hardware develops with scalable and accurate sentiment categorization models to follow.

III. Methodology

This study thoroughly examines the amalgamation of traditional machine learning methods with quantum computing strategies for sentiment analysis. Five primary phases define the methodological framework: data preparation, quantum embedding production, integration and model training, performance evaluation, and comparison investigation. With quantum-enhanced feature representations, the suggested approach is meant to overcome conventional method constraints and improve the accuracy of sentiment classification. Strong validation techniques like cross-valuation and hyperparameter optimization are applied in order to evaluate the resilience of the conclusions. To increase openness and repeatability, also offered are concise explanations of the simulation tools, dataset partitioning, and experimental design.

A. Data Preprocessing

With more than 213,000 evaluations and accompanying sentiment labels, the UCI ML Drug Review Dataset is the major dataset used in this work, therefore providing a rich base for training and evaluating sentiment classification models. The dataset was split into training, validation, and testing subsets to help the models to avoid overfitting and improve their generalizing capacity. Model training uses the training subset; validation subset for hyperparameter optimization; testing subset for evaluation of model performance on unprocessed data [12]. As shown by Fig. 1, preprocessing of raw text data is necessary for its efficient incorporation in conventional as well as quantum modeling methodologies. It starts with tokenization that is, breaking out reviews into tokens or words [13]. The procedure establishes a basis for additional processing. To give consistency over the dataset, normalizing the text by lowering every character to lowercase and eliminating special characters and punctuation follows. Next, stopwords are eliminated to exclude the frequent words but semantically meaningless words "the," "is," and "and," which do not help to classify sentiment meaning.




Fig. 1. Architecture

Then words are turned to their base forms using stemming and lemmatization techniques. The phrases "running," "runs," and "ran," for instance, will all be shortened to the basic word "run." This keeps the conceptual core while lowering redundancy. Finally, Term Frequency-Inverse Document Frequency (TF-IDF) [14] analyzes the word relevance in every review by means of feature extraction:

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:09:43 UTC from IEEE Xplore. Restrictions apply.

$$\text{TF-IDF}(t,d) = \text{TF}(t,d) \times \log\left(\frac{N}{\text{DF}(t)}\right)$$

Here, t is a word; d is a document; N is the total number of documents; and DFt is the count of papers including the phrase t [15]. TF-IDF gives rare but important terms more weight and reduces weights to often occurring but less instructive words.

$$X_{\text{reduced}} = X \cdot W$$

where W is the matrix of principal components and X the original feature matrix. It reduces the computational load and puts the data into a stage ready for quantum embedding.

B. Quantum Embedding Creation

This work comes up with a quantum embedding that is an advance that further improves textual feature representations. In using concepts related to quantum mechanics, such embeddings use quantum circuit technology; in particular, each of the TF-IDF features is represented by an angle-embedded quantum state via 4-qubit. A rotation gate efficiently maps a feature onto the Hilbert space of a quantum as illustrated:

$$R_y(x_i) = \exp\left(-i\frac{x_i}{2}\sigma_y\right)$$

This brings us to the normalized feature value of x_i, where σ_y is the Pauli-Y matrix [16]. Angle embeddings allow the data to be represented within high-dimensional quantum states that capture subtle patterns otherwise ignored by classical models. Strongly entangled layers are used to model dependencies between features. Quantum entanglement ensures that the relationships between features are preserved, which allows the quantum embeddings to capture both the individual feature values and the interdependencies [17]. Quantum measurements translate quantum states into classical data following the embedding. These measures are now included into conventional models and become enhanced feature representations.

C. Model Integration and Training

The influence of quantum embeddings is assessed in this work under both classical and quantum-augmentated models. Among all the models used in sentiment analysis, classical ones are RF, DT, and SGD-the most often used ones. These can be used as baselines to compare the performance of their quantum-augmented variants.Quantum-augmented models add quantum embeddings into the feature space. For instance, Quantum Random Forest, Quantum Decision Tree, and Quantum SGD make use of features enhanced by quantum in the prior stage [18]. Training is obtained by feeding the preprocessed dataset to these models by iteratively updating their parameters to minimize classification errors. Hyperparameter tuning is executed using cross-validation so that these models are achieved with optimal performances while generalizing well toward unseen data.

D. Performance Evaluation

The following metrics-accuracy, precision, recall, and F1-score help one evaluate the model: Accuracy is the fraction of correctly categorized events:

$$\text{Accuracy} = \frac{\text{TP} + \text{TN}}{\text{TP} + \text{TN} + \text{FP} + \text{FN}}$$

Precision measures the proportion of true positive predictions as follows:

$$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}}$$

Recall = Number of True Positives Predicted / Total Number of Actual Positives:

$$\text{Recall} = \frac{\text{TP}}{\text{TP} + \text{FN}}$$

The F1-score, which is the harmonic mean of precision and recall, provides an overall measure of performance:

$$\text{F1-Score} = 2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}}$$

Development of confusion matrices allows one to determine the classification accuracy of every model into true positives, true negatives, false positives and false negatives.

E. Comparative Analysis

The performance of quantum-enhanced models relative to their classical counterparts is evaluated by means of comparative analysis. In terms of accuracy, recall, and F1-score, the results show Quantum Random Forest and Quantum Decision Tree outperform their conventional forms. This is so because quantum embeddings improve the richer feature representations, hence allowing models to better depict intricate text relationships.

The work also addresses computational feasibility, recognizing that although quantum embeddings provide promising benefits, their practical deployment is presently limited by the support of quantum hardware. Computations are carried out on Python-based quantum computing platforms like Qiskit and Pennylane, promoting reproducibility and uniformity in results [18]. The results demonstrate how hybrid quantum-classical models can enhance sentiment analysis by increasing feature expressivity and contextual awareness.

By combining quantum embeddings with traditional machine learning methods, this work proves the possibility of employing quantum computing for sentiment analysis. The outcome indicates that technological progress in quantum hardware will allow still more improvements, leading to scalable and efficient sentiment classification systems across multiple fields, such as healthcare, finance, and social media analysis.

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:09:43 UTC from IEEE Xplore. Restrictions apply.

TABLE I
COMPARISON OF CLASSICAL AND QUANTUM PREDICTIONS

Review ID	Actual Sentiment	Classical Prediction	Quantum Prediction
1	Positive	Positive	Positive
2	Negative	Positive	Negative
3	Positive	Positive	Positive
4	Negative	Negative	Negative
5	Positive	Negative	Positive
6	Negative	Negative	Negative
7	Positive	Positive	Positive
8	Negative	Negative	Negative
9	Positive	Positive	Positive
10	Negative	Positive	Negative

IV. RESULT AND ANALYSIS

The proposed quantum-enhanced sentiment analysis method is experimentally compared in this part with classical and quantum-augmentated models. The impact of quantum embeddings on classification accuracy, precision, recall, and F1-score is investigated exhaustively in this work. Along with traditional machine learning libraries, substantial tests were conducted using Python-based quantum computing libraries for robustness and repeatability. To guarantee the validity of the suggested hybrid models, the experimental strategy consists in hyperparameter optimization, dataset splitting, and extensive performance benchmarking.

A. Experimental Design and Thorough Discussion

The suggested strategy was evaluated mostly using the UCI ML Drug Review Dataset. Comprising more than 213,000 patient medicine reviews, each with sentiment scores reflecting either positive or negative experiences, the dataset The data was split into test (15%), validation (15%), and training (70%), generalizing sets. Raw text was turned into structured numerical representations using preprocessing methods including tokenization, normalizing, stopword elimination, stemming, lemmatization, and TF-IDF vectorizing. Quantum embeddings were generated following feature extraction using angle embedding techniques whereby every TF-IDF feature was embedded onto quantum states using a 4-qubit circuit using Pauli rotation gates.

The integration of machine learning frameworks such as Scikit-learn with Python-based quantum computing libraries like Qiskit and Pennylane facilitated the training of hybrid quantum-classical models. Grid search and cross-validation were employed for hyperparameter tuning, namely for adjusting the learning rate in SGD classifiers, the maximum depth in Decision Trees, and the number of estimators in Random Forest. Several validation runs were used to choose the hyperparameter in order to prevent overfitting and get consistent performance among several model versions. Stable convergence was achieved by training with a batch size of 128, adaptive gradient-based learning rate, and maximum number of iterations equal to 1000 [19].

B. Performance Comparison

Comparative evaluation of the classical and quantum-augmented models helped to confirm the performance of the latter models. Table I shows the variations in the sentiment categorization output of both models, therefore reflecting a sample prediction of both.

TABLE II
PERFORMANCE METRICS FOR CLASSICAL AND QUANTUM-ENHANCED MODELS

Model	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)
Classical Random Forest	85.09	84.20	83.75	83.97
Quantum Random Forest	89.59	88.62	87.45	88.03
Classical Decision Tree	75.13	76.20	74.80	75.49
Quantum Decision Tree	86.15	85.30	83.90	84.59
Classical SGD	75.10	75.35	74.90	75.12
Quantum SGD	75.10	75.32	74.92	75.12

V. CONCLUSION

The effectiveness of applying quantum embeddings with conventional machine learning models for sentiment analysis is shown in this paper. The results confirm that Quantum Random Forest and Quantum Decision Tree outperform their classical counterparts, therefore proving the capacity of quantum embeddings to acquire nuanced language patterns and improve classification accuracy. Particularly in sectors like healthcare and finance where accuracy counts most, the better recall and lowered false-negative rates point to a more context-sensitive sentiment categorization method produced by quantum-augmentated models.

The results reveal that quantum embeddings enable better sentiment identification by increasing feature expressivity over standard TF-IDF techniques. Still, there are pragmatic problems mostly related to processing overhead and the usage of quantum circuit simulations. Although modern experiments rely on simulated quantum systems, future research should apply these models on actual quantum hardware to reach their complete computing capability.

To raise performance even more, later research would also investigate various quantum encoding approaches like quantum kernel methods and variational quantum circuits. Moreover, adding quantum embeddings into deep learning models such as transformer-based models including BERT may lead to even more developments To demonstrate even more that QNLP is a scalable and effective technique, these models could be expanded to other general uses in NLP including multilingual sentiment analysis and emotional detection.

All told, our work shows that quantum-boosted models can surpass classical constraints and offers a strong basis for QNLP in sentiment analysis. By improving scalability, economy, and accuracy in practical applications, these methods can perhaps transform sentiment analysis with more developments in quantum computing.

REFERENCES

[1] S. Adhikari, "Importance of Data Preprocessing and Parameters Tuning for Supervised Machine Learning Models on Tweets Sentiment Analysis," The Batuk, vol. 10, no. 1, pp. 133–151, Jan. 2024, doi: 10.3126/batuk.v10i1.62303.

[2] Joshi, N., Katyayan, P. and Ahmed, S.A., 2021, April. Comparing classical ml models with quantum ml models with parametrized circuits for sentiment analysis task. In Journal of Physics: Conference Series (Vol. 1854, No. 1, p. 012032). IOP Publishing.

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:09:43 UTC from IEEE Xplore. Restrictions apply.

[3] Sharma, M., 2023, November. Classification of health care text using NLP and ML. In Proceedings of the 5th International Conference on Information Management & Machine Intelligence (pp. 1-7).
[4] T. Hasan and A. Matin, "Extract Sentiment from Customer Reviews: A Better Approach of TF-IDF and BOW-Based Text Classification Using N-Gram Technique, "Proceedings of International Joint Conference on Advances in Computational Intelligence, pp. 231–244, 2021, doi:10.1007/978-981-16-0586-4 19.
[5] Havlíček, V., Córcoles, A.D., Temme, K., Harrow, A.W., Kandala, A., Chow, J.M. and Gambetta, J.M., 2019. Supervised learning with quantum-enhanced feature spaces. Nature, 567(7747), pp.209-212.
[6] Martinez, V. and Leroy-Meline, G., 2022. A multiclass Q-NLP sentiment analysis experiment using DisCoCat. arXiv preprint arXiv:2209.03152.
[7] Kartsaklis, D., Fan, I., Yeung, R., Pearson, A., Lorenz, R., Toumi, A., de Felice, G., Meichanetzidis, K., Clark, S. and Coecke, B., 2021. lambeq: An efficient high-level python library for quantum NLP. arXiv preprintarXiv:2110.04236.
[8] P. K. Rangarjan et al., "The social media sentiment analysis framework: deep learning for sentiment analysis on social media," International Journal of Electrical and Computer Engineering (IJECE), vol. 14, no. 3, p. 3394, Jun. 2024, doi: 10.11591/ijece.v14i3.pp3394-3405.
[9] Zhang, Y., Song, D., Li, X., Zhang, P., Wang, P., Rong, L., Yu, G. and Wang, B., 2020. A quantum-like multimodal network framework for modeling interaction dynamics in multiparty conversational sentiment analysis. Information Fusion, 62, pp.14-31.
[10] Zeng, W. and Coecke, B., 2016. Quantum algorithms for compositional natural language processing. arXiv preprint arXiv:1608.01406.
[11] S. Adhikari, "Importance of Data Preprocessing and Parameters Tuning for Supervised Machine Learning Models on Tweets Sentiment Analysis," The Batuk, vol. 10, no. 1, pp. 133–151, Jan. 2024, doi: 10.3126/batuk.v10i1.62303.
[12] F. Z. Ruskanda et al., "Quantum Representation for Sentiment Classification", 2022 IEEE International Conference on Quantum Computing and Engineering (QCE), vol. 19, pp. 67–78, Sep. 2022, doi: 10.1109/qce53715.2022.00025
[13] Kadhim, A.I., 2018. An evaluation of preprocessing techniques for text classification. International Journal of Computer Science and Information Security (IJCSIS), 16(6), pp.22-32.
[14] Nafis, N.S.M. and Awang, S., 2021. An enhanced hybrid feature selection technique using term frequency-inverse document frequency and support vector machine-recursive feature elimination for sentiment classification. Ieee Access, 9, pp.52177-52192.
[15] Schuld, M. and Killoran, N., 2019. Quantum machine learning in feature hilbert spaces. Physical review letters, 122(4), p.040504.
[16] Wu, S., Li, J., Zhang, P. and Zhang, Y., 2021, November. Natural language processing meets quantum physics: A survey and categorization. In Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (pp. 3172-3182).
[17] S. Ganguly, S. N. Morapakula, and L. M. P. Coronado, "Quantum Natural Language Processing Based Sentiment Analysis Using Lambeq Toolkit," 2022 Second International Conference on Power, Control and Computing Technologies (ICPC2T), vol. 2, pp. 1–6, Mar. 2022, doi: 10.1109/icpc2t53885.2022.9776836.
[18] L. J. O'Riordan, M. Doyle, F. Baruffa, and V. Kannan, "A hybrid classical-quantum workflow for natural language processing," Machine Learning: Science and Technology, vol. 2, no. 1, p. 015011, Dec. 2020, doi: 10.1088/2632-2153/abbd2e.
[19] D. Peral-Garc´ıa, J. Cruz-Benito, and F. J. Garc´ıa-Pe˜nalvo, "Comparing Natural Language Processing and Quantum Natural Processing approaches in text classification tasks," Expert Systems with Applications, vol. 254, p. 124427, Nov. 2024, doi: 10.1016/j.eswa.2024.124427.

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:09:43 UTC from IEEE Xplore. Restrictions apply.