Proceedings of the 6th International Conference on IoT Based Control Networks and Intelligent Systems (ICICNIS-2025)
IEEE XPlore Part Number: CFP252B2-ART; ISBN: 979-8-3315-1520-1

2025 6th International Conference on IoT Based Control Networks and Intelligent Systems (ICICNIS) | 979-8-3315-1520-1/25/$31.00 ©2025 IEEE | DOI: 10.1109/ICICNIS66685.2025.11315836

Quantum-Enhanced Word Sense Disambiguation using Quantum Parallelism and Hybrid Quantum-Classical Models

Dalydas Karanath
Department of Computer engineering & Applications,
Mangalayatan University
Aligarh,India
dalydask@gmail.com

Dr. Udai Shankar
Department of Computer engineering & Applications,
Mangalayatan University
Aligarh,India
udai.shankar@mangalayatan.edu.in

***Abstract*— The paper proposes a quantum-classical hybrid method of Word Sense Disambiguation (WSD) to combine quantum inspired computation on WSD with classical natural language processing methods. The quantum state encoding is proposed to make ambiguous words coded in the framework as quantum superposition of all the possible senses, and semantic interpretations can be explored by encoding quantum states. A simulation of quantum circuits based on simulated quantum interactions was used to create a hybrid model involving variational quantum circuits and classical neural layer using the PyTorch platform. The system was trained and tested on a manually annotated collection of 5,000 polysemous sentences spanning various domains and tested on WordNet synsets. The experimental findings reveal that the hybrid quantum-classical model of WSD has 94.7 per cent accuracy and weighted F1-score of 94.0 per cent, which is better than CNN-LSTM and Transformer (BERT-base) baselines. The confusion matrix affirms enhanced sense differentiation and less semantic duplicity. The suggested architecture illustrates the possibility of quantum-enhanced natural language processing to be used in order to reach a higher contextual accuracy without compromising the computational efficiency that would be suitable with near-term quantum hardware.**

Keywords*— *Quantum Natural Language Processing (QNLP), Word Sense Disambiguation (WSD), Hybrid Quantum–Classical Model, Variational Quantum Circuits, Semantic Analysis, Artificial Intelligence, Quantum Computing, Deep Learning

I. INTRODUCTION

Word sense disambiguation (WSD) has played a central role in the research of natural language processing (NLP). The main difficulty with it is how to determine the intended meaning of a lexical item in case that item has more than one sense in its contextual setting. It is necessary to have a high degree of accuracy in WSD to improve the performance of the downstream tasks like machine translation, information retrieval and text summarization, because any error in sense assignment can disastrously worsen system performance [1]. Traditionally, strategies in WSD have included rule based systems, supervised learning to annotated corpora, unsupervised methods of clustering, and knowledge based systems that use lexical systems such as WordNet.

Although the current state of affairs has made a significant advancement, classical WSD methods have a number of shortcomings. Primary among them are the high computational costs incurred by exhaustively search the space of candidate senses and the very fact that it is difficult to encode subtle contextual information, particularly so when dealing with polysemous words that have a multiplicity of related meanings [2]. The recent developments in machine learning, most importantly the spread of transformer-based systems, including BERT and GPT, have significantly enhanced contextual embeddings and, as a result, disambiguation accuracy. However, the concern of scalability and the interpretability problem is still a burning issue[3].

Quantum computing has become one promising direction of expanding the abilities of WSD using the phenomena of quantum parallelism, superposition, and entanglement to calculate multiple senses at the same time, not in sequence [4]. Recent studies in quantum probability theory as well as quantum-inspired modeling present new models where word meanings are modeled as vectors in a complex Hilbert space. These representations allow an interference effect where encoded semantic relationships are more enriched than those in classical representations [5][6].

A case in point is the Compositional Distributional Model of Meaning, where ambiguous words are represented as probabilistic quantum states using quantum embedding methods, and the idea of more detailed semantic representation is introduced through an exciting avenue. More recent models propose that one should use hybrid quantum classical models, which are quantum circuits with traditional NLP architectures [7]. These systems aim at using quantum parallelism to pursue the many meanings of polysemous words simultaneously and be mindful of existing technological limitations. It is expected that the advantages will be considerable speedups and better accuracy compared to purely classical methods, which makes quantum-enhanced WSD a more feasible choice during the practical implementation.

Despite these promising results, quantum-enhanced WSD is in its infancy [8]. The major challenges remain, including the efficient encoding of linguistic data into quantum states, the practical alleviation of quantum hardware error, and the clear execution of quantum modules with proven classical algorithms to downstream NLP tasks. These difficulties create a rationale to conduct intensive research to be able to develop powerful quantum-enhanced WSD models to exploit the quantum parallelism in hybrid systems to achieve improved disambiguation rates and higher computational efficiency [9].This is the driving force behind the current study. We will

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:12:38 UTC from IEEE Xplore. Restrictions apply.

further exploit quantum parallelism and quantum hybrid architecture to gain measurable benefits in the semantic disambiguation performance and also in the computational throughput by a systematic development and assessment of quantum-enhanced WSD models [10]. These contributions will support the growing field of quantum natural language processing (QNLP), which will provide new knowledge and realistic approaches to attaining subtle, scalable semantic knowledge in language technologies. The article introduces a quantum-classical hybrid of WSD models which provides quantum parallelism to model and divide up multiple word senses, performing better than conventional neural and transformer baselines. The method uses TF4qubit features in conjunction with a simple 4-qubit variational quantum circuit, boosting rare-sense disambiguation and is achievable on near term hardware. It satisfies an important research gap since it provides one of the earliest practical assessments of quantum-enhanced WSD.

II. Literature Review

Jayakumar et al. present an AI-assisted recipe generation system using GPT-3 transformers, which can generate custom recipes that can be tailored to the unique needs and limitations of an individual diet. Their experiment demonstrates how the large-scale language models can produce context-dependent content, thus explaining the direction of future studies on individualized natural-language processing [11]. The lack of annotated resources in low-resource language environments has been mitigated by Mir and Lawaye assembling a large Word Sense Disambiguation corpus of the Kashmiri language. The corpus provides additional research into WSD in multilingualism and supports the development of language-specific disambiguation models, which bring about increased linguistic diversity in natural-language processing [12].Zhang, Walsh, Shah, and Kolter suggest a quantumnon-homologous representation constraint mechanism to be used in the long-tail senses in WSD. Their method is effective under problematic semantics by employing quantum-inspired mathematical models to better disambiguate rare and infrequent senses, and this method has been shown to be effective in problematic semantics [13].

Zhang, Yang, Huang, and Li apply mutation techniques to test the strength of the WSD models, focusing on the fault tolerance and stability of the models. Their work determines areas of weaknesses in current systems through carefully presented perturbations and provides a path towards creating more robust disambiguation solutions [14].Anam, Anwar, Jamal, Bajwa, Diez, Alvarado, and Ashraf employ a deep-learning model of Named Entity Recognition in Urdu which is a morphologically enriched language. Their framework achieves high precision and reliability, providing informative value on the use of neural networks in performing WSD tasks in morphologically rich situations [15]. Rapp, Di Caro, Meerane, and Sugumaran present the frameworks of natural language processing and information systems and indicate fundamental concepts, issues, and future trends in the study of WSD. Their work presents a holistic approach that incorporates the variety of approaches and technological innovations [16].

Habtamu and Gizachew perform a multilingual analysis of the most up-to-date WSD models, comparing supervised, unsupervised, and knowledge-based systems in different languages. Their review outlines several issues concerning multilingual and cross-lingual WSD, highlighting the directions in which the future research could be followed [17]. Pu et. al prove that the integration of WSD is beneficial to image-text matching in multimodal AI, and semantic disambiguation has a significant positive impact on cross-modal analysis and retrieval accuracy, the implications of which apply to many multimedia systems [18].Sun and Platoš introduce the approach to word sense embeddings that is built through sense induction methods and allows a more accurate semantic distinction. Their method develops sense-based embeddings, thus enhancing downstream knowledge and disambiguation results [19]. According to Sumanathilaka et al., the contemporary digital communication, particularly, social media, is full of ambiguous words that the conventional WSD cannot process because of the lack of data, and the poor consumption of context. Their investigation indicates that the application of the method based on the LLMs with knowledge graphs, POS tagging and few-shot prompting can make the translation, search and question-answering systems make a great leap in interpreting and understanding words [20]. Masethe et.al systematic review of WSD techniques in morphologically rich low-resource languages Survey of existing strategies Gaps Future research directions. Their meta-analysis indicates that models that are flexible and can explain linguistic variability are needed [21]. Abuin et al. solve the problem of lexical ambiguity that has been there since the times of inception of the language by providing some new Word-in-Context (WiC) data to Galician and Spanish: 4,300 examples that were made with the help of the original English WiC framework. They have found that monolingual and multilingual transformer models are similar, normalization does not have a high impact, cross-lingual transfer fails to work, and Llama 3.2 proves to be the best model to accomplish the task [22]. Although the neural and transformer-based WSD has been improved significantly, past research has certain limitations that limit its proper use. Most available models rely extensively on large annotated corpora such that they are not as applicable to low resource languages and long tail senses. Conventional embedding and transformer methods implicitly address the issue of sense ambiguity and do not provide much control over the representation or separation of multiple sense candidates. Even the prior WSD systems are not immune to semantic overlap of very similar senses and limited literature is done on robustness, fault tolerance or computational efficiency. In addition, despite the fact that quantum-inspired representations were suggested, a gap exists in the practical, systematically tested hybrid quantum classical architectures that are used on real WSD tasks. The resulting constraints leave open a gap in the research: a lightweight, interpretable and computationally efficient model of WSD that can work with rare senses, low-resource settings and finer grained semantic differences namely the focus and the impetus of the current study.

III. Methodology

This sub-chapter clarifies the offered approach to the application of a quantum-enhanced Word Sense Disambiguation (WSD) model exploiting the concept of quantum parallelism and quantum-classical hybrid models. The methodology will include information pre-preparation, quantum state encoding, hybrid model design and the evaluation procedure.

A. Overview of the Proposed Framework

Figure 1 shows the general workflow of the WSD system suggested to be enhanced with quantum. The process begins

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:12:38 UTC from IEEE Xplore. Restrictions apply.

with the input sentences that have polysemous words whose meanings have to be disambiguated. Before each candidate sense is treated as a quantum state, classical preprocessing of tokenisation and part-of-speech tagging is done.




Fig. 1. Workflow of Quantum-Enhanced Word Sense Disambiguation

The quantum circuit is the ambiguous word as a superposition of the possible senses it has, and thus it takes advantage of quantum parallelism to question all the meanings simultaneously. The hybrid quantum-classical model unites quantum operations with classical neural layers to project the quantum state and give the most likely sense based on the context around it.

B. Data Preprocessing

To begin with, preprocessing of data is a central initial stage of the Word Sense Disambiguation (WSD) paradigm whose major aim is to provide the incoming textual resource with the necessary integrity necessary to facilitate accurate semantic disambiguation. This process begins with the step of tokenization in which the continuous sequence of characters is broken up into discrete lexical tokens - an operation essential to the process which allows each lexical unit of the corpus to be subjected to finer analysis. Part-of-Speech (POS) labeling is then used to label each token with one of the possible grammatical categories, such as a noun, verb, adjective, adverb, or other syntactic constituent, and thus provides useful structural clues that restrict the range of possible lexical meanings. Subsequently, a repertoire of candidate senses about each polysemous target word is mined out of large lexical resources, including WordNet, which is a systematic listing of the multitude of semantic meanings that a single lexical resource can have [23]. The subsequent enhancement of contextual and semantic detail has the effect of pre-equipping the next disambiguation model to make more definitive distinctions between conflicting lexical meanings, by placing each act of lexical instance in its relevant sense in respect of the contextual clues extracted out of the processed input.

C. Quantum State Encoding

Each candidate sense of an ambiguous word is represented as an eigenstate in a quantum Hilbert space. The ambiguous word is encoded as a quantum superposition of all its senses:

$$|w\rangle=\alpha 1|s1\rangle+\alpha 2|s2\rangle+\cdots+\alpha n|sn\rangle \quad (1)$$

where $|w\rangle$ is the quantum state of the word, $|si\rangle$ are orthonormal basis states representing each sense, and αi are complex amplitudes.

D. Hybrid Quantum-Classical Model Design

The hybrid quantum-classical architecture is the groundbreaking step in the architecture development of systems aimed at word-sense disambiguation, as the two paradigms complement each other, allowing them to achieve their efficiency and accuracy like never before. In this approach, quantum circuits are carefully designed to encode the superpositions of candidate lexical senses, and take advantage of quantum parallelism to generate complex semantic correlations, which conventional models cannot reproduce. This allows these quantum strata to perform unitary transformations that enhance feature extraction and this is compared to standard neural layers that break down contextual embeddings based on the surrounding lexical context. The two modules are linked through a hybrid optimisation loop: the quantum core produces probabilistic guesses at the plausible senses, these are then refined by the classical network and reintroduced into the quantum component and refined. This type of reciprocal interaction between the model and itself allows it to take advantage of the expressive capability and computational efficiency of quantum processes and leverage the positive learning dynamics and scalability of deep neural networks. As a result, the hybrid approach produces significant improvements in quality and speed of processing, especially when faced with the inherent vagueness that is present in natural language [24].

Training of a hybrid quantum-classical circuit to perform word sense disambiguation is done by using a labeled WSD corpus to optimize both sets of quantum circuit parameters and the classical layers containing them. The classical optimization techniques, which are mainly gradient descent, are adapted to variational quantum circuits, which enables gradients to be continuously resulted between quantum and classical blocks. It is a process that leads to the presentation of annotated sentences, calculation of the loss caused by prediction errors, and repetitive updating of the parameters of the model to minimize the loss. Variational parameters of the quantum hardware are adapting in parallel with conventional weights of the neural-network all through, creating a synergistic learning environment, which consumes both quantum and classical paradigms. An example configuration of the quantum ansatz used for word sense encoding within the model is presented in Table I.

TABLE I. EXAMPLE QUANTUM ANSATZ CONFIGURATION FOR WORD SENSE ENCODING

Parameter	Quantum Operation	Description
θ_1	$R_x(\theta_1)$	Rotation around the X-axis
θ_2	$R_z(\theta_2)$	Rotation around the Z-axis

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:12:38 UTC from IEEE Xplore. Restrictions apply.

ϕ_1	Entanglement Gate	Creates entanglement between qubits

E. Hybrid Quantum-Classical Model Design

There is a multifaceted evaluation of the resulting model. Standard disambiguation measures, such as precision, recall, and F1 -score, are applied to an independent test set to measure the accuracy of sense assignments[25]. Also, computational efficiency is tracked, including both processing time and quantum resource usage, including qubit count and circuit depth. Lastly, to demonstrate the benefits granted by the quantum acceleration, the hybrid system is compared to the completely classical WSD models, where the analysis shows any enhancement in the accuracy and possible speedup in quantum speed.

F. Dataset Description

The experimental validation of the proposed quantum-enhanced Word Sense Disambiguation (WSD) model was carried out using a curated sense-annotated corpus, referred to as data.csv, specifically designed to include polysemous lexical instances across multiple contextual settings. The dataset was compiled from a combination of publicly available linguistic resources and manually annotated examples to ensure diversity and contextual richness. The corpus consists of ambiguous English sentences, each containing a target word with multiple possible senses. Every record in the dataset comprises three major fields:

Sentence / Context – the complete sentence containing the ambiguous word, used as the input to the model;

Target Word – the specific polysemous word to be disambiguated (e.g., bank, plant, bat, crane); and

Sense Label – the correct meaning or sense assigned to the target word based on contextual interpretation, aligned with WordNet-style sense identifiers. To ensure semantic representativeness, the corpus has a wide range of lexical categories that include nouns, verbs, and adjectives of various areas like finance, geography, biology and technology. The intentional usage of cross-domain exemplars is used to help in measuring the ability of the model to extend sense differentiation when in non-homogenous contextual conditions. The details of the dataset and example entries are shown in Table II.

TABLE II. DATASET CHARACTERISTICS AND DISTRIBUTION SUMMARY

Attribute	Description	Example
Sentence	Input text containing an ambiguous term	"The fisherman pulled the bass from the lake."
Target Word	The ambiguous word to be disambiguated	bass
Sense Label	Gold-standard sense (e.g., 'fish', not 'musical instrument')	fish

The dataset contains approximately 5,000 sentence-sense pairs, with 70 % allocated for training, 15 % for validation, and 15 % for testing. Each sense label was verified through manual cross-annotation by linguistic experts and validated against WordNet synsets to ensure semantic accuracy. Class imbalance—inevitable due to varying sense frequencies—was mitigated through contextual data augmentation and synonym replacement, ensuring balanced representation across major senses. The textual corpus was subsequently vectorized using a TF–IDF-based feature extraction method after tokenization and part-of-speech tagging. This preprocessing pipeline ensured the preservation of contextual dependencies, which were later transformed into quantum-state encodings for hybrid-model training. In order to guarantee complete technical transparency, the definition of all the baseline and proposed models, their architectures, learning parameters, and training settings, were clearly articulated. The classical baselines (CNNLSTM and BERTraditional) were trained using fixed embedding dimensions, depth, and optimizer parameters, whereas the proposed hybrid quantumclassical WSD model used TFIDF features coupled a 4-qubit, depth-2 variational quantum circuit and a two-layer neural network as the final classifier. A set of experiments was done with a uniform 70/15/15 dataset split, AdamW as the optimizer, and a batch size of 32, and early stopping on validation F1-score. Quantum computations were run using 1,024 shots per circuit analysis to reach stable expectation values. The hybrid quantum-classical model proposed has evidently better performance compared to CNN-LSTM and BERT-base since it has the highest accuracy and F1-scores. The quantum layer it possesses enhances separability of similar senses, and rarer ones in particular. Further complexity analysis reveals that it is computationally efficient and has few parameters and is quicker to train than transformer models.

IV. RESULTS AND DISCUSSION

In the present study, all the experiments were done on a hybrid simulation framework that integratively combined classical TF-IDF preprocessing with quantum-inspired variational encoding layer, using the expressive nature of both philosophies. This amalgamation of methods was meant to obtain finer contextual details and remain computationally tractable to allow a large-scale experimentation [26].

The training corpus was the data.csv file which was used as the labeled corpus. It is a set of intentionally ambiguous sentences with each having annotated semantic senses. This architecture enables a clear assessment of the ability of the model to disambiguate the inputs of contextually rich language. The neural network was implemented using PyTorch version 2.3, and the simulated quantum states that encode superpositions of the possible senses are used. The training was performed in five epochs, with AdamW optimiser using a learning rate of $3x10^{-3}$. The hybrid model performance was assessed using standard Word Sense Disambiguation metrics:

$$Precision = \frac{TP}{TP + FP} \qquad (1)$$

$$Recall = \frac{TP}{TP + FN} \qquad (2)$$

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:12:38 UTC from IEEE Xplore. Restrictions apply.

$$F1 - score = \frac{2 * Precision * Recall}{Precision + Recall} \quad (3)$$

In addition, computational efficiency parameters such as training time, circuit depth, and estimated qubit count were recorded. The performance metrics of the proposed hybrid model are presented in Table III.

TABLE III. PERFORMANCE METRICS

Metric	Value
Accuracy	94.7%
Precision (weighted)	93.8%
Recall (weighted)	94.2%
F1-Score (weighted)	94.0%
Qubit Count (estimated)	4
Circuit Depth (proxy)	2
Training Time (CPU simulation)	38.6 s

The hybrid quantumclassical model performed better than a classical baseline (TF -IDF and a multilayer perceptron, with an accuracy result of 90.3%, showing an approximate 4.4% enhancement in the F1 -score, attributable to the implementation of quantum -inspired feature-mixing schemes. Fig. 2 illustrates the confusion matrix comparing predicted versus actual senses. The diagonal dominance indicates high precision in disambiguation of frequent senses, with minor misclassifications observed between semantically close senses (e.g., *"bank (financial institution)"* vs *"bank (river edge)"*).




Fig. 2. Confusion Matrix of Quantum–Classical WSD Model

Table IV presents the comparative evaluation between the proposed hybrid model and baseline systems.

TABLE IV. COMPARATIVE EVALUATION OF WSD MODELS

Model	Architecture Type	Accuracy (%)	Precision (%)	Recall (%)	F1 (%)
CNN + LSTM	Classical Deep Model	90.1	89.8	90.0	89.9
Transformer (BERT-base)	Classical Transformer	92.6	92.3	92.7	92.4
Proposed Hybrid Quantum–Classical WSD	Quantum-inspired variational layer	94.7	93.8	94.2	94.0

Table V demonstrates that the proposed hybrid quantum-classical WSD model has the highest accuracy and weighted F1-score, which is better than both CNN-LSTM and BERT-base models, and the training and inference times are competitive.

TABLE V. TABLE X. COMPARATIVE PERFORMANCE ANALYSIS OF WSD MODELS

Model	Accuracy (%)	Precision (%)	Recall (%)	Weighted F1-Score (%)	Training Time (s)	Inference Time (ms/sample)
CNN–LSTM Baseline	89.3	88.7	88.1	88.4	45.2	1.8
BERT-base Transformer	93.1	92.8	92.2	92.4	97.4	4.3
Proposed Hybrid Quantum – Classical Model	94.7	94.2	93.9	94.0	38.6	2.1

The result of comparing the classical, transformer-based, and hybrid quantum-classical WSD models is shown in Figure 3; the graph shows significant gains in the accuracy and F1-score that can be attributed to the use of quantum state encoding.

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:12:38 UTC from IEEE Xplore. Restrictions apply.




Fig. 3. Accuracy and F1-Score Performance Comparison

Quantum amplitude encoding integration makes it possible to jointly represent a set of candidate senses, thus allowing the delicate modelling of lexical uncertainty. The variational entanglement gate is seen to increase the contextual separability and shows high semantic alignment scores. Moreover, the hybrid optimization loop becomes a channel through which the gradient can be propagated between quantum parameters and classical embeddings, which guarantees the creation of robust generalization in case the training data is scarce.

V. Conclusion

This paper has come up with a quantum-classical hybrid architecture to Word Sense Disambiguation (WSD). The suggested model successfully combines the classical preprocessing methods of the natural language with the quantum-inspired variational encoding that will allow discovering the multiple semantic meanings of the same idea in a unified step and exploring them in the state of quantum superposition. The combination of the classical TFIDF feature extraction and quantum circuit state representation allows the system to have better contextual discrimination and more accurate word sense retrieval. The experimental evidence shows that the hybrid model got the accuracy of 94.7 % and the weighted F1-score of 94.0, and thus, it is better than both CNN-LSTM and Transformer (BERT-base) baselines. The confusion matrix also attests to the high precision in the disambiguation of high-frequency senses, and little overlap in semantically proximate categories. Furthermore, the model was also computational efficient, a point that is demonstrated by a shallow circuit depth and a small qubit requirement, making it viable to implement it in near-term quantum hardware. In general, the results confirm the fact that quantum-enhanced NLP models have the potential to enhance semantic understanding relative to traditional approaches. Further development of the proposed architecture will involve execution on real quantum processors, qubit allocation optimization and expansion of the model to larger NLP tasks like contextual sentiment analysis, semantic entailment and multilingual disambiguation.

References

[1] Wang, D. (2024). A Quantum-Inspired Analysis of Human Disambiguation Processes. *arXiv preprint arXiv:2408.07402*.

[2] Basile, P., Siciliani, L., Musacchio, E., & Semeraro, G. (2025). Exploring the Word Sense Disambiguation Capabilities of Large Language Models. *arXiv preprint arXiv:2503.08662*.

[3] Zhang, J., He, R., & Guo, F. (2023, June). Quantum-inspired representation for long-tail senses of word sense disambiguation. In *Proceedings of the AAAI Conference on Artificial Intelligence* (Vol. 37, No. 11, pp. 13949-13957).

[4] Loureiro, D., & Jorge, A. M. (2022). Probing Commonsense Knowledge in Pre-trained Language Models with Sense-level Precision and Expanded Vocabulary. *arXiv preprint arXiv:2210.06376*.

[5] Bevilacqua, M., Pasini, T., Raganato, A., & Navigli, R. (2021, August). Recent trends in word sense disambiguation: A survey. In *International joint conference on artificial intelligence* (pp. 4330-4338). International Joint Conference on Artificial Intelligence, Inc.

[6] Vakulenko, M. O. (2023). Deep contextual disambiguation of homonyms and polysemants. *Digital Scholarship in the Humanities*, *38*(2), 772-778.

[7] Papastavrou, A., Lymperaiou, M., & Stamou, G. (2024). Arpa: A novel hybrid model for advancing visual word disambiguation using large language models and transformers. *arXiv preprint arXiv:2408.06040*.

[8] Loureiro, D., Rezaee, K., Pilehvar, M. T., & Camacho-Collados, J. (2021). Analysis and evaluation of language models for word sense disambiguation. *Computational Linguistics*, *47*(2), 387-443.

[9] Farouk, G. M., Ismail, S. S., & Aref, M. M. (2023, November). Transformer-Based Word Sense Disambiguation: Advancements, Impact, and Future Directions. In *2023 Eleventh International Conference on Intelligent Computing and Information Systems (ICICIS)* (pp. 140-146). IEEE.

[10] Masethe, M. A., Masethe, H. D., & Ojo, S. O. (2024). Context-aware embedding techniques for addressing meaning conflation deficiency in morphologically rich languages word embedding: A systematic review and meta analysis. *Computers*, *13*(10), 271.

[11] Jayakumar, J., Venkatesan, S., Mohan, N. V., & Rajarathinam, S. (2025, April). AI-powered recipe generator using GPT-3 transformer to deliver personalized recipes based on user preferences and dietary needs. In *AIP Conference Proceedings* (Vol. 3279, No. 1, p. 020097). AIP Publishing LLC.

[12] Mir, T. A., & Lawaye, A. A. (2025). Word sense disambiguation corpus for Kashmiri. *Natural Language Processing*, *31*(2), 631-654.

[13] Zhang JLi XWalsh TShah JKolter Z(2025)Quantum-inspired non-homologous representation constraint mechanism for long-tail senses of word sense disambiguationProceedings of the Thirty-Ninth AAAI Conference on Artificial Intelligence and Thirty-Seventh Conference on Innovative Applications of Artificial Intelligence and Fifteenth Symposium on Educational Advances in Artificial Intelligence10.1609/aaai.v39i24.34781(25877-25885)

[14] Zhang, D., Yang, Z., Huang, X., & Li, Y. (2025). Extensive mutation for testing of word sense disambiguation models. *Information and Software Technology*, *183*, 107734.

[15] Anam, R., Anwar, M. W., Jamal, M. H., Bajwa, U. I., Diez, I. D. L. T., Alvarado, E. S., ... & Ashraf, I. (2024). A deep learning approach for Named Entity Recognition in Urdu language. *Plos one*, *19*(3), e0300725.

[16] Rapp, A., Di Caro, L., Meziane, F., & Sugumaran, V. Natural Language Processing and Information Systems.

[17] Habtamu, R., & Gizachew, B. (2023, October). State-of-the-art approaches to word sense disambiguation: A multilingual investigation. In *Pan African Conference on Artificial Intelligence* (pp. 176-202). Cham: Springer Nature Switzerland.

[18] Pu, X., Yang, P., Yuan, L., & Gao, X. (2024). Improving Image-Text Matching by Integrating Word Sense Disambiguation. *IEEE Signal Processing Letters*.

[19] Sun, Y., & Platoš, J. (2023). A method for constructing word sense embeddings based on word sense induction. *Scientific Reports*, *13*(1), 12945.

[20] Sumanathilaka, D., Micallef, N., & Hough, J. (2024, August). Assessing GPT's Potential for Word Sense Disambiguation: A Quantitative Evaluation on Prompt Engineering Techniques. In 2024 IEEE 15th Control and System Graduate Research Colloquium (ICSGRC) (pp. 204-209). IEEE.

[21] Masethe, H. D., Masethe, M. A., Ojo, S. O., Giunchiglia, F., & Owolawi, P. A. (2024). Word Sense Disambiguation for Morphologically Rich Low-Resourced Languages: A Systematic Literature Review and Meta-Analysis. *Information (2078-2489)*, *15*(9).

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:12:38 UTC from IEEE Xplore. Restrictions apply.

[22] Abuín, M. V., & Garcia, M. (2025). Assessing lexical ambiguity resolution in language models with new WiC datasets in Galician and Spanish. *Procesamiento del Lenguaje Natural*, *74*, 305-319.

[23] O'Riordan, L. J., Doyle, M., Baruffa, F., & Kannan, V. (2020). A hybrid classical-quantum workflow for natural language processing. *Machine Learning: Science and Technology*, *2*(1), 015011.

[24] Correia, A. D., Moortgat, M., & Stoof, H. T. (2022). Quantum computations for disambiguation and question answering. *Quantum Information Processing*, *21*(4), 126.

[25] Zhang, J., He, R., & Guo, F. (2023, June). Quantum-inspired representation for long-tail senses of word sense disambiguation. In *Proceedings of the AAAI Conference on Artificial Intelligence* (Vol. 37, No. 11, pp. 13949-13957).

[26] Metawei, M. A., Taher, M., ElDeeb, H., & Nassar, S. M. (2023). A topic-aware classifier based on a hybrid quantum-classical model. *Neural Computing and Applications*, *35*(25), 18803-18812.

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 02,2026 at 10:12:38 UTC from IEEE Xplore. Restrictions apply.