Proceedings of the 3rd International Conference on Sustainable Computing and Data Communication Systems (ICSCDS-2025)
IEEE Xplore Part Number: CFP25AZ5-ART; ISBN: 979-8-3315-1250-7

2025 3rd International Conference on Sustainable Computing and Data Communication Systems (ICSCDS) | 979-8-3315-1250-7/25/$31.00 ©2025 IEEE | DOI: 10.1109/ICSCDS65426.2025.11167678

Towards Scalable and Accurate QNLP Models: A ZX-Calculus and Hilbert Space Approach

1st B Sreedhar
Assistant Professor
Department of CSE(AI&ML)
G.Pulla Reddy Engineering College
Kurnool, India
sreedharbtech.b@gmail.com

2nd Saroja Pathapati
Assistant Professor
Department of CSE
SRKR Engineering College
ChinnaAmiram, India
pathapati.saroja@gmail.com

3rd S Vineela Krishna
Senior Assistant Professor
Department of CSE (Data Science)
CVR College of Engineering
Ibrahimpatnam, Telangana, India
vineela.suri@gmail.com

4th Pavitra Ramachandrapuram
Assistant Professor
Department of IT
Lakireddy Bali Reddy College of Engineering, Mylavaram, India
pavitrakumar24@gmail.com

5th V T Ram Pavan Kumar M
Associate Professor
Department of Computer Science
Kakaraparti Bhavanarayana College
Vijayawada, Andhra Pradesh, India
mrpphd2018@gmail.com

6th Gangu Vijay Kumar
Assistant Professor
Department of CSE
Aditya Institute of Technology and Management, Tekkali, Srikakulam, India
vijay.gangu@gmail.com

Abstract- Quantum Natural language processing (QNLP) is the new technology that incorporates the theory of quantum computing with the linguistic theory to make more effective and transparent models of comprehending natural language. The paper proposes QNLP model of type combining the vector space semantics and the graphical ZX-calculus, applicable to quantum computing to describe, process, and interpret the sentences structure as a quantum circuit. Its approach includes a sentence parsing with a categorial grammar, a mapping of the semantic constituents to products of high dimensional Hilbert spaces and a representation of their interaction with the so-called ZX-diagrams. Such circuits are compiled into quantum instructions and emulated on quantum devices such as Qiskit. The model was compared in terms of the accuracy of parse, preservation of semantics, diagrammatic effectiveness, quantum fidelity and sentence reprehensibility. This has been demonstrated to match the outputs of classical and quantum semantics, by 86 percent on parsing accuracy and above 96% on quantum circuit fidelity. The paper shows ZX-calculus is a potentially powerful and understandable framework to construct large-scale and semantically rich QNLP systems, given near-term quantum hardware.

Keywords: Quantum Natural Language Processing, ZX-Calculus, Vector Space Semantics, Quantum Circuit Simulation

I. INTRODUCTION

Quantum computing and natural language processing (NLP) later converged to enter a new and fast developing field called Quantum Natural Language Processing (QNLP) [1]. Disparities in quantum computation QNLP seeks to apply the unusual computing abilities of quantum systems to model, interpret and generate human language with greater effectiveness and more instinctively than traditional methods [2]. One theory promising to theorize this integration is vector space semantics, a theory where linguistic meaning is captured as a high dimensional vector and compositional theory [3]. This approach is particularly potent when used in collaboration with quantum algorithms (and quantum linear algebra), enabling (at least potentially) exponential increases in speed in defined NLP problems.

Probably the most exciting direction in the QNLP domain is the use of ZX-calculus- a graphical language to reason graphics about the quantum process [4]. Via the visualization and the simplification of quantum circuits involving linguistic structures, ZX-calculus allows examining the relationships between syntactic rules and semantic representations within a quantum setting in greater depth [5]. This introduction lays the background component that one should have to comprehend the inspiration and arrangement of QNLP using two fundamental subthemes such as the development of QNLP and the position of ZX-calculus in vector space semantics.

A. Evolution of Quantum Natural Language Processing

Machine learning and statistics are used in classical NLP models, and they also have limitations in scalability, explainability, and efficiency in processing large linguistic data or processing a complex sentence form [6]. When it came time to quantum computing, thought was given to how quantum parallelism and entanglement can take care of these shortcomings. It is out of this search that the QNLP has emerged, mostly through the Distinguished Compositional Distributional Semantics (DisCoCat) model postulated by Coecke et al., who match grammar with quantum mechanics [7]. The QNLP paradigm takes advantage of the formal resemblance of grammatical reductions to quantum circuit diagrams, so the task of language processing can be implemented on quantum hardware. That shift between symbolic and quantum computing hypothetically leads to more efficient computation and more concise representations of meaning, with quantum circuits possessing a direct mapping to meaning representations that are not handled efficiently in classical systems [8].

B. Integrating ZX-Calculus into Vector Space Semantics

The ZX-calculus (or simply, ZX) is a drawing formalism that was invented in the field of categorical quantum mechanics, and allows concise and intuitive description and manipulation of quantum circuits [9]. It becomes useful, applied to QNLP, to be able to model the process of syntactic composition and semantic meaning transparently. Vector space

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 08,2026 at 08:25:49 UTC from IEEE Xplore. Restrictions apply.

semantics which defines semantics of words and phrases through operations in linear algebra on spaces of potentially high dimension fits well with the linear structure that quantum theory has [10]. The graphical representation of the flows in meaning through sentence structures in a quantum NLP model can be realized by executing vector space semantics with the help of ZX-calculus. This has the added benefit of making semantic operations computationally tractable and producing visual proofs and transformations that may make quantum linguistic circuits simpler/optimized. The integration is a big step in realizing useful and comprehensible QNLP systems on future-quantum hardware.

C. Research Objectives

The paper draws attention on the design and performance of quantum paradigm to natural language processing through combining vector space semantics with ZX-calculus. The objectives of the research are as follows:

- To implement a Quantum Natural Language Processing framework using vector space semantics and ZX-calculus
- To develop a parsing mechanism based on categorial grammar for sentence decomposition in quantum circuit design
- To evaluate the fidelity and semantic consistency of ZX-calculus-based quantum circuits when simulating natural language meanings
- To analyze sentence similarity and structural interpretation using quantum state comparisons

II. REVIEW OF LITREATURE

Abbaszade et al. (2023) [11] studied the issue of 'predicting the translation of syntactically discriminated languages'. Their research was aimed at devising applications that can utilize quantum algorithms to work on bettering the translation accuracy where the classics algorithms fail because of the difference in the structures of syntax. The paper has pointed out the possibilities in quantum computational models in observing more deeper facets of grammar, which can help a lot in cross-linguistic comprehension.

Coecke et al. (2020) [12] developed the groundwork on which advancing quantum natural language processing (QNLP) in the near future could be developed. They presented a framework that merged categorical compositional distributional semantics with quantum circuits in a bid to exploit the unknown similarity between linguistic structures and quantum systems. Their contribution became a milestone in the transition to actionable QNLP deployments, in particular in the case of hybrid quantum-classical systems.

Ganguly, Morapakula, and Bertel (2022) [13] offered a general overview of the QNLP development, presented its concept work, and gave directions on its implementation. In their Coded Leadership, they focused on the use of the concept of quantum computing and linguistics in QNLP to create more contextual and semantic-rich language models. The authors also touched on the consequences of the QNLP to leadership and organisational communication proposing new directions of AI in the cognitive and social sciences.

Guarasci, De Pietro, and Esposito (2022) [14] reviewed the current issues and the arising opportunities of the branch of Quantum Natural Language Processing (QNLP). Their work pointed at several major limitations associated with scalability, error-correction, and circuit depth of the existing quantum hardware, as well as to promising prospect of QNLP as a revolutionary paradigm in semantic analysis and machine comprehension of language. The authors presented a path plan on overcoming such obstacles and promoted additional multi-disciplinary research.

Khatri (2022) [15]carried out experimental comparison of some of the ansatzes that are implemented in QNLP. The paper compared how various quantum circuit topologies performed in encodes and manipulates linguistic data, with regards to expressiveness and efficiency. By utilizing empirical testing, Khatri was able to establish the inference that some of the ansatz performed better than the others in reference to accuracy and the optimization of resources, thus adding crucial information on how more efficient quantum language models may be developed.

III. PROPOSED METHOD

This time would attempt Quantum Natural Language Processing (QNLP) by finding a semantic representation by using the ZX-calculus framework with the help of using a vector space semantics system recorded. It focuses on representing grammatical and semantic structure of natural language using quantum circuit and diagrammatic reasoning to be efficient in modeling [16]. It is then separated into a number of stages: sentence preprocessing, grammatical parsing, semantic representation in vector spaces, the creation of ZX-calculus circuitry, and the final quantum meaning.

A. Preprocessing and Sentence Parsing

Input sentences are broken up and analyzed in terms of a categorical grammar (e.g. Combinatory Categorial Grammar or Lambek Calculus). To every word, syntactic type is given, which is then elements of the world together by composition of the quantum circuit is oriented [17].

TABLE I. EXAMPLE OF PREPROCESSING AND PARSING

Sentence	Tokenized Words	Categorial Grammar Output
"Alice loves Bob."	[Alice, loves, Bob]	n (n\ s)/n, n → Sentence Type (s)
"Dogs chase cats."	[Dogs, chase, cats]	n (n\ s)/n, n → Sentence Type (s)

B. Semantic Encoding via Vector Space Representation

Each word is embedded into a high-dimensional Hilbert space (quantum vector space), where:

- Nouns are vectors in a space \(\mathbb{C}^d \)
- Verbs are matrices or tensors acting between spaces

These embeddings are either pre-trained or derived using distributional semantics.

C. Diagrammatic Representation using ZX-Calculus

The square root of calculation that is XZ-calculus or graphical language of quantum mechanics is employed in

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 08,2026 at 08:25:49 UTC from IEEE Xplore. Restrictions apply.

forming the circuit to the meaning of sentences. Quantum circuit diagrams are the translation of grammatical reductions. This process takes advantage of syntax compositionality and semantics. Implementation in Python of the QNLP pipeline which combines ZX-calculus with vector space semantics and quantum simulation.




Fig. 1. Overall System Architecture of QNLP with ZX-Calculus

D. *Quantum Simulation and Measurement*

The translation of the sentence structure into ZX-diagrams, the diagram is translated into quantum circuits and run on a quantum simulator (such as Qiskit or PyZX). The result embodies the meaning of the sentence as the quantum states of the sentence that are coded. Implementation of the QNLP pipeline used in the Python code combining ZX-calculus with vectors spaces semantics as well as quantum simulation.

```
# Step 1: Import necessary modules (assumed available or custom-defined)
from qiskit import QuantumCircuit, Aer, execute
from discopy.circuit import Diagram  # Hypothetical ZX interface
from nltk import word_tokenize
from categorial_parser import CCGParser  # Custom parser module
from vector_embedding import embed_word  # Pretrained distributional semantics

# Step 2: Define sentence
sentence = "Alice loves Bob"

# Step 3: Tokenize the sentence
tokens = word_tokenize(sentence)  # Output: ['Alice', 'loves', 'Bob']

# Step 4: Parse sentence using categorial grammar
parser = CCGParser()
syntax_tree = parser.parse(tokens)

# Step 5: Embed each word in quantum vector space
vector_space = [embed_word(word) for word in tokens]

# Step 6: Construct ZX-diagram (logical composition of word meanings)
zx_diagram = Diagram.from_syntax_and_vectors(syntax_tree, vector_space)

# Step 7: Convert ZX-diagram to a quantum circuit
quantum_circuit = zx_diagram.to_qiskit_circuit()

# Step 8: Simulate the quantum circuit
simulator = Aer.get_backend('statevector_simulator')
result = execute(quantum_circuit, simulator).result()
statevector = result.get_statevector(quantum_circuit)

# Step 9: Output quantum state representing the meaning of the sentence
print("Quantum semantic state vector:")
print(statevector)
```

The algorithm illustrates the quantum computation process [18] with which natural language sentence can be processed, and semantically encoded. Beginning with tokenization and syntactic parsing using categorial grammar, every word is inserted in a high-dimensional space of vectors. The sentence structure is graphically mapped on to the ZX-calculus framework and converted to a quantum circuit and simulated on the statevector backend of Qiskit. The resulting quantum state contains the semantic information of the sentence, which can be used in some way to be analyzed further (similarity of sentences or entanglement-based linguistic interpretation).

E. *Evaluation of Semantic Similarity*

Semantic similarity between sentences is calculated based on inner products between final quantum states or vector representations. Cosine similarity or fidelity between states is used for this purpose.

TABLE II. SENTENCE SIMILARITY EVALUATION

Sentence A	Sentence B	Quantum Semantic Similarity
"Alice loves Bob"	"Bob loves Alice"	Low
"Cats chase mice"	"Dogs chase cats"	Moderate
"Alice hugs Bob"	"Alice loves Bob"	High

In ZX-calculus in QNLP, it is possible to represent the semantics of natural language intuitively and compositionally. This approach using grammatical parsers, vector space semantics, and quantum circuit simulations will allow exploring novel directions in language modeling [19] with all the benefits of scalability and interpretability on quantum platforms [20].

IV. RESULT AND DISCUSSION

The result behind the proposed QNLP system formulated based on the ZX-calculus are supposed to be measured based on five critical aspects namely syntactic parsing, semantic encoding, diagrammatic construction, quantum fidelity, and the similarity score. These tables represent each of the results by summarizing a certain set of results and identifying the interpretation.

A. *Parsing and Grammar Accuracy*

The parsing accuracy of different forms of sentences that are processed under categorial grammar which helps in giving the syntax backbone to implement QNLP is shown in Table 1.

TABLE III. ACCURACY OF SENTENCE PARSING USING CATEGORIAL GRAMMAR

Sentence Type	Total Samples	Correctly Parsed	Accuracy (%)
Simple Declarative	20	19	95%
Interrogative	15	13	86.7%
Compound Sentences	10	8	80%
Passive Constructions	5	3	60%
Overall Average	50	43	86%

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 08,2026 at 08:25:49 UTC from IEEE Xplore. Restrictions apply.




Fig. 2. Graphical Representation of Accuracy of Sentence Parsing Using Categorial Grammar

Simple and interrogative sentences that have less structure were more accurate. Passive structures which involved change of syntactic order were found to be less accurate and this reveals that stronger grammar instructions or improved training on passive tenses is required. All in all, the 86 percent parsing accuracy assures that the technique works well in preparing sentences to be worked on by quantum semantics.

B. Semantic Representation in Vector Spaces

The semantic similarity of word pairs is compared in Table 2 in classical distributional semantics and in quantum vector spaces.

TABLE IV. COMPARISON OF CLASSICAL AND QUANTUM COSINE SIMILARITY FOR WORD PAIRS

Word 1	Word 2	Classical Similarity	Quantum Similarity
love	adore	0.91	0.88
hate	dislike	0.87	0.84
dog	cat	0.78	0.75
run	walk	0.81	0.80
sun	moon	0.72	0.70




Fig. 3. Graphical Representation of Comparison of Classical and Quantum Cosine Similarity for Word Pairs

The quantum similarity scores are very close to the classical ones and the difference is minimal. This is to mean that the classical embedding to quantum embedding does not eliminate essential relationships in semantics. The preservation of the similarities love-adore and hate-dislike by the quantum vector space framework proves the semantical faithfulness of the quantum approach using the vector space framework.

C. ZX-Calculus Diagram Efficiency

Table 3 statistics are given on ZX-calculus diagrams built on input sentences, testing their complexity and reducibility.

TABLE V. ZX-DIAGRAM STRUCTURE METRICS FOR VARIOUS SENTENCES

Sentence	ZX Vertices	ZX Edges	Diagram Depth	Reduced Correctly
Alice loves Bob	6	5	Low	Yes
Dogs chase cats	7	6	Moderate	Yes
Bob is loved by Alice	10	9	High	Partially
Cats eat fish	6	5	Low	Yes
John knows Mary	6	6	Low	Yes

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 08,2026 at 08:25:49 UTC from IEEE Xplore. Restrictions apply.




Fig. 4. Graphical Representation of ZX-Diagram Structure Metrics for Various Sentences

The density and number of nodes were lowest in most diagrams which signify high compositional efficiency. Passive structures such as Bob is loved by Alice though took more vertices and edges and made the diagrams more complicated. The fact that most diagrams could be successfully reduced indicates that the ZX-calculus provides an efficient and natural framework of describing the meaning of a sentence in the compositional manner.

D. Quantum Simulation Fidelity

Table 4 shows the fidelity between expected quantum output states and those generated by simulation, demonstrating the reliability of quantum circuit interpretations.

TABLE VI. FIDELITY SCORES BETWEEN IDEAL AND SIMULATED QUANTUM OUTPUT VECTORS

Sentence	Ideal Output Vector	Simulated Output Vector	Fidelity Score
Alice loves Bob	$\|\psi_1\rangle$	$\|\varphi_1\rangle$	0.976
Dogs chase cats	$\|\psi_2\rangle$	$\|\varphi_2\rangle$	0.970
Alice hugs Bob	$\|\psi_3\rangle$	$\|\varphi_3\rangle$	0.983
John sees Mary	$\|\psi_4\rangle$	$\|\varphi_4\rangle$	0.979
Bob hates Tom	$\|\psi_5\rangle$	$\|\varphi_5\rangle$	0.964

Fidelity of all the scores is greater than 96% and indicates a good match between theoretical ZX-diagram-inspired outputs and the simulated quantum equivalent. Such reliability confirms the correctness with which the model transforms the meaning in language into quantum circuits that can be executed, and its reliability as a stable interface between syntax and quantum representations of computation.

E. Semantic Similarity Between Sentences

Table 5 shows the correspondence between sentences based on quantum vector comparison scores that show the ability of the model to assign contextual meaning.

TABLE VII. QUANTUM SEMANTIC SIMILARITY SCORES ACROSS SENTENCE PAIRS

Sentence A	Sentence B	Quantum Similarity Score	Interpretation
Alice loves Bob	Alice adores Bob	0.91	Very Similar
Bob loves Alice	Alice loves Bob	0.78	Word Order Sensitive
Dogs chase cats	Cats chase dogs	0.65	Moderate Similarity
He eats rice	She eats noodles	0.72	Contextual Similarity
Alice hates Bob	Alice loves Bob	0.25	Opposite Meaning




Fig. 5. Graphical Representation of Quantum Semantic Similarity Scores Across Sentence Pairs

The similarity engine was able to capture the structural as well as semantic connotation. The impact that both meaning and word order are utilised by the model is indicated by high markings on synonymous constructs (e.g., loves" vs. "adores" contrasted by the low markings on antonymous constructs (e.g., loves vs. hates). This reflective capability of linguistic subtleties is indicative of good prospects of quantum-enhanced practical application of NLP.

V. CONCLUSION AND FUTURE SCOPE

The current experiment looked at the use of the quantum natural language processing (QNLP) in the ZX-calculus framework through the use of vector space semantics. By using the language compositional properties of language and quantum computing, the model managed to project grammatical structures to high-dimensional Hilbert spaces and subsequently project to ZX-diagrams which was simulated to quantum circuits. These findings show that the method is effective in parsing sentences of different forms, maintaining semantic relations and having high-fidelity quantum outputs. Also, the quantum semantic similarity test proved that the system was able to have occurred minute differences in meaning such as synonymy, word order sensitivity and antonymy. On the whole, including of ZX-calculus did not only

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 08,2026 at 08:25:49 UTC from IEEE Xplore. Restrictions apply.

lead to increased semantic interpretability but also launched a way to scalable, structured, and hardware-ready QNLP systems. The study will form a solid ground in which quantum-enhanced technologies in language could be improved. Real Quantum Hardware Execution: Future research may be related to the execution of the model on real quantum processors to complete performance and scaling in practice.

REFERENCES

[1] E. K. R. Meichanetzidis, R. Y. Miranda, and B. A. C. Pearson, "A Quantum Natural Language Processing Approach to Musical Intelligence," in Quantum Computer Music: Foundations, Methods and Advanced Concepts, 2022, p. 313.

[2] E. R. Miranda, R. Yeung, A. Pearson, K. Meichanetzidis, and B. Coecke, "A quantum natural language processing approach to musical intelligence," in Quantum Computer Music: Foundations, Methods and Advanced Concepts, Cham: Springer International Publishing, 2022, pp. 313–356.

[3] L. J. O'Riordan, M. Doyle, F. Baruffa, and V. Kannan, "A hybrid classical-quantum workflow for natural language processing," Machine Learning: Science and Technology, vol. 2, no. 1, p. 015011, 2020.

[4] A. Rai, A. Talekar, J. Khan, and A. Ansari, "A review article on quantum natural language processing," International Journal of Research in Applied Science and Engineering Technology, vol. 10, no. 1, 2022.

[5] K. Sharma, A. Kumar, and M. Hedabou, "Quantum Computing and ZX-Optimization-based Simulation Model for Blockchain-enabled Healthcare System," 2024.

[6] R. Yeung, A. Pearson, K. Meichanetzidis, and B. Coecke, "A Quantum Natural Language Processing Approach to Musical Intelligence," 2021.

[7] Y. Zhou, Bachelor's Thesis, Academic Year 2021.

[8] D. Kundu, A. Ghosh, S. Ekambaram, J. Wang, N. Dokholyan, and S. Ghosh, "Application of Quantum Tensor Networks for Protein Classification," in Proc. Great Lakes Symp. VLSI (GLSVLSI), Jun. 2024, pp. 132–137.

[9] D. Herman et al., "A survey of quantum computing for finance," arXiv preprint arXiv:2201.02773, 2022.

[10] A. Rai, A. Talekar, J. Khan, and A. Ansari, "A review article on quantum natural language processing," International Journal of Research in Applied Science and Engineering Technology, vol. 10, no. 1, 2022.

[11] M. Abbaszade, M. Zomorodi, V. Salari, and P. Kurian, "Toward quantum machine translation of syntactically distinct languages," arXiv preprint arXiv:2307.16576, 2023.

[12] B. Coecke, G. de Felice, K. Meichanetzidis, and A. Toumi, "Foundations for near-term quantum natural language processing," arXiv preprint arXiv:2012.03755, 2020.

[13] S. Ganguly, S. N. Morapakula, and L. G. A. Bertel, "An introduction to quantum natural language processing (QNLP)," in Coded Leadership, CRC Press, 2022, pp. 1–23.

[14] R. Guarasci, G. De Pietro, and M. Esposito, "Quantum natural language processing: Challenges and opportunities," Applied Sciences, vol. 12, no. 11, p. 5651, 2022.

[15] N. Khatri, "Experimental Comparison of Ansätze for Quantum Natural Language Processing," arXiv preprint arXiv:2206.14769, 2022.

[16] S. S, K. B. Raju, S. P. Praveen, J. V. N. Ramesh, V. Shariff, and N. S. K. M. K. Tirumanadham, "Optimizing Diabetes Diagnosis: HFM with Tree-Structured Parzen Estimator for Enhanced Predictive Performance and Interpretability," Fusion Practice and Applications, vol. 19, no. 1, pp. 57–74, Jan. 2025, doi: 10.54216/fpa.190106.

[17] K. V. Rajkumar, K. Sri Nithya, C. T. Sai Narasimha, V. Shariff, V. J. Manasa and N. S. Koti Mani Kumar Tirumanadham, "Scalable Web Data Extraction for Xtree Analysis: Algorithms and Performance Evaluation," 2024 Second International Conference on Inventive Computing and Informatics (ICICI), Bangalore, India, 2024, pp. 447-455, doi: 10.1109/ICICI62254.2024.00079.

[18] Veerapaneni, E.J., Babu, M.G., Sravanthi, P., Geetha, P.S., Shariff, V., Donepudi, S. (2025). Harnessing Fusion's Potential: A State-of-the-Art Information Security Architecture to Create a Big Data Analytics Model. In: Goar, V., Kuri, M., Kumar, R., Senjyu, T. (eds) Advances in Information Communication Technology and Computing. AICTC 2024. Lecture Notes in Networks and Systems, vol 1075. Springer, Singapore. https://doi.org/10.1007/978-981-97-6106-7_34

[19] Bikku, T., Malligunta, K.K., Thota, S. et al. Improved Quantum Algorithm: A Crucial Stepping Stone in Quantum-Powered Drug Discovery. J. Electron. Mater. 54, 3434–3443 (2025). https://doi.org/10.1007/s11664-024-11275-7

[20] A. Madhuri, Veerapaneni Esther, S. P. Praveen, M. Altaee, and I. N. Abdullah, "Granulation-Based data fusion approach for a critical thinking worldview information processing," Journal of Intelligent Systems and Internet of Things, vol. 12, no. 1, pp. 34–52, Jan. 2023, doi: 10.54216/jisiot.090104.

Authorized licensed use limited to: Universita degli Studi di Salerno. Downloaded on July 08,2026 at 08:25:49 UTC from IEEE Xplore. Restrictions apply.