

Advanced Programming COEN 11



- Waiting List with 4 ranges of group sizes
 - -1-2
 - -3-4
 - -5-6
 - Greater than 6
- Use an array of linked lists
 - One list per range



- The waiting list is created interactively with the following commands
 - 1 name number insert a node with the name and number of people specified in the corresponding list
 - 2 opening show and delete the oldest nodes that fit the opening, smallest first
 - Do not traverse lists with sizes larger than the opening
 - 3 print the list for each range: name and number, from oldest to newest
 - 4 size print the entries that have group <= size</p>
 - Do not traverse lists with groups larger than the size
 - -0 quit



- Do not allow names to repeat
 - Check all the lists before inserting
- Keep your lists in the oldest-to-newest order
 - Always insert a new entry at the end of the appropriate list
 - Have tail pointers
- To show the lists
 - Traverse each list using the the pointers
- To remove entries
 - Traverse each list, from the smallest to the largest range
 - Change pointers to eliminate the node
 - Free the node at the end



- Requirements
 - Define a struct list
 - Head and Tail
 - Array of struct list
 - Heads and tails need to be initialized
 - Free all the nodes before quitting
 - New function for option zero



- Extra Credit
 - Add an option to change the size of a group for a reservation
 - 5 name old_size new_size
 - Traverse the right list searching for name



End