



UNIVERSITY OF TRENTO

Department of Information Engineering and Computer Science

Master's Degree in
Computer Science

FINAL DISSERTATION

MAINTAINING HITTING SETS IN TEMPORAL HYPERGRAPHS

Subtitle

Supervisor
Alberto Montresor
Co-Supervisor
Quintino Francesco Lotito

Student
Luca Prigione
242880

Academic year 2025/2026

Contents

Abstract	1
1 Introduction	2
1.1 Context	2
1.2 Problem Statement	2
2 Background and Related Work	3
3 Proposed Approach	4
3.1 Formal Problem Definition	4
3.1.1 Introduction	4
3.1.2 Objective	4
4 Experimental evaluation	5
5 Conclusions and Future Work	6
Bibliography	6
A Attachment	7

Abstract

1 Introduction

1.1 Context

The increasing availability of relational data that has been studied in recent years has led to a growing interest in the study of data structures capable of representing complex interactions between entities. In the literature, such type of relationship were originally managed by means of *graphs*, which are mathematical structures used to model one-to-one relations between objects. However, many real-world scenarios find this representation too restrictive, when considering interactions between more than just two entities.

Several real-life scenarios are by default not representable as graphs. Some examples include conversations between multiple people, usually found online in forums, chat or more generally in social media, while others include the interactions between multiple objects or entities, such as those involved in a bank transaction. In these types of contexts, the loss of information when representing these interactions as graphs is unavoidable.

In order to be able to manage this type of data relationship, the concept of *hypergraph* was introduced. An hypergraph is a generalization of a graph, characterized by the introduction of many-to-many relationships between entities, which are called *hyperedges*. This type of data structure is particularly useful when the goal is to represent complex interactions without losing sensitive information, as it is the case with graphs.

In real life scenarios, the interactions between entities are not static, but they evolve over time. New interactions are created, while others tend to disappear, this brings to a complex dynamic system that brings a theoretically static data structure to evolve over time. This type of challenge makes the management of this temporal evolution a necessity, in order to be able to represent the data always in an accurate way.

The analysis of large dynamic structures also introduces important computational problems. In particular, it is often necessary to continuously update the information of interest without being able to recalculate the entire solution from scratch each time. Consequently, the study of efficient techniques for the maintenance of combinatorial properties and structures in dynamic and temporal environments assumes a central role.

1.2 Problem Statement

2 Background and Related Work

3 Proposed Approach

3.1 Formal Problem Definition

3.1.1 Introduction

We consider an online variant of the Temporal Hitting Set problem under a sliding window model. To this end, we model the input as a temporal hypergraph $H = (V, E)$, where each hyperedge (S, t) consist of a subset of vertices $S \subseteq V$ and a discrete time step $t \in \mathbb{T}$.

Given a time window of size ϵ , we define the set of active hyperedges at time t as:

$$W(t) = \{(S, t') \in E \mid t - \epsilon \leq t' \leq t\}.$$

At each time step t , the algorithm maintains a hitting set $X(t) \subseteq V$ such that:

$$\forall (S, t') \in W(t), \quad X(t) \cap S \neq \emptyset.$$

3.1.2 Objective

The goal is to maintain a feasible hitting set over time while optimizing the following criteria:

- **Solution size:** minimize $|X(t)|$ at each time step;
- **Update cost:** minimize the number of new nodes taken in consideration when updating the hitting set from $X(t-1)$ to $X(t)$;
- **Computational efficiency:** minimize the time required to update the solution as the sliding window evolves.

Overall, the objective is to maintain a small and stable hitting set while efficiently handling the insertion and expiration of hyperedges induced by the sliding window.

4 Experimental evaluation

5 Conclusions and Future Work

Appendix A Attachment

Acknowledgements

Thanks to ...