```
CREATE TABLE tbl1
(
    UserID UInt64,
    PageViews UInt8,
    Duration UInt8,
    Sign Int8,
    Version UInt8
)
ENGINE = CollapsingMergeTree()
ORDER BY UserID;
```

```
INSERT INTO tbl1 VALUES (4324182021466249494, 5, 146, -1, 1);
INSERT INTO tbl1 VALUES (4324182021466249494, 5, 146, 1, 1),(4324182021466249494, 6, 185, 1, 2);

SELECT * FROM tbl1;

SELECT * FROM tbl1 final;
```

```
ch1 :) INSERT INTO tbl1 VALUES (4324182021466249494, 5, 146, -1, 1);
INSERT INTO tbl1 FORMAT Values
Query id: db71a50e-b600-4695-8679-bcbb7fce5ff4
1 row in set. Elapsed: 0.040 sec.
ch1 :) INSERT INTO tbl1 VALUES (4324182021466249494, 5, 146, 1, 1),(4324182021466249494, 6, 185, 1, 2);
INSERT INTO tbl1 FORMAT Values
Query id: c2b9748c-8517-4e82-a108-d3f506f53453
2 rows in set. Elapsed: 0.008 sec.
ch1 :) SELECT * FROM tbl1;
SELECT *
FROM tbl1
Query id: 919b5113-b434-4974-877e-77cf6a11db6d
                    −UserID−<sub>↑</sub>−PageViews−<sub>↑</sub>−Duration−
                                                        -Sign-
                                                                -Version-
     4324182021466249494
                    -UserID-<sub>|</sub>--PageViews--<sub>|</sub>
                                           -Duration-
                                                        -Sign-
                                                                -Version-
     4324182021466249494
2 rows in set. Elapsed: 0.007 sec.
ch1 :) SELECT * FROM tbl1 final;
SELECT *
FROM tbl1
Query id: b3bf1d2c-c3e3-4cf1-8ae5-1a30c93f1ffc
                   −UserID−<sub>↑</sub>−PageViews−<sub>↑</sub>−Duration−<sub>↑</sub>
                                                        -Sign-<sub>|</sub>-Version-
     4324182021466249494
ch1 :)
```

```
CREATE TABLE tbl2
(
    key UInt32,
    value UInt32
)
ENGINE = SummingMergeTree(value)
ORDER BY key;
```

INSERT INTO tbl2 Values(1,1),(1,2),(2,1);

select * from tbl2;

```
ch1 :) INSERT INTO tbl3 VALUES (23, 'success', '2000', 'Cancelled');
INSERT INTO tbl3 FORMAT Values
Query id: 992556fe-5351-4866-a3b2-f150124f02d2
1 row in set. Elapsed: 0.009 sec.
ch1 :) SELECT * from tbl3 WHERE id=23;
SELECT *
FROM tbl3
WHERE id = 23
Query id: c3fd2603-189c-4b01-8159-dafb731dcedd
                    -price-
     ∙id-
          -status-
                            -comment
                    2000
                             Cancelled
     ·id-
          -status-
                    -price
                             -comment-
                    1000
                             Confirmed
2 rows in set. Elapsed: 0.012 sec.
ch1 :) SELECT * from tbl3 FINAL WHERE id=23;
SELECT *
FROM tbl3
FINAL
WHERE id = 23
Query id: d997d715-4e60-4063-b34d-3190d5b3605b
                    -price-
                            -comment
     ·id-
         -status-
                    2000
                            Cancelled
1 row in set. Elapsed: 0.070 sec.
ch1 :)
```

```
CREATE TABLE tbl4
( CounterID UInt8,
    StartDate Date,
    UserID UInt64
) ENGINE = MergeTree
PARTITION BY toYYYYMM(StartDate)
ORDER BY (CounterID, StartDate);
INSERT INTO tbl4 VALUES(0, '2019-11-11', 1);
INSERT INTO tbl4 VALUES(1, '2019-11-12', 1);
```

```
CREATE TABLE tbl4
    `CounterID` UInt8,
    `StartDate` Date,
    `UserID` UInt64
ENGINE = MergeTree
PARTITION BY toYYYYMM(StartDate)
ORDER BY (CounterID, StartDate)
Query id: 00bb3a41-50c5-4a41-a4e1-32f0a9842fe6
0 rows in set. Elapsed: 0.021 sec.
ch1 :) INSERT INTO tbl4 VALUES(0, '2019-11-11', 1);
INSERT INTO tbl4 FORMAT Values
Query id: 250cd082-6e57-48ee-b3b7-751b511df919
Ok.
1 row in set. Elapsed: 0.011 sec.
ch1 :)
ch1 :) INSERT INTO tbl4 VALUES(1, '2019-11-12', 1);
INSERT INTO tbl4 FORMAT Values
Query id: 911976d3-353a-4d1c-8d5f-cb5923f0526f
Ok.
1 row in set. Elapsed: 0.007 sec.
ch1 :)
```

```
CREATE TABLE tbl5
( CounterID UInt8,
    StartDate Date,
    UserID AggregateFunction(uniq, UInt64)
) ENGINE = AggregatingMergeTree
PARTITION BY toYYYYMM(StartDate)
ORDER BY (CounterID, StartDate);
```

INSERT INTO tbl5 select CounterID, StartDate, uniqState(UserID) from tbl4 group by CounterID, StartDate;

```
INSERT INTO tbl5 SELECT
     CounterID,
     StartDate,
     uniqState(UserID)
FROM tbl4
GROUP BY
     CounterID,
     StartDate

Query id: c9c87e66-3747-40a6-8ac7-b36284d0eef0

Ok.
0 rows in set. Elapsed: 0.015 sec.
```

INSERT INTO tbl5 VALUES (1,'2019-11-12',1);

```
ch1 :) INSERT INTO tb15 VALUES (1,'2019-11-12',1);

INSERT INTO tb15 FORMAT Values

Query id: c0f6e869-13a6-4d43-b1f2-be2059983fac

Ok.

Exception on client:
Code: 53. DB::Exception: Cannot convert UInt64 to AggregateFunction(uniq, UInt64): While executing ValuesBlockInputFormat: data for INSERT was parsed from query. (TYPE_MISMATCH)

ch1 :)
```

Попытка вставить в tbl5 в поле UserID, но это поле для агрегации(могу термин путать) для вставки как бы форму лы для решения на сколько понял.

```
SELECT *
FROM tbl5

Query id: 5elbe335-7ce2-4df7-84b0-9elfa597bbd0

CounterID StartDate UserID

0 2019-11-11 , 004
2. 1 2019-11-12 , 004
2 rows in set. Elapsed: 0.009 sec.

ch1 :)
```

SELECT uniqMerge(UserID) AS state FROM tbl5 GROUP BY CounterID, StartDate;

Чтобы получить в обработку новые данные, нужно добавлять в tbl4

```
ch1 :) INSERT INTO tbl4 VALUES (1,'2021-05-12',1);
INSERT INTO tbl4 FORMAT Values
Query id: c34956a3-3808-4f94-a916-e994816a67a9
Ok.
1 row in set. Elapsed: 0.009 sec.
```

```
SELECT
    uniqMerge(UserID) AS state,
    CounterID,
    StartDate
FROM tbl5
GROUP BY
    CounterID,
    StartDate
Query id: 168e3f5c-4614-4bdf-a59a-014f1a2b49ac
    -state-
            -CounterID-
                         -StartDate
                         2020-11-12
         1
                     3
         1
                        2021-11-12
         1
                     1
                         2019-11-12
         1
                     0
                         2019-11-11
         1
                         2020-11-12
5 rows in set. Elapsed: 0.007 sec.
ch1 :)
```

```
INSERT INTO tbl5 SELECT
    CounterID,
    StartDate,
    uniqState(UserID)
FROM tbl4
GROUP BY
    CounterID,
    StartDate

Query id: 382d2bf9-c590-4358-88d8-e6e078f0790e

Ok.

0 rows in set. Elapsed: 0.031 sec.
```

```
SELECT
    uniqMerge(UserID) AS state,
    CounterID,
    StartDate
FROM tbl5
GROUP BY
    CounterID,
    StartDate
Query id: bf06dd06-37ae-490c-8f05-69b495a379ae
            -CounterID-
                         -StartDate-
    -state—
         1
                     3
                         2020-11-12
         1 |
                     1 |
                        2021-11-12
         1
                        2019-11-12
                     0 |
                         2019-11-11
         1
                         2021-05-12
         1
                     1
         1
                     1
                         2020-11-12
6 rows in set. Elapsed: 0.007 sec.
```

```
CREATE TABLE tbl6
(
    'id` Int32,
    'status` String,
    'price` String,
    'comment` String,
    'sign` Int8
```

```
INSERT INTO tbl6 VALUES (23, 'success', '1000', 'Confirmed', 1);
INSERT INTO tbl6 VALUES (23, 'success', '1000', 'Confirmed', -1), (23, 'success', '2000', 'Cancelled', 1);

SELECT * FROM tbl6;
SELECT * FROM tbl6 FINAL;
```