



TECHNICAL GUIDE

Box3D Metal Architecture

A compact guide to the Apple Silicon command graph, shared-memory ownership, constraint colors, and deterministic overflow.



One ordered command graph

Supported constrained worlds encode every substep into one Metal command buffer, wait once, and read body state back once. This minimizes ownership changes on Apple unified memory.

Phase	Stage	Work
1	Integrate velocity	Forces, damping, gyroscopic term, speed limits
2	Warm start	Ordered overflow, then conflict-free graph colors
3	Solve	Biased contact and supported-joint iterations
4	Integrate position	Position and normalized quaternion update
5	Relax	Unbiased constraint iterations
6	Restitution	Eligible convex and mesh contacts
7	Finalize	Optional body state and awake-shape AABBs
8	Refit + pairs	Resident leaves, internal bounds, stable candidates

Unconstrained worlds use a smaller fused path. Unsupported constrained worlds keep the CPU solver and may use only the independent Metal position stage.

Unified memory is not free synchronization

Persistent shared buffers avoid PCIe copies, but command submission, cache coherence, residency, and CPU/GPU ownership transitions still determine crossover.

Data layout and ownership

- Body state and compact body properties use geometrically grown persistent buffers.
- CPU contact preparation writes directly into shared Metal constraint allocations.
- Distance and parallel joints use separate compact type-dense buffers.
- Only accumulated joint solver state is unpacked after the command buffer.
- C/Metal size and offset assertions guard every shared ABI.
- Scalar shader vectors avoid native float3 padding surprises.

Graph colors

Constraints inside one non-overflow color never write the same dynamic body, so one GPU thread can own one constraint without atomics. Colors remain ordered with buffer barriers.

Deterministic overflow

Overflow constraints may share bodies. A single Metal thread walks them in upstream order. Mixed distance/parallel overflow uses an eight-byte type/index descriptor, preserving order with one launch per phase.

Experimental pair traversal

Metal retains Box3D tree topology, updates enlarged leaves, refits parents by height, and compacts candidates in exact upstream order. Pair records carry resident query metadata. A stable 256-lane scan emits one 32-byte record per enlarged shape, avoiding a full-result rescan and second body/shape-list walk during proxy bookkeeping. Topology changes invalidate residency; CPU filters and contact creation remain unchanged.

Apple GPU implementation choices

- One command buffer amortizes submission; shared storage avoids redundant copies; device-derived group widths follow occupancy; conflict-free colors avoid atomics while body-sharing overflow stays serial.