DIVA LUCE

LIMA series

RECESSED ADJUSTABLE DOWNLIGHT













Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED		AC220~240V	3000K	25°	DL-9331-08-3025-P-C
				40°	DL-9331-08-3040-P-C
				60°	DL-9331-08-3060-P-C
COB LED		AC220~240V	4000K	25°	DL-9331-08-4025-P-C
				40°	DL-9331-08-4040-P-C
				60°	DL-9331-08-4060-P-C
COB LED		AC220~240V	5000K	25°	DL-9331-08-5025-P-C
				40°	DL-9331-08-5040-P-C
				60°	DL-9331-08-5060-P-C
COB LED	20W	AC220~240V	3000K	25°	DL-9345-20-3025-P-C
				40°	DL-9345-20-3040-P-C
				60°	DL-9345-20-3060-P-C
COB LED	20W	AC220~240V	4000K	25°	DL-9345-20-4025-P-C
				40°	DL-9345-20-4040-P-C
				60°	DL-9345-20-4060-P-C
COB LED	20W	AC220~240V	5000K	25°	DL-9345-20-5025-P-C
				40°	DL-9345-20-5040-P-C
				60°	DL-9345-20-5060-P-C
COB LED	35W	AC220~240V	3000K	25°	DL-9333-35-3025-P-C
				40°	DL-9333-35-3040-P-C
				60°	DL-9333-35-3060-P-C
COB LED	35W	AC220~240V	4000K	25°	DL-9333-35-4025-P-C
				40°	DL-9333-35-4040-P-C
				60°	DL-9333-35-4060-P-C
COB LED	35W	AC220~240V	5000K	25°	DL-9333-35-5025-P-C
				40°	DL-9333-35-5040-P-C
				60°	DL-9333-35-5060-P-C
					22 0000 00 0000 1 0

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)










Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm

DL-9331-13









DL-9345-20



DL-9333-35



