





Simple and elegant designed led track light with aluminum die-cast housing, with multiple lens angles, specially designed heatsink with excellent dissipation to minimize degradation of the lumens.

APPLICATION fashion stores, chain store, shopping mall, showrooms, art galleries.



















www.divaluce.com

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)

Colour Finish: C (WW-White / White BB-Black / Black | WB-White / Black | BW-Black / White | WS-White / Silver BS-Black / Silver BR-Black / Rose Gold BG-Black / Gold)



White Reflector



Black Reflector







Silver Reflector Rose Gold Reflector Gold Reflector

Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm





COMO series





SURFACE CEILING SPOTLIGHT











	١.		
2 1			
U		•	
YEARS	•	•	

Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED 20W	20W	AC220~240V	3000K	13°	DL-4027A-20-3013-P-C
				30°	DL-4027A-20-3030-P-C
				46°	DL-4027A-20-3046-P-C
COB LED 20W	20W	AC220~240V	4000K	13°	DL-4027A-20-4013-P-C
				30°	DL-4027A-20-4030-P-C
			46°	DL-4027A-20-4046-P-C	
COB LED 20W	20W	AC220~240V	5000K	13°	DL-4027A-20-5013-P-C
				30°	DL-4027A-20-5030-P-C
			46°	DL-4027A-20-5046-P-C	
COB LED 30W	30W	AC220~240V	3000K	13°	DL-4028A-30-3013-P-C
				30°	DL-4028A-30-3030-P-C
			46°	DL-4028A-30-3046-P-C	
COB LED 30W	30W	AC220~240V	4000K	13°	DL-4028A-30-4013-P-C
				30°	DL-4028A-30-4030-P-C
				46°	DL-4028A-30-4046-P-C
COB LED	30W	AC220~240V	5000K	13°	DL-4028A-30-5013-P-C
				30°	DL-4028A-30-5030-P-C
				46°	DL-4028A-30-5046-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)

Colour Finish: C (WW-White / White BB-Black / Black | WB-White / Black | BW-Black / White | WS-White / Silver BS-Black / Silver BR-Black / Rose Gold BG-Black / Gold)











Gold Reflector Rose Gold Reflector

Controller: On / Off, Dimmable, Dali

DIMENSION

DL-4027A-20



DL-4028A-30

