DIVA LUCE

## **TURBINE** series

## RECESSED GRILLE DOWNLIGHT





















Light Source	Power	Voltage	CCT	Beam Angle	Code
COB LED	2x2.5W	AC220~240V	3000K	15°	DL-9748S1-05-3015-P-C
				24°	DL-9748S1-05-3024-P-C
				50°	DL-9748S1-05-3050-P-C
COB LED	2x2.5W	AC220~240V	4000K	15°	DL-9748S1-05-4015-P-C
				24°	DL-9748S1-05-4024-P-C
				50°	DL-9748S1-05-4050-P-C
COB LED	2x2.5W	AC220~240V	5000K	15°	DL-9748S1-05-5015-P-C
				24°	DL-9748S1-05-5024-P-C
				50°	DL-9748S1-05-5050-P-C
COB LED	4x2.5W	AC220~240V	3000K	15°	DL-9748S2-10-3015-P-C
				24°	DL-9748S2-10-3024-P-C
				50°	DL-9748S2-10-3050-P-C
COB LED	4x2.5W	AC220~240V	4000K	15°	DL-9748S2-10-4015-P-C
				24°	DL-9748S2-10-4024-P-C
				50°	DL-9748S2-10-4050-P-C
COB LED	4x2.5W	AC220~240V	5000K	15°	DL-9748S2-10-5015-P-C
				24°	DL-9748S2-10-5024-P-C
				50°	DL-9748S2-10-5050-P-C
COB LED	8x2.5W	AC220~240V	3000K	15°	DL-9748S2-20-3015-P-C
				24°	DL-9748S2-20-3024-P-C
				50°	DL-9748S2-20-3050-P-C
COB LED	8x2.5W	AC220~240V	4000K	15°	DL-9748S2-20-4015-P-C
				24°	DL-9748S2-20-4024-P-C
				50°	DL-9748S2-20-4050-P-C
COB LED	8x2.5W	AC220~240V	5000K	15°	DL-9748S2-20-5015-P-C
				24°	DL-9748S2-20-5024-P-C
				50°	DL-9748S2-20-5050-P-C

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)

Colour Finish: C (WW-White / White BB-Black / Black WB-White / Black)





Controller: On / Off, Dimmable, Dali


DL-9748S1-5





DL-9748S2-10













## **TURBINE** series





66x37 Celling Thickness

DL-9748S2-20