



PENDANT LIGHT

www.divaluce.com

8W	Ra >90	UGR <19	IP20	3 (6
1	1	1		1

	Light Source	Power	Voltage	Code
Pendant Light	SMD LED	8W	AC220-240V	DLF-010-S-08-K-P-B DLF-010-S-08-K-P-W DLF-010-S-08-K-P-R DLF-010-S-08-K-P-G
Pendant Light	SMD LED	3x8W	AC220-240V	DLF-010-S-24-L-K-P-B DLF-010-S-24-L-K-P-W DLF-010-S-24-L-K-P-R DLF-010-S-24-L-K-P-G
Pendant Light	SMD LED	3x8W	AC220-240V	DLF-010-S-24-T-K-P-B DLF-010-S-24-T-K-P-W DLF-010-S-24-T-K-P-R DLF-010-S-24-T-K-P-G

Color Temperature: K (3000K 4000K)


Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)

Colour Finish: B-Black W-White R-Red G-Green

Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm

DLF-010-S-08







	Light Source	Power	Voltage	Code
Pendant Light	SMD LED	8W	AC220-240V	DLF-010-SS-08-K-P-B DLF-010-SS-08-K-P-W DLF-010-SS-08-K-P-R DLF-010-SS-08-K-P-G
Pendant Light	SMD LED	3x8W	AC220~240V	DLF-010-SS-24-L-K-P-B DLF-010-SS-24-L-K-P-W DLF-010-SS-24-L-K-P-R DLF-010-SS-24-L-K-P-G
Pendant Light	SMD LED	3x8W	AC220~240V	DLF-010-SS-24-T-K-P-B DLF-010-SS-24-T-K-P-W DLF-010-SS-24-T-K-P-R DLF-010-SS-24-T-K-P-G

Color Temperature: K (3000K 4000K)

Power Supply: P (1-On / Off 2-Phase Dim 3-DALI Dim 4-1-10V Dim)

Colour Finish: B-Black W-White R-Red G-Green


Controller: On / Off, Dimmable, Dali

DIMENSION unit:mm

DLF-010-SS-08







DLF-010-SS-24-T

CANDLE series