

```
/*
    0. 数组空间是否足够？数组空间是否足够？数组空间是否足够？数据范围开int还是long long?

    1. 多想一点，少错一点！
    是否有你的算法的反例？

    2. 注意边界条件！
    n = 1考虑了吗？ p = 0考虑了吗？ 是否对有关-1的东西有特判？

    3. 不要犯愚蠢的错误！
    时间复杂度有没有写假？空间足够吗？精度是否正确？
*/

#include <bits/stdc++.h>
using namespace std;
using ll = long long;
using ull = unsigned long long;
namespace pbds = __gnu_pbds;

int main() {
    cin.tie(nullptr)->sync_with_stdio(false);

    return 0;
}
```

板子

目录

- [让代码跑起来](#)
 - [编译运行](#)
 - [对拍器](#)
- [数据结构](#)
 - [线段树](#)
 - [主席树](#)
 - [树状数组](#)
 - [差分数组](#)
 - [分块](#)
 - [并查集](#)
 - [无旋Treap](#)
 - [树的倍增数组](#)
 - [树链剖分](#)
 - [ST表](#)
 - [01-Trie](#)
 - [CDQ分治](#)
 - [莫队](#)
 - [单调栈、单调队列](#)
- [图论](#)
 - [Dijkstra](#)
 - [Floyd](#)
 - [SPFA](#)
 - [或值最短路](#)
 - [Tarjan全家桶](#)

- 同余最短路
 - Kruskal
 - Prim
 - Boruvka
 - Dinic
 - 匈牙利算法
 - 2-SAT
 - 搜索
 - 迭代加深
 - 动态规划
 - 背包DP
 - 区间DP
 - 数位DP
 - 计数DP
 - 线段树优化DP
 - 数学
 - 快速幂和模整数类
 - 组合数
 - EXGCD
 - 中国剩余定理
 - 斯特林数
 - 质数筛
 - 多项式乘法
 - 线性基
 - 矩阵乘法、矩阵快速幂
 - 构造增广状态转移矩阵
 - Lehmer码
 - 计算几何
 - 平面凸包
 - 字符串
 - KMP
 - Z函数/扩展KMP
 - 字典树
 - Manacher
 - AC自动机
 - 贪心
 - 一组交叉直线经过所有点
 - 二分
 - 最长上升子序列
 - 二分答案
 - 三分
 - 杂项
 - 高精
 - 快读
-

让代码跑起来

编译运行

```
g++ -std=c++20 test.cpp -o test.out
./test.out < input.txt
```

对拍器

```
# 请根据实际的C++版本修改-std版本
g++ generator.cpp -o generator.out -std=c++20 -O2 || exit 1
g++ solution.cpp -o solution.out -std=c++20 -O2 || exit 1
g++ brute_force.cpp -o brute_force.out -std=c++20 -O2 || exit 1
mkdir -p testcases
count=1
while true; do
    echo "Running test $count"
    ./generator.out > testcases/input.txt
    timeout 2s ./solution.out < testcases/input.txt > testcases/output_solution.txt
    exit_code=$?
    if [ $exit_code -eq 124 ]; then
        echo -e "\033[31mTime Limit Exceeded on solution\033[0m"
        break
    elif [ $exit_code -eq 139 ]; then
        echo -e "\033[31mRuntime Error (Segmentation fault) on solution\033[0m"
        cat testcases/input.txt
        break
    elif [ $exit_code -eq 134 ]; then
        echo -e "\033[31mRuntime Error (Aborted) on solution\033[0m"
        cat testcases/input.txt
        break
    elif [ $exit_code -eq 136 ]; then
        echo -e "\033[31mRuntime Error (Floating point exception) on solution\033[0m"
        cat testcases/input.txt
        break
    fi
    timeout 2s ./brute_force.out < testcases/input.txt > testcases/output_brute_force.txt
    if [ $exit_code -eq 124 ]; then
        echo -e "\033[31mTime Limit Exceeded on brute force\033[0m"
        break
    fi
    if ! diff -wB testcases/output_solution.txt testcases/output_brute_force.txt > /dev/null; then
        echo -e "\033[31mWrong Answer on test case $count\033[0m"
        echo "Input:"
        cat testcases/input.txt
        echo -e "\nSolution output:"
        cat testcases/output_solution.txt
        echo -e "\nBrute force output:"
        cat testcases/output_brute_force.txt
        break
    fi
    echo -e "\033[32mAccepted\033[0m"
    ((count++))
done
```

数据结构

线段树

```
struct SegTree {
    int n;
    SegTree(const vector<ll> &v)
        : n(v.size()), sum(v.size() * 4), lazy(v.size() * 4, 0) {
        _build(v, 0, 0, n);
    }
    SegTree(int sz) : n(sz), sum(sz * 4, 0), lazy(sz * 4, 0) {}
    SegTree() : n(0) {}
    void assign(int sz) {
        n = sz;
        sum.assign(n * 4, 0);
        lazy.assign(n * 4, 0);
    }
    void assign(const vector<ll> &v) {
        n = v.size();
        sum.assign(v.size() * 4, 0);
        lazy.assign(v.size() * 4, 0);
        _build(v, 0, 0, n);
    }
    ll query(int l, int r) const {
        if(l == r) return 0;
        return _query(l, r, 0, 0, n);
    }
    void update(int l, int r, ll dval) {
        if(l == r) return;
        _update(l, r, dval, 0, 0, n);
    }
private:
    void _build(const vector<ll> &v, int r, int r1, int rr) {
        if(rr - r1 == 1) {
            sum[r] = v[r1];
            return;
        }
        int m = (r1 + rr) / 2;
        _build(v, r * 2 + 1, r1, m);
        _build(v, r * 2 + 2, m, rr);
        sum[r] = sum[r * 2 + 1] + sum[r * 2 + 2];
    }
    void _pushdown(int root, int r1, int rr) const {
        if(lazy[root] == 0) return;
        int m = (r1 + rr) / 2;
        sum[root * 2 + 1] += lazy[root] * (m - r1);
        lazy[root * 2 + 1] += lazy[root];
        sum[root * 2 + 2] += lazy[root] * (rr - m);
        lazy[root * 2 + 2] += lazy[root];
        lazy[root] = 0;
    }
    ll _query(int ql, int qr, int root, int r1, int rr) const {
        if(ql <= r1 && qr >= rr) return sum[root];
        _pushdown(root, r1, rr);
        int mid = (r1 + rr) / 2;
        ll ans = 0;
        if(ql < mid) {
            ans += _query(ql, qr, root * 2 + 1, r1, mid);
        }
    }
}
```

```

        if(qr > mid) {
            ans += _query(ql, qr, root * 2 + 2, mid, rr);
        }
        return ans;
    }
// 区间修改
void _update(int ul, int ur, ll dv, int root, int r1, int rr) {
    if(ul <= r1 && ur >= rr) {
        sum[root] += dv * (rr - r1);
        lazy[root] += dv;
        return;
    }
    _pushdown(root, r1, rr);
    int mid = (r1 + rr) / 2;
    if(ul < mid) {
        _update(ul, ur, dv, root * 2 + 1, r1, mid);
    }
    if(ur > mid) {
        _update(ul, ur, dv, root * 2 + 2, mid, rr);
    }
    sum[root] = sum[root * 2 + 1] + sum[root * 2 + 2];
}
// 单点修改
void __update(int x, ll v, int root, int r1, int rr) {
    if(r1 == rr - 1) {
        sum[root] += v;
        return;
    }
    int mid = (r1 + rr) / 2;
    if(x < mid) {
        __update(x, v, root * 2 + 1, r1, mid);
    } else {
        __update(x, v, root * 2 + 2, mid, rr);
    }
    sum[root] = sum[root * 2 + 1] + sum[root * 2 + 2];
}
mutable vector<ll> sum, lazy;
};

```

主席树

```
// persistent segment tree
struct PST {
    const int n;
    PST(int n_) : n(n_) {
        nodes.reserve(2 * n * (int)log2(n));
        vers.reserve(n + 1);
        vers.push_back(_build(0, n - 1));
    }
    void update(int k) {
        vers.push_back(_update(k, vers.back(), 0, n - 1));
    }
    // 这里为解决静态区间第k小问题设计, 传入k, l, r
    int query(int k, int ver1, int ver2) const {
        return _query(k, vers[ver1 - 1], vers[ver2], 0, n - 1);
    }
private:
    struct Node {
        int l, r;
        int cnt;
    };
    vector<Node> nodes;
    vector<int> vers;
    int _build(int l, int r) {
        int ret = nodes.size();
        if(l == r) {
            nodes.emplace_back(-1, -1, 0);
            return ret;
        }
        nodes.emplace_back(-1, -1, 0);
        int mid = (l + r) >> 1;
        nodes[ret].l = _build(l, mid);
        nodes[ret].r = _build(mid + 1, r);
        return ret;
    }
    int _update(int k, int root, int l, int r) {
        int ret = nodes.size();
        nodes.emplace_back(nodes[root]);
        nodes[ret].cnt++;
        if(l == r) {
            return ret;
        }
        int mid = (l + r) >> 1;
        if(k <= mid) {
            nodes[ret].l = _update(k, nodes[root].l, l, mid);
        } else {
            nodes[ret].r = _update(k, nodes[root].r, mid + 1, r);
        }
        return ret;
    }
    int _query(int k, int root1, int root2, int l, int r) const {
        if(l == r) return l;
        int mid = (l + r) >> 1;
        int cnt1 = nodes[nodes[root2].l].cnt - nodes[nodes[root1].l].cnt;
        if(k <= cnt1) {
            return _query(k, nodes[root1].l, nodes[root2].l, l, mid);
        } else {
            return _query(k - cnt1, nodes[root1].r, nodes[root2].r, mid + 1, r);
        }
    }
}
```

```

    }
};

```

树状数组（单点、区间）

```

// 单点
struct Fenwick {
    const int n;
    Fenwick(int n)
        : n(n), nums(n + 1) {}
    ll query(int x) const {
        ll ans = 0;
        for(; x; x -= lbit(x)) {
            ans += nums[x];
        }
        return ans;
    }
    void update(int x, ll v) {
        for(; x <= n; x += lbit(x)) {
            nums[x] += v;
        }
    }
private:
    vector<ll> nums;
    static int lbit(int x) {
        return x & -x;
    }
};

// 区间
struct RangeFenwick {
    const int n;
    RangeFenwick(int n)
        : n(n), f1(n), f2(n) {}
    void update(int l, int r, ll v) {
        _update(l, v);
        _update(r + 1, -v);
    }
    ll query(int l, int r) const {
        return _query(r) - _query(l - 1);
    }
private:
    Fenwick f1, f2;
    void _update(int x, ll v) {
        f1.update(x, v);
        f2.update(x, v * (x - 1));
    }
    ll _query(int x) const {
        return f1.query(x) * x - f2.query(x);
    }
};

```

差分数组

使用差分数组区间加等差数列

```
// 二次差分
vector<ll> diff(n + 3, 0);
// [1,l]第i项加i
diff[1] += val;
diff[l + 1] -= val;
// [r+1,l+r]第i项减i-r
diff[r + 1] -= val;
diff[l + r + 1] += val;
// 还原
for(int _ = 0; _ < 2; ++_) {
    for(int i = 1; i < n + 3; ++i) {
        diff[i] += diff[i - 1];
    }
}
```

树状数组在线处理

```
struct ArithmeticFenwick {
    ArithmeticFenwick(int n)
        : f1(n + 2), f2(n + 2) {}
    // a*idx+b
    void update(int l, int r, ll a, ll b) {
        f1.update(l, b);
        f1.update(r + 1, -b - a * (r - l + 1));
        f2.update(l, a);
        f2.update(r + 1, -a);
    }
    ll query(ll idx) const {
        return f1.query(idx) + idx * f2.query(idx);
    }
private:
    Fenwick f1, f2;
};
```

分块

```
struct Block {
    Block() : l(-1), r(-1) {}
    // 注意左闭右开
    Block(int l, int r, const vector<ll> &nums_)
        : nums(r - 1), lazy(0), sum(0), l(l), r(r) {
        for(int i = l; i < r; ++i) {
            nums[i - 1] = nums_[i];
            sum += nums[i - 1];
        }
    }
    // 注意左闭右开
    void update(int ul, int ur, ll dval) {
        if(ul > r || ur < l) {
            return;
        }
        if(ul <= l && ur >= r) {
            lazy += dval;
            sum += dval * (r - l);
            return;
        }
        for(int i = max(ul, l); i < min(ur, r); ++i) {
            nums[i - 1] += dval;
        }
        sum += dval * (min(ur, r) - max(ul, l));
    }
    // 注意左闭右开
    ll query(int ql, int qr) const {
        if(ql >= r || qr <= l) {
            return 0;
        }
        if(ql <= l && qr >= r) {
            return sum;
        }
        ll ans = lazy * (min(qr, r) - max(ql, l));
        for(int i = max(ql, l); i < min(qr, r); ++i) {
            ans += nums[i - 1];
        }
        return ans;
    }
private:
    vector<ll> nums;
    ll lazy;
    ll sum;
    int l, r;
};

struct BlockedArray {
    BlockedArray(const vector<ll> &nums) {
        int r = nums.size();
        int len = sqrt(r + 0.5);
        int size = (r + len - 1) / len;
        blocks.reserve(size);
        for(int i = 0; i < size; ++i) {
            int ll = i * len, rr = min((i + 1) * len, r);
            blocks.emplace_back(ll, rr, nums);
        }
    }
    void update(int l, int r, ll d) {
        for(auto &blk : blocks) {
```

```
        blk.update(l, r, d);
    }
}
ll query(int l, int r) const {
    ll ans = 0;
    for(const auto &blk : blocks) {
        ans += blk.query(l, r);
    }
    return ans;
}
vector<Block> blocks;
};
```

并查集

```
// 按秩合并
struct DSU {
    DSU(int n) : fa(n), rk(n, 1) {
        iota(fa.begin(), fa.end(), 0);
    }
    int find(int x) const {
        if(fa[x] != x) {
            fa[x] = find(fa[x]);
        }
        return fa[x];
    }
    bool is_connected(int x, int y) const {
        return find(x) == find(y);
    }
    void connect(int x, int y) {
        x = find(x);
        y = find(y);
        if(x == y) return;
        if(rk[x] < rk[y]) {
            swap(x, y);
        }
        if(rk[x] == rk[y]) {
            rk[x]++;
        }
        fa[y] = x;
    }
private:
    mutable vector<int> fa, rk;
};

// 随机合并
struct DSU_Random {
    DSU_Random(int n) : fa(n) {
        iota(fa.begin(), fa.end(), 0);
    }
    int find(int x) const {
        if(fa[x] != x) {
            fa[x] = find(fa[x]);
        }
        return fa[x];
    }
    bool is_connected(int x, int y) const {
        return find(x) == find(y);
    }
    void connect(int x, int y) {
        int fx = find(x), fy = find(y);
        if(rnd() % 2) {
            fa[fx] = fy;
        } else {
            fa[fy] = fx;
        }
    }
private:
    static inline mt19937 rnd{ (unsigned int)chrono::steady_clock::now()
        .time_since_epoch().count() };
    mutable vector<int> fa;
};
```

无旋Treap

```
constexpr int inf = 0x3f3f3f3f;
struct Treap {
    Treap() : rt(nullptr) {}
    ~Treap() {
        if(rt) {
            _dtor(rt);
        }
    }
    void insert(int v) {
        auto tmp = _sval(rt, v);
        auto l = _sval(tmp.first, v - 1);
        Node *node = l.second;
        if(!l.second) {
            node = new Node(v);
        } else {
            l.second->cnt++;
            l.second->usize();
        }
        Node *lc = _merge(l.first, node);
        rt = _merge(lc, tmp.second);
    }
    void erase(int v) {
        auto tmp = _sval(rt, v);
        auto l = _sval(tmp.first, v - 1);
        if(l.second->cnt > 1) {
            l.second->cnt--;
            l.second->usize();
            l.first = _merge(l.first, l.second);
        } else {
            if(tmp.first == l.second) {
                tmp.first = nullptr;
            }
            delete l.second;
            l.second = nullptr;
        }
        rt = _merge(l.first, tmp.second);
    }
    // 注意0-based
    int qrv(int v) const {
        return _qrv(rt, v);
    }
    // 注意0-based
    int qvr(int r) const {
        return _qvr(rt, r);
    }
    // 注意是小于的, 不是大于等于的
    int lower_bound(int v) const {
        auto tmp = _sval(rt, v - 1);
        int ret = -inf;
        if(tmp.first) {
            ret = _qvr(tmp.first, tmp.first->size - 1);
        }
        rt = _merge(tmp.first, tmp.second);
        return ret;
    }
    int upper_bound(int v) const {
        auto tmp = _sval(rt, v);
        int ret = -inf;
```

```

        if(tmp.second) {
            ret = _qvr(tmp.second, 0);
        }
        rt = _merge(tmp.first, tmp.second);
        return ret;
    }
private:
    struct Node {
        int val;
        int cnt;
        int size;
        int prio;
        Node *left, *right;
        static inline random_device rnd{};
        Node(int v)
            : val(v), cnt(1), size(1), prio(rnd()), left(nullptr), right(nullptr) {}
        void usize() {
            size = cnt;
            if(left) {
                size += left->size;
            }
            if(right) {
                size += right->size;
            }
        }
    };
    mutable Node *rt;
    static void _dtor(Node *ptr) {
        if(ptr->left) {
            _dtor(ptr->left);
            ptr->left = nullptr;
        }
        if(ptr->right) {
            _dtor(ptr->right);
            ptr->right = nullptr;
        }
        delete ptr;
    }
    static pair<Node *, Node *> _sval(Node *const ptr, int key) {
        if(!ptr) {
            return { nullptr, nullptr };
        }
        if(ptr->val <= key) {
            auto tmp = _sval(ptr->right, key);
            ptr->right = tmp.first;
            ptr->usize();
            return { ptr, tmp.second };
        } else {
            auto tmp = _sval(ptr->left, key);
            ptr->left = tmp.second;
            ptr->usize();
            return { tmp.first, ptr };
        }
    }
    static tuple<Node *, Node *, Node *> _srnk(Node *const ptr, int rnk) {
        if(!ptr) return { nullptr, nullptr, nullptr };
        int lsize = (ptr->left ? ptr->left->size : 0);
        if(rnk < lsize) {
            auto [lptr, mptr, rptr] = _srnk(ptr->left, rnk);
            ptr->left = rptr;

```

```

        ptr->usize();
        return { lptra, mptra, ptr };
    } else if(rnk < lsize + ptr->cnt) {
        Node *lptra = ptr->left;
        Node *rptra = ptr->right;
        ptr->left = ptr->right = nullptr;
        return { lptra, ptr, rptra };
    } else {
        auto [lptra, mptra, rptra] = _srnk(ptr->right, rnk - lsize - ptr->cnt);
        ptr->right = lptra;
        ptr->usize();
        return { ptr, mptra, rptra };
    }
}

static Node *_merge(Node *const u, Node *const v) {
    if(!u) return v;
    if(!v) return u;
    if(u->prio < v->prio) {
        u->right = _merge(u->right, v);
        u->usize();
        return u;
    } else {
        v->left = _merge(u, v->left);
        v->usize();
        return v;
    }
}

int _qrv(Node *const ptr, int val) const {
    auto [l, r] = _sval(ptr, val - 1);
    int ret = (l ? l->size : 0);
    rt = _merge(l, r);
    return ret;
}

int _qvr(Node *const ptr, int r) const {
    auto [lptra, mptra, rptra] = _srnk(ptr, r);
    int ret = mptra->val;
    rt = _merge(_merge(lptra, mptra), rptra);
    return ret;
}

};

```

树的倍增算法

```
constexpr int LOG = 20;
struct Increment {
    Increment(int n)
        : tree(n), anc(n, vector<int>(LOG, -1)), depth(n) {}
    void addedge(int u, int v) {
        tree[u].push_back(v);
        tree[v].push_back(u);
    }
    void build(int root) {
        dfs(root, -1);
    }
    int lca(int u, int v) {
        if(depth[u] < depth[v]) swap(u, v);
        for(int k = LOG - 1; k >= 0; --k) {
            if(anc[u][k] != -1) {
                if(depth[anc[u][k]] >= depth[v]) {
                    u = anc[u][k];
                }
            }
        }
        if(u == v) return u;
        for(int k = LOG - 1; k >= 0; --k) {
            if(anc[u][k] != anc[v][k]) {
                u = anc[u][k];
                v = anc[v][k];
            }
        }
        return anc[u][0];
    }
    int kth_ancestor(int x, int k) {
        for(int i = 0; i < LOG; ++i) {
            if((k >> i) & 1) {
                x = anc[x][i];
                if(x == -1) return -1;
            }
        }
        return x;
    }
    vector<vector<int>> tree;
private:
    vector<vector<int>> anc;
    vector<int> depth;
    void dfs(int root, int fa) {
        depth[root] = fa != -1 ? depth[fa] + 1 : 0;
        anc[root][0] = fa;
        for(int k = 1; k < LOG; ++k) {
            if(anc[root][k - 1] == -1) {
                anc[root][k] = -1;
            } else {
                anc[root][k] = anc[anc[root][k - 1]][k - 1];
            }
        }
        for(const int v : tree[root]) {
            if(v != fa) {
                dfs(v, root);
            }
        }
    }
}
```

}

};

树链剖分

// 请拿一个单点修改（更新值）、区间查询的线段树

```
struct Node {
    ll w;
    vector<int> e;
};

struct HLD {
    HLD(const vector<Node> &g, int r = 0)
        : nodes(g.size()), nfd(g.size()) {
        dfs1(g, r, -1);
        int now_index = 0;
        dfs2(g, r, -1, now_index, r);
        vector<ll> nums(g.size());
        for(int i = 0; i < g.size(); ++i) {
            nums[nodes[i].dfn] = g[i].w;
        }
        seg.assign(nums);
    }

    int lca(int u, int v) const {
        while(nodes[u].toc != nodes[v].toc) {
            if(nodes[nodes[u].toc].d < nodes[nodes[v].toc].d) {
                v = nodes[nodes[v].toc].fa;
            } else {
                u = nodes[nodes[u].toc].fa;
            }
        }
        return nodes[u].d < nodes[v].d ? u : v;
    }

    void modify(int x, ll v) {
        seg.modify(nodes[x].dfn, v);
    }

    ll query_sum(int u, int v) const {
        int lca_node = lca(u, v);
        auto query_to_lca = [&](int point) -> ll {
            ll ans = 0;
            for(; nodes[point].toc != nodes[lca_node].toc;
                point = nodes[nodes[point].toc].fa) {
                int pos1 = nodes[point].dfn;
                int pos2 = nodes[nodes[point].toc].dfn;
                ans += seg.query_sum(pos2, pos1 + 1);
            }
            int pos1 = nodes[lca_node].dfn;
            int pos2 = nodes[point].dfn;
            ans += seg.query_sum(pos1 + 1, pos2 + 1);
            return ans;
        };
        ll ans = query_to_lca(u);
        ans += query_to_lca(v);
        int lca_pos = nodes[lca_node].dfn;
        ans += seg.query_sum(lca_pos, lca_pos + 1);
        return ans;
    }

private:
    struct _Node {
        int d;
        int fa;
        int toc;
        int dfn;
        int sz;
    };
};
```

```

        int hs;
};

void dfs1(const vector<Node> &g, int x, int fa) {
    if(fa == -1) {
        nodes[x].d = 0;
    } else {
        nodes[x].d = nodes[fa].d + 1;
    }
    nodes[x].fa = fa;
    nodes[x].sz = 1;
    nodes[x].hs = -1;
    for(int i = 0; i < g[x].e.size(); ++i) {
        int next = g[x].e[i];
        if(next == fa) continue;
        dfs1(g, next, x);
        nodes[x].sz += nodes[next].sz;
        if(nodes[x].hs == -1 ||
            nodes[nodes[x].hs].sz < nodes[next].sz) {
            nodes[x].hs = next;
        }
    }
}

void dfs2(const vector<Node> &g, int x, int fa, int &dfn, int toc) {
    nodes[x].dfn = dfn++;
    nodes[x].toc = toc;
    if(nodes[x].hs != -1) {
        dfs2(g, nodes[x].hs, x, dfn, toc);
        for(int i = 0; i < g[x].e.size(); ++i) {
            int next = g[x].e[i];
            if(next != nodes[x].hs && next != fa) {
                dfs2(g, next, x, dfn, next);
            }
        }
    }
}

vector<_Node> nodes;
vector<int> nfd;
SegTree seg;
};

```

ST表

```
template<class T> struct Sparse {
    using func_type = function<T(T, T)>;
    Sparse(const vector<T> &vec, func_type fn) : func(fn) {
        int n = vec.size();
        _log.resize(n + 1);
        _log[0] = -1;
        for(int i = 1; i <= n; ++i) {
            _log[i] = _log[i >> 1] + 1;
        }
        int k = _log[n] + 1;
        table.resize(n, vector<T>(k));
        for(int i = 0; i < n; ++i) {
            table[i][0] = vec[i];
        }
        for(int j = 1; j < k; ++j) {
            int step = 1 << (j - 1);
            for(int i = 0; i + step < n; ++i) {
                table[i][j] = func(table[i][j - 1], table[i + step][j - 1]);
            }
        }
    }
    T query(int l, int r) const {
        int len = r - l + 1;
        int j = _log[len];
        return func(table[l][j], table[r - (1 << j) + 1][j]);
    }
private:
    vector<vector<T>> table;
    vector<int> _log;
    func_type func;
};
```

01-Trie

```
struct Trie01 {
    Trie01() : nodes(1) {}
    void insert(ll val) {
        int now = 0;
        for(ll i = 62; i >= 0; --i) {
            ll flag = (val >> i) & 1;
            if(nodes[now].nxt[flag] == -1) {
                nodes[now].nxt[flag] = nodes.size();
                nodes.emplace_back();
            }
            now = nodes[now].nxt[flag];
        }
    }
    ll qmax_xor(ll val) const {
        int now = 0;
        ll ans = 0;
        for(ll i = 62; i >= 0; --i) {
            ll flag = (val >> i) & 1;
            if(nodes[now].nxt[1 ^ flag] != -1) {
                ans += (1ll << i);
                now = nodes[now].nxt[1 ^ flag];
            } else {
                now = nodes[now].nxt[flag];
            }
        }
        return ans;
    }
private:
    static constexpr int height = 63;
    struct Node {
        int nxt[2];
        Node() {
            nxt[0] = nxt[1] = -1;
        }
    };
    vector<Node> nodes;
};
```

CDQ分治

```
struct Data {
    int x, y, z;
    int cnt;
    int ans;
    Data(int x_, int y_, int z_) : x(x_), y(y_), z(z_), cnt(1), ans(-1) {}
};

vector<int> threed_partial(int n, int k, vector<Data> &_datas) {
    Fenwick fwk(k);
    sort(_datas.begin(), _datas.end() - 1, [](const Data &l, const Data &r) {
        if(l.x != r.x) return l.x < r.x;
        if(l.y != r.y) return l.y < r.y;
        return l.z < r.z;
    });
    // 如果值域很大, 考虑离散化数据
    vector<Data> datas;
    datas.reserve(n);
    int cnt = 0;
    for(int i = 0; i < n; ++i) {
        ++cnt;
        if((_datas[i].x != _datas[i + 1].x) ||
            (_datas[i].y != _datas[i + 1].y) ||
            (_datas[i].z != _datas[i + 1].z)) {
            datas.emplace_back(_datas[i].x, _datas[i].y, _datas[i].z);
            cnt = 0;
        }
    }
    int m = datas.size();
    auto cdq = [&](auto &&cdq, int l, int r) -> void {
        if(r - l < 2) {
            return;
        }
        int mid = (l + r) >> 1;
        cdq(cdq, l, mid);
        cdq(cdq, mid, r);
        sort(datas.begin() + l, datas.begin() + mid, [](const Data &l, const Data &r) {
            if(l.y != r.y) return l.y < r.y;
            return l.z < r.z;
        });
        sort(datas.begin() + mid, datas.begin() + r, [](const Data &l, const Data &r) {
            if(l.y != r.y) return l.y < r.y;
            return l.z < r.z;
        });
        int j = 1;
        for(int i = mid; i < r; ++i) {
            while(datas[j].y <= datas[i].y && j < mid) {
                fwk.update(datas[j].z, datas[j].cnt);
                ++j;
            }
            datas[i].ans += fwk.query(datas[i].z);
        }
        for(int k = l; k < j; ++k) {
            fwk.update(datas[k].z, -datas[k].cnt);
        }
    };
    cdq(cdq, 0, m);
    vector<int> ans(n, 0);
    for(int i = 0; i < m; ++i) {
        ans[datas[i].ans + datas[i].cnt - 1] += datas[i].cnt;
    }
}
```

```
    }  
    return ans;  
}
```

莫队

```
struct Query {
    int idx;
    // 左闭右开
    int l, r;
    int ans;
};

// 查询区间内满足元素出现次数等于自身的数的个数
void mo_algo(vector<Query> &queries, const vector<int> &nums) {
    int n = nums.size();
    int len = sqrt(n);
    sort(queries.begin(), queries.end(), [&](const Query &q1, const Query &q2) {
        int at1 = q1.l / len, atr = q2.l / len;
        if(at1 != atr) {
            return at1 < atr;
        }
        return (bool)((at1 % 2 == 0) ^ (q1.r < q2.r));
    });
    int l = 0, r = 0, ans = 0;
    vector<int> count(n + 5, 0);
    auto add = [&](int x) {
        if(x >= n + 5) return;
        if(count[x] == x) --ans;
        count[x]++;
        if(count[x] == x) ++ans;
    };
    auto remove = [&](int x) {
        if(x >= n + 5) return;
        if(count[x] == x) --ans;
        count[x]--;
        if(count[x] == x) ++ans;
    };
    for(auto &q : queries) {
        // 抄板子时注意顺序，先加再更新还是先更新再加
        while(l > q.l) {
            --l;
            add(nums[l]);
        }
        while(l < q.l) {
            remove(nums[l]);
            ++l;
        }
        while(r < q.r) {
            add(nums[r]);
            ++r;
        }
        while(r > q.r) {
            --r;
            remove(nums[r]);
        }
        q.ans = ans;
    }
    sort(queries.begin(), queries.end(), [](const Query &l, const Query &r) {
        return l.idx < r.idx;
    });
}
```

单调栈、单调队列

```
// 单调栈: [l, r), 且有相同元素时, 左边取最左端, 右边取下一个自己
vector<pair<int, int>> max_range(const vector<int> &nums) {
    int n = nums.size();
    vector ret(n, pair(-1, -1));
    vector<pair<int, int>> stk; // 单调栈
    ret[0].first = 0;
    stk.emplace_back(nums[0], 0);
    for(int i = 1; i < n; ++i) {
        while(!stk.empty() && stk.back().first <= nums[i]) {
            ret[stk.back().second].second = i;
            stk.pop_back();
        }
        ret[i].first = stk.empty() ? 0 : stk.back().second + 1;
        stk.emplace_back(nums[i], i);
    }
    for(int i = n - 1; i >= 0; --i) {
        if(ret[i].second == -1) {
            ret[i].second = n;
        }
    }
    return ret;
}
// 可以有相同元素
```

```
vector ret(n, pair(0, n));
vector<int> stk;
for(int i = 0; i < n; ++i) {
    while(!stk.empty() && nums[stk.back()] <= nums[i]) {
        stk.pop_back();
    }
    if(!stk.empty()) {
        ret[i].first = stk.back() + 1;
    }
    stk.push_back(i);
}
stk.clear();
for(int i = n - 1; i >= 0; --i) {
    while(!stk.empty() && nums[stk.back()] <= nums[i]) {
        stk.pop_back();
    }
    if(!stk.empty()) {
        ret[i].second = stk.back();
    }
    stk.push_back(i);
}
```

// 最大滑动窗口: 单调队列

```
vector<int> max_sliding_window(const vector<int> &nums, int k) {
    int n = nums.size();
    vector<int> ret(n - k + 1);
    vector<pair<int, int>> que;
    for(int i = 0; i < k - 1; ++i) {
        while(!que.empty() && que.back().first < nums[i]) {
            que.pop_back();
        }
        que.emplace_back(nums[i], i);
    }
    int st = 0;
    for(int i = 0; i <= n - k; ++i) {
        int j = i + k - 1;
```

```

        if(que.size() > st && que[st].second < i) {
            ++st;
        }
        while(!que.empty() && que.back().first < nums[j]) {
            que.pop_back();
        }
        st = min(st, (int)que.size());
        que.emplace_back(nums[j], j);
        ret[i] = que[st].first;
    }
    return ret;
}

```

图论

Dijkstra

```

constexpr ll inf = 0x3f3f3f3f3f3f3f3f;
vector<ll> dijkstra(vector<vector<pair<int, ll>>> &graph, int start) noexcept {
    int v = graph.size();
    vector<ll> dist(v, inf);
    dist[start] = 0;
    vector<bool> visited(v, false);
    priority_queue<pair<ll, int>, vector<pair<ll, int>>, greater<>> pq;
    for(auto [vtx, w] : graph[start]) {
        dist[vtx] = w;
        pq.emplace(w, vtx);
    }
    while(!pq.empty()) {
        auto [w, vtx] = pq.top();
        pq.pop();
        if(visited[vtx]) continue;
        visited[vtx] = true;
        for(auto [vt, ww] : graph[vtx]) {
            if(!visited[vt]) {
                if(dist[vt] > dist[vtx] + ww) {
                    dist[vt] = dist[vtx] + ww;
                    pq.emplace(dist[vt], vt);
                }
            }
        }
    }
    return dist;
}

```

Floyd

```
// 操作后, graph就变成了最短路
void floyd(vector<vector<ll>> &graph) {
    for(int k = 0; k < graph.size(); ++k) {
        for(int i = 0; i < graph.size(); ++i) {
            for(int j = 0; j < graph.size(); ++j) {
                if(graph[i][j] > graph[i][k] + graph[k][j]) {
                    graph[i][j] = graph[i][k] + graph[k][j];
                }
            }
        }
    }
}
```

SPFA

```
constexpr ll inf = 0x3f3f3f3f3f3f3f3f;
// 返回空vector说明有负环
vector<ll> spfa(const vector<vector<pair<int, ll>>> &graph, int s) {
    int n = graph.size();
    vector<ll> dist(n, inf);
    vector<int> count(n, 0);
    vector<bool> inqueue(n, false);
    queue<int> q;
    q.push(s);
    dist[s] = 0;
    inqueue[s] = true;
    while(!q.empty()) {
        int u = q.front();
        q.pop();
        inqueue[u] = false;
        for(auto [v, w] : graph[u]) {
            if(dist[v] > dist[u] + w) {
                dist[v] = dist[u] + w;
                if(!inqueue[v]) {
                    inqueue[v] = true;
                    q.push(v);
                    count[v] = count[u] + 1;
                    if(count[v] > n) {
                        return {};
                    }
                }
            }
        }
    }
}
return dist;
}
```

或值最短路

```
// 并查集谢谢喵
int ans = (1 << 30) - 1;
for(int i = 29; i >= 0; i--) {
    ans ^= (1 << i);
    DSU dsu(n);
    for(auto &[u, v, w] : edges) {
        if((w & ans) == w) {
            dsu.connect(u, v);
        }
    }
    if(!dsu.is_connected(0, n - 1)) {
        ans ^= (1 << i);
    }
}
cout << ans << '\n';
```

Tarjan全家桶

// 强连通分量

```
struct Tarjan_SCC {
    Tarjan_SCC(int n) : nodes(n), graph(n) {}
    void addedge(int u, int v) {
        if(u == v) return;
        graph[u].push_back(v);
    }
    void solve() {
        int now_dfn = 0, scc_count = 0;
        for(int i = 0; i < nodes.size(); i++) {
            if(nodes[i].dfn == -1) {
                dfs(now_dfn, scc_count, i);
            }
        }
        dag.assign(scc_count, {});
        set<pair<int, int>> edges;
        for(int u = 0; u < graph.size(); ++u) {
            for(int v : graph[u]) {
                int bu = nodes[u].inscc, bv = nodes[v].inscc;
                if(bu != bv && !edges.contains({ bu, bv })) {
                    dag[bu].emplace_back(bv);
                    edges.insert({ bu, bv });
                }
            }
        }
    }
    struct Node {
        int dfn;
        int low;
        bool instack;
        int inscc;
        Node() : dfn(-1), low(-1), instack(false), inscc(-1) {}
    };
    vector<Node> nodes;
    vector<vector<int>> graph;
    vector<vector<int>> sccs;
    vector<vector<int>> dag;
private:
    stack<int> scc_stack;
    void dfs(int &now_dfn, int &scc_count, int u) {
        nodes[u].dfn = now_dfn;
        nodes[u].low = now_dfn;
        ++now_dfn;
        scc_stack.push(u);
        nodes[u].instack = true;
        for(int v : graph[u]) {
            if(nodes[v].dfn == -1) {
                dfs(now_dfn, scc_count, v);
                nodes[u].low = min(nodes[u].low, nodes[v].low);
            } else if(nodes[v].instack) {
                nodes[u].low = min(nodes[u].low, nodes[v].low);
            }
        }
        if(nodes[u].dfn == nodes[u].low) {
            vector<int> scc;
            int v = -1;
            while(v != u) {
                v = scc_stack.top();
```

```

        scc_stack.pop();
        nodes[v].instack = false;
        nodes[v].inscc = scc_count;
        scc.emplace_back(v);
    }
    sccs.emplace_back(move(scc));
    ++scc_count;
}

};

// 边双
struct Tarjan_BCC {
    Tarjan_BCC(int n)
        : nodes(n), graph(n) {}
    void addedge(int u, int v) {
        if(u == v) return;
        graph[u].emplace_back(v);
        graph[v].emplace_back(u);
    }
    void solve() {
        int dfn_now = 0;
        for(int i = 0; i < nodes.size(); ++i) {
            if(nodes[i].dfn == -1) {
                dfs(i, -1, dfn_now);
            }
        }
    }
    struct Node {
        int dfn;
        int low;
        bool instack;
        Node() : dfn(-1), low(-1), instack(false) {}
    };
    vector<Node> nodes;
    vector<vector<int>> graph;
    vector<vector<int>> dcc;
private:
    stack<int> stk;
    void dfs(int u, int father, int &dfn_now) {
        nodes[u].dfn = dfn_now;
        nodes[u].low = dfn_now;
        nodes[u].instack = true;
        dfn_now++;
        stk.push(u);
        for(int v : graph[u]) {
            if(v == father) continue;
            if(nodes[v].dfn == -1) {
                dfs(v, u, dfn_now);
                nodes[u].low = min(nodes[u].low, nodes[v].low);
            } else if(nodes[v].instack) {
                nodes[u].low = min(nodes[u].low, nodes[v].dfn);
            }
        }
        if(nodes[u].dfn == nodes[u].low) {
            vector<int> t;
            int n = -1;
            while(n != u) {
                n = stk.top();
                stk.pop();
                t.emplace_back(n);
            }
        }
    }
};

```

```

        nodes[n].instack = false;
    }
    dcc.emplace_back(move(t));
}
}
};
// 点双
struct Tarjan_DCC {
    Tarjan_DCC(int n)
        : nodes(n), graph(n) {}
    void addedge(int u, int v) {
        if(u == v) return;
        graph[u].emplace_back(v);
        graph[v].emplace_back(u);
    }
    void solve() {
        int dfn_now = 0;
        for(int i = 0; i < nodes.size(); ++i) {
            if(nodes[i].dfn == -1) {
                dfs(i, -1, i, dfn_now);
            }
        }
    }
    struct Node {
        int dfn;
        int low;
        Node() :dfn(-1), low(-1) {}
    };
    vector<Node> nodes;
    vector<vector<int>> graph;
    vector<vector<int>> dcc;
private:
    stack<int> stk;
    void dfs(int u, int parent, int root, int &dfn_now) {
        nodes[u].dfn = dfn_now;
        nodes[u].low = dfn_now;
        dfn_now++;
        stk.push(u);
        int child = 0;
        for(int v : graph[u]) {
            if(v == parent) continue;
            if(nodes[v].dfn == -1) {
                dfs(v, u, root, dfn_now);
                nodes[u].low = min(nodes[u].low, nodes[v].low);
                if(nodes[v].low >= nodes[u].dfn) {
                    ++child;
                    vector<int> f = { u };
                    while(!stk.empty()) {
                        int x = stk.top();
                        stk.pop();
                        f.emplace_back(x);
                        if(x == v) break;
                    }
                    dcc.emplace_back(move(f));
                }
            } else {
                nodes[u].low = min(nodes[u].low, nodes[v].dfn);
            }
        }
        if(u == root && graph[u].empty()) {

```

```

        dcc.emplace_back(vector<int>{u});
        return;
    }
}

};
// 割点
struct Tarjan_Cutpoint {
    Tarjan_Cutpoint(int n)
        : nodes(n), graph(n) {}
    void addedge(int u, int v) {
        graph[u].emplace_back(v);
        graph[v].emplace_back(u);
    }
    void solve() {
        int dfn_now = 0;
        for(int i = 0; i < nodes.size(); ++i) {
            if(nodes[i].dfn == -1) {
                dfs(i, -1, dfn_now);
            }
        }
        sort(cutpoints.begin(), cutpoints.end());
        cutpoints.erase(unique(cutpoints.begin(), cutpoints.end()), cutpoints.end());
    }
    struct Node {
        int dfn;
        int low;
        Node() : dfn(-1), low(-1) {}
    };
    vector<Node> nodes;
    vector<vector<int>> graph;
    vector<int> cutpoints;
private:
    void dfs(int u, int father, int &dfn_now) {
        nodes[u].dfn = dfn_now;
        nodes[u].low = dfn_now;
        dfn_now++;
        int child = 0;
        bool flag = false;
        for(int v : graph[u]) {
            if(nodes[v].dfn == -1) {
                child++;
                dfs(v, u, dfn_now);
                nodes[u].low = min(nodes[u].low, nodes[v].low);
                if(father != -1) {
                    flag |= (nodes[v].low >= nodes[u].dfn);
                }
            } else if(v != father) {
                nodes[u].low = min(nodes[u].low, nodes[v].dfn);
            }
        }
        if(father == -1) {
            flag = (child > 1);
        }
        if(flag) {
            cutpoints.emplace_back(u);
        }
    }
};
// 桥
struct Tarjan_Bridge {

```

```

Tarjan_Bridge(int n)
    : nodes(n), graph(n) {}
void addedge(int u, int v) {
    graph[u].emplace_back(v);
    graph[v].emplace_back(u);
}
void solve() {
    int dfn_now = 0;
    for(int i = 0; i < nodes.size(); ++i) {
        if(nodes[i].dfn == -1) {
            dfs(i, -1, dfn_now);
        }
    }
}
struct Node {
    int dfn;
    int low;
    Node() : dfn(-1), low(-1) {}
};
vector<Node> nodes;
vector<vector<int>> graph;
vector<pair<int, int>> bridges;
private:
void dfs(int u, int father, int &dfn_now) {
    nodes[u].dfn = nodes[u].low = dfn_now++;
    for(int v : graph[u]) {
        if(nodes[v].dfn == -1) {
            dfs(v, u, dfn_now);
            nodes[u].low = min(nodes[u].low, nodes[v].low);
            if(nodes[v].low > nodes[u].dfn) {
                bridges.emplace_back(min(u, v), max(u, v));
            }
        } else if(v != father) {
            nodes[u].low = min(nodes[u].low, nodes[v].dfn);
        }
    }
}
};

```

同余最短路

```
// 跑的dijkstra
ll remainder_mindist(ll k, vector<ll> dist) {
    ll modulo = 2 * min(dist[0], dist[3]);
    vector<vector<ll>> dp(4, vector<ll>(modulo, inf));
    vector<vector<bool>> visited(4, vector<bool>(modulo, false));
    dp[0][0] = 0;
    priority_queue<tuple<ll, ll, ll>, vector<tuple<ll, ll, ll>>, greater<>> pq;
    pq.emplace(0, 0, 0);
    auto get = [](ll a, ll b) -> ll {
        if(a == 3 && b == 0) {
            return 3;
        }
        if(b == 3 && a == 0) {
            return 3;
        }
        return min(a, b);
    };
    while(!pq.empty()) {
        auto [w, m, c] = pq.top();
        pq.pop();
        if(visited[c][m]) continue;
        visited[c][m] = true;
        ll d1 = (c + 1) % 4, d2 = (c + 3) % 4;
        ll w1 = dist[get(c, d1)], w2 = dist[get(c, d2)];
        if(chkmin(dp[d1][(w + w1) % modulo], w + w1)) {
            pq.emplace(w + w1, (w + w1) % modulo, d1);
        }
        if(chkmin(dp[d2][(w + w2) % modulo], w + w2)) {
            pq.emplace(w + w2, (w + w2) % modulo, d2);
        }
    }
    ll ans = inf;
    for(ll i = 0; i < modulo; ++i) {
        ll required = (k / modulo) * modulo + i;
        while(required < k) {
            required += modulo;
        }
        chkmin(ans, max(required, dp[0][i]));
    }
    return ans;
}
```

Kruskal

```
constexpr ll inf = 0x3f3f3f3f3f3f3f3f;
struct Edge {
    int u, v;
    ll w;
};
// 拿个并查集板子下来谢谢喵
ll kruskal(vector<Edge> &edges, int n) {
    DSU dsu(n);
    ll ans = 0;
    sort(edges.begin(), edges.end(), [](const Edge &a, const Edge &b) {
        return a.w < b.w;
    });
    for(auto &e : edges) {
        if(!dsu.is_connected(e.u, e.v)) {
            dsu.connect(e.u, e.v);
            ans += e.w;
        }
    }
    for(int i = 1; i < n; ++i) {
        if(!dsu.is_connected(i, 0)) {
            return inf;
        }
    }
    return ans;
}
```

Prim

```
constexpr ll inf = 0x3f3f3f3f3f3f3f3f;
ll prim(const vector<vector<pair<int, ll>>> &graph) {
    int n = graph.size();
    vector<bool> visited(n, false);
    vector<ll> dist(n, inf);
    dist[0] = 0;
    priority_queue<pair<ll, int>, vector<pair<ll, int>>, greater<>> pq;
    pq.emplace(0, 0);
    ll ret = 0;
    while(!pq.empty()) {
        auto [w, v] = pq.top();
        pq.pop();
        if(visited[v]) continue;
        visited[v] = true;
        ret += w;
        for(auto [u, w] : graph[v]) {
            if(!visited[u] && dist[u] > w) {
                dist[u] = w;
                pq.emplace(w, u);
            }
        }
    }
    for(bool b : visited) {
        if(!b) {
            return inf;
        }
    }
    return ret;
}
```

Boruvka

```
constexpr ll inf = 0x3f3f3f3f3f3f3f3f;
struct Edge {
    int u, v;
    ll w;
};

ll boruvka(const vector<Edge> &edges, int n) {
    DSU dsu(n);
    ll ans = 0;
    int c = n;
    vector<Edge> mst(n);
    while(c > 1) {
        for(int i = 0; i < n; ++i) {
            if(dsu.find(i) != i) continue;
            mst[i] = Edge(-1, -1, inf);
        }
        for(auto [u, v, w] : edges) {
            int fu = dsu.find(u), fv = dsu.find(v);
            if(fu == fv) continue;
            if(mst[fu].w > w) {
                mst[fu] = Edge(u, v, w);
            }
            if(mst[fv].w > w) {
                mst[fv] = Edge(u, v, w);
            }
        }
        bool flag = false;
        for(int i = 0; i < n; ++i) {
            if(dsu.find(i) != i) continue;
            auto [u, v, w] = mst[i];
            if(w == inf) return inf;
            if(!dsu.is_connected(u, v)) {
                dsu.connect(u, v);
                ans += w;
                --c;
                flag = true;
            }
        }
        if(!flag) {
            return inf;
        }
    }
    return ans;
}
```

Dinic

```
constexpr ll inf = 0x3f3f3f3f3f3f3f3f;
struct Dinic {
    Dinic(int n, int s, int e)
        : graph(n), level(n), start(s), end(e), n(n) {}
    void addedge(int u, int v, ll w) {
        graph[u].emplace_back(Edge{ v, (int)graph[v].size(), w });
        graph[v].emplace_back(Edge{ u, (int)graph[u].size() - 1, 0 });
    }
    ll solve() {
        ll ans = 0;
        while(bfs()) {
            ll flow = dfs(start, inf);
            while(flow > 0) {
                ans += flow;
                flow = dfs(start, inf);
            }
        }
        return ans;
    }
private:
    struct Edge {
        int to;
        int rev;
        ll cap;
    };
    vector<vector<Edge>> graph;
    vector<int> level;
    int n;
    int start, end;
    bool bfs() {
        fill(level.begin(), level.end(), -1);
        level[start] = 0;
        queue<int> q;
        q.emplace(start);
        while(!q.empty()) {
            int u = q.front();
            q.pop();
            for(const auto &e : graph[u]) {
                if(level[e.to] == -1 && e.cap > 0) {
                    level[e.to] = level[u] + 1;
                    q.emplace(e.to);
                }
            }
        }
        return level[end] != -1;
    }
    ll dfs(int u, ll max_flow) {
        if(u == end || max_flow == 0) return max_flow;
        ll total_flow = 0;
        for(auto &e : graph[u]) {
            if(level[e.to] == level[u] + 1 && e.cap > 0) {
                ll min_flow = min(max_flow, e.cap);
                ll pushed = dfs(e.to, min_flow);
                if(pushed > 0) {
                    e.cap -= pushed;
                    graph[e.to][e.rev].cap += pushed;
                    total_flow += pushed;
                    max_flow -= pushed;
                }
            }
        }
        return total_flow;
    }
};
```

```

        if(max_flow == 0) {
            return total_flow;
        }
    }
}
return total_flow;
}
};

```

匈牙利算法（不带权）

```

int hungarian(const vector<vector<int>> &graph, int vsz) {
    int usz = graph.size();
    vector<int> mu(usz, -1);
    vector<int> mv(vsz, -1);
    auto dfs = [&](auto &&dfs, int u, vector<bool> &visited) -> bool {
        for(int v : graph[u]) {
            if(visited[v]) continue;
            visited[v] = true;
            if(mv[v] == -1 || dfs(dfs, mv[v], visited)) {
                mv[v] = u;
                mu[u] = v;
                return true;
            }
        }
        return false;
    };
    int ret = 0;
    for(int u = 0; u < usz; ++u) {
        if(mu[u] == -1) {
            vector<bool> visited(vsz, false);
            if(dfs(dfs, u, visited)) {
                ret++;
            }
        }
    }
    return ret;
}

```

2-SAT

```
// 本题给的是析取式，在这里我转化为了蕴含式求解
// 请打一个Tarjan_SCC下来
// 注意：蕴含式也要加另一条边，A->B要加B' -> A'
int main() {
    cin.tie(nullptr)->sync_with_stdio(false);
    int n, m;
    cin >> n >> m;
    Tarjan_SCC solver(2 * n);
    for(int _ = 0; _ < m; ++_) {
        int i, flag_i, j, flag_j;
        cin >> i >> flag_i >> j >> flag_j;
        --i;
        --j;
        solver.addedge(2 * i + 1 - flag_i, 2 * j + flag_j);
        solver.addedge(2 * j + 1 - flag_j, 2 * i + flag_i);
    }
    solver.solve();
    for(int i = 0; i < n; ++i) {
        if(solver.nodes[2 * i].inscc == solver.nodes[2 * i + 1].inscc) {
            cout << "IMPOSSIBLE\n";
            return 0;
        }
    }
    cout << "POSSIBLE\n";
    vector<int> ans(n, -1);
    for(int i = 0; i < solver.sccs.size(); ++i) {
        for(int ii : solver.sccs[i]) {
            int u = ii / 2;
            int v = ii % 2;
            if(ans[u] == -1) {
                ans[u] = v;
            }
        }
    }
    for(int i : ans) {
        cout << i << ' ';
    }
    return 0;
}
```

搜索

迭代加深

```
pair<int, stack<int>> iddfs(array<array<int, 3>, 3> src, const array<array<int, 3>, 3> &dst) {
    constexpr int dx[] = { -1, 1, 0, 0 };
    constexpr int dy[] = { 0, 0, -1, 1 };
    int ans = 0;
    stack<int> stk;
    pair<int, int> zeropos;
    for(int i = 0; i < 3; ++i) {
        for(int j = 0; j < 3; ++j) {
            if(src[i][j] == 0) {
                zeropos = { i, j };
            }
        }
    }
    auto dfs = [&](auto &&dfs, int depth, int lastdir) -> bool {
        if(src == dst) {
            for(int i = 0; i < 3; ++i) {
                for(int j = 0; j < 3; ++j) {
                    stk.push(src[i][j]);
                }
            }
            return true;
        }
        if(depth >= ans) return false;
        auto revdir = [](int cur) -> int {
            if(cur < 2) return 1 - cur;
            return 5 - cur;
        };
        for(int nowdir = 0; nowdir < 4; ++nowdir) {
            if(nowdir == revdir(lastdir)) {
                continue;
            }
            auto [oldx, oldy] = zeropos;
            int newx = oldx + dx[nowdir], newy = oldy + dy[nowdir];
            if(newx < 0 || newx > 2 || newy < 0 || newy > 2) continue;
            swap(src[oldx][oldy], src[newx][newy]);
            zeropos = { newx, newy };
            if(dfs(dfs, depth + 1, nowdir)) {
                swap(src[oldx][oldy], src[newx][newy]);
                zeropos = { oldx, oldy };
                for(int i = 0; i < 3; ++i) {
                    for(int j = 0; j < 3; ++j) {
                        stk.push(src[i][j]);
                    }
                }
                return true;
            }
            swap(src[oldx][oldy], src[newx][newy]);
            zeropos = { oldx, oldy };
        }
        return false;
    };
    for(ans = 0; ans < 33; ++ans) {
        if(dfs(dfs, 0, 114514)) {
            return { ans, stk };
        }
    }
}
```

```
    }  
    return { -1, stack<int>{} };  
}
```

动态规划

背包DP

```
namespace OneD {
// 01背包
ll knapsack_01(const vector<pair<int, ll>> &objects, int maxw) {
    int n = objects.size();
    vector<ll> dp(maxw + 1, 0);
    for(auto [w, v] : objects) {
        for(int j = maxw; j >= w; --j) {
            dp[j] = max(dp[j], dp[j - w] + v);
        }
    }
    return dp[maxw];
}

// 完全背包
ll knapsack_complete(const vector<pair<int, ll>> &objects, int maxw) {
    int n = objects.size();
    vector<ll> dp(maxw + 1, 0);
    for(auto [w, v] : objects) {
        for(int j = w; j <= maxw; ++j) {
            dp[j] = max(dp[j], dp[j - w] + v);
        }
    }
    return dp[maxw];
}

struct Object {
    int cost, cnt;
    ll w;
};

// 多重背包
ll multi_knapsack(const vector<Object> &objects, int maxw) {
    vector<ll> dp(maxw + 1, 0);
    for(auto [cost, cnt, w] : objects) {
        for(int _ = 0; _ < cnt; ++_) {
            for(int j = maxw; j >= cost; --j) {
                dp[j] = max(dp[j], dp[j - cost] + w);
            }
        }
    }
    return dp[maxw];
}

// 多重背包的二进制优化
ll multi_knapsack_binary(const vector<Object> &objects, int maxw) {
    vector<pair<int, ll>> objs;
    for(auto [cost, cnt, w] : objects) {
        int k = 1;
        while(cnt > 0) {
            int take = min(k, cnt);
            objs.emplace_back(cost * take, w * take);
            cnt -= take;
            k *= 2;
        }
    }
    return knapsack_01(objs, maxw);
}

// 缺少：多重背包的单调队列优化
}
```

```

namespace TwoD {
struct Object {
    int u, v;
    ll w;
};
// 二维01背包
ll knapsack_01(int U, int V, const vector<Object> &objects) {
    vector<vector<ll>> dp(U + 1, vector<ll>(V + 1, 0));
    for(auto [u, v, w] : objects) {
        for(int i = U; i - u >= 0; --i) {
            for(int j = V; j - v >= 0; --j) {
                dp[i][j] = max(dp[i][j], dp[i - u][j - v] + w);
            }
        }
    }
    return dp[U][V];
}
}

```

区间DP

```

int main() {
    cin.tie(nullptr)->sync_with_stdio(false);
    int n;
    cin >> n;
    vector<ll> nums(n);
    for(int i = 0; i < n; ++i) {
        cin >> nums[i];
    }
    vector<int> s(2 * n + 1);
    for(int i = 0; i < 2 * n; ++i) {
        s[i + 1] = s[i] + nums[i];
    }
    vector<vector<int>> dp(2 * n + 1, vector<int>(2 * n + 1));
    for(int len = 2; len <= n; ++len) {
        for(int i = 0; i <= 2 * n - len; ++i) {
            int j = i + len;
            int mx = 0;
            for(int k = i + 1; k < j; ++k) {
                mx = max(mx, dp[i][k] + dp[k][j]);
            }
            dp[i][j] = mx + s[j] - s[i];
        }
    }
    int ans = 0;
    for(int i = 0; i < n; ++i) {
        ans = max(ans, dp[i][i + n]);
    }
    cout << ans << '\n';
    return 0;
}

```

数位DP

```
constexpr ll modulo = 10'0000'0007;
ll digit_dp(string k, int d) {
    vector<vector<ll>> memo(k.size(), vector<ll>(d, -1));
    auto dfs = [&](auto &&dfs, int idx, ll psum, bool isnum, bool islimit) -> ll {
        if(idx == k.size()) {
            return (ll)(isnum && (psum == 0));
        }
        if(memo[idx][psum] != -1 && isnum && !islimit) {
            return memo[idx][psum];
        }
        ll ans = 0;
        if(!isnum) {
            ans = (ans + dfs(dfs, idx + 1, 0, false, false)) % modulo;
        }
        int llim = isnum ? 0 : 1, hlim = islimit ? (k[idx] - '0') : 9;
        for(int i = llim; i <= hlim; ++i) {
            ans = (ans + dfs(dfs, idx + 1, ((psum + i) % d), true, (islimit && (i == hlim)))) % modulo;
        }
        if(isnum && !islimit) {
            memo[idx][psum] = ans;
        }
        return ans;
    };
    return dfs(dfs, 0, 0, false, true);
}
```

计数DP

```
constexpr ll modulo = 10'0000'0007;
ll count_dp(string s) {
    int n = s.size();
    vector<vector<ll>> dp(n, vector<ll>(n, 0));
    dp[0][0] = 1;
    vector<vector<ll>> sum(n, vector<ll>(n + 1, 0));
    sum[0][1] = 1;
    for(int i = 1; i < n; ++i) {
        for(int j = 0; j <= i; ++j) {
            if(s[i - 1] == '<') {
                dp[i][j] = sum[i - 1][j];
            } else {
                dp[i][j] = (sum[i - 1][i] - sum[i - 1][j] + modulo) % modulo;
            }
        }
        sum[i][0] = 0;
        for(int j = 1; j <= i + 1; ++j) {
            sum[i][j] = (sum[i][j - 1] + dp[i][j - 1]) % modulo;
        }
    }
    ll ans = 0;
    for(int j = 0; j < n; ++j) {
        ans = (ans + dp[n - 1][j]) % modulo;
    }
}
```

线段树优化DP

```
// SegTree区间最大值、单点加法线段树
int lis(const vector<int> &nums) {
    auto discrete = nums;
    sort(discrete.begin(), discrete.end());
    discrete.erase(unique(discrete.begin(), discrete.end()), discrete.end());
    unordered_map<int, int> mp;
    for(int i = 0; i < discrete.size(); i++) {
        mp[discrete[i]] = i;
    }
    SegTree seg(discrete.size());
    for(int i = 0; i < nums.size(); i++) {
        int x = mp[nums[i]];
        int v = seg.query(0, x) + 1;
        seg.update(x, v);
    }
    return seg.query(0, discrete.size());
}
```

数学

快速幂和模整数类

```
constexpr ll modulo = 9'9824'4353;
ll qpow(ll x, ll n) {
    ll ret = 1;
    while(n) {
        if(n & 1) ret = ret * x % modulo;
        x = x * x % modulo;
        n >>= 1;
    }
    return ret;
}

struct ModInt {
    ModInt(ll v = 0) : val(v % modulo) {}
    ModInt operator+(const ModInt &rhs) const {
        return ModInt((val + rhs.val) % modulo);
    }
    ModInt operator-(const ModInt &rhs) const {
        return ModInt((val - rhs.val + modulo) % modulo);
    }
    ModInt operator*(const ModInt &rhs) const {
        return ModInt((val * rhs.val) % modulo);
    }
    ModInt operator/(const ModInt &rhs) const {
        return ModInt(val * qpow(rhs.val, modulo - 2) % modulo);
    }
    ModInt power(int N) const {
        ModInt ret = 1;
        ModInt base = val;
        while(N) {
            if(N & 1) ret = ret * base;
            base = base * base;
            N >>= 1;
        }
        return ret;
    }
    operator ll &() {
        return val;
    }
private:
    ll val;
};

// 底数相同时的快速幂, 预处理O(sqrt(n)), 查询O(1)
constexpr ll maxn = 50005, modulo = 9'9824'4353;
ll power2[maxn], power2m[maxn];
int init = [] {
    power2[0] = power2m[0] = 1;
    for(int i = 1; i < maxn; ++i) {
        power2[i] = (power2[i - 1] * 2) % modulo;
    }
    power2m[1] = (power2[maxn - 1] * 2) % modulo;
    for(int i = 2; i < maxn; ++i) {
        power2m[i] = (power2m[i - 1] * power2m[1]) % modulo;
    }
    return 0;
}();
ll pow2(ll x) {
```

```

    ll i = x / maxn, j = x % maxn;
    return (power2m[i] * power2[j]) % modulo;
}

```

组合数

```

// 不预处理，一次性算一排
vector<ll> comb(ll n) {
    vector<ModInt> ret_(n + 1);
    ret_[0] = ret_[n] = 1;
    for(int i = 1, j = n - 1; i < j; ++i, --j) {
        ret_[i] = ret_[j] = ret_[i - 1] * ModInt(n - i + 1) / ModInt(i);
    }
    vector<ll> ret(ret_.begin(), ret_.end());
    return ret;
}

// 预处理版
constexpr ll maxn = 10'0005, modulo = 10'0000'0007;
ll qpow(ll x, ll n) {
    ll ret = 1;
    while(n) {
        if(n & 1) ret = ret * x % modulo;
        x = x * x % modulo;
        n >>= 1;
    }
    return ret;
}

ll fact[maxn], invfact[maxn];
int init = [] {
    fact[0] = 1;
    for(int i = 1; i < maxn; ++i) {
        fact[i] = (fact[i - 1] * i) % modulo;
    }
    invfact[maxn - 1] = qpow(fact[maxn - 1], modulo - 2);
    for(int i = maxn - 2; i >= 0; --i) {
        invfact[i] = (invfact[i + 1] * (i + 1)) % modulo;
    }
    return 0;
}();

ll comb(ll n, ll m) {
    if(m < 0 || m > n) return 0;
    return (((fact[n] * invfact[m]) % modulo) * invfact[n - m]) % modulo;
}

```

EXGCD

```

// @returns (gcd, x, y) so that gcd = ax + by
tuple<ll, ll, ll> exgcd(ll a, ll b) {
    if(b == 0) return tuple(a, 1ll, 0ll);
    auto [g, x, y] = exgcd(b, a % b);
    return tuple(g, y, x - (a / b) * y);
}

```

中国剩余定理

```
// @returns (a, b) so that answer is a + kb, k\in N_+
pair<ll, ll> crt(const vector<ll> &rem, const vector<ll> &mod) {
    int n = rem.size();
    ll modulo_ = 1, ans = 0;
    for(int i = 0; i < n; ++i) {
        modulo_ *= mod[i];
    }
    for(int i = 0; i < n; ++i) {
        ll m = modulo_ / mod[i];
        auto [_, b, __] = exgcd(m, mod[i]);
        ans = (ans + ((rem[i] * m) % modulo_ * b) % modulo_) % modulo_;
    }
    return pair((ans % modulo_ + modulo_) % modulo_, modulo_);
}
```

二项式反演公式

$$f(n) = \sum_{k=0}^n \binom{n}{k} g(k) \rightarrow g(n) = \sum_{k=0}^n (-1)^{n-k} \binom{n}{k} f(k)$$

$$f(n) = \sum_{k=n}^m \binom{k}{n} g(k) \rightarrow g(n) = \sum_{k=n}^m (-1)^{k-n} \binom{k}{n} f(k)$$

斯特林数

```
constexpr int maxn = 5005;
ll sterling[maxn][maxn];
int init = [] {
    sterling[0][0] = 1;
    for(int i = 1; i < maxn; ++i) {
        sterling[i][0] = 0;
        for(int j = 1; j <= i; ++j) {
            sterling[i][j] = (sterling[i - 1][j - 1] + sterling[i - 1][j] * j) % modulo;
        }
    }
    return 0;
}();
```

质数筛和它能干的事

```
constexpr ll maxn = 500005;
ll phi[maxn], // 欧拉函数
mu[maxn], // 莫比乌斯函数
sigma0[maxn], // 因数个数
sigma1[maxn], // 因数和
lprime[maxn], // lowest prime, i==lprime[i]等价于i是质数
lpower[maxn], // lprime[i]的次数
powsum[maxn]; //  $\sum_{j=0}^{lpower[i]} (lprime[i])^j$ 

vector<ll> primes;
ll qpow(ll x, ll n);
int init = [] {
    primes.reserve(maxn / 10);
    phi[1] = mu[1] = sigma0[1] = sigma1[1] = powsum[1] = 1;
    lpower[1] = 0;
    for(ll i = 2; i < maxn; ++i) {
        if(lprime[i] == 0) {
            lprime[i] = i;
            primes.push_back(i);
            phi[i] = i - 1;
            mu[i] = -1;
            sigma0[i] = 2;
            lpower[i] = 1;
            powsum[i] = i + 1;
            sigma1[i] = powsum[i];
        }
        for(ll p : primes) {
            ll j = i * p;
            if(j >= maxn) break;
            lprime[j] = p;
            if(i % p == 0) {
                phi[j] = phi[i] * p;
                mu[j] = 0;
                lpower[j] = lpower[i] + 1;
                powsum[j] = powsum[i] + qpow(p, lpower[j]);
                sigma0[j] = sigma0[i] / qpow(lprime[j], lpower[j]) * (lpower[j] + 1);
                sigma1[j] = sigma1[i] / qpow(lprime[j], lpower[j]) * powsum[j];
                break;
            } else {
                phi[j] = phi[i] * (p - 1);
                mu[j] = -mu[i];
                lpower[j] = 1;
                powsum[j] = 1 + p;
                sigma1[j] = sigma1[i] * powsum[j];
                sigma0[j] = sigma0[i] * 2;
            }
        }
    }
    return 0;
}();
```

多项式乘法

FFT

```
using cd = complex<double>;
constexpr double pi = 3.14159265358979323846264338327950288;
vector<int> multiply(const vector<int> &a, const vector<int> &b) {
    int n = 1;
    while(n < (a.size() + b.size())) {
        n <<= 1;
    }
    vector<cd> fa(n), fb(n);
    for(int i = 0; i < a.size(); ++i) {
        fa[i] = a[i];
    }
    for(int i = 0; i < b.size(); ++i) {
        fb[i] = b[i];
    }
    auto fft = [](auto &fft, vector<cd> &f, bool invert) -> void {
        int n = f.size();
        if(n == 1) return;
        vector<cd> f0(n / 2), f1(n / 2);
        for(int i = 0; i < n / 2; ++i) {
            f0[i] = f[2 * i];
            f1[i] = f[2 * i + 1];
        }
        fft(fft, f0, invert);
        fft(fft, f1, invert);
        double theta = 2.1 * pi / n * (invert ? -1.1 : 1.1);
        cd wt = 1, w(cos(theta), sin(theta));
        for(int t = 0; t < n / 2; ++t) {
            cd u = f0[t], v = wt * f1[t];
            f[t] = u + v;
            f[t + n / 2] = u - v;
            wt *= w;
        }
    };
    fft(fft, fa, false);
    fft(fft, fb, false);
    for(int i = 0; i < n; ++i) {
        fa[i] *= fb[i];
    }
    fft(fft, fa, true);
    for(int i = 0; i < n; ++i) {
        fa[i] /= n;
    }
    vector<int> ret(n);
    for(int i = 0; i < n; ++i) {
        ret[i] = int(fa[i].real() + (fa[i].real() > 0.1 ? 0.51 : -0.51));
    }
    while(ret.size() > (a.size() + b.size() - 1)) {
        ret.pop_back();
    }
    return ret;
}
```

NTT

```
constexpr ll modulo = 9'9824'4353, g = 3;
// constexpr ll modulo = 10'0000'0007, g = 5; 不可以
ll qpow(ll x, ll n) {
    ll ret = 1;
    while(n) {
        if(n & 1) {
            ret = ret * x % modulo;
        }
        x = x * x % modulo;
        n >>= 1;
    }
    return ret;
}

vector<ll> multiply(const vector<ll> &a, const vector<ll> &b) {
    int n = 1;
    while(n < a.size() + b.size()) {
        n <<= 1;
    }
    vector<ll> ca(n), cb(n);
    for(int i = 0; i < a.size(); ++i) {
        ca[i] = a[i];
    }
    for(int i = 0; i < b.size(); ++i) {
        cb[i] = b[i];
    }
    auto ntt = [](auto &&ntt, vector<ll> &f, bool invert) -> void {
        int n = f.size();
        if(n == 1) return;
        vector<ll> f0(n / 2), f1(n / 2);
        for(int i = 0; i < n / 2; ++i) {
            f0[i] = f[2 * i];
            f1[i] = f[2 * i + 1];
        }
        ntt(ntt, f0, invert);
        ntt(ntt, f1, invert);
        ll w = 1, wn = qpow(g, (modulo - 1) / n);
        if(invert) {
            wn = qpow(wn, modulo - 2);
        }
        for(int t = 0; t < n / 2; ++t) {
            ll u = f0[t], v = w * f1[t] % modulo;
            f[t] = (u + v) % modulo;
            f[t + n / 2] = (u - v + modulo) % modulo;
            w = w * wn % modulo;
        }
    };
    ntt(ntt, ca, false);
    ntt(ntt, cb, false);
    for(int i = 0; i < n; ++i) {
        ca[i] = ca[i] * cb[i] % modulo;
    }
    ntt(ntt, ca, true);
    for(int i = 0; i < n; ++i) {
        ca[i] = ca[i] * qpow(n, modulo - 2) % modulo;
    }
    while(ca.size() > (a.size() + b.size() - 1)) {
        ca.pop_back();
    }
}
```

```
    return ca;
}
```

线性基

```
struct LinearBasis_XOR {
    LinearBasis_XOR() : base(61) {}
    void insert(ll val) {
        for(int i = 60; i >= 0; --i) {
            if(((val >> i) & 1) == 0) continue;
            if(base[i] == 0) {
                base[i] = val;
                return;
            }
            val ^= base[i];
        }
    }
    ll query_max() const {
        ll ans = 0;
        for(int i = 60; i >= 0; --i) {
            if((ans ^ base[i]) > ans) {
                ans ^= base[i];
            }
        }
        return ans;
    }
private:
    vector<ll> base;
};
```

矩阵乘法和快速幂

```
template<class T> vector<vector<T>> matmul(const vector<vector<T>> &lhs, const vector<vector<T>> &rhs) {
    int M = lhs.size(), N = lhs[0].size(), P = rhs[0].size();
    vector<vector<T>> ret(M, vector<T>(P, 0));
    for(int i = 0; i < M; ++i) {
        for(int j = 0; j < P; ++j) {
            for(int k = 0; k < N; ++k) {
                ret[i][j] = ret[i][j] + lhs[i][k] * rhs[k][j];
            }
        }
    }
    return ret;
}

template<class T> vector<vector<T>> matpow(vector<vector<T>> mat, ll N) {
    int M = mat.size();
    vector<vector<T>> ret(M, vector<T>(M, 0));
    for(int i = 0; i < M; ++i) {
        ret[i][i] = static_cast<T>(1);
    }
    while(N) {
        if(N & 1ll) {
            ret = matmul(ret, mat);
        }
        mat = matmul(mat, mat);
        N >>= 1;
    }
    return ret;
}
```

高斯消元

```
vector<double> gauss(const vector<vector<double>> &A, const vector<double> &B) {
    int n = A.size();
    if(n == 0 || A[0].size() != n) return {};
    vector<vector<double>> aug(n, vector<double>(n + 1));
    for(int i = 0; i < n; ++i) {
        for(int j = 0; j < n; ++j) {
            aug[i][j] = A[i][j];
        }
        aug[i][n] = B[i];
    }
    for(int i = 0; i < n; ++i) {
        int pivot = -1;
        double mx = 0;
        for(int j = i; j < n; ++j) {
            if(abs(aug[j][i]) > mx) {
                mx = abs(aug[j][i]);
                pivot = j;
            }
        }
        if(pivot == -1 || mx < 1e-10) return {};
        swap(aug[i], aug[pivot]);
        for(int j = i + 1; j < n; ++j) {
            double factor = aug[j][i] / aug[i][i];
            for(int k = i; k <= n; ++k) {
                aug[j][k] -= factor * aug[i][k];
            }
        }
    }
    vector<double> X(n);
    for(int i = n - 1; i >= 0; --i) {
        X[i] = aug[i][n];
        for(int j = i + 1; j < n; ++j) {
            X[i] -= aug[i][j] * X[j];
        }
        X[i] /= aug[i][i];
    }
    return X;
}
```

构造增广状态转移矩阵

问题	转移矩阵	初始值	结果
$\sum_{k=0}^n (aB^k)_{i,j}$	$T = \begin{bmatrix} B & 0 \\ e_j \cdot e_i^T & 1 \end{bmatrix}$	$z_0 = \begin{bmatrix} a \\ a_i \end{bmatrix}$	$z_n = T^n z_0$
$\sum_{k=0}^n \langle u, B^k v \rangle$	$T = \begin{bmatrix} B & 0 \\ u^T & 1 \end{bmatrix}$	$z_0 = \begin{bmatrix} v \\ \langle u, v \rangle \end{bmatrix}$	$s_n = T^n z_0[back]$
$\sum_{i=0}^n A^i$	$T = \begin{bmatrix} A & I \\ 0 & I \end{bmatrix}$	无	T^{n+1} 的 右上角分块

Lehmer码

l[i] = k 代表后面有k个数比 a[i] 小

// 均为0-based排列

```
vector<int> lehmer(const vector<int> &a) {
    int n = a.size();
    vector<int> l(n);
    Fenwick bit(n);
    for(int i = 1; i <= n; ++i) {
        bit.update(i, 1);
    }
    for(int i = 0; i < n; ++i) {
        int x = a[i] + 1;
        l[i] = bit.query(n) - bit.query(x);
        bit.update(x, -1);
    }
    return l;
}

vector<int> rev_lehmer(const vector<int> &l) {
    int n = l.size();
    Treap treap;
    for(int i = 0; i < n; ++i) {
        treap.insert(i);
    }
    vector<int> ret(n);
    for(int i = 0; i < n; ++i) {
        ret[i] = treap.qvr(l[i] + 1);
        treap.erase(ret[i]);
    }
    return ret;
}
```

计算几何

平面凸包

```
struct Point {
    double x, y;
};

double cross(const Point &a, const Point &b, const Point &c) {
    return (b.x - a.x) * (c.y - a.y) - (b.y - a.y) * (c.x - a.x);
}

vector<Point> andrew(vector<Point> &points) {
    sort(points.begin(), points.end(), [](const Point &a, const Point &b) {
        return a.x == b.x ? a.y < b.y : a.x < b.x;
    });
    int n = points.size();
    vector<Point> stk;
    for(int i = 1; i < n; ++i) {
        while(stk.size() > 1 &&
            cross(stk[stk.size() - 2], stk.back(), points[i]) <= 0) {
            stk.pop_back();
        }
        stk.push_back(points[i]);
    }
    int t = stk.size();
    for(int i = n - 1; i >= 0; --i) {
        while(stk.size() > t &&
            cross(stk[stk.size() - 2], stk.back(), points[i]) <= 0) {
            stk.pop_back();
        }
        stk.push_back(points[i]);
    }
    return stk;
}
```

字符串

KMP

```
// 得到用于KMP的数组
vector<int> kmp_f(const string &s) {
    int n = s.size();
    vector<int> f(n, 0);
    for(int i = 1, j = 0; i < n; ++i) {
        while(j > 0 && s[i] != s[j]) {
            j = f[j - 1];
        }
        if(s[i] == s[j]) {
            ++j;
        }
        f[i] = j;
    }
    return f;
}

// 寻找第一次在off后面haystack中的needle
int kmp_find(const string &haystack, const string &needle, int off = 0) {
    int n = needle.size(), m = haystack.size();
    vector<int> f = kmp_f(needle);
    for(int i = 0, j = off; j < m; ) {
        if(haystack[j] == needle[i]) {
            ++i;
            ++j;
            if(i == n) {
                return j - n;
            }
        } else {
            if(i == 0) {
                ++j;
            } else {
                i = f[i - 1];
            }
        }
    }
    return -1;
}

// 返回haystack中有多少个needle, 可重 (即10101有两个101)
int kmp_count(const string &haystack, const string &needle) {
    int n = needle.size(), m = haystack.size();
    int ret = 0;
    vector<int> f = kmp_f(needle);
    for(int i = 0, j = 0; j < m; ) {
        if(haystack[j] == needle[i]) {
            ++i;
            ++j;
            if(i == n) {
                ++ret;
                i = f[i - 1];
            }
        } else {
            if(i == 0) {
                ++j;
            } else {
                i = f[i - 1];
            }
        }
    }
}
```

```

    }
}
return ret;
}

```

Z函数 (扩展KMP)

```

vector<int> zfn(const string &s) {
    int n = s.size();
    vector<int> z(n);
    for(int i = 1, l = 0, r = 0; i < n; ++i) {
        if(i <= r && z[i - l] < r - i + 1) {
            z[i] = z[i - l];
        } else {
            z[i] = max(0, r - i + 1);
            while(i + z[i] < n && s[z[i]] == s[i + z[i]]) {
                ++z[i];
            }
        }
        if(i + z[i] - 1 > r) {
            l = i;
            r = i + z[i] - 1;
        }
    }
    return z;
}

```

字典树

```
struct Trie {
    Trie() : nodes(1) {}
    void insert(const string &str) {
        int rt = 0;
        for(int i = 0; i < str.size(); ++i) {
            if((nodes[rt].nxt[getnum(str[i])]) == -1) {
                nodes[rt].nxt[getnum(str[i])] = nodes.size();
                nodes.emplace_back();
            }
            nodes[rt].cnt++;
            rt = nodes[rt].nxt[getnum(str[i])];
        }
        nodes[rt].cnt++;
        nodes[rt].end = true;
    }
    bool find(const string &str) const {
        int rt = 0;
        for(int i = 0; i < str.size(); ++i) {
            if((nodes[rt].nxt[getnum(str[i])]) == -1) {
                return false;
            }
            rt = nodes[rt].nxt[getnum(str[i])];
        }
        return nodes[rt].end;
    }
    int find_prefix(const string &str) const {
        int rt = 0;
        for(int i = 0; i < str.size(); ++i) {
            if((nodes[rt].nxt[getnum(str[i])]) == -1) {
                return 0;
            }
            rt = nodes[rt].nxt[getnum(str[i])];
        }
        return nodes[rt].cnt;
    }
private:
    struct Node {
        array<int, 65> nxt;
        bool end;
        int cnt;
        Node() : end(false), cnt(0) {
            nxt.fill(-1);
        }
    };
    vector<Node> nodes;
    static int getnum(char x) {
        if(x >= 'A' && x <= 'Z') {
            return x - 'A';
        } else if(x >= 'a' && x <= 'z') {
            return x - 'a' + 26;
        } else {
            return x - '0' + 52;
        }
    }
};
```

Manacher

```
string manacher(const string &_s) {
    string s = "$";
    for(char ch : _s) {
        s += ch;
        s += '$';
    }
    int n = s.size();
    int max_right = 0;
    int center = 0;
    vector<int> dp(n, 0);
    auto expand = [&](int left, int right) {
        while(left >= 0 && right < n && s[left] == s[right]) {
            --left;
            ++right;
        }
        return (right - left) / 2;
    };
    for(int i = 0; i < n; ++i) {
        int mirror = 2 * center - i;
        if(i >= max_right) {
            dp[i] = expand(i, i);
            max_right = i + dp[i];
            center = i;
        } else if(dp[mirror] == max_right - i) {
            dp[i] = expand(i - dp[mirror], i + dp[mirror]);
            max_right = i + dp[i];
            center = i;
        } else {
            dp[i] = min(dp[mirror], max_right - i);
        }
    }
    auto it = max_element(dp.begin(), dp.end());
    int id = it - dp.begin(), len = *it;
    string ret;
    for(int i = id - len + 1; i < id + len; ++i) {
        if(s[i] != '$') {
            ret += s[i];
        }
    }
    return ret;
}
```

AC自动机

```
struct ACAM {
    ACAM() : nodes(1) {}
    void insert(const string &str) {
        int now = 0;
        for(char ch : str) {
            int id = ch - 'a';
            int v = nodes[now].nxt1[id];
            if(v == -1) {
                v = nodes[now].nxt1[id] = nodes[now].nxt2[id] = nodes.size();
                nodes.emplace_back();
            }
            now = v;
        }
        nodes[now].cnt++;
    }
    void build() {
        queue<int> q;
        nodes[0].fail = 0;
        for(int i = 0; i < 26; ++i) {
            int v = nodes[0].nxt2[i];
            if(v == -1) {
                nodes[0].nxt2[i] = 0;
            } else {
                nodes[v].fail = 0;
                q.push(v);
            }
        }
        while(!q.empty()) {
            int now = q.front();
            q.pop();
            for(int i = 0; i < 26; ++i) {
                int v = nodes[now].nxt2[i];
                if(v == -1) {
                    nodes[now].nxt2[i] = nodes[nodes[now].fail].nxt2[i];
                } else {
                    nodes[v].fail = nodes[nodes[now].fail].nxt2[i];
                    q.push(v);
                }
            }
        }
        q.push(0);
        while(!q.empty()) {
            int u = q.front();
            q.pop();
            for(int i = 0; i < 26; ++i) {
                int v = nodes[u].nxt1[i];
                if(v == -1) {
                    continue;
                }
                q.push(v);
                int fu = nodes[u].fail;
                if(fu != 0 && nodes[fu].cnt == 0) {
                    nodes[u].fail = nodes[fu].fail;
                }
            }
        }
    }
    int find(const string &s) const {
```

```

        int now = 0;
        for(char ch : s) {
            int v = nodes[now].nxt1[ch - 'a'];
            if(v == -1) {
                return -1;
            }
            now = v;
        }
        return now;
    }

    vector<int> query(const string &str) const {
        int now = 0;
        vector<int> ret(nodes.size(), 0);
        for(char ch : str) {
            int id = ch - 'a';
            now = nodes[now].nxt2[id];
            int u = now;
            while(u != 0) {
                ret[u]++;
                u = nodes[u].fail;
            }
        }
        return ret;
    }

    int size() const {
        return nodes.size();
    }

private:
    struct Node {
        int cnt;
        int fail;
        array<int, 26> nxt1, nxt2;
        Node() : cnt(0), fail(0) {
            nxt1.fill(-1);
            nxt2.fill(-1);
        }
    };

    vector<Node> nodes;
};

```

后缀数组

```
vector<int> suffix_array(const string &str) {
    int n = str.size();
    int m = 128;
    vector<int> rk(n * 3, -1), sa(n), id(n), cnt(max(n, m), 0);
    int p = 0;
    for(int i = 0; i < n; ++i) {
        rk[i] = str[i];
        cnt[rk[i]]++;
    }
    for(int i = 1; i < m; ++i) {
        cnt[i] += cnt[i - 1];
    }
    for(int i = n - 1; i >= 0; --i) {
        cnt[rk[i]]--;
        sa[cnt[rk[i]]] = i;
    }
    for(int w = 1; ; w <= 1, m = p + 1) {
        int cur = 0;
        for(int i = n - w; i < n; ++i) {
            id[cur] = i;
            ++cur;
        }
        for(int i = 0; i < n; ++i) {
            if(sa[i] >= w) {
                id[cur] = sa[i] - w;
                ++cur;
            }
        }
        cnt.assign(max(n, m), 0);
        for(int i = 0; i < n; ++i) {
            cnt[rk[i]]++;
        }
        for(int i = 1; i < m; ++i) {
            cnt[i] += cnt[i - 1];
        }
        for(int i = n - 1; i >= 0; --i) {
            cnt[rk[id[i]]]--;
            sa[cnt[rk[id[i]]]] = id[i];
        }
        p = 0;
        vector<int> oldrk = rk;
        rk[sa[0]] = 0;
        for(int i = 1; i < n; ++i) {
            if(oldrk[sa[i]] != oldrk[sa[i - 1]] || oldrk[sa[i] + w] != oldrk[sa[i - 1] + w]) {
                ++p;
            }
            rk[sa[i]] = p;
        }
        if(p == n - 1) {
            break;
        }
    }
    return sa;
}
```

贪心

一组交叉直线经过所有点

```
struct Point {
    int x, y;
};

bool cross_all(const vector<Point> &points) {
    bool okx = true, oky = true;
    int xb = -1, yb = -1;
    for(auto [x, y] : points) {
        if(x != points[0].x) {
            if(yb == -1) {
                yb = y;
            } else if(yb != y) {
                okx = false;
            }
        }
        if(y != points[0].y) {
            if(xb == -1) {
                xb = x;
            } else if(xb != x) {
                oky = false;
            }
        }
    }
    return okx || oky;
}
```

二分

最长上升子序列

```
int lis(const vector<int> &nums) {
    vector<int> lis;
    for(int i : nums) {
        auto it = lower_bound(lis.begin(), lis.end(), i);
        if(it == lis.end()) {
            lis.push_back(i);
        } else {
            *it = i;
        }
    }
    return lis.size();
}
```

二分答案

```
int binary(...) {
    auto check = [&](int val) -> bool {
        // 检查函数, 有效返回true, 否则false
    };
    int lo = 0, hi = 0x3f3f3f3f;
    int ans = -1;
    while(lo < hi) {
        int mid = (lo + hi) >> 1;
        if(check(mid)) {
            ans = mid;
            hi = mid - 1;
        } else {
            lo = mid + 1;
        }
    }
    return ans;
}
```

三分

```
int peak(const vector<int> &nums) {
    int n = nums.size();
    int l = 0, r = n - 1;
    int ll = (r - 1) / 3, rr = (r - 1) * 2 / 3;
    while(l < r) {
        if(nums[ll] < nums[rr]) {
            l = ll + 1;
        } else {
            r = rr;
        }
        ll = l + (r - l) / 3;
        rr = l + (r - l) * 2 / 3;
    }
    return l;
}
```

杂项

高精

```
struct StrNum {
    StrNum() noexcept : number("0") {}
    StrNum(long long num) noexcept : number(to_string(num)) {}
    StrNum(const string &num) noexcept : number(num) {}
    StrNum(string &&num) noexcept : number(move(num)) {}
    StrNum operator+(const StrNum &r) const noexcept {
        return StrNum(move(add(number, r.number)));
    }
    StrNum &operator+=(const StrNum &r) noexcept {
        number = move(add(number, r.number));
        return *this;
    }
    StrNum operator-(const StrNum &r) const noexcept {
        return StrNum(move(minus(number, r.number)));
    }
    StrNum &operator-=(const StrNum &r) noexcept {
        number = move(minus(number, r.number));
        return *this;
    }
    StrNum operator*(const StrNum &r) const noexcept {
        return StrNum(move(mul(number, r.number)));
    }
    StrNum &operator*=(const StrNum &r) noexcept {
        number = move(mul(number, r.number));
        return *this;
    }
    StrNum operator-() const noexcept {
        if(number[0] == '-') return StrNum(number.substr(1, number.size() - 1));
        return StrNum('-' + number);
    }
    bool operator>(const StrNum &r) const noexcept {
        return gt(number, r.number);
    }
    bool operator<(const StrNum &r) const noexcept {
        return gt(r.number, number);
    }
    bool operator>=(const StrNum &r) const noexcept {
        return !gt(r.number, number);
    }
    bool operator<=(const StrNum &r) const noexcept {
        return !gt(number, r.number);
    }
    bool operator==(const StrNum &r) const noexcept {
        return number == r.number;
    }
    friend ostream &operator<<(ostream &os, const StrNum &r) noexcept {
        os << r.number;
        return os;
    }
    friend istream &operator>>(istream &is, StrNum &r) noexcept {
        is >> r.number;
        return is;
    }
private:
    string number;
```

```

static bool gt(const string &a, const string &b) noexcept {
    if(a[0] == b[0] && a[0] == '-') {
        string suba = a.substr(1, a.size() - 1);
        string subb = b.substr(1, b.size() - 1);
        return (gt(subb, suba));
    }
    if(a[0] == '-') return false;
    if(b[0] == '-') return true;
    if(a.size() > b.size()) return true;
    if(a.size() < b.size()) return false;
    int n = a.size();
    for(int i = 0; i < n; i++) {
        if(a[i] > b[i]) return true;
        if(a[i] < b[i]) return false;
    }
    return false;
}

static string add(const string &a, const string &b) noexcept {
    if(a[0] == '-' && b[0] == '-') {
        string suba = a.substr(1, a.size() - 1);
        string subb = b.substr(1, b.size() - 1);
        return ("-" + add(suba, subb));
    }
    if(a[0] == '-') {
        string suba = a.substr(1, a.size() - 1);
        return minus(b, suba);
    }
    if(b[0] == '-') {
        string subb = b.substr(1, b.size() - 1);
        return minus(a, subb);
    }
    if(a.size() < b.size()) return add(b, a);
    string ans;
    string stra = a, strb = b;
    ranges::reverse(stra);
    ranges::reverse(strb);
    int s = stra.size();
    int carry = 0;
    for(int i = 0; i < s; i++) {
        if(i < strb.size()) {
            int m = (int)(stra[i] - '0'), n = (int)(strb[i] - '0');
            int p = m + n + carry;
            carry = 0;
            if(p < 10) ans.push_back((char)(p + '0'));
            else {
                ans.push_back((char)(p - 10 + '0'));
                carry = 1;
            }
        } else {
            int m = (int)(stra[i] - '0') + carry;
            carry = 0;
            if(m < 10) ans.push_back((char)(m + '0'));
            else {
                ans.push_back((char)('0'));
                carry = 1;
            }
        }
    }
    if(carry == 1) ans.push_back('1');
    ranges::reverse(ans);
}

```

```

        return ans;
    }

    static string mul(const string &a, const string &b) noexcept {
        if(a == "0" || b == "0") return "0";
        if(a == "1") return b;
        if(b == "1") return a;
        bool negative = (a[0] == '-') ^ (b[0] == '-');
        string stra = (a[0] == '-') ? a.substr(1) : a;
        string strb = (b[0] == '-') ? b.substr(1) : b;
        int n = stra.size();
        int m = strb.size();
        vector<int> result(n + m, 0);
        for(int i = n - 1; i >= 0; --i) {
            for(int j = m - 1; j >= 0; --j) {
                int mul = (stra[i] - '0') * (strb[j] - '0');
                int sum = mul + result[i + j + 1];
                result[i + j + 1] = sum % 10;
                result[i + j] += sum / 10;
            }
        }
        string ans;
        for(int num : result) {
            if(!(ans.empty() && num == 0)) {
                ans.push_back(num + '0');
            }
        }
        return negative ? '-' + ans : ans;
    }

    static string minus(const string &a, const string &b) noexcept {
        if(a == b) return "0";
        if(b[0] == '-') {
            string str = b.substr(1, b.size() - 1);
            return add(a, str);
        }
        if(a[0] == '-') {
            string str = a.substr(1, a.size() - 1);
            return '-' + add(str, b);
        }
        if(!lt(a, b)) {
            return '-' + minus(b, a);
        }
        string ans = "", stra = a, strb = b;
        ranges::reverse(stra);
        ranges::reverse(strb);
        int s = stra.size();
        int subtract = 0;
        for(int i = 0; i < s; i++) {
            if(i < strb.size()) {
                int k = stra[i] - strb[i] - subtract;
                subtract = 0;
                if(k < 0) {
                    subtract = 1;
                    k += 10;
                }
                ans.push_back((char)(k + '0'));
            } else {
                int k = stra[i] - subtract - '0';
                subtract = 0;
                if(k < 0) {
                    subtract = 1;
                }
            }
        }
    }

```

```

        k += 10;
    }
    ans.push_back((char)(k + '0'));
}
}
while(ans[ans.size() - 1] == '0') {
    ans.pop_back();
}
ranges::reverse(ans);
return ans;
}
};

```

快读

```

struct Qread {
    Qread() noexcept : state(true) {}
    template<integral T> Qread &operator>>(T &val) noexcept {
        if(!state) {
            val = 0;
            return *this;
        }
        T x = 0, f = 1;
        char ch = cin.rdbuf()->sgetc();
        while(ch < '0' || ch > '9') {
            if(ch == EOF) {
                state = false;
                val = 0;
                return *this;
            }
            if(ch == '-') {
                f = -1;
            }
            ch = cin.rdbuf()->sgetc();
        }
        while(ch >= '0' && ch <= '9') {
            x = x * 10 + ch - '0';
            ch = cin.rdbuf()->sgetc();
        }
        val = x * f;
        return *this;
    }
    explicit operator bool() const noexcept {
        return state;
    }
private:
    bool state;
};
Qread qread;

```

自定义哈希

```
struct MyHash {
    size_t operator()(ll x) const noexcept {
        x ^= (x >> 21);
        x ^= (x << 37);
        x ^= (x >> 4);
        x *= 0x27d4eb2f165667c5;
        x ^= (x >> 28);
        x *= 0x165667b19e3779f9;
        x ^= (x >> 31);
        return x ^ c;
    }
private:
    static inline size_t c = (size_t)chrono::steady_clock::now().time_since_epoch().count();
};
```