

The Conscious/Unconscious Distinction Matters, But Consciousness Theories Don't: Emergent Cooperation in a Thermodynamic Multi-Agent Engine

Tristan Stoltz
Luminous Dynamics

tristan.stoltz@evolvingresonantcocreationism.com

Abstract

We present Symtropy, an open-source multi-agent simulation engine where a consciousness-inspired integration variable (Φ) modulates rigid body dynamics through five coupling channels. Across 1,800+ simulation runs with 8 experimental conditions, we establish three findings: (1) Thermodynamic enforcement combined with free energy gradient descent produces spatial clustering, with agents forming groups 35% tighter than unconscious agents ($\Phi=0$). (2) A six-condition ablation shows the FEP gradient is the clustering mechanism and epistemic offloading is the survival mechanism—neither alone is sufficient. (3) Critically, the *specific* consciousness metric is interchangeable: IIT-inspired Φ , Shannon entropy, and constant scalars produce statistically identical clustering (5.57 ± 0.48 vs 5.65 ± 0.83 vs 5.57 ± 0.48 , 20 seeds). Only the $\Phi=0$ condition differs (7.50 ± 3.41). This demonstrates that the conscious/unconscious distinction matters for social organization, but the choice between consciousness theories does not. Cooperation scales with population (55% survival at $N=12$, 92% at $N=96$), and a phase diagram shows population density, not energy cost, is the critical factor. Two emergent properties match published biological data without parameter fitting: per-capita energy scaling ($\beta = -0.178$ vs -0.19 in eusocial insects, Hou et al. 2010) and consciousness energy threshold (45% vs 42% of normal cortical metabolism, Stender et al. 2015). The engine supports N -dimensional physics (2D–9D) with 102ns GJK collision detection. Code: AGPL-3.0, 230+ tests.

Keywords: emergent cooperation, thermodynamic enforcement, consciousness metrics, free energy principle, multi-agent systems, ablation study

1 Introduction

The relationship between consciousness and multi-agent social organization remains poorly understood. Integrated Information Theory (Tononi, 2004) proposes consciousness is identical to integrated information (Φ), while the Free Energy Principle (Friston, 2010) proposes that conscious systems minimize variational free energy. Both frameworks are computationally formal, yet neither has been tested as a real-time modulator of physics in multi-agent simulation.

We ask three questions: (1) Does energy-costly information processing produce spatial cooperation? (2) Which mechanism drives clustering—the gradient, the cost reduction, or both? (3) Does the specific consciousness metric matter?

We present Symtropy, a consciousness-physics engine where Φ modulates rigid body dynamics through five coupling channels. Under strict energy conserva-

tion with a Landauer-bounded floor, agents that minimize variational free energy form spatial clusters. Critically, we show this clustering is invariant to the choice of consciousness metric but sensitive to the conscious/unconscious distinction.

1.1 Contributions

1. Five-channel consciousness-physics coupling model (Section 3)
2. Thermodynamic enforcement with epistemic offloading (Section 4)
3. Six-condition ablation disentangling clustering and survival mechanisms
4. Metric independence: Φ , entropy, random, and constant produce identical behavior

5. Causal test: $\Phi=0$ clusters 35% less when wired into the gradient
6. Scaling and phase diagram showing cooperation is robust across regimes

2 Related Work

IIT has been implemented computationally (Oizumi et al., 2014) but exclusively as a measurement tool. Active inference agents (Pio-Lopez et al., 2016; Fountas et al., 2020) operate in fixed environments. Tierra (Ray, 1991) demonstrated energy-gated ecosystems; Flow Lenia (Plantec et al., 2023) showed mass conservation enables coexistence. No existing physics engine supports consciousness-coupled dynamics.

Our mechanism is closest to Nowak’s network reciprocity (Nowak, 2006) but the network structure *emerges* from thermodynamics rather than being imposed. This parallels Prigogine’s dissipative structures (Prigogine & Nicolis, 1977): the pattern depends on the physics, not the medium.

3 Consciousness-Physics Coupling

An agent i at time t has state $S_i = (x_i, v_i, \omega_i, \Phi_i, E_i, h_i, \sigma_i, \pi_i)$ where $x_i \in R^D$ is position, $\Phi_i \in [0, 1]$ is the integration variable, E_i is energy, $h_i \in [0, 1]^8$ is the harmony activation vector, σ_i is prediction error, and $\pi_i = 1/(1 + \sigma_i)$ is motor precision.

Channel 1: Force Modulation. Applied force scales by $G_i = g(\Phi_i) \times \pi_i$ where g is a 4-tier safety function.

Channel 2: Energy Budget. Energy depletes through movement ($c_{\text{move}} \times |v|$), consciousness maintenance ($c_{\text{maint}} \times (1 + 0.5\Phi)$), and collisions ($c_{\text{coll}} \times |J_n|$).

Channel 3: Sanctuary Zones. When Sacred Stillness harmony $h_7 > 0.6$, a zone dampens collision impulses by up to 90%.

Channel 4: Harmony Fields. Each agent emits a harmony field with $1/r^2$ falloff, inspired by McFadden’s CEMI theory (McFadden, 2020). Friction modulates as $\mu_{\text{eff}} = \mu(1 - 0.5R)$ where R is the resonance (cosine similarity of harmony vectors).

Channel 5: Prediction Error Feedback. On collision, prediction error spikes ($\Delta\sigma = \min(0.01|J|, 2.0)$), reducing motor precision temporarily. Based on Adams et al. (2013): motor commands are proprioceptive predictions.

4 Thermodynamic Enforcement

Energy is strictly conserved. Cooperation reduces costs through **epistemic offloading**: when agents with resonance $R > 0.5$ are within range, prediction error decays 10% faster and maintenance cost is refunded by $50\% \times (R - 0.5) \times 2$. This is grounded in Landauer’s principle (Landauer, 1961): processing information has a minimum thermodynamic cost of $k_B T \ln 2$ per bit.

Cooperation does NOT generate energy. It reduces expenditure. Solo survival: ~ 4 minutes. With offloading: ~ 6 minutes. Only energy wells provide indefinite survival.

5 Experiments (1,800+ Runs)

5.1 Ablation Study

Six conditions, 12 agents, 5000 ticks, 5 seeds, 2 energy wells (Table ??).

Finding 1: The FEP gradient is the clustering mechanism ($15.1 \rightarrow 1.8$). Epistemic offloading is the survival mechanism ($72\% \rightarrow 45\%$ collapse). Neither alone is sufficient.

5.2 Metric Independence

Five consciousness metrics, 30 seeds each, Φ not coupled into the gradient (Table ??).

Finding 2: All five metrics produce statistically identical clustering. The specific consciousness metric is interchangeable.

5.3 Causal Test: Φ Wired Into the Gradient

We coupled Φ into three behavioral pathways: cooperation urgency ($0.5 + \Phi$), resonance gating ($0.3 + \Phi \times 0.7$), and danger sensitivity ($0.5 - \Phi \times 0.4$). Six conditions, 24 agents, 20 seeds (Table ??).

Finding 3 (central result): When wired into the gradient, $\Phi > 0$ produces 35% tighter clustering than $\Phi = 0$ (5.57 vs 7.50). But Φ , entropy, and constant 0.5 are interchangeable (~ 5.6). The conscious/unconscious distinction matters; the choice between theories does not.

Finding 4: Unconscious agents survive 5% longer (2993 vs 2859). Consciousness amplifies social drive at a survival cost.

5.4 Scaling and Phase Diagram

Cooperation scales: 55% survival at $N=12$, 92% at $N=96$ (20 seeds per condition). Phase diagram (8 costs $\times$ 4 densities, 10 seeds): above 24 agents, cooperation emerges at all tested energy costs (0.02–0.50 J/tick).

Finding 5: Population density, not energy cost, is the critical factor for cooperation.

5.5 Biological Validation

We compared two emergent properties of our simulation against published clinical and ecological data. These constants were tuned for gameplay (~ 4 -minute solo survival), not for biological fidelity.

Finding 6: Cooperative metabolic scaling. Per-capita energy consumption across 10 population sizes ($N=4$ –128, 20 seeds each, Table ??) follows a power law $E_{pc} \propto N^\beta$ with $\beta = -0.178$ ($R^2 = 0.60$).

This matches the $\beta = -0.19$ measured across 168 eusocial insect species (Hou et al., 2010) (whole-colony exponent 0.81, 95% CI: 0.55–1.08). The isolated control (no social interaction) gives $\beta = 0.000$ exactly, matching Waters et al. (2010): isolated ant workers show isometric scaling. The cooperative scaling only emerges in the social context — the same pattern as biology.

Finding 7: Consciousness energy threshold. Gradually depleting agent energy while measuring Φ reveals a functional consciousness threshold at 45% of maximum energy capacity. Below this fraction, Φ drops below the functional minimum (Red safety tier). This matches the 42% of normal cortical metabolism identified by Stender et al. (2015) as the boundary between vegetative and minimally conscious states (131 patients, 18F-FDG PET, 88% classification accuracy). No hysteresis was observed in either our model or the clinical data (Stender et al., 2016).

Table ?? summarizes both comparisons.

Neither parameter was calibrated to match biological data. The metabolic scaling emerges from the cost structure of epistemic offloading; the consciousness threshold emerges from the relationship between maintenance cost and safety tier boundaries.

References

Adams, R.A., Shipp, S., & Friston, K.J. (2013). Predictions not commands: active inference in the motor system. *Brain Structure and Function*, 218(3), 611–643.

6 Discussion

6.1 Limitations

Φ is a softmin bottleneck approximation, not full IIT partition analysis. The FEP gradient uses handcrafted heuristics, not learned policies. The $O(n^2)$ broadphase limits scale to ~ 500 bodies. Agents do not learn or adapt strategies.

6.2 Implications

Our metric independence result is a universality finding analogous to Prigogine’s dissipative structures (Prigogine & Nicolis, 1977) and Reynolds’ flocking (Reynolds, 1987): the macro-pattern depends on the thermodynamic cost structure, not the internal state metric. The conscious/unconscious finding adds nuance: having *some* nonzero integration variable amplifies social behavior, but which theory generates it is irrelevant.

This aligns with the “behavioral inference principle” for machine consciousness: behavioral equivalence holds across radically different internal metrics, but the presence/absence of integration creates a measurable behavioral difference.

7 Conclusion

Across 2,200+ runs and 10 experimental conditions, we establish 7 findings: (1) clustering requires both gradient descent and cost reduction; (2) the specific consciousness metric is interchangeable; (3) the conscious/unconscious distinction produces a 35% clustering difference; (4) cooperation scales with population; (5) density, not cost, is the critical factor; (6) per-capita metabolic scaling matches eusocial insects ($\beta = -0.178$ vs -0.19); (7) consciousness energy threshold matches clinical data (45% vs 42%).

The biological matches were not engineered—they emerged from the thermodynamic cost structure of information-processing cooperation. This suggests the same scaling laws governing ant colony metabolism also constrain artificial agents under energy scarcity, supporting a universality hypothesis for thermodynamic cooperation.

The Symtropy engine and all experiments are open-source. Results are reproducible via `cargo run -example`.

- Fountas, Z. et al. (2020). Deep active inference agents using Monte-Carlo methods. *NeurIPS*.
- Friston, K. (2010). The free-energy principle: a unified brain theory? *Nature Reviews Neuroscience*, 11(2), 127–138.
- Landauer, R. (1961). Irreversibility and heat generation in the computing process. *IBM J. Res. Dev.*, 5(3), 183–191.
- McFadden, J. (2020). Integrating information in the brain’s EM field. *Neuroscience of Consciousness*, 2020(1).
- Nowak, M.A. (2006). Five rules for the evolution of cooperation. *Science*, 314(5805), 1560–1563.
- Oizumi, M. et al. (2014). From phenomenology to mechanisms of consciousness: IIT 3.0. *PLOS Comp. Biol.*, 10(5).
- Pio-Lopez, L. et al. (2016). Active inference and robot control. *J. Royal Soc. Interface*, 13(122).
- Plantec, E. et al. (2023). Flow Lenia: mass conservation for virtual creatures. *ALIFE Conference*.
- Prigogine, I. & Nicolis, G. (1977). *Self-Organization in Nonequilibrium Systems*. Wiley.
- Ray, T.S. (1991). An approach to the synthesis of life. *Artificial Life II*, 371–408.
- Reynolds, C.W. (1987). Flocks, herds and schools. *ACM SIGGRAPH*, 21(4), 25–34.
- Tononi, G. (2004). An information integration theory of consciousness. *BMC Neuroscience*, 5(1), 42.
- Hou, C. et al. (2010). Energetic basis of colonial living in social insects. *PNAS*, 107(8), 3634–3638.
- Waters, J.S. et al. (2010). Allometric scaling of metabolism, growth, and activity in whole colonies of the seed-harvester ant *Pogonomyrmex californicus*. *Am. Nat.*, 176(4), 501–510.
- Stender, J. et al. (2015). Quantitative rates of brain glucose metabolism distinguish minimally conscious from vegetative state patients. *J Cereb Blood Flow Metab*, 35(1), 58–65.
- Stender, J. et al. (2016). The minimal energetic requirement of sustained awareness after brain injury. *Current Biology*, 26(11), 1462–1467.