

### §3 Compare the Algorithms

【Example】 Given (possibly negative) integers  $A_1, A_2, \dots, A_N$ , find the maximum value of  $\sum_{k=i}^j A_k$ .

#### Algorithm 1

```
int MaxSubsequenceSum ( const int A[ ], int N )
{
    int ThisSum, MaxSum, i, j, k;
    /* 1*/ MaxSum = 0; /* initialize the maximum sum */
    /* 2*/ for( i = 0; i < N; i++ ) /* start from A[ i ] */
    /* 3*/     for( j = i; j < N; j++ ) { /* end at A[ j ] */
    /* 4*/         ThisSum = 0;
    /* 5*/         for( k = i; k <= j; k++ )
    /* 6*/             ThisSum += A[ k ]; /* sum of A[ i ] to A[ j ] */
    /* 7*/         if ( ThisSum > MaxSum )
    /* 8*/             MaxSum = ThisSum; /* update max sum */
    /* 9*/     } /* end for-j and for-i */
    return MaxSum;
}
```

$$T(N) = O(N^3)$$

Detailed analysis  
is given on p.18-  
19.

## Algorithm 2

```


int MaxSubsequenceSum ( const int A[ ], int N )
{
    int ThisSum, MaxSum, i, j;
/* 1*/   MaxSum = 0; /* initialize the maximum sum */
/* 2*/   for( i = 0; i < N; i++ ) { /* start from A[ i ] */
/* 3*/       ThisSum = 0;
/* 4*/       for( j = i; j < N; j++ ) { /* end at A[ j ] */
/* 5*/           ThisSum += A[ j ]; /* sum from A[ i ] to A[ j ] */
/* 6*/           if ( ThisSum > MaxSum )
/* 7*/               MaxSum = ThisSum; /* update max sum */
        } /* end for-j */
    } /* end for-i */
/* 8*/   return MaxSum;
}

```

$$T(N) = O(N^2)$$

## Algorithm 3

## Divide and Conquer



$$T(N) = 2T(N/2) + cN, \quad T(1) = O(1)$$

$$= 2[2T(N/2^2) + cN/2] + cN$$

$$= 2^k O(1) + c k N \quad \text{where } N/2^k$$

$$= O(N \log N)$$

The program  
can be found  
on p.21.

## Algorithm 4 On-line Algorithm

```

int MaxSubsequenceSum( const int A[ ], int N )
{
    int ThisSum, MaxSum, j;
    /* 1*/ ThisSum = MaxSum = 0;
    /* 2*/ for ( j = 0; j < N; j++ ) {
    /* 3*/     ThisSum += A[ j ];
    /* 4*/     if ( ThisSum > MaxSum )
    /* 5*/         MaxSum = ThisSum;
    /* 6*/     else if ( ThisSum < 0 )
    /* 7*/         ThisSum = 0;
    /* 8*/ } /* end for-j */
    return MaxSum;
}

```



At any point in time, the algorithm can correctly give an answer to the **subsequence** problem for the data it has already read.

$$T(N) = O(N)$$

A[ ] is scanned **once** only.

## Running times of several algorithms for maximum subsequence sum (in seconds)

Algorithm		1	2	3	4
Time		$O(N^3)$	$O(N^2)$	$O(N \log N)$	$O(N)$
Input Size	$N=10$	0.00103	0.00045	0.00066	0.00034
	$N=100$	0.47015	0.01112	0.00486	0.00063
	$N=1,000$	448.77	1.1233	0.05843	0.00333
	$N=10,000$	NA	111.13	0.68631	0.03042
	$N=100,000$	NA	NA	8.0113	0.29832

**Note:** The time required to read the input is not included.


## §4 Logarithms in the Running Time

### [[Example]] Binary Search:

Given:  $A[0] \leq A[1] \leq \dots \leq A[N-1]$  ;  $X$

Task: Find  $X$

Output:  $i$  if  $X == A[i]$   
-1 if  $X$  is not found



```

int BinarySearch ( const ElementType A[ ],
                  ElementType X, int N )
{
    int Low, Mid, High;
    /* 1*/ Low = 0; High = N - 1;
    /* 2*/ while ( Low < High )
    /* 3*/ {
    /* 4*/     Mid = ( Low + High ) / 2;
    /* 5*/     if ( A[Mid] == X )
    /* 6*/         return Mid;
    /* 7*/     else if ( A[Mid] < X )
    /* 8*/         Low = Mid + 1;
    /* 9*/     else
    /* 10*/         High = Mid;
    } /* end while */
    /* 11*/ return NotFound; /* NotFound is defined as -1 */
}

```

Very useful in  
data are

**Home work:  
Self-study Euclid's Algorithm  
and Exponentiation**

$$T_{\text{worst}}(N) = O(\log N)$$

## §5 Checking Your Analysis

### Method 1

When  $T(N) = O(N)$ , check if  $T(2N)/T(N) \approx 2$

When  $T(N) = O(N^2)$ , check if  $T(2N)/T(N) \approx 4$

When  $T(N) = O(N^3)$ , check if  $T(2N)/T(N) \approx 8$

... ..

### Method 2

When  $T(N) = O(f(N))$ , check if

$$\lim_{N \rightarrow \infty} \frac{T(N)}{f(N)} \approx \text{Constant}$$

Read the example given on p.28 (Figures 2.12 & 2.13).





# Laboratory Project 1

## Performance Measurement

Normal: Search

*Hard: A+B*

Due: Tuesday, March 12<sup>th</sup>, 2024 at 10:00pm

don't c  
If it v  
it should be  
and harden

I will **not** read and grade  
any program which has  
less than **30%** lines  
commented.

