


MESSAGING PATTERNS

52

52

Enterprise Integration Patterns

- A pattern language on messaging
- 65 patterns
- Several code examples





53

53

Basic Patterns

- Message
 - Self-contained
- Channel
 - Location-independent, separate from applications
 - Asynchronous and reliable
- Message Endpoint
- Concepts
 - Fire-and-forget
 - Store-and-forward




54

54

Point-to-Point Channel

- Make sure only one receiver will consume each message
- Send the message on a Point-to-Point Channel
 - Channel ensures only one receiver consumes a message




55

55

Publish-Subscribe Channel


- How can the sender broadcast an event to all interested receivers?
- Send event on a Publish-Subscribe Channel
 - Channel delivers copy to each subscriber



56

Datatype Channel


- Send a data item so the receiver knows how to process it
- Use a separate Datatype Channel for each data type
 - Data on a channel is all one type



57

Command Message

- Use messaging to invoke a procedure in another application
- Command Message
 - Packages the invocation as a message
 - Makes the invocation reliable




58

58

Data Message

- Use messaging to transfer data
 - Ex: for reply in request-response
- Document Message
 - Put the data structure in a message




59

59

Event Message

- Fire-and-forget notification of an event
- Data-driven
 - No acknowledgement
- Event producer must send in a timely fashion
 - Ex: pet care giver
 - Absence of messages carries information




60

60

Event Message

- Fire-and-forget notification of an event
- Data-driven
 - No acknowledgement
- Event producer must send in a timely fashion
 - Ex: pet care giver
 - Absence of messages carries information



61


61

REQUEST-REPLY PATTERNS


62

62

Request-Reply




- Separate request and reply channels
 - Request as command message
 - Return address pattern




63

63

Request-Reply



- Separate request and reply channels
 - Response as data message
 - Correlation ID pattern



64

64

Processing Request


- Request message has several requirements
 - Proper datatype (Datatype Channel pattern)
 - Method to invoke
 - Parameters for method
 - Return address
- What if request message isn't right?

65

65

Invalid Message Channel

- What if message has wrong format?
- Put message on an Invalid Message Channel
 - Channel for “unprocessable” messages
 - Don’t just dump bad messages back on queue




66

66

Dead Letter Channel

- Set expiration period on a message
- Move message to Dead Letter Channel if not delivered by expiration time



67

67

Dead Letter Channel vs Invalid Message Channel

- Dead Letter
 - One for every queue manager
 - Every place where messages may be stored
- Invalid Message
 - Error log
 - Global to the enterprise

68

68

Review of Request-Reply Example

- Use Request-Reply
 - Request is Command Message
 - Reply is Document Message
 - Request has Return Address
 - Reply has Correlation Identifier
 - Malformed requests/replies go to Invalid Message Channel
 - Requests can expire (Message Expiration)
 - Expired messages go to Dead Letter Channel

69

69


ENDPOINT PATTERNS

70

70

Consumer Endpoints

- Polling Consumer
- Event-Driven Consumer




71

71

Consumer Endpoints

- Competing Consumers
- Message Dispatcher




72

72

Consumer Endpoints


- Messaging Gateway
 - Encapsulate queuing logic
- Channel Adapter
 - Legacy wrapper



73

73

Multiple Entry Points



74

Summary of Entrypoint Patterns

- Polling Consumer
- Event-Driven Consumer
- Competing Consumers
- Message Dispatcher
- Messaging Gateway
- Channel Adapter
- Translator

75

75

ROUTING PATTERNS

76

76

Separate Messages


- Separate messages based on:
 - Attributes
 - Ex: urgent vs non-urgent patients
 - Ex: high vs low security
 - Types
 - Ex: treatment types (drugs, radiology, surgery, ...)
 - Ex: prescription requests, appointments, consultations

77

77

Content Based Router


- Redirects messages based on attributes, types
- One input channel, multiple output channels



78

Splitter

- Break a compound message into smaller messages
- Typically followed by content-based router




79

79


Aggregator

- Collects and stores messages until a complete set has been received
 - *Completeness condition*
 - *Aggregation algorithm*
- Typically preceded by Splitter or Publish-Subscribe



80


80



81


81

Composed Message Processor




82

82




83

83




84



85

Pattern: Scatter-Gather



86


86

Routing Slip


- Publish-subscribe, Splitter & Content Router:
 - Process components in parallel
- Routing Slip:
 - Process sequentially
 - Ensure that prerequisites satisfied at each step
- Process Manager:
 - Runtime routing decisions
 - Dynamic logic for ensuring prerequisites

87

87




88



89

Claim Check

- Store the data, just transmit the key
 - Suitable for very large message contents
 - Reduces data volume without sacrificing content




90

90

Wrapper Envelope

- Tunneling a message, with headers, as data through middleware



91

91

Summary of Routing Patterns

- Point-to-point channel
- Publish-subscribe
- Splitter
- Context-based router
- Aggregator
- Composed message processor
- Recipient list
- Message store
- Scatter-gather
- Routing slip
- Process Manager

92

92

Message Conversion Patterns

- Claim check
- Content enricher
- Wrapper envelope
- Canonical data model
- ...

93

93