


Service Oriented Architecture

Dominic Duggan
Stevens Institute of Technology

1

1

Domain-Driven



2


2

DATA TYPES AND OPERATIONS: LISTS AS AN EXAMPLE

3

3

List == “Grocery list”




4

4

Lists

List




Empty
List



5

5



insert

10 ,




insert

10 ,

insert

25 ,



insert

10 ,

insert


5 ,

insert


25 ,

insert


25 ,




6




7



8



9



10

Constructors vs Selectors

Selectors of L	Constructors of L	
	empty	insert(n,L1)
isEmpty(L)	true	false
head(L)	-	n
tail(L)	-	L1
append(L,L2)	L2	insert(n, append(L1,L2))

11

11

CONSTRUCTOR-ORIENTED REPRESENTATION

12

12

Constructors vs Selectors

Selectors of L	Constructors of L	
	empty	insert(n,L1)
isEmpty(L)	true	false
head(L)	-	n
tail(L)	-	L1
append(L,L2)	L2	insert(n, append(L1,L2))

13

13

Constructor-Oriented Representation of Lists

```

public interface List {
    public boolean isEmpty();
    public int head() throws EmptyListExn;
    public int tail() throws EmptyListExn;
    public List append(List L2);
}
public class EmptyListExn extends Exception { }
public class Empty implements List {
    public Empty() { }
    public boolean isEmpty() { return true; }
    public int head() throws EmptyListExn { throw new EmptyListExn(); }
    public int tail() throws EmptyListExn { throw new EmptyListExn(); }
    public List append(List L2) { return L2; }
}
public class Insert implements List {
    private int n;
    private List L;
    public Insert(int n2, List L2) { this.n = n2; this.L = L2; }
    public boolean isEmpty() { return false; }
    public int head() throws EmptyListExn { return this.n; }
    public int tail() throws EmptyListExn { return this.L; }
    public List append(List L2) {
        return new Insert(this.n, this.L.append(L2));
    }
}

```

14

14

Constructor-Oriented Representation of Lists

```
public interface List {
    public boolean isEmpty();
    public int head() throws EmptyListExn;
    public int tail() throws EmptyListExn;
    public List append(List L2);
}
public class EmptyListExn extends Exception { }
public class Empty implements List {
    public Empty() { }
    public boolean isEmpty() { return true; }
    public int head() throws EmptyListExn { throw new EmptyListExn(); }
    public int tail() throws EmptyListExn { throw new EmptyListExn(); }
    public List append(List L2) { return L2; }
}
public class Insert implements List {
    private int n;
    private List L;
    public Insert(int n2, List L2) { this.n = n2; this.L = L2; }
    public boolean isEmpty() { return false; }
    public int head() throws EmptyListExn { return this.n; }
    public int tail() throws EmptyListExn { return this.L; }
    public List append(List L2) {
        return new Insert(this.n, this.L.append(L2));
    }
}
```

15

15

Constructor-Oriented Representation of Lists

```
public interface List {
    public boolean isEmpty();
    public int head() throws EmptyListExn;
    public int tail() throws EmptyListExn;
    public List append(List L2);
}
public class EmptyListExn extends Exception { }
public class Empty implements List {
    public Empty() { }
    public boolean isEmpty() { return true; }
    public int head() throws EmptyListExn { throw new EmptyListExn(); }
    public int tail() throws EmptyListExn { throw new EmptyListExn(); }
    public List append(List L2) { return L2; }
}
public class Insert implements List {
    private int n;
    private List L;
    public Insert(int n2, List L2) { this.n = n2; this.L = L2; }
    public boolean isEmpty() { return false; }
    public int head() throws EmptyListExn { return this.n; }
    public int tail() throws EmptyListExn { return this.L; }
    public List append(List L2) {
        return new Insert(this.n, this.L.append(L2));
    }
}
```

16

16

OBSERVER-ORIENTED REPRESENTATION

17

17

Constructors vs Selectors

Selectors of L	Constructors of L	
	empty	insert(n,L1)
isEmpty	true	false
head(L)	-	n
tail(L)	-	L1
append(L1,L2)	L2	insert(n, append(L1,L2))

18

18

Constructors vs Selectors

Selectors of L	Constructors of L	
	empty	insert(n,L1)
isEmpty	true	false
head(L)	-	n
tail(L)	-	L1
append(L1,L2)	L2	insert(n, append(L1,L2))

19

19

Observer-Oriented Representation of Lists

```

public interface List { }
class Insert implements List {
    int n; List L;
    Insert(int n2, List L2) { this.n = n2; this.L = L2; }
}
class Empty implements List { Empty() { } }
public class ListFactory {
    public static List empty() { return new Empty(); }
    public static List insert(int n, List l) { return new Insert(n,l); }
}
public class ListObservers {
    public boolean isEmpty(List lst) { return (lst instanceof Empty); }
    public int head(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).n;
        else throw new EmptyListExn();
    }
    public List tail(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).L;
        else throw new EmptyListExn();
    }
    public List append(List lst, List L2) {
        if (lst instanceof Insert) {
            Insert lstc = (Insert)lst; return new Insert (lstc.n, this.append (lstc.L, L2));
        } else {
            return L2;
        }
    }
}

```

20

20

Observer-Oriented Representation of Lists

```
public interface List { }
class Insert implements List {
    int n; List L;
    Insert(int n2, List L2) { this.n = n2; this.L = L2; }
}
class Empty implements List { Empty() { } }
public class ListFactory {
    public static List empty() { return new Empty(); }
    public static List insert(int n, List l) { return new Insert(n,l); }
}
public class ListObservers {
    public boolean isEmpty(List lst) { return (lst instanceof Empty); }
    public int head(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).n;
        else throw new EmptyListExn();
    }
    public List tail(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).L;
        else throw new EmptyListExn();
    }
    public List append(List lst, List L2) {
        if (lst instanceof Insert) {
            Insert lstc = (Insert)lst; return new Insert (lstc.n, this.append (lstc.L, L2));
        } else {
            return L2;
        }
    }
}
```

21

21

Observer-Oriented Representation of Lists

```
public interface List { }
class Insert implements List {
    int n; List L;
    Insert(int n2, List L2) { this.n = n2; this.L = L2; }
}
class Empty implements List { Empty() { } }
public class ListFactory {
    public static List empty() { return new Empty(); }
    public static List insert(int n, List l) { return new Insert(n,l); }
}
public class ListObservers {
    public boolean isEmpty(List lst) { return (lst instanceof Empty); }
    public int head(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).n;
        else throw new EmptyListExn();
    }
    public List tail(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).L;
        else throw new EmptyListExn();
    }
    public List append(List lst, List L2) {
        if (lst instanceof Insert) {
            Insert lstc = (Insert)lst; return new Insert (lstc.n, this.append (lstc.L, L2));
        } else {
            return L2;
        }
    }
}
```

22

22

Observer-Oriented Representation of Lists

```
public interface List { }
class Insert implements List {
    int n; List L;
    Insert(int n2, List L2) { this.n = n2; this.L = L2; }
}
class Empty implements List { Empty() { } }
public class ListFactory {
    public static List empty() { return new Empty(); }
    public static List insert(int n, List l) { return new Insert(n,l); }
}
public class ListObservers {
    public boolean isEmpty(List lst) { return (lst instanceof Empty); }
    public int head(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).n;
        else throw new EmptyListExn();
    }
    public List tail(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).L;
        else throw new EmptyListExn();
    }
    public List append(List lst, List L2) {
        if (lst instanceof Insert) {
            Insert lstc = (Insert)lst; return new Insert (lstc.n, this.append (lstc.L, L2));
        } else {
            return L2;
        }
    }
}
```

23

23

Observer-Oriented Representation of Lists

```
public interface List { }
class Insert implements List {
    int n; List L;
    Insert(int n2, List L2) { this.n = n2; this.L = L2; }
}
class Empty implements List { Empty() { } }
public class ListFactory {
    public static List empty() { return new Empty(); }
    public static List insert(int n, List l) { return new Insert(n,l); }
}
public class ListObservers {
    public boolean isEmpty(List lst) { return (lst instanceof Empty); }
    public int head(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).n;
        else throw new EmptyListExn();
    }
    public List tail(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).L;
        else throw new EmptyListExn();
    }
    public List append(List lst, List L2) {
        if (lst instanceof Insert) {
            Insert lstc = (Insert)lst; return new Insert (lstc.n, this.append (lstc.L, L2));
        } else {
            return L2;
        }
    }
}
```

24

24

Observer-Oriented Representation of Lists

```
public interface List { }
class Insert implements List {
    int n; List L;
    Insert(int n2, List L2) { this.n = n2; this.L = L2; }
}
class Empty implements List { Empty() { } }
public class ListFactory {
    public static List empty() { return new Empty(); }
    public static List insert(int n, List l) { return new Insert(n,l); }
}
public class ListObservers {
    public boolean isEmpty(List lst) { return (lst instanceof Empty); }
    public int head(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).n;
        else throw new EmptyListExn();
    }
    public List tail(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).L;
        else throw new EmptyListExn();
    }
    public List append(List lst, List L2) {
        if (lst instanceof Insert) {
            Insert lstc = (Insert)lst; return new Insert (lstc.n, this.append (lstc.L, L2));
        } else {
            return L2;
        }
    }
}
```

25

25

Observer-Oriented Representation of Lists

```
public interface List { }
class Insert implements List {
    int n; List L;
    Insert(int n2, List L2) { this.n = n2; this.L = L2; }
}
class Empty implements List { Empty() { } }
public class ListFactory {
    public static List empty() { return new Empty(); }
    public static List insert(int n, List l) { return new Insert(n,l); }
}
public class ListObservers {
    public boolean isEmpty(List lst) { return (lst instanceof Empty); }
    public int head(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).n;
        else throw new EmptyListExn();
    }
    public List tail(List lst) {
        if (lst instanceof Insert) return ((Insert)lst).L;
        else throw new EmptyListExn();
    }
    public List append(List lst, List L2) {
        if (lst instanceof Insert) {
            Insert lstc = (Insert)lst; return new Insert (lstc.n, this.append (lstc.L, L2));
        } else {
            return L2;
        }
    }
}
```

26


26

SERVICE-ORIENTED ARCHITECTURE

27

27

Domain-Driven



28

28

Patterns

- Data Access Object (DAO)
 - Encapsulates and abstracts logic for data access and storage
- Persistence Domain Object (PDO)
 - Used to persist a domain entity object in the database
- **Data Transfer Object (DTO)**
 - Container for entity state to be transferred
 - Not the same as a value object

29

29


Service Oriented Architecture

- Move domain logic out of the entity objects
 - Out of the PDOs
- Entity object becomes data transfer object (DTO)
- Logic is enshrined (as use case logic) in **services**
- **Service Façade Pattern:** Collection of procedures encapsulates resources and domain logic, abstracts domain details

30

30

Service-Oriented



31

31

DDA vs SOA

- | | |
|--|---|
| <ul style="list-style-type: none"> • DDA <ul style="list-style-type: none"> – Key pattern: Gateway – Expose domain objects – Data in PDOs – Domain logic in PDOs | <ul style="list-style-type: none"> • SOA <ul style="list-style-type: none"> – Key pattern: Service Façade – Encapsulate & abstract domain objects – Data in DTOs – Domain logic in services |
|--|---|

32

32