Inner Loop:
The inner loop in Nearest Insertion would be in the while loop that runs every time a point needs to be added to the list. This also does all the drawing to add the point to the path. The same goes for Smallest Insertion, which has its own while loop that calls back to the tour class. Within the Tour class, there is also a loop that runs for Nearest or Smallest insertion to check the distances of points and add them to the list.

Predicted Order of Growth:
We think that based on these two loops, one of which is running inside the other, that the order of growth would be quadratic, for both Nearest Insertion and Smallest Insertion. Since the methods for insertion contain while loops and these methods are called in while loops in the main method, it is as if they are a 2D loop. Operations are squared and the loops run until they have gone through the whole list making the big O quadratic or N^2.

Methodology:
We decided to use System.currentTimeMillis for recording the time it took to run the operations in our program because it felt like the simplest option, it being already embedded in the java code. To create a stopwatch, we would have had to make a separate class and implement it, currentTimeMillis is just a couple operations in the main method. We also decided to record our time data in milliseconds which also requires less operations because we don't need to convert our currentTimeMillis raw data into seconds or any other larger scales.

Order of Growth:
We used the slope and intercepts of our log plots to predict our T(N). The predicted T(N) was different from the results we actually got; it had a ratio between times of approximately 2 whereas the results we saw from the program had an approximate time ratio of 1. 1 would suggest constant growth, 2 would suggest linear growth, both different from our predicted quadratic growth. This, however, was consistent across all experiments, smallest and nearest insertion. Perhaps more data points or larger data sets would predict a more consistent outcome.

System Differences:
Different computers may have contributed to the varying answers. Tour group one's program on average ran faster than tour group two's though both order of growth results were the same. This may be used to code differences or amount of available memory on personal computers running the programs, as we used different ones for each group.