

102. Crea un comando de artisan para eliminar los carritos abandonados

Crear el comando en cmd

```
C:\Users\llemi\Desktop\Lunk\Laravel\ola>php artisan make:command RemoveOldCarts  
Console command created successfully.
```

App\Console\Commands

```
<?php  
  
namespace App\Console\Commands;  
  
use App\Models\Cart;  
use Illuminate\Console\Command;  
  
class RemoveOldCarts extends Command {  
    /**  
     * The name and signature of the console command.  
     *  
     * @var string  
     */  
    // Sintaxis = 'categoría:comando'  
    protected $signature = 'carts:remove-old [--days=7 : Los días tras los que se eliminará  
el carrito.]';  
  
    /**  
     * The console command description.  
     *  
     * @var string  
     */  
    protected $description = 'Elimina carritos más antiguos que los días que  
especifiquemos.';  
  
    /**  
     * Create a new command instance.  
     *  
     * @return void  
     */  
    public function __construct() {  
        parent::__construct();  
    }  
  
    /**  
     * Execute the console command.  
     *  
     * @return int  
     */  
    public function handle() {  
        $deadline = now()->subDays($this->option('days'));  
  
        $counter = Cart::whereDate('updated_at', '<=', $deadline)->delete();  
  
        $this->info("Hecho. Se han eliminado {$counter} carritos.");  
    }  
}
```

```
}  
}
```

Ejecutar el comando

El resultado de ejecutar

```
php artisan carts:remove-old
```

es

```
Hecho. Se han eliminado 0 carritos.
```

```
C:\Users\llemi\Desktop\Lunk\Laravel\ola>php artisan carts:remove-old --help  
Description:  
  Elimina carritos más antiguos que los días que especifiquemos.  
  
Usage:  
  carts:remove-old [options]  
  
Options:  
  --days[=DAYS]      Los días tras los que se eliminará el carrito. [default: "7"]  
  -h, --help          Display help for the given command. When no command is given display help for the list command  
  -q, --quiet         Do not output any message  
  -V, --version       Display this application version  
  --ansi|--no-ansi   Force (or disable --no-ansi) ANSI output  
  -n, --no-interaction Do not ask any interactive question  
  --env[=ENV]        The environment the command should run under  
  -v|vv|vvv, --verbose Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debugging
```