

Xây Dựng Ứng Dụng Theo Mô hình MVC:

COS

..\MVCSample\WebContent

- login.jsp
- welcome.jsp

..\MVCSample\SRC

- controller\CheckLoginServlet.java
- model:
 - + bean: Wife.java
 - + bo: CheckLoginBO.java
 - + dao: CheckLoginDAO.java


login.jsp:

```
1 <%@ page language="java" contentType="text/html; charset=ISO-8859-1"
2   pageEncoding="ISO-8859-1"%>
3 <!DOCTYPE html>
4 <html>
5 <head>
6 <meta charset="UTF-8">
7 <title>Login</title>
8 </head>
9 <body>
10 <form action="CheckLoginServlet" method="post">
11   Username: <input type="text" name="username">
12   Password: <input type="password" name="password">
13   <br>
14   <br>
15   <input type="submit" value="Login">
16   <input type="reset" value="Reset">
17 </form>
18 </body>
```


The screenshot shows a code editor with the login.jsp file open. The code is a JSP page that renders a login form. The form has two input fields: 'Username' and 'Password'. Below the password field are two buttons: 'Login' (a submit button) and 'Reset' (a reset button). The form's action is 'CheckLoginServlet' and the method is 'post'. The page is titled 'Login'. At the bottom of the editor, there is a tab bar showing the following files: login.jsp, welcome.jsp, Wife.java, CheckLoginServlet.j, CheckLoginBO.java, and CheckLoginDAO.jav.

CheckLoginServlet.java:


```
1 package controller;
2
3 import java.io.IOException;
4 import java.sql.SQLException;
5 import java.util.ArrayList;
6
7 import javax.servlet.RequestDispatcher;
8 import javax.servlet.ServletException;
9 import javax.servlet.annotation.WebServlet;
10 import javax.servlet.http.HttpServlet;
11 import javax.servlet.http.HttpServletRequest;
12 import javax.servlet.http.HttpServletResponse;
13
14 import model.bean.Wife;
15 import model.bo.CheckLoginBO;
16
17 @WebServlet("/CheckLoginServlet")
18
19 |
```



```
18
19
20 public class CheckLoginServlet extends HttpServlet {
21     private static final long serialVersionUID = 1L;
22
23     protected void doGet(HttpServletRequest request, HttpServletResponse response)
24         throws ServletException, IOException {
25         doPost(request, response);
26     }
27
28     protected void doPost(HttpServletRequest request, HttpServletResponse response)
29         throws ServletException, IOException {
30         String destination = null;
31         String username = request.getParameter("username");
32         String password = request.getParameter("password");
33         CheckLoginBO checkLoginBO = new CheckLoginBO();
34         ArrayList<Wife> wifeArray = null;
35
36 |
```



```
37     try {
38         if (checkLoginBO.isValidUser(username, password)) {
39             wifeArray = checkLoginBO.getWifeList(username);
40             request.setAttribute("wifeArray", wifeArray);
41             destination = "/welcome.jsp";
42             RequestDispatcher rd = getServletContext().getRequestDispatcher(destination);
43             rd.forward(request, response);
44
45         } else {
46             destination = "/login.jsp";
47             RequestDispatcher rd = getServletContext().getRequestDispatcher(destination);
48             rd.forward(request, response);
49         }
50     } catch (ClassNotFoundException | SQLException | ServletException | IOException e) {
51         // TODO Auto-generated catch block
52         e.printStackTrace();
53     }
54 }
55 }
```



CheckLoginBO:

```
4 import java.util.ArrayList;
5 |
6 import model.bean.Wife;
7 import model.dao.CheckLoginDAO;
8
9 public class CheckLoginBO {
10
11     CheckLoginDAO checkLoginDAO = new CheckLoginDAO();
12     public boolean isValidUser(String userName, String password) throws ClassNotFoundException, SQLException {
13         return checkLoginDAO.isExistUser(userName, password);
14     }
15     public ArrayList<Wife> getWifeList(String userName){
16         return checkLoginDAO.getWifeList(userName);
17     }
18 }
19
```

login.jsp welcome.jsp Wife.java CheckLoginServlet.j CheckLoginBO.java CheckLoginDAO.jav

For Help, press F1 In 5 col 1 19 00 PC REC INS READ

CheckLoginDAO:

```
1 package model.dao;
2
3 import java.sql.Connection;
4 import java.sql.DriverManager;
5 import java.sql.ResultSet;
6 import java.sql.SQLException;
7 import java.sql.Statement;
8 import java.util.ArrayList;
9
10 import model.bean.Wife;
11 public class CheckLoginDAO {
12     public boolean isExistUser(String username, String password) throws ClassNotFoundException, SQLException {
13         //Connect vao db
14         // Tat ca nhung cau SQL deu phai dat o DAO
15         return true;
16     }
17
18
19
20 |
21
22
```

login.jsp welcome.jsp Wife.java CheckLoginServlet.j CheckLoginBO.java CheckLoginDAO.jav

```
37
38     public ArrayList<Wife> getWifeList(String username) {
39         ArrayList<Wife> result = new ArrayList<Wife>();
40         Wife wife = new Wife();
41         wife.setName("Nguyen Thi No");
42         wife.setAddress("Lo Voi");
43         wife.setAlive(false);
44         result.add(wife);
45         wife = new Wife();
46         wife.setName("Tran Van Tam");
47         wife.setAddress("Ho ca");
48         wife.setAlive(true);
49         result.add(wife);
50         return result;
51     }
52 }
53
```

login.jsp welcome.jsp Wife.java CheckLoginServlet.j CheckLoginBO.java CheckLoginDAO.jav

Bean\Wife.java:

```

1 package model.bean;
2 public class Wife {
3     private String name ;
4     private String address ;
5     private boolean alive ;
6     public String getName() {
7         return name;
8     }
9     public void setName(String name) {
10        this.name= name;
11    }
12    public String getAddress() {
13        return address;
14    }
15    public void setAddress(String address) {
16        this.address = address;
17    }
18    public boolean isAlive() {
19        return alive;
20    }
21    public void setAlive(boolean alive) {    this.alive = alive;
22    }}

```

welcome.jsp:

```

1 <%@page import="java.util.ArrayList, model.bean.Wife"%>
2 <%@ page language="java" contentType="text/html; charset=ISO-8859-1"
3   pageEncoding="ISO-8859-1"%>
4 <html>
5 <head>
6 <meta charset="ISO-8859-1">
7 </head>
8 <body>
9 <table>
10 <%
11     ArrayList<Wife> wifeArray = (ArrayList<Wife>) request.getAttribute("wifeArray");
12     for (int i = 0; i<wifeArray.size(); i++) {
13 %>
14 <tr>
15 <td><%=wifeArray.get(i).getName() %></td>
16 <td><%=wifeArray.get(i).getAddress() %></td>
17 <td><%=wifeArray.get(i).isAlive() %></td>
18 </tr>
19 <%} %>
20 </table>
21 </body>

```