

# Администрирование сетевых подсистем

## Лабораторная работа №3

---

Чилеше Лупупа

2025

Российский университет дружбы народов, Москва, Россия

## Цель работы

---

Приобретение навыков по установке и конфигурированию DHCP-сервера Kea, а также интеграции его с DNS-сервером Bind9 с поддержкой динамических обновлений (DDNS).

## Выполнение работы


---

```
Installed:
  kea-2.6.3-1.el10_0.x86_64
  libpq-16.8-2.el10_0.x86_64
  mariadb-connector-c-3.4.4-1.el10.x86_64
  kea-libs-2.6.3-1.el10_0.x86_64
  log4cplus-2.1.1-8.el10.x86_64
  mariadb-connector-c-config-3.4.4-1.el10.noarch


Complete!
[root@server.chileshe.net ~]#
[root@server.chileshe.net ~]# cp /etc/kea/kea-dhcp4.conf /etc/kea/kea-dhcp4.conf_$(date -I)
[root@server.chileshe.net ~]# gedit /etc/kea/kea-dhcp4.conf
[root@server.chileshe.net ~]#
```

Рис. 1: Резервное копирование конфигурации

# Изменение конфигурации DHCP



```
141 // domain-name-servers you could do this:
142 // {
143 //     "name": "domain-name-servers",
144 //     "code": 6,
145 //     "csv-format": "true",
146 //     "space": "dhcp4",
147 //     "data": "192.0.2.1, 192.0.2.2"
148 // }
149 // but it's a lot of writing, so it's easier to do this instead:
150 {
151     "name": "domain-name-servers",
152     "data": "192.168.1.1, 192.0.2.2"
153 },
154
155 // Typically people prefer to refer to options by their names, so they
156 // don't need to remember the code names. However, some people like
157 // to use numerical values. For example, option "domain-name" uses
158 // option code 15, so you can reference to it either by
159 // "name": "domain-name" or "code": 15.
160 {
161     "code": 15,
162     "data": "chileshe.net"
163 },
164
165 // Domain search is also a popular option. It tells the client to
166 // attempt to resolve names within those specified domains. For
167 // example, name "foo" would be attempted to be resolved as
168 // foo.mydomain.example.com and if it fails, then as foo.example.com
169 {
170     "name": "domain-search",
171     "data": "chileshe.net"
172 },
173
```



```
279 // }
280 // ],
281
282 // Below an example of a simple IPv4 subnet declaration. Uncomment to enable
283 // it. This is a list, denoted with [ ], of structures, each denoted with
284 // { }. Each structure describes a single subnet and may have several
285 // parameters. One of those parameters is "pools" that is also a list of
286 // structures.
287 "subnet4": [
288     {
289
290         "id": 1,
291
292         "subnet": "192.168.1.0/24",
293
294         "pools": [ { "pool": "192.168.1.30 - 192.168.1.199" } ],
295
296         "option-data": [
297             {
298                 // For each IPv4 subnet you most likely need to specify at
299                 // least one router.
300                 "name": "routers",
301                 "data": "192.168.1.1"
302             }
303         ]
304     }
305 // You can add more subnets there.
306 ]
307 ],
308
```


Рис. 3: Настройка подсети DHCP

# Проверка конфигурации

```
[root@server.chileshe.net ~]#  
[root@server.chileshe.net ~]# kea-dhcp4 -t /etc/kea/kea-dhcp4.conf  
2025-11-16 10:43:11.605 INFO [kea-dhcp4.hosts/16551.140228964001984] HOSTS_BACKENDS_REGISTERED the following host back  
end types are available: mysql postgresql  
2025-11-16 10:43:11.606 WARN [kea-dhcp4.dhcp4/16551.140228964001984] DHCP4_MT_DISABLED_QUEUE_CONTROL disabling dh  
cp queue control when multi-threading is enabled.  
2025-11-16 10:43:11.606 WARN [kea-dhcp4.dhcp4/16551.140228964001984] DHCP4_RESERVATIONS_LOOKUP_FIRST_ENABLED Multi-th  
reading is enabled and host reservations lookup is always performed first.  
2025-11-16 10:43:11.606 INFO [kea-dhcp4.dhcp4/16551.140228964001984] DHCP4_CFGMGR_NEW_SUBNET4 a new subnet has be  
en added to configuration: 192.168.1.0/24 with params: t1=900, t2=1800, valid-lifetime=3600  
2025-11-16 10:43:11.606 INFO [kea-dhcp4.dhcp4/16551.140228964001984] DHCP4_CFGMGR_SOCKET_TYPE_SELECT using socket  
type raw  
2025-11-16 10:43:11.606 INFO [kea-dhcp4.dhcp4/16551.140228964001984] DHCP4_CFGMGR_ADD_IFACE listening on interfac  
e eth1  
2025-11-16 10:43:11.606 INFO [kea-dhcp4.dhcp4/16551.140228964001984] DHCP4_CFGMGR_SOCKET_TYPE_DEFAULT "dhcp-socket-  
type" not specified, using default socket type raw  
[root@server.chileshe.net ~]#  
[root@server.chileshe.net ~]# systemctl --system daemon-reload  
[root@server.chileshe.net ~]# systemctl enable kea-dhcp4.service  
Created symlink '/etc/systemd/system/multi-user.target.wants/kea-dhcp4.service' → '/usr/lib/systemd/system/kea-dhcp4.s  
ervice'.  
[root@server.chileshe.net ~]#
```


Рис. 4: Проверка Kea

## Настройка прямой DNS-зоны



```
1 $TTL 1D
2 @      IN SOA  @ server.chileshe.net. (
3                                     2025111600      ; serial
4                                     1D              ; refresh
5                                     1H              ; retry
6                                     1W              ; expire
7                                     3H )            ; minimum
8      NS      @
9      A      192.168.1.1
10 $ORIGIN chileshe.net.
11 server A    192.168.1.1
12 ns     A    192.168.1.1
13 dhcp   A    192.168.1.1
14
```

Рис. 5: Прямая зона



```
1 $TTL 1D
2 @      IN SOA  @ server.chileshe.net. (
3                                     2025111600      ; serial
4                                     1D              ; refresh
5                                     1H              ; retry
6                                     1W              ; expire
7                                     3H )            ; minimum
8      NS      @
9      A       192.168.1.1
10     PTR     server.chileshe.net.
11 $ORIGIN 1.168.192.in-addr.arpa.
12 1        PTR     server.chileshe.net.
13 1        PTR     ns.chileshe.net.
14 1        PTR     dhcp.chileshe.net.
15
```

Рис. 6: Обратная зона

```
[root@server.chileshe.net ~]# systemctl restart named
[root@server.chileshe.net ~]# ping dhcp.chileshe.net
PING dhcp.chileshe.net (192.168.1.1) 56(84) bytes of data:
64 bytes from server.chileshe.net (192.168.1.1): icmp_seq=1 ttl=64 time=0.013 ms
64 bytes from server.chileshe.net (192.168.1.1): icmp_seq=2 ttl=64 time=0.049 ms
64 bytes from server.chileshe.net (192.168.1.1): icmp_seq=3 ttl=64 time=0.107 ms
64 bytes from server.chileshe.net (192.168.1.1): icmp_seq=4 ttl=64 time=0.045 ms
64 bytes from server.chileshe.net (192.168.1.1): icmp_seq=5 ttl=64 time=0.109 ms
64 bytes from server.chileshe.net (192.168.1.1): icmp_seq=6 ttl=64 time=0.024 ms
64 bytes from server.chileshe.net (192.168.1.1): icmp_seq=7 ttl=64 time=0.051 ms
```

Рис. 7: Проверка DNS

```
[root@server.chileshe.net ~]#  
[root@server.chileshe.net ~]# firewall-cmd --add-service=dhcp  
success  
[root@server.chileshe.net ~]# firewall-cmd --add-service=dhcp --permanent  
success  
[root@server.chileshe.net ~]# restorecon -vR /etc  
Relabeled /etc/NetworkManager/system-connections/eth1.nmconnection from unconfined_u:object_r:user_tmp_t:s0 to unconfi  
ned_u:object_r:NetworkManager_etc_rw_t:s0  
[root@server.chileshe.net ~]# restorecon -vR /var/named/  
[root@server.chileshe.net ~]# restorecon -vR /var/lib/kea/  
[root@server.chileshe.net ~]# systemctl start kea-dhcp4.service  
[root@server.chileshe.net ~]#
```

Рис. 8: Firewall и SELinux

```
1  #!/bin/bash
2  echo "Provisioning script $0"
3  nmcli connection modify "eth1" ipv4.gateway "192.168.1.1"
4  nmcli connection up "eth1"
5  nmcli connection modify eth0 ipv4.never-default true
6  nmcli connection modify eth0 ipv6.never-default true
7  nmcli connection down eth0
8  nmcli connection up eth0
9  # systemctl restart NetworkManager
10
```

Рис. 9: Скрипт маршрутизации

```
chileshe@client:~  
~  
RX packets 1872  bytes 225622 (220.3 KiB)  
RX errors 0  dropped 0  overruns 0  frame 0  
TX packets 1598  bytes 263773 (257.5 KiB)  
TX errors 0  dropped 0  overruns 0  carrier 0  collisions 0  
  
eth1: flags=4163<UP,BROADCAST,RUNNING,MULTICAST>  mtu 1500  
    inet 192.168.1.30  netmask 255.255.255.0  broadcast 192.168.1.255  
    inet6 fe80::66d9:ac49:342:9398  prefixlen 64  scopeid 0x20<link>  
    ether 08:00:27:a6:73:3b  txqueuelen 1000  (Ethernet)  
    RX packets 23  bytes 3461 (3.3 KiB)  
    RX errors 0  dropped 0  overruns 0  frame 0  
    TX packets 175  bytes 17537 (17.1 KiB)  
    TX errors 0  dropped 0  overruns 0  carrier 0  collisions 0  
  
lo: flags=73<UP,LOOPBACK,RUNNING>  mtu 65536  
    inet 127.0.0.1  netmask 255.0.0.0  
    inet6 ::1  prefixlen 128  scopeid 0x10<host>  
    loop txqueuelen 1000  (Local Loopback)  
    RX packets 17  bytes 2045 (1.9 KiB)  
    RX errors 0  dropped 0  overruns 0  frame 0  
    TX packets 17  bytes 2045 (1.9 KiB)  
    TX errors 0  dropped 0  overruns 0  carrier 0  collisions 0  
  
[chileshe@client.chileshe.net ~]$
```

```
[root@server.chileshe.net ~]#  
[root@server.chileshe.net ~]# cat /var/lib/kea/kea-leases4.csv  
address,hwaddr,client_id,valid_lifetime,expire,subnet_id,fqdn_fwd,fqdn_rev,hostname,state,user_context,pool_id  
192.168.1.30,08:00:27:a6:73:3b,01:08:00:27:a6:73:3b,3600,1763293865,1,0,0,client,0,,0  
192.168.1.30,08:00:27:a6:73:3b,01:08:00:27:a6:73:3b,3600,1763293865,1,0,0,client,0,,0  
192.168.1.30,08:00:27:a6:73:3b,01:08:00:27:a6:73:3b,3600,1763293870,1,0,0,client,0,,0  
[root@server.chileshe.net ~]#
```

Рис. 11: kea-leases4.csv

```
[root@server.chileshe.net ~]#  
[root@server.chileshe.net ~]# mkdir -p /etc/named/keys  
[root@server.chileshe.net ~]# tsig-keygen -a HMAC-SHA512 DHCP_UPDATER > /etc/named/keys/dhcp_updater.key  
[root@server.chileshe.net ~]# cat /etc/named/keys/dhcp_updater.key  
key "DHCP_UPDATER" {  
    algorithm hmac-sha512;  
    secret "g3bICzGG3iM4vLjJhhLE8XsAlUHwrM5rVzi93JYc0B7dnzpnUFg0GqeWSsT0Gt2ju1vswV9ZrrKL6qPeJbtYEA==";  
};  
[root@server.chileshe.net ~]# chown -R named:named /etc/named/keys/  
[root@server.chileshe.net ~]#
```


Рис. 12: TSIG-ключ

## Подключение ключа в named

```
44
45 logging {
46     channel default_debug {
47         file "data/named.run";
48         severity dynamic;
49     };
50 };
51
52 zone "." IN {
53     type hint;
54     file "named.ca";
55 };
56
57 include "/etc/named.rfc1912.zones";
58 include "/etc/named.root.key";
59 include "/etc/named/chileshe.net";
60 include "/etc/named/keys/dhcp_updater.key";
```

Рис. 13: Вставка ключа

# Настройка политики обновлений прямой зоны



```
1 // named.rfc1912.zones:
2 //
3 // Provided by Red Hat caching-nameserver package
4 //
5 // ISC BIND named zone configuration for zones recommended by
6 // RFC 1912 section 4.1 : localhost TLDs and address zones
7 // and https://tools.ietf.org/html/rfc6303
8 // (c)2007 R W Franks
9 //
10 // See /usr/share/doc/bind*/sample/ for example named configuration files.
11 //
12 // Note: empty-zones-enable yes; option is default.
13 // If private ranges should be forwarded, add
14 // disable-empty-zone "."; into options
15 //
16
17 zone "chileshe.net" IN {
18     type master;
19     file "master/fz/chileshe.net";
20     update-policy {
21         grant DHCP_UPDATER wildcard *.chileshe.net A DHCID;
22     };
23 };
24
25 zone "1.168.192.in-addr.arpa" IN {
26     type master;
27     file "master/rz/192.168.1";
28     update-policy {
29         grant DHCP_UPDATER wildcard *.1.168.192.in-addr.arpa PTR DHCID;
30     };
31 };
32
```

## Настройка политики обновлений обратной зоны

A screenshot of a text editor window titled 'tsig-keys.json' with a subtitle '/etc/kea'. The editor shows a JSON array with one object. The object has three fields: 'name' with value 'DHCP\_UPDATER', 'algorithm' with value 'hmac-sha512', and 'secret' with a long base64-encoded string. Line numbers 1 through 7 are visible on the left margin.

```
1 "tsig-keys" [
2     {
3         "name": "DHCP_UPDATER",
4         "algorithm": "hmac-sha512",
5         "secret":
6         "g3bICzGG3iM4vLjJhhLE8XsA1UHwrM5rVzi93JYcOB7dnzpnUFg0GqeWSsTOGt2ju1vswV9ZirKL6qPeJbtYEA=="
7     }
8 ]
```

Рис. 15: update-policy RZ

## Конфигурация tsig-keys.json

```
21 {
22   "ip-address": "127.0.0.1",
23   "port": 53001,
24   "control-socket": {
25     "socket-type": "unix",
26     "socket-name": "/run/kea/kea-ddns-ctrl-socket"
27   },
28   <?include "/etc/kea/tsig-keys.json" ?>
29
30   "forward-ddns" : {
31     "ddns-domains" : [
32       {
33         "name": "chileshe.net.",
34         "key-name": "DHCP_UPDATER",
35         "dns-servers": [
36           { "ip-address": "192.168.1.1" }
37         ]
38       }
39     ]
40   },
41
42   "reverse-ddns" : {
43     "ddns-domains" : [
44       {
45         "name": "1.168.192.in-addr.arpa.",
46         "key-name": "DHCP_UPDATER",
47         "dns-servers": [
48           { "ip-address": "192.168.1.1" }
49         ]
50       }
51     ]
52   },
```

## Конфигурация Kea DHCP-DDNS

```
53
54 // Logging configuration starts here. Kea uses different loggers to log various
55 // activities. For details (e.g. names of loggers), see Chapter 18.
56 "loggers": [
57     {
58
59         "name": "kea-dhcp-ddns",
60         "output-options": [
61             {
62                 "output": "stdout",
63
64                 "pattern": "%-5p %m\n"
65
66             }
67         ],
68         // This specifies the severity of log messages to keep. Supported values
69         // are: FATAL, ERROR, WARN, INFO, DEBUG
70         "severity": "INFO",
71
72         // If DEBUG level is specified, this value is used. 0 is least verbose,
73         // 99 is most verbose. Be cautious, Kea can generate lots and lots
74         // of logs if told to do so.
75         "debuglevel": 0
76     }
77 ]
78 }
79 }
```

Рис. 17: kea-dhcp-ddns.conf

```
[root@server.chileshe.net ~]#
[root@server.chileshe.net ~]# chown kea:kea /etc/kea/kea-dhcp-ddns.conf
[root@server.chileshe.net ~]# kea-dhcp-ddns -t /etc/kea/kea-dhcp-ddns.conf
2025-11-16 11:11:57.243 INFO [kea-dhcp-ddns.dctl/20846.139770689831232] DCTL_CONFIG_CHECK_COMPLETE server has completed configuration check: listening on 127.0.0.1, port 53001, using UDP, result: success(0), text=Configuration check successful
[root@server.chileshe.net ~]# systemctl enable --now kea-dhcp-ddns.service
Created symlink '/etc/systemd/system/multi-user.target.wants/kea-dhcp-ddns.service' -> '/usr/lib/systemd/system/kea-dhcp-ddns.service'.
[root@server.chileshe.net ~]# systemctl status kea-dhcp-ddns.service
● kea-dhcp-ddns.service - Kea DHCP-DDNS Server
   Loaded: loaded (/usr/lib/systemd/system/kea-dhcp-ddns.service; enabled; preset: disabled)
   Active: active (running) since Sun 2025-11-16 11:12:16 UTC; 8s ago
 Invocation: 975d7e85b87145789bb7754902f4a873
    Docs: man:kea-dhcp-ddns(8)
   Main PID: 21065 (kea-dhcp-ddns)
     Tasks: 5 (limit: 10381)
    Memory: 1.7M (peak: 6.1M)
       CPU: 10ms
   CGroup: /system.slice/kea-dhcp-ddns.service
           └─21065 /usr/sbin/kea-dhcp-ddns -c /etc/kea/kea-dhcp-ddns.conf

Nov 16 11:12:16 server.chileshe.net systemd[1]: Started kea-dhcp-ddns.service - Kea DHCP-DDNS Server.
Nov 16 11:12:16 server.chileshe.net kea-dhcp-ddns[21065]: 2025-11-16 11:12:16.089 INFO [kea-dhcp-ddns.dctl/21065.1408
Nov 16 11:12:16 server.chileshe.net kea-dhcp-ddns[21065]: INFO COMMAND_ACCEPTOR_START Starting to accept connections
Nov 16 11:12:16 server.chileshe.net kea-dhcp-ddns[21065]: INFO DCTL_CONFIG_COMPLETE server has completed configuration
Nov 16 11:12:16 server.chileshe.net kea-dhcp-ddns[21065]: INFO DHCP_DDNS_STARTED Kea DHCP-DDNS server version 2.6.3
lines 1-17/17 (END)
```

Рис. 18: Kea DDNS status

```
28 "Dhcp4": {
29     // Add names of your network interfaces to listen on.
30     "interfaces-config": {
31         // See section 8.2.4 for more details. You probably want to add just
32         // interface name (e.g. "eth0" or specific IPv4 address on that
33         // interface name (e.g. "eth0/192.0.2.1").
34         "interfaces": [ "eth1" ]
35
36         // Kea DHCPv4 server by default listens using raw sockets. This ensures
37         // all packets, including those sent by directly connected clients
38         // that don't have IPv4 address yet, are received. However, if your
39         // traffic is always relayed, it is often better to use regular
40         // UDP sockets. If you want to do that, uncomment this line:
41         // "dhcp-socket-type": "udp"
42     },
43
44     "dhcp-ddns": {
45         "enable-updates": true
46     },
47     "ddns-qualifying-suffix": "chileshe.net",
48     "ddns-override-client-update": true,
49     // Kea supports control channel, which is a way to receive management
50     // commands while the server is running. This is a Unix domain socket that
51     // receives commands formatted in JSON, e.g. config-set (which sets new
```

## Проверка DDNS через dig

```
[chileshe@client.chileshe.net ~]$ dig @192.168.1.1 client.chileshe.net

; <<>> DiG 9.18.33 <<>> @192.168.1.1 client.chileshe.net
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 11008
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
; COOKIE: afc53246b429f390010000006919b2f6f69971e0db8f348b (good)
;; QUESTION SECTION:
;client.chileshe.net.          IN      A

;; ANSWER SECTION:
client.chileshe.net.  1200    IN      A      192.168.1.30

;; Query time: 1 msec
;; SERVER: 192.168.1.1#53(192.168.1.1) (UDP)
;; WHEN: Sun Nov 16 11:18:14 UTC 2025
;; MSG SIZE rcvd: 92

[chileshe@client.chileshe.net ~]$
```

Рис. 20: dig результат

```
1  #!/bin/bash
2  echo "Provisioning script $0"
3  echo "Install needed packages"
4  dnf -y install kea
5  echo "Copy configuration files"
6  cp -R /vagrant/provision/server/dhcp/etc/kea/* /etc/kea/
7  echo "Fix permissions"
8  chown -R kea:kea /etc/kea
9  chmod 640 /etc/kea/tsig-keys.json
10 restorecon -vR /etc
11 restorecon -vR /var/lib/kea
12 echo "Configure firewall"
13 firewall-cmd --add-service dhcp
14 firewall-cmd --add-service dhcp --permanent
15 echo "Start dhcpd service"
16 systemctl --system daemon-reload
17 systemctl enable --now kea-dhcp4.service
18 systemctl enable --now kea-dhcp-ddns.service
```

Рис. 21: dhcp.sh

## Итоги работы

---

Настроен DHCP-сервер Kea, интегрированный с Bind9 через TSIG-ключи. Динамические обновления DNS функционируют корректно: клиенты автоматически получают IP-адреса, а соответствующие A- и PTR-записи создаются в DNS-зонах. Инфраструктура полностью автоматизирована и прошла успешное тестирование.