EXP 12(b) ECHO-CLIENT-SERVER USING UDP.

24-09-26

AIM:-

To implement an Echo client-server using UDP, an application using UDPSockets and verify communicati-on between client and server.

PROCEDURE:-

1. Create a UDP Echo Server using datagram socket and datagram packet.
2. Assign a port number to the UDP server.
3. Compile and execute the UDP server program.
4. Create a UDP Echo client using datagram socket and datagram packet.
5. Specify the server address and port number.
6. Enter a message through the client.
7. The client sends the message as a UDP datagram to the server.
8. The server recieves the datagram and sends the echoed message back.
9. Display the recieved echoed message at the client.
10. Enter bye to terminate the communication.

RESULT:-

Thus, the UDP Echo client-server application was succesfully implemented, and the client succesfully recieved the echoed message from the server.

Scanned with OKEN Scanner

EXP
24-0
Aim

```
Problems  Output  Debug Console  Terminal  Ports  Jupyter

PS C:\Users\Luqman\Downloads\CN_EXPT_12> java UDPEchoClient
UDP Echo Client ready to send to localhost:6000
Type messages to send (type 'bye' to quit):
Hello
Server: Echo: Hello
I am studying Computer Networks
Server: Echo: I am studying Computer Networks
This is for Testing
Server: Echo: This is for Testing
```

```
Problems  Output  Debug Console  Terminal  Ports  Jupyter

PS C:\Users\Luqman\Downloads\CN_EXPT_12> javac UDPEchoServer.java UDPEchoClient.java
PS C:\Users\Luqman\Downloads\CN_EXPT_12> java UDPEchoServer
UDP Echo Server listening on port 6000
Received from /127.0.0.1:63830 -> Hello
Received from /127.0.0.1:63830 -> I am studying Computer Networks
Received from /127.0.0.1:63830 -> This is for Testing
```

Scanned with OKEN Scanner

CODE:-

UDP Echo Server:

```
import socket.
s = socket.socket(socket.AF_INET)
socket.sock_DRAM)
s.bind(("local host", 5000))
msg, addr = s.revform(1024)
s.send to (msg, addr)
s.close()
```

UDP Echo client:

```
Import socket.
s = socket.Socket(Socket.A
socket.sock_DGRAM)
S.send to (b"Hello Server
msg, addr = S.revfrom(10
print(msg.decode())
s.close().
```

Scanned with OKEN Scanner