EXP:11 a. ROUTING AT NETWORK LAYER.

17-09-26

AIM:-

To simulate and configure static routing protocol using Cisco packet tracer and observe packet routing between networks.

PROCEDURE:-

1. Open Cisco Packet Tracer, place three routers, two switches and four PCs.
2. Connect devices using ethernet cables.
3. Configure IP addresses of router interface and PCs.
4. Enable the router interfaces using no shutdown command.
5. Configure static route on routers using IP route command.
6. Configure static route and backup route.
7. Verify the routing tables using and testing connectivity.

RESULT:-

Thus, static routing was successfully stimulated and configured using Cisco packet tracer and packet transmission of backup was verified.

EXP: 11.b

ROUTING INFORMATION PROTOCOL.

17-09-26

AIM:-

To stimulate RIP (Routing Information Protocol) using Cisco Packet Tracer and observe packet dynamic routing b/w different networks.

PROCEDURE:-

1. Open Cisco Packet Tracer.
2. Place three routers and two PC's.
3. Connect three routers in a triangular.
4. Connect PC0 to router0 and topology PC1 to router2.
5. Configure the IP address for all router interfaces and PC enable ~~PC0~~
6. Configure RIP on each router using router rip.
7. Advertise the directly connected network using network command.
8. Verify the routing table and test the connectivity using ping.

RESULT:-

The RIP was successfully stimulated using Cisco packet tracer and dynamic router selection and automatic routing were verified.