CptS 122 - Data Structures



Programming Assignment 4: Basic Fitness Application in C++

Assigned: Tuesday, June 27, 2017 **Due:** Friday, July 7, 2017 by midnight

I. Learner Objectives:

At the conclusion of this programming assignment, participants should be able to:

- Design, implement and test classes in C++
- Declare and define constructors
- Declare and define destructors
- Compare and contrast public and private access specifiers in C++
- Describe what is an attribute or data member of a class
- Describe what is a method of a class
- Apply and implement overloaded functions
- Apply and implement overloaded operators (stream insertion and stream extraction)
- Distinguish between pass-by-value and pass-by-reference
- Discuss classes versus objects
- Apply basic file operations on file streams

II. Prerequisites:

Before starting this programming assignment, participants should be able to:

- Analyze a basic set of requirements for a problem
- Compose basic C++ language programs
- Create basic test cases for a program
- Apply arrays, strings, and pointers

III. Overview & Requirements:

You are to write a basic fitness application, in C++, that allows the user of the application to manually edit "diet" and "exercise" plans. For this application you will need to create three classes: *DietPlan*, *ExercisePlan*, and *FitnessAppWrapper*.

Diet Plan Attributes:

The class *DietPlan* is used to represent a *daily diet* plan. Your class must include three data members to represent your *goal* calories (an integer), plan *name* (a std::string), and *date* for which the plan is intended (a std::string). The maximum intake of calories for a day is stored in the *goal* calories.

Exercise Plan Attributes:

The class *ExercisePlan* is used to represent a *daily exercise* plan. Your class must include three data members to represent your *goal* steps (an integer), plan *name* (a std::string), and *date* for which the plan is intended (a std::string). Your *goal* steps represent the number of desired steps for a day.

Diet and Exercise Plan Operations:

Both the *DietPlan* and *ExercisePlan* should provide several *member* functions including: a constructor, copy constructor, and destructor. Remember that you will have to think about other appropriate member functions (think about *set*ter and *get*ter functions!). Member function *editGoal* () should prompt the user for a new goal, and use the value to change the goal in the plan. Each time a plan is changed, the plan must be displayed to the screen, using an overloaded stream insertion operator (see below).

In the same file in which each class declaration exists, three *nonmember* functions must be declared. Note: an overloaded *operator* is considered an overloaded *function*. The overloaded stream insertion (<<) for both displaying a plan to the screen and for writing a plan to a file, and the extraction (>>) operator for reading a plan from a file.

Observation: please notice that the *DietPlan* and *ExercisePlan* classes define very similar attributes and operations. In the future, we will be able to design around these similarities (using inheritance and polymorphism).

Fitness Application:

Each of the daily plans will be read from a file. Each file must consist of exactly seven daily plans, representing a full week of plans. The daily diet plans will be read from a file called "dietPlans.txt" and the daily exercise plans will be read from a file called "exercisePlans.txt". The format of the files must be represented in the following way:

Plan name
Goal
Date in the form mm/dd/yyyy
(blank line)
Plan name
Goal
Date in the form mm/dd/yyyy

You must read in each of the daily plans by applying an *overloaded* stream *extraction* operator: fileStream >> DietPlan or fileStream >> ExercisePlan. The overloaded operator must be defined as a *nonmember* function to the DietPlan and ExercisePlan classes. Each plan is stored into the next available position in your linear data structure whether it be an array, vector, or linked list.

Observation: Inserting at the end of an array and vector requires (amortized) constant time. Inserting at the end of a linked list (with only a head pointer) requires linear time. Consider this idea as you develop your solution!

The class *FitnessAppWrapper* is used to "wrap" the application. This class should contain two lists (must be an array, vector, or linked list) of weekly (7 days) plans: one diet and one exercise weekly plan. It must also contain two fstream objects (input/output file streams): one for each file. It must define the following member functions (some prototypes are given to you, but not all!):

- void runApp (void): starts the main application.
- void loadDailyPlan (fstream &fileStream, DietPlan &plan): must define two of these functions; one for a DietPlan and
 one for an ExercisePlan. This function reads one record from the given stream. These will be considered overloaded
 functions! Precondition: file is already open!
- void loadWeeklyPlan (fstream &fileStream, DietPlan weeklyPlan[]): must define two of these functions; one for a
 DietPlan and one for an ExercisePlan. This function must read in all seven daily plans from the given stream. Note:
 the array parameter would change if using a vector or linked list! This function should call loadDailyPlan () directly.
 Precondition: file is already open!
- displayDailyPlan (): writes a daily plan to the screen. You must apply the overloaded stream insertion operator here! Note: you must determine the appropriate parameters and return type. Once again you must define two of these!
- displayWeeklyPlan (): writes a weekly plan to the screen. This function must call displayDailyPlan (). Note: you must determine the appropriate parameters and return type. Once again you must define two of these!
- storeDailyPlan (): writes a daily plan to a file. You must apply the overloaded stream insertion operator here! Note: you must determine the appropriate parameters and return type. Once again you must define two of these!
- storeWeeklyPlan (): writes a weekly plan to a file. This function must call *storeDailyPlan* (). You must apply the overloaded stream insertion operator here! Note: you must determine the appropriate parameters and return type. Once again you must define two of these!
- displayMenu (): displays nine menu options. These include:
 - 1. Load weekly diet plan from file.
 - 2. Load weekly exercise plan from file.
 - 3. Store weekly diet plan to file.
 - 4. Store weekly exercise plan to file.
 - 5. Display weekly diet plan to screen.

- 6. Display weekly exercise plan to screen.
- 7. Edit daily diet plan.
- 8. Edit daily exercise plan.
- 9. Exit. // Note: this must write the most recent weekly plans to the corresponding files.
- Other functions? There should be!

Observation: Many of the functions in the FitnessAppWrapper class are overloaded. There's one version for use on a DietPlan and one version for use on an ExercisePlan. We know these functions are considered overloaded because they have the same name, but different parameter types. In the future, we could use templates, and let the compiler generate code for us, instead of implementing several versions of the same function ourselves.

BONUS:

Implement classes for *ListNode* and *List* to store the diet and exercise plans. You may need to implement a different linked list for each of the plans. In the future, this could be resolved by using templates.

IV. Submitting Assignments:

- 1. Using Blackboard Learn https://learn.wsu.edu/webapps/login/ submit your assignment to your TA through the link ending with "-LEC". Under the "Content" link navigate to the "Programming Assignment Submissions" folder and upload your solutions to the appropriate "Assignment" space. You must upload your solutions as <your last name> pa4.zip by the due date and time.
- 2. Your .zip file should contain a project workspace. Your project folder must have at least one header file (a .h file), two C source files (which must be .c files), and project workspace. Delete the debug folder before you zip your project folders.
- 3. Your project must build properly. The most points an assignment can receive if it does not build properly is 65 out of 100.

V. Grading Guidelines:

This assignment is worth 100 points. Your assignment will be evaluated based on a successful compilation and adherence to the program requirements. We will grade according to the following criteria:

- 5 pts Appropriate top-down design, style, and commenting according to class standards
- * 18 pts Appropriate design and implementation of Class *DietPlan* (including member functions and data members)
 - 1. 3 pts 1 pt/each for declaring goal calories, plan name, and date
 - 2. 2 pts declaring and defining a constructor
 - 3. 2 pts declaring and defining a copy constructor
 - 4. 1 pt declaring and defining a destructor
 - 5. 4 pts declaring and defining setters/getters
 - 6. 4 pts declaring and defining an editGoal function
 - 7. 2 pts others?
- 18 pts Appropriate design and implementation of Class ExercisePlan (including member functions and data members)
 - 1. 3 pts 1 pt/each for declaring goal steps, plan name, and date
 - 2. 2 pts declaring and defining a constructor
 - 3. 2 pts declaring and defining a copy constructor
 - 4. 1 pt declaring and defining a destructor
 - 5. 4 pts declaring and defining setters/getters
 - 6. 4 pts declaring and defining an editGoal function
 - 7. 2 pts others?
- 47 pts Appropriate implementation of Class FitnessAppWrapper (including menu options, etc.)
 - 1. 8 pts 2 pts/each for declaring a list of diet plans, a list of exercise plans, a file stream associated with "dietPlans.txt", and a file stream associated with "exercisePlans.txt"
 - 2. 4 pts declaring and defining *runApp* function
 - 3. 4 pts 2 pts/each for declaring and defining loadDailyPlan functions
 - 4. 4 pts 2 pts/each for declaring and defining loadWeeklyPlan functions
 - 5. 4 pts 2 pts/each for declaring and defining displayDailyPlan functions
 - 6. 4 pts 2 pts/each for declaring and defining displayWeeklyPlan functions
 - 7. 4 pts 2 pts/each for declaring and defining storeDailyPlan functions
 - 8. 4 pts 2 pts/each for declaring and defining storeWeeklyPlan functions
 - 9. 2 pts declaring and defining displayMenu function

10. 4 pts - opening and closing the files

11.5 pts - others?

- 12 pts 2 pts/each for the nonmember overloaded stream extraction and stream insertion operators (4 total stream insertion operators, 2 total stream extraction operators)
- BONUS: Up to 10 pts Linked list implementation using ListNode and List classes