## Exercise 2

```
SELECT COUNT(ID) as number of employees
FROM employees_db. Employees
```

| number of employees |
|---|
| 10 |

## 2. SUM() Function

```
SELECT SUM(department) AS Total salary
FROM Employee_db. employees
WHERE department = 'IT'
```

~~department~~ salo

| department | Total salary |
|---|---|
| IT | 220 000 |

## 3. AVerage() Function

```
SELECT AVG(department) AS average salary
FROM Employee_db. employees
WHERE department = 'HR'
```

| department | average salary |
|---|---|
| HR | 49, 500 |

## 4. MIN() and MAX Functions

```
SELECT MAX(salary) AS highest salary
FROM employee_db.employees
```

| highest salary |
|---|
| 62 000 |

```
SELECT MIN(salary) AS Lowest salary
FROM employee_db.employees
```

| Lowest salary |
|---|
| 48 |

## 5 GROUP BY statement

```
SELECT SUM(salary) as total salary paid in each department
FROM employees_db.employee
GROUP BY department
```

| department | total salary paid in each department |
|---|---|
| IT | 220 000 |
| HR | 99 000 |
| finance | 119 000 |
| marketing | 105 000 |

## 6. GROUP BY and COUNT()

```
SELECT COUNT(ID) AS employees
FROM employees_db.employees
GROUP BY City
```

| City | employees |
|---|---|
| New York | 2 |
| Chicago | 3 |
| Los Angeles | 2 |
| San Francisco | 2 |
| Houston | 1 |

## 7 GROUP BY and ORDER BY

```
SELECT AVG(Salary) AS Average salary
FROM employee_db.employees
ORDER BY average salary DESC
GROUP BY departments
```

| department | average salary |
|---|---|
| IT | 55 000 |
| HR | 49 000 |
| Finance | 59 500 |
| Marketing | 51 500 |

## 8. Having clause

```
SELECT sum(salary) as total salary
FROM employee_db.employees
GROUP BY department
WHERE 'total salary' < 100 000
```

| departments | salary total |
|---|---|
| IT | 220 000 |
| HR | - |
| Finance | 119 000 |
| marketing | 105 000 |

## 9. Combining GROUP BY, HAVING and order BY

```
SELECT COUNT(ID) AS employees
FROM employees_db.employees
ORDER BY 'number of employees' DESC
GROUP BY City
WHERE ~~employee~~ city has <1 employee
```

~~fm~~

| City | employees |
|---|---|
| Chicago | 3 |
| New York | 2 |
| Los Angeles | 2 |
| San Francisco | 2 |

## 10. Combining Aggregate Functions

```
SELECT    AVG(Salary) As average Salary,
          MAX(average Salary) AS highes AVG Salary
          department
FROM      employees_db.employees
```

| department | highest AVG salary |
|---|---|
| Finance | 59 800 |