

PRODUCTION & COSTING PACK

70S 2-Track Sliding Door
System

Fabrication & Machining Stencils, 1D Bar Nesting,
and Vendor Costing Sheet

OPENING WIDTH	OPENING HEIGHT	TOTAL ALU NET WT	ESTIMATED MATERIAL COST
2500 mm	2100 mm	14.94 kg	\$ 218.96

STOCK BARS TO PULL

7 Bars

Standard 6000 mm Bars

OVERALL CUTTING YIELD

92.4 %

Kerf: 3.5 mm accounted

TOTAL CUT PIECES

12 Pieces

4 Frame + 8 Sash Bars

SAFETY GLASS AREA

4.906 m²

2 Panels (6mm Clear Float)

 1D Linear Bar Nesting Plans (6000 mm Stock Bars)

Visual cut sequences, saw blade kerf allowance (3.5mm), and offcut recovery mapping

70S-1001-1 Top Track Frame Head

Bars: 1 x 6000mm | Yield: 41.7% | Wt: 2.35 kg

STOCK BAR #1 (6000 mm)		Cuts: 1 pcs Used: 2500 mm Offcut: 3500 mm
Frame Head 2500 mm		REUSABLE 3500 mm

70S-1101-1 Bottom Track Sill

Bars: 1 x 6000mm | Yield: 41.7% | Wt: 2.63 kg

STOCK BAR #1 (6000 mm)		Cuts: 1 pcs Used: 2500 mm Offcut: 3500 mm
Frame Sill 2500 mm		REUSABLE 3500 mm

70S-1201-1 Side Wall Upright Jamb

Bars: 1 x 6000mm | Yield: 70% | Wt: 3.28 kg

STOCK BAR #1 (6000 mm)			Cuts: 2 pcs Used: 4200 mm Offcut: 1796.5 mm
Right Jamb 2100 mm	Left Jamb 2100 mm		REUSABLE 1796.5 mm

70S-1401 Top Sash Horizontal Rail

Bars: 1 x 6000mm | Yield: 40.1% | Wt: 1.11 kg

STOCK BAR #1 (6000 mm)			Cuts: 2 pcs Used: 2408 mm Offcut: 3588.5 mm
Top Sash Rail 1204 mm	Top Sash Rail 1204 mm		REUSABLE 3588.5 mm

70S-1501 Bottom Sash Horizontal Rail

Bars: 1 x 6000mm | Yield: 40.1% | Wt: 1.74 kg

STOCK BAR #1 (6000 mm)			Cuts: 2 pcs Used: 2408 mm Offcut: 3588.5 mm
Bottom Sash Rail 1204 mm	Bottom Sash Rail 1204 mm		REUSABLE 3588.5 mm

70S-1701 Handle Side Sash Stile

Bars: 1 x 6000mm | Yield: 69.1% | Wt: 1.79 kg

STOCK BAR #1 (6000 mm)		Cuts: 2 pcs Used: 4144 mm Offcut: 1852.5 mm
------------------------	--	---

Handle Stile 2072 mm			Handle Stile 2072 mm			REUSABLE 1852.5 mm		
-------------------------	--	--	-------------------------	--	--	-----------------------	--	--

70S-1601 Interlock Meeting Stile

Bars: 1 x 6000mm | Yield: 69.1% | Wt: 2.05 kg

STOCK BAR #1 (6000 mm)			Cuts: 2 pcs Used: 4144 mm Offcut: 1852.5 mm					
Interlock Stile 2072 mm			Interlock Stile 2072 mm			REUSABLE 1852.5 mm		