ISL6236A Project

Variant Name = 6 to 24V Variant

Friday, February 23, 2018 V1I1

RELEASED 23-FEB-2018

Page	Index	Page Index		Page	Index		
1	COVER PAGE	11		21			
2	BLOCK DIAGRAM	12		22			
3	+1.5V / +1.05V POWER SUPPLY	13		23			
4	PADS AND TESTPOINTS	14		24			
5	REVISION HISTORY	15		25			
6		16		26			
7		17		27			
8		18		28			
9		19		29			
10		20		30			

DESIGN CONSIDERATION

DESIGN NOTE: Example text for informational design notes.

DESIGN NOTE: Example text for cautionary design notes. DESIGN NOTE: Example text for debug notes.


DESIGN NOTE: Example text for critical design notes.

DESIGN NOTE: Example text for critical layout guidelines.

TOP VIEW




BOTTOM VIEW



EEDEVE!
FEDEVEL
Academy

(c) 2017	FEDEVEL Academy	http://www.fedevel.com/academy						
Title:		Variant:						
ISL6236	SA Project	<core design=""></core>						
Page: 01) CO\	/ER PAGE	Checked by: <checked by=""></checked>						
Size: Custom	Document: LEOA	Designed by: Robert Feranec				Rev: V1I1		
Date:	Friday, February 23, 2018	Sheet:	1	of	- 5			


ISL6236A PROJECT (Block Diagram)






(c) 2017	FEDEVEL Academy	http://www.fedevel.com/academy					
Title:		Variant:					
ISL6236	SA Project	6 to 24V Variant Checked by: <checked by=""></checked>					
Page:							
02) BLC	OCK DIAGRAM						
Size:	Document:	Designed by:	Rev:				
Custom	LEOA	Robert Feranec	V1I1				
Data	Wodnoodov Echruony 21	2010 Phasts 2 of					

1.5V / 1.05V POWER SUPPLY



Enable/Disable regulators




FFDF1/FI
FEDEVEL
Acadomy
Academy

(c) 20	17 FE	EDEVEL Academy	http://www.fedevel.com/academy					
Title:					Variant:			
ISL62	36A	Project	6 to 24V Variant					
Page			Checked by:					
03) +	03) +1.5V / +1.05V POWER SUPPLY		<checked by=""></checked>					
Size:	Т	Document:	Designed by:				Rev:	
Custo	ו ויי	_EOA	Robert Feranec				V1I1	
Date:		Friday, February 23, 2018	Sheet:	3	of	5		
			- 1					


PADS, TESTPOINTS, MECHANICAL

Soldering pads for input and output wires


+VIN: Main input power (Default from +6V to +24V)



Power supply output 1 (Default +1.5V)




Power supply output 2 (Default +1.05V)




Testpoints




POK Testpoints



Mounting holes



Fiducials



PCB





(c) 2017	FEDEVEL Academy	http://www.fedevel.com/academy					
Title:		Variant: 6 to 24V Variant Checked by:					
ISL6236	SA Project						
Page:							
04) PAI	OS, TESTPOINTS, MECHANICAL		<checked by=""></checked>				
Size:	Document:	Designed by:				Rev:	
Custom	LEOA	Robert Feranec				V1I1	
Date:	Wednesday, February 21, 201	8 Sheet:	4	of	5		

REVISION HISTORY

01-NOV-2017: Put here a brief info about the change

Detailed description of all the changes - Testing Lite



(c) 2017 FEDEVEL Academy ISL6236A Project 6 to 24V Variant Checked by: Page: 05) REVISION HISTORY

<Checked by> LEOA Robert Feranec

Learn Schematic and PCB Design - ONLINE

Wednesday, February 21, 2018 Sheet:

Rev: V1I1