

RWorksheet_Freires#4b

2024-10-29

Using Loop Function

for() loop

1. Using the for loop, create an R script that will display a 5x5 matrix as shown in Figure 1. It must contain vectorA = [1,2,3,4,5] and a 5 x 5 zero matrix. Hint Use abs() function to get the absolute value

```
vectorA <- c(1, 2, 3, 4, 5)
zero_matrix <- matrix(0, nrow = 5, ncol = 5)

for (i in 1:5) {
  for (j in 1:5) {
    zero_matrix[i, j] <- abs(vectorA[i] - vectorA[j])
  }
}
print(zero_matrix)
```

```
##      [,1] [,2] [,3] [,4] [,5]
## [1,]    0    1    2    3    4
## [2,]    1    0    1    2    3
## [3,]    2    1    0    1    2
## [4,]    3    2    1    0    1
## [5,]    4    3    2    1    0
```

2. Print the string "*" using for() function. The output should be the same as shown in Figure

```
for (i in 1:5) {
  cat(rep("*", i), "\n")
}
```

```
## "*"
## "*" "*"
## "*" "*" "*"
## "*" "*" "*" "*"
## "*" "*" "*" "*" "*"
```

3. Get an input from the user to print the Fibonacci sequence starting from the 1st input up to 500. Use repeat and break statements. Write the R Scripts and its output.

```
x <- 0
y <- 1

num <- readline(prompt = "Enter the starting number: ")

## Enter the starting number:
3

## [1] 3
```

```
repeat {  
  num <- x + y  
  if (num > 500) break  
  x <- y  
  y <- num  
  print(num)  
}
```

```
## [1] 1  
## [1] 2  
## [1] 3  
## [1] 5  
## [1] 8  
## [1] 13  
## [1] 21  
## [1] 34  
## [1] 55  
## [1] 89  
## [1] 144  
## [1] 233  
## [1] 377
```