



Keys — Part 2


Relational Databases Basics



TRAINING
CENTER



Keys hierarchy



Foreign key – in a relation, one or a group of attributes that corresponds to a primary key in another relation.

Recursive foreign key – a foreign key that references some key of relation itself.

Foreign key

Primary key

employee


<u>id</u>	passport	name
1	AA1122334	Ivanov I.I.
2	AB4455667	Petrov P.P.
3	AC5566778	Sidorov S.S.
4	BP8877665	Sidorov S.S.

Foreign key


payment

<u>id</u>	person	money
1	2	100
2	2	100
3	4	200
4	4	150
5	4	130

Recursive foreign key




Recursive foreign key



page

<u>id</u>	parent	name
1	NULL	Main
2	1	For readers
3	2	News
4	2	Statistics
5	1	Contacts
6	5	Adverts
7	6	Actions
8	4	Current
9	4	Archive


Keys hierarchy (in reality)



How to create a key?

With an SQL query

```
-- Simple natural PK
CREATE TABLE `employee`
(
  `passport` CHAR(9) NOT NULL,
  `name` VARCHAR(50) NOT NULL,
  CONSTRAINT `PK_employee`
  PRIMARY KEY (`passport`)
)
```


employee 	
«column»	
*PK passport: CHAR(9)	
* name: VARCHAR(50)	
«PK»	
+ PK_employee(CHAR)	

How to create a key?

With an SQL query

```
-- Surrogate PK (+ index on Alt. key)
CREATE TABLE `employee`
(
  `id` INT UNSIGNED NOT NULL AUTO_INCREMENT,
  `passport` CHAR(9) NOT NULL,
  `name` VARCHAR(50) NOT NULL,
  CONSTRAINT `PK_employee`
  PRIMARY KEY (`id`)
);

ALTER TABLE `employee`
  ADD CONSTRAINT `UQ_passport`
  UNIQUE (`passport`);
```

employee 	
«column»	
*PK id: INT	
* <u>passport</u> : CHAR(9)	
* name: VARCHAR(50)	
«PK»	
+ PK_employee(INT)	
«unique»	
+ UQ_passport(CHAR)	

How to create a key?

With an SQL query

```
-- Compound natural PK
CREATE TABLE `employee`
(
  `pass` INT UNSIGNED NOT NULL AUTO_INCREMENT,
  `department` VARCHAR(50) NOT NULL,
  `name` VARCHAR(50) NOT NULL,
  `phone` VARCHAR(50) NULL,
  CONSTRAINT `PK_employee`
  PRIMARY KEY (`pass`, `department`)
)
```

employee	
«column»	
*PK	pass: INT
*PK	department: VARCHAR(50)
*	name: VARCHAR(50)
	phone: VARCHAR(50)
«PK»	
+	PK_employee(INT, VARCHAR)

How to create a key?


With an SQL query

```
-- Foreign key and corresponding relationship
CREATE TABLE `employee`
(
  `id` INT UNSIGNED NOT NULL AUTO_INCREMENT,
  `passport` CHAR(9) NOT NULL,
  `name` VARCHAR(50) NOT NULL,
  CONSTRAINT `PK_employee` PRIMARY KEY (`id`)
);

CREATE TABLE `payment`
(
  `id` INT UNSIGNED NOT NULL AUTO_INCREMENT,
  `person` INT UNSIGNED NOT NULL,
  `money` DECIMAL(10,2) NOT NULL,
  CONSTRAINT `PK_payment` PRIMARY KEY (`id`)
);

ALTER TABLE `employee`
  ADD CONSTRAINT `UQ_passport` UNIQUE (`passport`);

ALTER TABLE `payment`
  ADD CONSTRAINT `FK_payment_employee`
    FOREIGN KEY (`person`) REFERENCES `employee` (`id`)
    ON DELETE CASCADE ON UPDATE RESTRICT;
```




How to create a key?

With an SQL query

```
-- Recursive foreign key
-- and corresponding relationship
CREATE TABLE `sitemap`
(
  `id` INT UNSIGNED
    NOT NULL AUTO_INCREMENT,
  `parent` INT UNSIGNED NULL,
  `name` VARCHAR(50) NULL,
  CONSTRAINT `PK_sitemap`
    PRIMARY KEY (`id`)
);

ALTER TABLE `sitemap`
  ADD CONSTRAINT
    `FK_sitemap_sitemap`
    FOREIGN KEY (`parent`)
      REFERENCES `sitemap` (`id`)
    ON DELETE CASCADE
    ON UPDATE RESTRICT;
```



How to create a key?

Using some special tool

```
-- Here goes live demo :)
```

Live demo in Sparx Enterprise Architect



Keys — Part 2

Relational Databases Basics



TRAINING
CENTER

