

Going Further

From regression to classification





Laurence Moroney, Google


X





Y











Data

Label



[1, 0]



[0, 1]

0 [1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0]

1 [0, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0]

2 [0, 0, 1, 0, 0, 0, 0, 0, 0, 0, 0]

3 [0, 0, 0, 1, 0, 0, 0, 0, 0, 0, 0]

4 [0, 0, 0, 0, 1, 0, 0, 0, 0, 0, 0]

5 [0, 0, 0, 0, 0, 1, 0, 0, 0, 0, 0]

6 [0, 0, 0, 0, 0, 0, 1, 0, 0, 0, 0]

7 [0, 0, 0, 0, 0, 0, 0, 1, 0, 0, 0]

8 [0, 0, 0, 0, 0, 0, 0, 0, 1, 0, 0]

9 [0, 0, 0, 0, 0, 0, 0, 0, 0, 1, 0]


```
import tensorflow as tf
```

```
data = tf.keras.datasets.mnist  
(training_images, training_labels), (val_images, val_labels) = data.load_data()
```

```
training_images = training_images / 255.0
```

```
val_images = val_images / 255.0
```

```
model = tf.keras.models.Sequential(  
    [tf.keras.layers.Flatten(input_shape=(28,28)),  
     tf.keras.layers.Dense(20, activation=tf.nn.relu),  
     tf.keras.layers.Dense(10, activation=tf.nn.softmax)])
```



60,000 Labelled Training Examples
10,000 Labelled Validation Examples

```
import tensorflow as tf

data = tf.keras.datasets.mnist
(training_images, training_labels), (val_images, val_labels) = data.load_data()

training_images = training_images / 255.0
val_images = val_images / 255.0


model = tf.keras.models.Sequential([
    tf.keras.layers.Flatten(input_shape=(28,28)),
    tf.keras.layers.Dense(20, activation=tf.nn.relu),
    tf.keras.layers.Dense(10, activation=tf.nn.softmax)])
```


```
import tensorflow as tf

data = tf.keras.datasets.mnist
(training_images, training_labels), (val_images, val_labels) = data.load_data()

training_images = training_images / 255.0
val_images = val_images / 255.0

model = tf.keras.models.Sequential(
    [tf.keras.layers.Flatten(input_shape=(28,28)),
     tf.keras.layers.Dense(20, activation=tf.nn.relu),
     tf.keras.layers.Dense(10, activation=tf.nn.softmax)])
```





```
import tensorflow as tf

data = tf.keras.datasets.mnist
(training_images, training_labels), (val_images, val_labels) = data.load_data()

training_images = training_images / 255.0
val_images = val_images / 255.0

model = tf.keras.models.Sequential(
    [tf.keras.layers.Flatten(input_shape=(28,28)),
      tf.keras.layers.Dense(20, activation=tf.nn.relu),
      tf.keras.layers.Dense(10, activation=tf.nn.softmax)])
```



```
import tensorflow as tf

data = tf.keras.datasets.mnist
(training_images, training_labels), (val_images, val_labels) = data.load_data()

training_images = training_images / 255.0
val_images = val_images / 255.0

model = tf.keras.models.Sequential(
    [tf.keras.layers.Flatten(input_shape=(28,28)),
     tf.keras.layers.Dense(20, activation=tf.nn.relu),
     tf.keras.layers.Dense(10, activation=tf.nn.softmax)])
```

```
model.compile(optimizer='adam',  
              loss='sparse_categorical_crossentropy',  
              metrics=['accuracy'])  
  
model.fit(training_images, training_labels, epochs=20)
```

```
model.compile(optimizer='adam',  
              loss='sparse_categorical_crossentropy',  
              metrics=['accuracy'])  
  
model.fit(training_images, training_labels, epochs=20)
```

```
model.compile(optimizer='adam',  
              loss='sparse_categorical_crossentropy',  
              metrics=['accuracy'])
```

```
model.fit(training_images, training_labels, epochs=20)
```

```
classifications = model.predict(val_images)
print(classifications[0])
print(test_labels[0])
```

```
[2.4921512e-09  1.3765138e-10  8.8281205e-08
 1.0477231e-03  2.8455029e-12  4.0820678e-06
 2.0070659e-16  9.9894780e-01  1.0296049e-07
 2.9972372e-07]
```

7

Your turn!