

Throughout this course we will develop a project in several stages. The project consists of managing and operating a language to program a factory robot in a two-dimensional world. The robot is able to move in the world (delimited by an $n \times n$ matrix); the robot moves from cell to cell. Cells are indexed by rows and columns. The top left cell is indexed as (1,1). North is top; West is left. The robot interacts (picks and puts down) with two different types of objects (chips and balloons). Additionally, note that the robot cannot move on, or interact with obstacles in the world (gray cells).

Robot Description

In this project, Project 0, we will try to understand the robot language. That is, given a program for the robot, we will like to see if this satisfies the language specification and robot behavior, explained in the following.

Below we define a language for programs for the robot.

A program for the robot is simply a secuence of command blocks and definitions.

- A definition can be a variable definition or a procedure definition.
 - A variable definition starts with the keyword defVar followed by a name followed by an initial value.
 - A procedure definition starts with the keyword defProc followed by a name, followed by a list of parameter in parenthesis separated by commas, followed by a block of commands.
- A block of commands is a sequence of commands separated by semicolons within curly brackets {} .
- A value is a number or a previously defined variable
- Command can be a simple command, a control structure or a procedure call
 - A simple command can be any one of the following:
 - * An assignment which is of the form name = v where name is a variable's name and n is a value. The result of this instruction is to assign the value of to the variable.
 - * jump(x,y) where x and y are values. The robot should go to position (x, y).
 - * walk(v) where v is a value. The robot should move v steps forward.



- * walk(v, D) where v is a value. D is a direction, either front, right, left, back. The robot should move n positions to the front, to the left, the right or back and end up facing the same direction as it started.
- * walk (v, 0) where v is a value. 0 is north, south, west, or east. The robot should face 0 and then move n steps forward.
- * leap(v) where v is a value. The robot should jumo v steps forward.
- * leap(v, D) where v is a value. D is a direction, either front, right, left, back. The robot should jump n positions to the front, to the left, the right or back and end up facing the same direction as it started.
- * leap (v, 0) where v is a value. 0 is north, south, west, or east. The robot should face 0 and then move n steps.
- * turn(D) where D can be left, right, or around. The robot should turn 90 degrees in the direction of the parameter.
- * turnto(0) where 0 can be north, south, east or west. The robot should turn so that it ends up facing direction 0.
- * **drop**(v) where v is a value. The robot should drop v chips.
- * get(v) where v is a value. The robot should pickup v chips.
- * grab(v) where v is a value. The robot should pick v balloons.
- * letGo(v) where v is a value. The robot put v balloons.
- * nop() The robot does not do anything.
- a procedure is invoked using the procedure's name followed by followed by its arguments in parenthesis separated by commas.
- A control structure can be:

Conditional: if condition Block1 else Block2 - Executes Block1 if condition is true and Block2 if condition is false.

Loop: while condition Block - Executes Block while condition is true.

RepeatTimes: repeat v times Block - Executes Block n times, where v is a value.

- A condition can be:
 - * facing(0) where 0 is one of: north, south, east, or west
 - * can(C) where C is a simple command. This condition is true when the simple command can be executed without error.
 - * **not**: cond where cond is a condition

Spaces, newlines, and tabulators are separators and should be ignored.



ISIS-1106 Lenguajes y máquinas Project 0

Fecha: August 17, 2023

The language is not case-sensitive. This is to say, it does not distinguish between upper and lower case letters.

Remember the robot cannot walk over obstacles, and when leaping it cannot land on an obstacle. The robot cannot walk off the board or land off the board when leaping.

Task 1. The task of this project is to use Python or Java to implement a simple yes/no parser. The program should read a text file that contains a program for the robot, and verify whether the syntax is correct.

You must verify that used function names and variable names have been previously defined or in the case of functions, that they are the function's arguments. You must allow recursion.

Spaces and tabulators are separators and should be ignored.

Below we show an example of a valid program.



Fecha: August 17, 2023

```
_1\, \hbox{defVar nom} \,\, 0
_2\, \hbox{defVar} \,\, x \,\, \, 0
_3\,\text{defVar} y 0
4 defVar one 0
6 defProc putCB (c, b)
7 {
      drop(c);
      letGo(b);
      walk(n)
<sub>11</sub> }
13 defProc goNorth()
14 {
      while can(walk(1,north)) { walk(1,north)}
18 }
20 defProc goWest()
      if can(walk(1,west)) { walk(1,west)} else nop()
23
25 }
27 {
28 jump (3,3);
29 putCB(2,1)
30 }
```