

PSoC METEO_Soft_Interno
DIAGRAMA v20Thies Main()
R.OLIVA 16-02-2014

Notas de Proyecto (METEO V20) 16.02.2014

ARCHIVOS:

main.c -> contiene funcion main(),
comm.c -> Rutinas de PuertoSerie
compilar con PD4.4 en WinXP
cjo con Interrupcion de Boot.asm/tpl FREQ
v20 En amarillo, modificar source code

PACKET STRUCTURE FROM METEO v20 / Thies uses higher freq, send 'SSSS'
instead of 'SSS':
-> (Temperature is Txd in 100*K = 100*(T°C+273.15) =
100*(273.15+20.1)=29335);
char TestCStr[] = "UUU\$29335.10156.2562.15100.125.1095*QQQ";
So the sscanf() function is %5d for the first.. (total 39c)

For v20 Thies- 2014 :

Maintains same packet "UUU\$ttttt.bbbbb.ddddd.sssss.vvv.CRCC*QQQ" but:

ttttt is 00000 08191 Raw Temperature ADC reading,

can be 0-5V(Direct sensor with G=2) or 1-5V (4-20mA)

bbbbbb is 00000 08191 Raw BaroPressure ADC reading,

can be 0-5V(Direct sensor with G=1) or 1-5V (4-20mA)

dddd is 0000 to 3600, WDIR*10 in UWORD

sssss is 00000 to 99999, 0 to 9999.9Hz (no scaling) from Thies Anemometer.

(15100 reading would be 1510Hz, or Typical: V= 0.04597*1510+0.21=69.6m/s)

vvv was voltage, not used.

CRCC is simple checksum

