

Network Defenses

KAMI VANIEA

21 JANUARY

First, the news...


- The silencing of KrebsOnSecurity opens a troubling chapter for the Internet
- <http://arstechnica.co.uk/security/2016/09/why-the-silencing-of-krebsonsecurity-opens-a-troubling-chapter-for-the-net/>

Today


- Open System Interconnect (OSI) model
- Firewalls
- Intrusion detection systems (IDS)
- Time allowing:
 - Network Address Translation (NAT)

Open Systems Interconnect model

- A good way to think about networking steps logically
- Not how software is actually built



OSI in terms of debugging errors



Can your browser open another website?

Do you have a viewer that supports jpg (image format)?

Can you ping the webserver you are trying to reach?

Can you ping the gateway or DNS server?


Do you have an IP address?

Is the light on the modem on?

Is the network cable plugged in?

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
<!-- DOCTYPE needs to be the very first thing on the page, or IE 6 goes
into quirks mode, rather than standards mode -->
<!-- START: ssi/doctype.inc -->
<html>
<head>
<!-- END: ssi/doctype.inc -->
<!-- TITLE HERE -->
<!-- START: ssi/bin/metadata -->
<!-- Metadata information automatically generated -->
<META NAME="DC.Title" CONTENT="Computer Security Course - University of Ed
<META NAME="DC.Creator" CONTENT="Neil Brown">
<META NAME="DC.Creator.Address" CONTENT="neilb@inf.ed.ac.uk">
```

Sender:
Apache server

7	 Application Network process to application
6	Presentation Data representation and encryption
5	Session Interhost communication
4	Transport End-to-end connection and reliability
3	Network Path determination and IP (Logical Addressing)
2	Data Link MAC and LLC (Physical Addressing)
1	Physical Media, signal, and binary transmission


Data starts at the top
of the OSI stack at
level 7.


It progresses down
the stack with each
successive level
adding or changing
information.

At level 1 it travels
across the physical
layer to the recipient
computer.

The recipient then
processes the data up
the stack. At level 7 an
application processes
the data.


Recipient:
Firefox user

7	 Application Network process to application
6	Presentation Data representation and encryption
5	Session Interhost communication
4	Transport End-to-end connection and reliability
3	Network Path determination and IP (Logical Addressing)
2	Data Link MAC and LLC (Physical Addressing)
1	Physical Media, signal, and binary transmission



- Levels 7 and 6 involve the internal representation of the message
- Levels 5 and 4 involve setting up the connection
- Levels 3, 2, and 1 add header (H) and tail (T) information to each packet


Information is added to the message as it travels down the OSI levels



7	Application Network process to application
6	Presentation Data representation and encryption
5	Session Interhost communication
4	Transport End-to-end connection and reliability
3	Network Path determination and IP (Logical Addressing)
2	Data Link MAC and LLC (Physical Addressing)
1	Physical Media, signal, and binary transmission

Header data on a packet

1. Physical
2. Data link
3. Network
4. Transport
- ...
7. Application



Frame header data on a packet

1. Physical
2. Data link
3. Network
4. Transport
- ...
7. Application

Wireshark · Packet 82 · wireshark_pcapng_2357B808-9420-432A-BC45-66CA7D0AFB79_20160119150417_a03436

Frame 82: 1514 bytes on wire (12112 bits), 1514 bytes captured (12112 bits) on interface 0
Interface id: 0 (\Device\NPF_{2357B808-9420-432A-BC45-66CA7D0AFB79})
Encapsulation type: Ethernet (1)
Arrival Time: Jan 19, 2016 15:04:22.682715000 GMT Standard Time
[Time shift for this packet: 0.000000000 seconds]
Epoch Time: 1453215862.682715000 seconds
[Time delta from previous captured frame: 0.000002000 seconds]
[Time delta from previous displayed frame: 0.000002000 seconds]
[Time since reference or first frame: 4.854353000 seconds]
Frame Number: 82
Frame Length: 1514 bytes (12112 bits)
Capture Length: 1514 bytes (12112 bits)
[Frame is marked: False]
[Frame is ignored: False]
[Protocols in frame: eth:ethertype:ip:tcp]
[Coloring Rule Name: HTTP]
[Coloring Rule String: http || tcp.port == 80 || http2]

Ethernet II, Src: a2:db:03:00:00:1a (a2:db:03:00:00:1a), Dst: IntelCor_3e:53:41 (34:02:86:3e:53:41)
Internet Protocol Version 4, Src: 216.34.181.45, Dst: 172.20.107.11
Transmission Control Protocol, Src Port: 80 (80), Dst Port: 59356 (59356), Seq: 12645, Ack: 984, Len: 1460

No.: 82 · Time: 4.854353 · Source: 216.34.181.45 · Destination: 172.20.107.11 · Protocol: TCP · Length: 1514 · Info: [TCP segment of a reassembled PDU]

Close Help

Information needed to physically transport the packet

IP header data on a packet

1. Physical
2. Data link
3. Network
4. Transport
- ...
7. Application

Wireshark · Packet 82 · wireshark_pcapng_2357B808-9420-432A-BC45-66CA7D0AFB79_20160119150417_a03436

Frame 82: 1514 bytes on wire (12112 bits), 1514 bytes captured (12112 bits) on interface 0

Ethernet II, Src: a2:db:03:00:00:1a (a2:db:03:00:00:1a), Dst: IntelCor_3e:53:41 (34:02:86:3e:53:41)

Internet Protocol Version 4, Src: 216.34.181.45, Dst: 172.20.107.11

0100 = Version: 4

.... 0101 = Header Length: 20 bytes

Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)

Total Length: 1500

Identification: 0xf76f (63343)

Flags: 0x02 (Don't Fragment)

Fragment offset: 0

Time to live: 243

Protocol: TCP (6)

Header checksum: 0xe63b [validation disabled]

Source: 216.34.181.45

Destination: 172.20.107.11

[Source GeoIP: Unknown]

[Destination GeoIP: Unknown]

Transmission Control Protocol, Src Port: 80 (80), Dst Port: 59356 (59356), Seq: 12645, Ack: 984, Len: 1460

No.: 82 · Time: 4.854353 · Source: 216.34.181.45 · Destination: 172.20.107.11 · Protocol: TCP · Length: 1514 · Info: [TCP segment of a reassembled PDU]

Close Help

Annotations:


- Version 4
- Type of the next header
- Source and destination IP addresses
- Internet Protocol (IP) information

Firewalls


Firewalls

- Firewalls divide the untrusted outside of a network from the more trusted interior of a network
- Often they run on dedicated devices
 - Less possibilities for compromise – no compilers, linkers, loaders, debuggers, programming libraries, or other tools an attacker might use to escalate their attack
 - Easier to maintain few accounts
 - Physically divide the inside from outside of a network

Sample Network




- Questionable things come from the internet AND from the local network
- Firewall applies a set of rules
- Based on rules, it allows or denies the traffic
- Firewalls can also act as routers deciding where to send traffic




Rule	Type	Source Address	Destination Address	Destination Port	Action
1	TCP	*	192.168.1.*	22	Permit
2	UDP	*	192.168.1.*	69	Permit
3	TCP	192.168.1.*	*	80	Permit
4	TCP	*	192.168.1.18	80	Permit
5	UDP	*	192.168.1.*	*	Deny


```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
"http://www.w3.org/TR/html4/loose.dtd">
<!-- DOCTYPE needs to be the very first thing on the page, or IE 6 goes
into quirks mode, rather than standards mode -->
<!-- DOCUMENT STARTS -->
<!-- START: ssi/doctype.inc -->
<html>
<head>
<!-- END: ssi/doctype.inc -->
<!-- TITLE HERE -->
<!-- START: ssi/bin/metadata -->
<!-- Metadata information automatically generated -->
<META NAME="DC.Title" CONTENT="Computer Security Course - University of Edinburgh School of Informatics" />
<META NAME="DC.Creator" CONTENT="Neil Brown" />
<META NAME="DC.Creator.Address" CONTENT="neilb@inf.ed.ac.uk" />
```

Sender:
Apache server

7	 <div>Application Network process to application</div>
6	<div>Presentation Data representation and encryption</div>
5	<div>Session Interhost communication</div>
4	<div>Transport End-to-end connection and reliability</div>
3	<div>Network Path determination and IP (Logical Addressing)</div>
2	<div>Data Link MAC and LLC (Physical Addressing)</div>
1	<div>Physical Media, signal, and binary transmission</div>

Recipient:
Firefox user



7	 <div>Application Network process to application</div>
6	<div>Presentation Data representation and encryption</div>
5	<div>Session Interhost communication</div>
4	<div>Transport End-to-end connection and reliability</div>
3	<div>Network Path determination and IP (Logical Addressing)</div>
2	<div>Data Link MAC and LLC (Physical Addressing)</div>
1	<div>Physical Media, signal, and binary transmission</div>



Sender:
Apache server

7	Application Network process to application
6	Presentation Data representation and encryption
5	Session Interhost communication
4	Transport End-to-end connection and reliability
3	Network Path determination and IP (Logical Addressing)
2	Data Link MAC and LLC (Physical Addressing)
1	Physical Media, signal, and binary transmission

A firewall takes in network traffic and compares it to a set of rules. In order to do so it must first process several OSI levels to reach the data it needs.

For example, to filter out all traffic from IP 216.34.181.45 the packet needs to be processed through level 3 where IP addresses can be read.

Firewall

3	Network Path determination and IP (Logical Addressing)
2	Data Link MAC and LLC (Physical Addressing)
1	Physical Media, signal, and binary transmission



Recipient:
Firefox user

7	Application Network process to application
6	Presentation Data representation and encryption
5	Session Interhost communication
4	Transport End-to-end connection and reliability
3	Network Path determination and IP (Logical Addressing)
2	Data Link MAC and LLC (Physical Addressing)
1	Physical Media, signal, and binary transmission

Firewall ruleset from a custom home router

- Taken from an ARSTechnica article

```
root@ars-router: ~  
##### Service rules  
# OpenVPN  
-A INPUT -p udp -m udp --dport 1194 -j ACCEPT  
  
# ssh - drop any IP that tries more than 10 connections per minute  
-A INPUT -p tcp -m tcp --dport 22 -m state --state NEW -m recent --set --name DE  
FAULT --mask 255.255.255.255 --rsource  
-A INPUT -p tcp -m tcp --dport 22 -m state --state NEW -m recent --update --seco  
nds 60 --hitcount 11 --name DEFAULT --mask 255.255.255.255 --rsource -j LOGDROP  
-A INPUT -p tcp -m tcp --dport 22 -j ACCEPT  
  
# www - accept from LAN  
-A INPUT -i p1p1 -p tcp -m tcp --dport 80 -j ACCEPT  
-A INPUT -i p1p1 -p tcp -m tcp --dport 443 -j ACCEPT  
  
# DNS - accept from LAN  
-A INPUT -i p1p1 -p tcp --dport 53 -j ACCEPT  
-A INPUT -i p1p1 -p udp --dport 53 -j ACCEPT  
  
# default drop because I'm awesome  
-A INPUT -j DROP  
  
##### forwarding ruleset
```

Image: <http://arstechnica.co.uk/gadgets/2016/01/numbers-dont-lie-its-time-to-build-your-own-router/>

There are many types of Firewalls

Key differences include:

- How implemented
 - Software – slower, easier to deploy on personal computers
 - Hardware – faster, somewhat safer, harder to add in
- Number of OSI levels of processing required
 - Packet size (level 1)
 - MAC (level 2) and IP (level 3) filtering
 - Port filtering (level 3)
 - Deep packet (level 4+)

Today we will talk about:

- Packet filtering gateway
- Stateful inspection firewall
- Application proxy
- Personal firewalls

Packet filtering gateway or screening router


- Simplest – compares information found in the headers to the policy rules
- Operate at OSI level 3
- Source addresses and ports can be forged, which a packet filter cannot detect
- Design is simple, but tons of rules are needed, so it is challenging to maintain

Stateful inspection firewall

- Maintains state from one packet to another
- Similar to a packet filtering gateway, but can remember recent events
- For example, if a outside host starts sending packets to many internal destination ports (aka a port scan) a stateful firewall would record the number of ports probed and once it is over the threshold specified in the policy it would block all further traffic

Port scan

- An attacker is looking for applications listening on ports
- A single IP address (right) is contacting many ports (left) to see if any respond



Application proxy

- Simulates the (proper) effects of an application at OSI level 7
- Effectively a protective Man In The Middle that screens information at an application layer (OSI 7)
- Allows an administrator to block certain application requests.
- For example:
 - Block all web traffic containing certain words
 - Remove all macros from Microsoft Word files in email
 - Prevent anything that looks like a credit card number from leaving a database

Personal firewalls

- Runs on the workstation that it protects (software)
- Provides basic protection, especially for home or mobile devices
- Malicious software can disable part or all of the firewall
- Any rootkit type software can disable the firewall

Intrusion Detection Systems (IDS)



Firewalls are preventative, IDS detects a potential incident in progress

- At some point you have to let some traffic into and out of your network (otherwise users get upset)
- Most security incidents are caused by a user letting something into the network that is malicious, or by being an insider threat themselves
- These cannot be prevented or anticipated in advance
- The next step is to identify that something bad is happening quickly so you can address it

Signature based

- Perform simple pattern matching and report situations that match the pattern
- Requires that admin anticipate attack patterns in advance
- Attacker may test attack on common signatures
- Impossible to detect a new type of attack
- High accuracy, low false positives

Heuristic based

- Dynamically build a model of acceptable or “normal” behavior and flag anything that does not match
- Admin does not need to anticipate potential attacks
- System needs time to warm up to new behavior
- Can detect new types of attacks
- Higher false positives, lower accuracy

Number of alarms is a big problem

- In the Target breach the IDS did correctly identify that there was an attack on the Target network
- There were too many alarms going off to investigate all of them in great depth
- Some cyberattack insurance policies state that if you know about an attack and do nothing they will not cover the attack.
- Having a noisy IDS can potentially be a liability

Network Address Translation (NAT)

IPv4

- Version 4 of the Internet Protocol
 - 192.168.2.6
- There are less than 4.3 billion IPv4 addresses available
- We do not have enough addresses for every device on the planet

Questions
