

Auth Actions

Add a user

```
curl --request POST \  
  --url http://localhost:3000/api/auth/signup \  
  --header 'Content-Type: application/json' \  
  --data '{  
    "username": "",  
    "email_unverified": "",  
    "password": ""  
  }'
```

Login

```
curl --request POST \  
  --url http://localhost:3000/api/auth/login \  
  --header 'Content-Type: application/json' \  
  --data '{  
    "email": "",  
    "password": ""  
  }'
```

Logout

```
curl --request POST \  
  --url http://localhost:3000/api/auth/logout \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Verify email address

```
curl --request GET \  
  --url http://localhost:3000/api/auth/verify/insert_user_id/insert_token
```

Resend Verification Email

```
curl --request GET \  
  --url http://localhost:3000/api/auth/resend \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Cancel Verification Request

```
curl --request GET \  
  --url http://localhost:3000/api/auth/insert_user_id/insert_token/verify/cancel
```

Refresh

```
curl --request POST \  
  --url http://localhost:3000/api/auth/refresh \  
  --header 'Authorization: Bearer insert_jwt_token' \  
  --header 'Cookie: refresh_token=insert_refresh_token'
```

Update password

- For an authenticated user, not for forgotten password resets

```
curl --request PATCH \  
  --url http://localhost:3000/api/auth/password \  
  --header 'Authorization: Bearer insert_jwt_token' \  
  --header 'Content-Type: application/json' \  
  --data '{  
    "oldPassword": "",  
    "newPassword": ""  
  }'
```

User Actions

Remove a user

```
curl --request DELETE \  
  --url http://localhost:3000/api/user/ \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Update username/email/avatar/desc

- All fields optional, include only the ones you want to change
- If included: username and email_unverified must be valid (can't be empty/null)
- Avatar and desc: empty string to delete from db

```
curl --request PATCH \  
  --url http://localhost:3000/api/user/update \  
  --header 'Authorization: Bearer insert_jwt_token' \  
  --header 'Content-Type: application/json' \  
  --data '{  
    "username": "",  
    "email_unverified": "",  
    "avatar": "",  
    "desc": ""  
  }'
```

Get own profile

```
curl --request GET \  
  --url http://localhost:3000/api/user/me \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Get user by id

```
curl --request GET \  
  --url http://localhost:3000/api/user/id/insert_user_id_to_find \  
  --header 'Authorization: Bearer insert_jwt_token'
```

```
--header 'Authorization: Bearer insert_jwt_token'
```

Get user by username

```
curl --request GET \
```

```
--url http://localhost:3000/api/user/username/insert_username_to_find \
```

```
--header 'Authorization: Bearer insert_jwt_token'
```

Get all users sorted by username

```
curl --request GET \
```

```
--url http://localhost:3000/api/user/all/username \
```

```
--header 'Authorization: Bearer insert_jwt_token'
```

Get all users sorted by date

```
curl --request GET \
```

```
--url http://localhost:3000/api/user/all/date \
```

```
--header 'Authorization: Bearer insert_jwt_token'
```

Admin Actions

Modify a user account details

- Similar to the user version:
- All fields except targetId are optional
- If username is included, it must not be empty
- If avatar/desc is empty, it will set the db field to null

```
curl --request PATCH \  
  --url http://localhost:3000/api/admin/modify \  
  --header 'Authorization: Bearer insert_jwt_token' \  
  --header 'Content-Type: application/json' \  
  --data '{  
    "targetId": "",  
    "username": "",  
    "avatar": "",  
    "desc": ""  
  }'
```

Change a user rank

```
curl --request PATCH \  
  --url http://localhost:3000/api/admin/rank \  
  --header 'Authorization: Bearer insert_jwt_token' \  
  --header 'Content-Type: application/json' \  
  --data '{  
    "targetId": "",  
    "rank": ""  
  }'
```

Remove a user

```
curl --request DELETE \  
  --url http://localhost:3000/api/admin/remove \  
  --header 'Authorization: Bearer insert_jwt_token' \  
  --header 'Content-Type: application/json' \  
  --data '{  
    "targetId": ""  
  }'
```

--url http://localhost:3000/api/admin/**insert_target_user_id** \

--header 'Authorization: Bearer **insert_jwt_token**'

Friend Actions

Add a friend

```
curl --request POST \  
  --url http://localhost:3000/api/rel/friend/ \  
  --header 'Authorization: Bearer insert_jwt_token' \  
  --header 'Content-Type: application/json' \  
  --data '{  
    "targetId": ""  
  }'
```

Remove a friend

```
curl --request DELETE \  
  --url http://localhost:3000/api/rel/friend/targetId \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Accept friend request

```
curl --request PATCH \  
  --url http://localhost:3000/api/rel/friend/accept \  
  --header 'Authorization: Bearer insert_jwt_token' \  
  --header 'Content-Type: application/json' \  
  --data '{  
    "targetId": ""  
  }'
```

Reject friend request

```
curl --request DELETE \  
  --url http://localhost:3000/api/rel/friend/reject/targetId \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Cancel friend request

```
curl --request DELETE \  
  --url http://localhost:3000/api/rel/friend/cancel/targetId \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Get friends list

```
curl --request GET \  
  --url http://localhost:3000/api/rel/friend/ \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Get sent requests

```
curl --request GET \  
  --url http://localhost:3000/api/rel/friend/sent \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Get received requests

```
curl --request GET \  
  --url http://localhost:3000/api/rel/friend/received \  
  --header 'Authorization: Bearer insert_jwt_token'
```


Block Actions

Block user

```
curl --request POST \  
  --url http://localhost:3000/api/rel/block \  
  --header 'Authorization: Bearer insert_jwt_token' \  
  --header 'Content-Type: application/json' \  
  --data '{  
    "targetId": ""  
  }'
```

Unblock user

```
curl --request DELETE \  
  --url http://localhost:3000/api/rel/block/targetId \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Get blocked user list

```
curl --request GET \  
  --url http://localhost:3000/api/rel/block/ \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Email Actions

Send Email

```
curl --request POST \  
  --url http://localhost:3000/api/sendMail \  
  --header 'Content-Type: application/json' \  
  --data '{  
    "email": "",  
    "object": "",  
    "message": ""  
  }'
```

Export User Data

Extract user data csv format

```
curl --request GET \  
  --url http://localhost:3000/api/gdpr/exportCSV \  
  --header 'Authorization: Bearer insert_jwt_token'
```

Extract user data JSON format

```
curl --request GET \  
  --url http://localhost:3000/api/gdpr/exportJSON \  
  --header 'Authorization: Bearer insert_jwt_token'
```