


The github-bub

Sharing projects and working on shared projects

Michael Colaresi


Git repository

- Holds snapshots of information
 - Organized into trees (directories/paths) and blobs (file contents)
 - SHA1 hash used to fingerprint information
 - A commit object is a snapshot of information across files within directories




Git repository

Each circle is a commit
Object




Git repository

Each circle is a commit
Object




Git repository

Remember we can move between commits!




Git repository

Each circle is a commit
Object



Git is a **DISTRIBUTED** version control system

- Every local or remote repository is a FULL repository
 - The work is DISTRIBUTED around to many systems (lots of copies)
 - There is not one centralized repository but MANY!




Your local machine can hold many repos


Local machine




Your local machine can hold many repos



+ local machine can share code with others






Remote servers “serve” as connections








REMOTE


repositories are
on servers (in the
cloud)
That can be
accessed through
https, ssh, or other
protocols









Like Github!











REMOTE
repositories are
on servers (in the
cloud)
That can be
accessed through
https, ssh, or other
protocols







Repositories
Can be on servers too
(in the cloud)









Repositories
Can be on servers too
(in the cloud)




There are
other popular
remote servers
too...








Push




YOU can share your code
On these servers
UPLOAD








Create a “remote”
repo...

This is just a directory
On the server...



<https://github.com/colaresi/repo1>




Push







Create a “remote”
repo...
This is just a directory
On the server...



<https://github.com/colaresi/repo4>



Create a new repository

A repository contains all project files, including the revision history. Already have a project repository elsewhere? [Import a repository.](#)

Owner *



Repository name *

NoiseExample

Great repository names are short and memorable. Need inspiration? How about [bookish-waffle?](#)

Description (optional)

Pipeline to create interactive graphics from city of Pittsburgh noise data



Public

Anyone on the internet can see this repository. You choose who can commit.



Private

You choose who can see and commit to this repository.

Initialize this repository with:

Skip this step if you're importing an existing repository.



Add a README file

This is where you can write a long description for your project. [Learn more.](#)



Add .gitignore

Choose which files not to track from a list of templates. [Learn more.](#)





Choose a license

A license tells others what they can and can't do with your code. [Learn more.](#)

Create repository


You do this on github
For example, and it is looks like this




Push






Push



<https://github.com/colaresi/repo1>




Now you need to
tell your local repo
about this new remote
repo







Push





<https://github.com/colaresi/repo1>



Now you need to
tell your local repo
about this new remote
repo



Remote: <https://github.com/colaresi/repo1>




```
git remote add origin git@github.com:colaresi/repo1
```






Push





<https://github.com/colaresi/repo1>

Git team now suggests
Main as the “main”
branch names




git branch -M main






Push




<https://github.com/colaresi/repo1>





-M implies -m and -f
-m == move branch name
-f == force

Avoids problems with
master/main naming
conflicts right now

Git team now suggests
Main as the “main”
branch names




git branch -M main








Push



<https://github.com/colaresi/repo1>

This is going to “push”/upload the repo you are currently in to the “origin” remote... that is the name we gave the GitHub repo we created at <https://github.com/colaresi/repo1>

Next PUSH up
the local repo
to the remote!





`git push -u origin main`








Push



Now the commit objects and references that were in your local repo1 are on github.
This remote can be public or private (setting are within GitHub web-interface)

Next PUSH up the local repo to the remote!





git push -u origin main





Push




<https://github.com/colaresi/repo1>



BUT WAIT!
This remote now has a local parent!

Do the git flip (it is the new dance!)

Next PUSH up
the local repo
to the remote!





`git push -u origin main`





Push




<https://github.com/colaresi/repo1>



BUT WAIT!
This remote now has a local parent!
Do the git flip (it is the new dance!)

Arrows point to “parents”
... the “source” of
information in a current
state of information

Next PUSH up
the local repo
to the remote!





`git push -u origin main`






Push




<https://github.com/colaresi/repo1>

Next PUSH up
the local repo
to the remote!



`git push -u origin main`

Arrows point to “parents”
... the “source” of
information in a current
state of information





-u means —set-upstream
Allows you to “pull” down
content later...









If the repo is public,
now others
can “**clone**”, or
“**fork**” your
repo and you
or they can
“**pull**” in new
commits
DOWNLOADS





<https://github.com/colaresi/repo1>











you might want
to replicate/
clone work that
is in awesome/
repo4




<https://github.com/colaresi/repo1>










<https://github.com/colaresi/repo1>




git clone REPO_ADDRESS






git clone git@github:awesome/repo4





<https://github.com/colaresi/repo1>




git clone is going to do a number of things ... in sequence for you



git clone git@github:awesome/repo4






<https://github.com/colaresi/repo1>





git clone is going to do a number of things ... in sequence for you

mkdir repo4; cd repo4
git init



git clone git@github:awesome/repo4








git clone is going to do a number of things ... in sequence for you



```
mkdir repo4; cd repo4
```

```
git init
```

```
git remote add origin git@github.com:awesome/repo4
```






```
git clone git@github:awesome/repo4
```





git clone is going to do a number of things ... in sequence for you

```
mkdir repo4; cd repo4
git init
git remote add origin git@github.com:awesome/repo4
git fetch --all
```



```
git clone git@github:awesome/repo4
```



git clone is going to do a number of things ... in sequence for you

mkdir repo4; cd repo4





git init

git remote add origin git@github.com:awesome/repo4

git fetch --all



git checkout --track origin/main

Switch to main branch that
is tracking/paired to the
remote main branch




git clone git@github:awesome/repo4






<https://github.com/colaresi/repo1>





git clone is going to do a number of things ... in sequence for you

```
mkdir repo4; cd repo4
git init
git remote add origin git@github.com:awesome/repo4
git fetch --all
git checkout --track origin/main
```

FINALLY:
cd ..



Remote: <https://github.com/colaresi/repo1>





git clone git@github:awesome/repo4









Git clone is just the start... you can “pull” new commits into your repos







Eventually,
Awesome might
push a new
commit to
awesome/repo4








In order to “pull”
down the new
commit in that
repo.. you
actually are
doing 2 things!




<https://github.com/colaresi/repo1>

Pull






In order to “pull”
down the new
commit in that
repo.. you
actually are
doing 2 things!




Pull

git fetch
git merge






You want to
“**fetch**” that
commit from the
server,




Pull

git fetch
git merge






You want to
“**fetch**” that
commit from the
server, and
“**merge**” it into
your local repo




Pull

git fetch
git merge








You want to
“**fetch**” that
commit from the
server, and
“**merge**” it into
your local repo



Pull

git fetch
git merge









<https://github.com/colaresi/repo1>

Pull

“pull”-ing code
IS
Fetching and
merging

`git fetch`
`git merge origin/master`] = `git pull`



Does both 





So you “pull”
code into your
repo

You pull done
code a lot when
working as part
of teams







<https://github.com/colaresi/repo1>

Pull

`git fetch`
`git merge origin/master`] = `git pull`


Does both






So you “pull”
code into your
repo



You pull done
code a lot when
working as part
of teams




`git fetch`
`git merge origin/master`] = `git pull`

Does both 








<https://github.com/colaresi/repo1>





Forking a repo is similar
Except you create
The repo in your
Account on the server first

You do this on github











Forking is like a
git clone on the
server




<https://github.com/colaresi/repo1>









<https://github.com/colaresi/repo1>



Now you can git clone it back down to your local machine following the same steps as before... but with colaresi/repo4 as the remote location (or YOUR_GIT_ID/repo4) instead of awesome/repo4



`git clone git@github.com:colaresi/repo4`





Github has other useful tools for sharing code and working as a team:

Issues (we all have issues)

Pull requests

... like Actions, ...



Issues (we all have issues)

Github is a useful platform for tracking “**issues**”.
This means keeping notes on what is not working, who is assigned to fix it, and ideas for future enhancements

[colaresi](#) / [vladdsim](#) PrivateWatch 1Star 0Fork 0

[Code](#) [Issues 4](#) [Pull requests](#) [Actions](#) [Projects](#) [Wiki](#) [Security](#) [Insights](#) [Settings](#)

Filters is:issue is:open

Labels 10 Milestones 0 New issue

<input type="checkbox"/>	4 Open 6 Closed	Author ▼	Label ▼	Projects ▼	Milestones ▼	Assignee ▼	Sort ▼
<input type="checkbox"/>	! When attribute names (or methods) are changed (for example rounds to periods or vice-versa) change docs too documentation						
	<small>#7 opened on Aug 17, 2019 by colaresi</small>						
<input type="checkbox"/>	! When adding attributes and methods, update docstring documentation						
	<small>#6 opened on Aug 17, 2019 by colaresi</small>						
<input type="checkbox"/>	! another suggestion for code organization - agent methods question reorganization						5
	<small>#2 opened on Aug 10, 2019 by jonwoon</small>						
<input type="checkbox"/>	! suggestion for code structure - main and model files question reorganization						6
	<small>#1 opened on Aug 10, 2019 by jonwoon</small>						

ProTip! Exclude your own issues with `-author:colaresi`.



Pull requests

Other people write code and suggest you “pull” it into your repo

[colaresi / vladdsim](#) Private

Watch 1 Star 0 Fork 0

[Code](#) [Issues 4](#) [Pull requests](#) [Actions](#) [Projects](#) [Wiki](#) [Security](#) [Insights](#) [Settings](#)

Filters

Labels 10 Milestones 0 New issue

<input type="checkbox"/> 4 Open 6 Closed		Author	Label	Projects	Milestones	Assignee	Sort
<input type="checkbox"/>	! When attribute names (or methods) are changed (for example rounds to periods or vice-versa) change docs too documentation						
#7 opened on Aug 17, 2019 by colaresi							
<input type="checkbox"/>	! When adding attributes and methods, update docstring documentation						
#6 opened on Aug 17, 2019 by colaresi							
<input type="checkbox"/>	! another suggestion for code organization - agent methods question reorganization						5
#2 opened on Aug 10, 2019 by jonwoon							
<input type="checkbox"/>	! suggestion for code structure - main and model files question reorganization						6
#1 opened on Aug 10, 2019 by jonwoon							

ProTip! Exclude your own issues with `-author:colaresi`.



Pull requests

Actions: Run some code automatically

I use these less, but **actions** are getting popular

colaresi / vladdsim Private

Watch 1 Star 0 Fork 0

Code Issues 4 Pull requests Actions Projects Wiki Security Insights Settings

Filters is:issue is:open

Labels 10 Milestones 0 New issue

☐ 4 Open ✓ 6 Closed

Author Label Projects Milestones Assignee Sort

☐ When attribute names (or methods) are changed (for example rounds to periods or vice-versa) change docs too documentation #7 opened on Aug 17, 2019 by colaresi

☐ When adding attributes and methods, update docstring documentation #6 opened on Aug 17, 2019 by colaresi

☐ another suggestion for code organization - agent methods question reorganization #2 opened on Aug 10, 2019 by jonwoon

☐ suggestion for code structure - main and model files question reorganization #1 opened on Aug 10, 2019 by jonwoon

💡 ProTip! Exclude your own issues with `-author:colaresi`.