



FACULTY OF ENGINEERING

Department of Telecommunications and Electronics Engineering



EXCEPTION HANDLING


Basic Java Course

Advisor: Prof. Thap Thareoun

Present By : Ngouch HongCheng
: Saing LymChhun

INTRODUCTION

- **Exception Handling** in Java is one of the effective means to handle runtime errors so that the regular flow of the application can be preserved.
- **Java Exception** Handling is a mechanism to handle runtime errors such as `ClassNotFoundException`, `IOException`, `SQLException`, `RemoteException`, etc.





1. THROWABLE

- In Java, **Throwable** is the superclass for all errors and exceptions that can be thrown and caught.
- It's at the root of the exception hierarchy, which means both Exception and Error are subclasses of Throwable.
- **Throwable** is used to handle both exceptions (which are recoverable issues) and errors (which are usually critical problems).



2. ERRORS

- In Java, **an Error** is a subclass of Throwable and represents serious issues that a reasonable application typically cannot handle.
- **Errors** usually indicate problems with the Java Virtual Machine (JVM) or other critical resources, which are not intended to be caught or managed within the application code.
- **Errors** are typically unrecoverable and indicate conditions where the program is unable to continue operating safely.



2. ERRORS

- Key Points about Errors
- **Unrecoverable:** Errors usually represent conditions that the application cannot recover from, such as resource exhaustion or system-level failures.
- **JVM-related Issues:** Many errors are related to JVM issues, such as memory problems, class loading issues, or problems in native code.
- **Should Not Be Caught:** Errors should generally not be caught or handled in application code. They often indicate critical conditions where continuing execution could lead to inconsistent program states or further errors.



Four red chevrons pointing downwards, stacked vertically.

3. EXCEPTION

- In Java, **an Exception** is an event that disrupts the normal flow of a program.
- **Exceptions** are situations that a program might want to handle to prevent crashing or incorrect behavior.
- They represent conditions that applications can anticipate and attempt to recover from, unlike Error types, which are usually unrecoverable.
- **Exceptions** often represent issues that can be anticipated and handled within the program, like a file not being found or a network connection failing.

3. EXCEPTION

Common Exception Types

- **IOException:** Thrown when an I/O operation fails, such as reading from or writing to a file that doesn't exist.
- **SQLException:** Thrown when there is an issue with accessing a database, like a bad query or connection failure.
- **ArithmeticException:** Thrown when there is an illegal arithmetic operation, such as dividing by zero.
- **NullPointerException:** Thrown when trying to access an object that has not been initialized.
- **ArrayIndexOutOfBoundsException:** Thrown when accessing an array with an invalid index.

4. CHECKED EXCEPTION

- A **checked exception** in Java is a type of exception that is checked at compile time.
- These exceptions must be either caught using a try-catch block or declared in the method signature using the throws keyword.
- The compiler checks for these exceptions during the compilation process, ensuring that the programmer handles them properly.
- This mechanism encourages robust error handling and makes the code more reliable.

4. CHECKED EXCEPTION

A. USING TRY-CATCH BLOCKS

- A try-catch block is the most common way to handle checked exceptions.
- The code that might throw an exception is placed within the try block, and if an exception occurs, it is caught by one or more catch blocks.
- This allows you to handle the exception directly where it occurs.

Syntax

```
try {  
    // Code that may throw an exception  
} catch (SpecificExceptionType e) {  
    // Code to handle the specific exception  
}
```

4. CHECKED EXCEPTION

B. THROWS KEYWORD

- The throws keyword is used in a method declaration to indicate that the method might throw specific checked exceptions.
- This approach shifts the responsibility of handling the exception to the calling method, rather than catching it directly within the method.

Syntax

```
returnType methodName(parameters) throws ExceptionType1, ExceptionType2 {  
    // Method code that may throw ExceptionType1 or ExceptionType2  
}
```

4. CHECKED EXCEPTION

SUMMARY

- Use **try-catch** when you want to handle exceptions directly within a method, allowing for specific responses to each exception type.
- Use **throws** to delegate exception handling to the calling method, which is useful in layered applications where exceptions may be handled at a higher level.

Four red chevrons pointing downwards, stacked vertically on the left side of the slide.

4. UNCHECKED EXCEPTION

- Unchecked exceptions in Java are exceptions that do not require explicit handling in the code.
- They are subclasses of the RuntimeException class and are typically indicative of programming errors, such as logic mistakes or incorrect assumptions in the code.
- Since they are not checked at compile time, programmers are not forced to handle them using try-catch blocks or to declare them using the throws clause in method signatures.

END