

《数据库系统原理》实验报告（2）

题目：DDL 实验语言

学号

姓名

日期

2024.4.3

实验环境：

Search: oceanCtrl+K

vigilant_fermi

oceanbase/oceanbase-ce:latest

60e8c45cac96

STATUS

Running (7 seconds ago)

LogsInspectBind mountsExecFilesStats

sh-4.4# obclient -uroot@sys -h127.1 -P2881
Welcome to the OceanBase. Commands end with ; or \g.
Your OceanBase connection id is 322122553
Server version: OceanBase_CE 4.2.2.0 (r100010012024022719-c984fe7cb7a4cef85a40323a0d073f0c9b7b8235) (Built Feb 27 2024 19:20:54)

Copyright (c) 2000, 2018, OceanBase and/or its affiliates. All rights reserved.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

obclient [(none)]> create database second
-> ;
ERROR 8001 (08004): Server is initializing
[127.0.0.1:2882] [2024-04-03 02:23:09.871244] [YB427F000001-00061527E8178162-0-0]
obclient [(none)]> create database second;
Query OK, 1 row affected (0.015 sec)

obclient [(none)]> use second;
Database changed

实验步骤及结果截图：

1. 参照下表中内容，在数据库中建立教学管理系统相关数据表。

表名：students

字段	类型	约束
No	Integer	主键，非空
Name	Varchar	非空
Gender	Varchar	非空，只能为 Female 或者 Male
Age	Integer	非空
D_no	Integer	非空，外键

表名：depts

字段	类型	约束
No	Integer	主键，非空
Name	Varchar	非空

表名：courses

字段	类型	约束
No	Integer	主键，非空
Name	Varchar	非空
Credit	Integer	非空
D_no	Integer	非空，外键

表名：scores

字段	类型	约束
S_no	Integer	非空，外键
C_no	Integer	非空，外键
Score	Integer	非空

解答:

```
obclient [second]> create table depts(
    -> no int not null,
    -> name varchar(20) not null,
    -> primary key (no)
    -> );
```

Query OK, 0 rows affected (0.037 sec)

```
obclient [second]> create table students(
    -> no int not null,
    -> name varchar(20) not null,
    -> gender varchar(20) not null,
    -> age int not null,
    -> d_no int not null,
    -> primary key (no),
    -> foreign key (d_no) references depts (no),
    -> check (gender in ('female','male'))
    -> );
```

Query OK, 0 rows affected (0.082 sec)

```
obclient [second]> create table courses(
    -> no int not null,
    -> name varchar(20) not null,
    -> credit int not null,
    -> d_no int not null,
    -> primary key (no),
    -> foreign key (d_no) references depts (no)
    -> );
```

Query OK, 0 rows affected (0.045 sec)

```
obclient [second]> create table scores(
    -> s_no int not null,
    -> c_no int not null,
    -> score int not null,
    -> foreign key (s_no) references students(no),
    -> foreign key (c_no) references courses(no)
    -> );
```

Query OK, 0 rows affected (0.096 sec)

一、插入数据样例

```

insert into students values
  (202415120,'Michael','Male',21,3),
  (202415121,'Tommy','Male',20,1),
  (202415122,'Michael','Female',19,1),
  (202415123,'Ale','Female',18,2),
  (202415125,'Billy','Male',19,3);
insert into depts values
  (1,'Computer Science'),
  (2,'Mathematics'),
  (3,'English'),
  (4,'Management');
insert into courses values
  (1,'Database',5,1),
  (2,'Mathematics',2,2),
  (3,'Information System',1,4),
  (4,'Operating System',6,1),
  (5,'Data Structure',4,1),
  (6,'Data Processing',2,4),
  (7,'PASCAL',3,1);
insert into scores values
  (202415121,1,92),
  (202415121,2,85),
  (202415121,3,88),
  (202415122,2,90),
  (202415122,3,80);

```

```

obclient [second]> insert into depts values
  -> (1,'Computer Science'),
  -> (2,'Mathematics'),
  -> (3,'English'),
  -> (4,'Management');

```

Query OK, 4 rows affected (0.005 sec)
 Records: 4 Duplicates: 0 Warnings: 0

```

obclient [second]> insert into students values
  -> (202415120,'Michael','Male',21,3),
  -> (202415121,'Tommy','Male',20,1),
  -> (202415122,'Michael','Female',19,1),
  -> (202415123,'Ale','Female',18,2),
  -> (202415125,'Billy','Male',19,3);

```

Query OK, 5 rows affected (0.008 sec)
 Records: 5 Duplicates: 0 Warnings: 0

```

obclient [second]> insert into courses values
  -> (1,'Database',5,1),
  -> (2,'Mathematics',2,2),
  -> (3,'Information System',1,4),
  -> (4,'Operating System',6,1),
  -> (5,'Data Structure',4,1),
  -> (6,'Data Processing',2,4),
  -> (7,'PASCAL',3,1);

```

Query OK, 7 rows affected (0.007 sec)
 Records: 7 Duplicates: 0 Warnings: 0

```
obclient [second]> insert into scores values
```

```
-> (202415121,1,92),
```

```
-> (202415121,2,85),
```

```
-> (202415121,3,88),
```

```
-> (202415122,2,90),
```

```
-> (202415122,3,80);
```

```
Query OK, 5 rows affected (0.012 sec)
```

```
Records: 5 Duplicates: 0 Warnings: 0
```

```
obclient [second]> select *
```

```
-> from students;
```

```
+-----+-----+-----+-----+-----+
| no      | name    | gender | age | d_no |
+-----+-----+-----+-----+-----+
| 202415120 | Michael | Male   | 21  | 3    |
| 202415121 | Tommy   | Male   | 20  | 1    |
| 202415122 | Michael | Female | 19  | 1    |
| 202415123 | Ale     | Female | 18  | 2    |
| 202415125 | Billy   | Male   | 19  | 3    |
+-----+-----+-----+-----+-----+
```

```
5 rows in set (0.003 sec)
```

```
obclient [second]> select * from depts;
```

```
+----+-----+
| no | name          |
+----+-----+
| 1  | Computer Science |
| 2  | Mathematics      |
| 3  | English          |
| 4  | Management       |
+----+-----+
```

```
4 rows in set (0.002 sec)
```

```
obclient [second]> select * from courses;
```

```
+----+-----+-----+-----+
| no | name                | credit | d_no |
+----+-----+-----+-----+
| 1  | Database             | 5      | 1    |
| 2  | Mathematics          | 2      | 2    |
| 3  | Information System   | 1      | 4    |
| 4  | Operating System     | 6      | 1    |
| 5  | Data Structure       | 4      | 1    |
| 6  | Data Processing      | 2      | 4    |
| 7  | PASCAL               | 3      | 1    |
+----+-----+-----+-----+
```

```
7 rows in set (0.009 sec)
```

```
obclient [second]> select * from scores;
```

```
+-----+-----+-----+
| s_no   | c_no | score |
+-----+-----+-----+
| 202415121 | 1 | 92 |
| 202415121 | 2 | 85 |
| 202415121 | 3 | 88 |
| 202415122 | 2 | 90 |
| 202415122 | 3 | 80 |
+-----+-----+-----+
5 rows in set (0.005 sec)
```

2. 使用比较运算符查询所有年龄在 21 岁以下的学生姓名及其年龄

```
obclient [second]> select name,age
-> from students
-> where age<21;
```

```
+-----+-----+
| name   | age |
+-----+-----+
| Tommy  | 20 |
| Michael | 19 |
| Ale    | 18 |
| Billy  | 19 |
+-----+-----+
4 rows in set (0.002 sec)
```

3. 查询选 2 号课程 (S_no='2') 且成绩在 80--90 的学号

```
obclient [second]> select s_no
-> from scores
-> where c_no='2' and score between 80 and 90;
```

```
+-----+
| s_no   |
+-----+
| 202415121 |
| 202415122 |
+-----+
2 rows in set (0.005 sec)
```

4. 查询姓名第二个字母是'e'的学生姓名

```
obclient [second]> select name
-> from students
-> where name like '_e%';
Empty set (0.002 sec)
```

5. 查询全体男学生的学号、系、年龄结果按所在的系升序排列，同一系中的学生按年龄降序排列

```
obclient [second]> select no,d_no,age
-> from students
-> where gender='male'
-> order by d_no asc,age desc;
+-----+-----+-----+
| no      | d_no | age |
+-----+-----+-----+
| 202415121 | 1 | 20 |
| 202415120 | 3 | 21 |
| 202415125 | 3 | 19 |
+-----+-----+-----+
3 rows in set (0.003 sec)
```

6. 查询女学生的总人数和平均年龄

```
obclient [second]> select count(distinct no),avg(age)
-> from students
-> where gender='female';
+-----+-----+
| count(distinct no) | avg(age) |
+-----+-----+
| 2 | 18.5000 |
+-----+-----+
1 row in set (0.009 sec)
```

7. 查询选修 2 号课程并及格（分数大于 60）的学生的最高分、最低分及总分

```
obclient [second]> select max(score),min(score),sum(score)
-> from scores
-> where c_no='2' and score>60;
+-----+-----+-----+
| max(score) | min(score) | sum(score) |
+-----+-----+-----+
| 90 | 85 | 175 |
+-----+-----+-----+
1 row in set (0.002 sec)
```

8. 向 scores 表中插入一条记录 (200266666,1,85)

```
obclient [second]> insert into students values(200266666,'mike','male',21,2);
Query OK, 1 row affected (0.005 sec)
```

```
obclient [second]> insert into scores(s_no,c_no,score) value(200266666,1,85);
Query OK, 1 row affected (0.002 sec)
```

```
obclient [second]> select *
-> from scores;
```

s_no	c_no	score
202415121	1	92
202415121	2	85
202415121	3	88
202415122	2	90
202415122	3	80
200266666	1	85

```
6 rows in set (0.001 sec)
```

9. 求每个学生（号）的平均成绩，并将其超过 70 分的按学号输出

```
obclient [second]> select s_no,avg(score)
-> from scores
-> group by s_no
-> having avg(score)>70
-> order by s_no;
```

s_no	avg(score)
200266666	85.0000
202415121	88.3333
202415122	85.0000

```
3 rows in set (0.003 sec)
```

10. 查询选修了课程 1 或者选修了课程 3 的学生姓名

```
obclient [second]> select *
-> from students;
+-----+-----+-----+-----+-----+
| no      | name    | gender | age | d_no |
+-----+-----+-----+-----+-----+
| 200266666 | mike    | male   | 21  | 2    |
| 202415120 | Michael | Male   | 21  | 3    |
| 202415121 | Tommy   | Male   | 20  | 1    |
| 202415122 | Michael | Female | 19  | 1    |
| 202415123 | Ale     | Female | 18  | 2    |
| 202415125 | Billy   | Male   | 19  | 3    |
+-----+-----+-----+-----+-----+
6 rows in set (0.001 sec)

obclient [second]> select * from scores;
+-----+-----+-----+
| s_no      | c_no | score |
+-----+-----+-----+
| 202415121 | 1    | 92    |
| 202415121 | 2    | 85    |
| 202415121 | 3    | 88    |
| 202415122 | 2    | 90    |
| 202415122 | 3    | 80    |
| 200266666 | 1    | 85    |
+-----+-----+-----+
6 rows in set (0.001 sec)

obclient [second]> (select distinct name
-> from scores,students
-> where c_no='1' and scores.s_no=students.no)
-> union
-> (select distinct name
-> from scores,students
-> where c_no='3' and scores.s_no=students.no);
+-----+
| name    |
+-----+
| mike    |
| Tommy   |
| Michael |
+-----+
3 rows in set (0.000 sec)
```


11. 查询既选修了课程 1 又选修了课程 2 的学生姓名

```
obclient [second]> select *
-> from students;
```

```
+-----+-----+-----+-----+
| no      | name    | gender | age | d_no |
+-----+-----+-----+-----+
| 200266666 | mike    | male   | 21  | 2    |
| 202415120 | Michael | Male   | 21  | 3    |
| 202415121 | Tommy   | Male   | 20  | 1    |
| 202415122 | Michael | Female | 19  | 1    |
| 202415123 | Ale     | Female | 18  | 2    |
| 202415125 | Billy   | Male   | 19  | 3    |
+-----+-----+-----+-----+
6 rows in set (0.001 sec)
```

```
obclient [second]> select * from scores;
```

```
+-----+-----+-----+
| s_no    | c_no | score |
+-----+-----+-----+
| 202415121 | 1    | 92    |
| 202415121 | 2    | 85    |
| 202415121 | 3    | 88    |
| 202415122 | 2    | 90    |
| 202415122 | 3    | 80    |
| 200266666 | 1    | 85    |
+-----+-----+-----+
6 rows in set (0.001 sec)
```

```
obclient [second]> (select distinct name
-> from scores,students
-> where c_no='1' and scores.s_no=students.no)
-> intersect
-> (select distinct name
-> from scores,students
-> where c_no='2' and scores.s_no=students.no);
```

```
+-----+
| name |
+-----+
| Tommy |
+-----+
1 row in set (0.006 sec)
```

12. 查询选修 Database 这门课最高分学生所在的系名

```
obclient [second]> select depts.name
-> from scores,students,depts
-> where scores.s_no=students.no
-> and students.d_no=depts.no
-> and score=(select max(score) from scores where c_no=(select no from courses where name ='database'))
+-----+
| name          |
+-----+
| Computer Science |
+-----+
1 row in set (0.008 sec)
```

13. 建立一个包含学生学号，姓名，年龄，以及所在系名的视图（赋予列名为 sno,sname,sage,deptname）【create view】

```
obclient [second]> create view stu(sno,sname,sage,deptname)
-> as(select students.no,students.name,students.age,depts.name
-> from students,depts
-> where students.d_no=depts.no);
Query OK, 0 rows affected (0.062 sec)
```

```
obclient [second]> select * from stu;
+-----+-----+-----+-----+
| sno      | sname  | sage | deptname      |
+-----+-----+-----+-----+
| 200266666 | mike   | 21   | Mathematics    |
| 202415120 | Michael | 21   | English        |
| 202415121 | Tommy  | 20   | Computer Science |
| 202415122 | Michael | 19   | Computer Science |
| 202415123 | Ale    | 18   | Mathematics    |
| 202415125 | Billy  | 19   | English        |
+-----+-----+-----+-----+
6 rows in set (0.010 sec)
```

出现的问题：（问题与下面的解决方案每条对应）

1. 插入数据时首先插入了 `students` 的数据，插入失败

```
obclient [second]> insert into students values
-> (202415120,'michael','male',21,3),
-> (202415121,'Tommy','Male',20,1),
-> (202415122,'Michael','Female',19,1),
-> (202415123,'Ale','Female',18,2),
-> (202415125,'Billy','Male',19,3);
ERROR 1452 (23000): Cannot add or update a child row: a foreign key constraint fails
```

2. 在做插入的小题时，又忽略了插入顺序的问题，欲直接插入题目所需数据

```
obclient [second]> insert into scores(s_no,c_no,score) value(200266666,1,85);
ERROR 1452 (23000): Cannot add or update a child row: a foreign key constraint fails
```

解决方案：

1. 原因还是外码的问题，因为 `students` 的 `d_no` 是参考 `depts` 的外码，所以需要先把 `depts` 中对应的数据插入进去才能在 `students` 插入相应的数据
2. 原因同上，想要在 `scores` 里面插入一个之前不存在的学号，需要先在 `students` 里创建该学号对应的信息。

```
obclient [second]> insert into scores(s_no,c_no,score) value(200266666,1,85);
ERROR 1452 (23000): Cannot add or update a child row: a foreign key constraint fails
obclient [second]> insert into students values(200266666,'mike','male',21,2);
Query OK, 1 row affected (0.005 sec)
```

```
obclient [second]> insert into scores(s_no,c_no,score) value(200266666,1,85);
Query OK, 1 row affected (0.002 sec)
```